

## 503PTZ Composite - For PTZ Cameras: CCTV + Control + Power



For more Information  
please call

1-800-Belden1



### Description:

(1) coax-20 AWG solid BC cond., gas-injected foam HDPE insul., 95% BC braid shield, PVC jkt., cabled with (1) pair-18 AWG stranded (19x30) BC cond., PO insul., Beldfoil® shield, PVC jkt., cabled with (2) cond.-14 AWG (19x27) BC cond.,PVC insul., PVC jkt.

### Coax

#### Physical Characteristics

##### Conductor

###### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	0.032

##### Insulation

###### Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected FHDP - Foam High Density Polyethylene	0.145

##### Outer Shield

###### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

##### Outer Jacket

###### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

###### Outer Jacket Diameter:

Nom. Dia. (in.)
0.227

###### Outer Jacket Color Code Chart:

Number	Color
Video	Black

#### Applicable Specifications and Agency Compliance

##### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU CE Mark: Yes

RG Type: 59/U

##### Flame Test

UL Flame Test: UL1666 Vertical Shaft

##### Suitability

Suitability - Indoor: Yes

#### Electrical Characteristics

##### Nom. Characteristic Impedance:

Impedance (Ohm)
-----------------

## 503PTZ Composite - For PTZ Cameras: CCTV + Control + Power

75

**Nom. Inductance:**

Inductance (µH/ft)
0.097

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)
16.300

**Nominal Velocity of Propagation:**

VP (%)
83.000

**Nominal Delay:**

Delay (ns/ft)
1.220

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
10.000

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
3.500

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.300
5.000	0.650
10.000	0.900
50.000	1.900
100.000	2.600
200.000	3.600
400.000	5.000
700.000	7.000
900.000	8.000
1000.000	8.500

**Max. Operating Voltage - UL:** 300 V RMS

### Twisted Pair

#### Physical Characteristics

##### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	18	19x30	BC - Bare Copper	0.044

##### Insulation

**Insulation Material:**

Insulation Material Dia. (in.)
PO - Polyolefin 0.080

**Twisted Pair Color Code Chart:**

Number	Color
1	Blue and White/Blue

##### Outer Shield

**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

## 503PTZ Composite - For PTZ Cameras: CCTV + Control + Power

### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Outer Jacket Diameter:**

Nom. Dia. (in.)
0.219

**Outer Jacket Color Code Chart:**

Number	Color
1	Blue

### Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/(UL) Specification: CMG

### Flame Test

UL Flame Test: UL1666 Vertical Shaft

### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)
44.000

**Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)
26.000

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
6.500

**Max. Operating Voltage - Other:**

Voltage
300 V RMS

**Max. Recommended Current:**

Description	Current
Data/Control	5.2 Amps

## Multi Conductor

### Physical Characteristics

#### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	14	19x27	BC - Bare Copper	0.070

### Insulation

**Insulation Material:**

Insulation Material
PVC - Polyvinyl Chloride

**Insulation Color Code Chart:**

Number	Color
1	Red
2	Black

## 503PTZ Composite - For PTZ Cameras: CCTV + Control + Power

### Individual Shield

#### Outer Jacket

Outer Jacket Diameter:

Nom. Dia. (in.)
0.236

Outer Jacket Color Code Chart:

Number	Color
1	White

### Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

### Flame Test

UL Flame Test: UL1666 Vertical Shaft

### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
21.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.520

Max. Operating Voltage - Other:

Voltage
300 V RMS

Max. Recommended Current:

Current
5 Amps per conductor @ 25°C

### Physical Characteristics (Overall)

#### Conductor

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

#### Overall Cable

Overall Nominal Diameter: 0.496 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 97.000 lbs/1000 ft.

Max. Recommended Pulling Tension: 190.000 lbs.

Min. Bend Radius/Minor Axis: 5.000 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

## 503PTZ Composite - For PTZ Cameras: CCTV + Control + Power

EU RoHS Compliance Date (mm/dd/yyyy): 08/22/2006

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

### Plenum/Non-Plenum

Plenum (Y/N): No

### Notes (Overall)

**Notes:** RG59 CCTV + 1 STP 18 AWG Control Grade + 2C 14 AWG CMR. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation. Banana Peel® US PATENT 7049523.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
503PTZ 0001000	1,000 FT	101.000 LB	NONE	C	2C18 + 2C14 + 1 RG59 PVC

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 0    Revision Date: 05-10-2010

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.