THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
FX	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D	REVISED PER ECO-09-011983	19MAY2009	DLD	WTW

KEYING OPTIONS
SCALE 2:1







SECTION A-A
SHOWN WITH TPA IN
IT'S PRE-LOADED POSITION
(DELIVERY CONDTION)



MINIMUM FEED THROUGH CONDITION
WITH 1mm CLEARANCE ALL AROUND



MINIMUM FEED THROUGH CONDITION
WITH 1mm CLEARANCE ALL AROUND
SHOWN WITH OPTION WIRESHIELD





SCALE 2:1



SCALE 2:1

1. APPLICABLE TERMINAL PART NUMBERS (SOLD SEPARATELY):
   FOR TIN APPLICATIONS: 1393367 AND 1393366.
   FOR GOLD APPLICATIONS: 1393365 AND 1393364.
   FOR TERMINATION AND REELING OPTIONS
   SEE DRAWINGS 1393367, 1393366, 1393365, AND 1393364.
2. COMPATIBLE WIRE SIZES FOR MAT SEAL DESIGN 1.19 TO 2.06 O.D.
   (22-18 AWG, 0.35-0.75 mm2)
3. TPA IS SHIPPED IN IT'S PRE-LOADED POSITION.
   ALL ASSEMBLIES ARE TO BE TRAY PACKAGED.
4. CUSTOMER PART NUMBER AND TRACEABILITY CODE (YY = TWO DIGIT YEAR, JJJ = JULIAN DAY, HH = TWO DIGIT MILITARY HOUR, A = ASSEMBLY PROCESS USED) ARE PRINTED IN THIS LOCATION.
5. PART ASSEMBLY WEIGHT WITHOUT TERMINALS AND WITH STANDARD PIN-OUT CONFIGURATION IS 15.35 GRAMS.
6. OPTIONAL WIRESHIELD P/N 7-1419157-8 (SOLD SEPARATELY). PLEASE CONTACT YOUR TYCO ELECTRONICS SALES REPRESENTATIVE FOR AVAILABILITY AND PRICING.
7. PART NUMBER IS LOADED WITH 4 SHORTING BARS. NO SHORTING BAR LOADED BETWEEN TERMINAL HOLE POSITIONS (9/10).



SCALE 1:1

KEYING OPTION "A" SHOWN

| 3-1924672-5 | 1924681-1 | 1924680-1 | 3-1924672-4 | 3-1924672-3 | 3-1924672-2 | 5-1924670-1 | 5-1924670-0 | 4-1924670-9 | 4-1924670-8 | 4-1924670-7 | 4-1924670-6 | 4-1924670-5 | 4-1924670-4 | 4-1924670-3 | 4-1924670-2 | 4-1924670-1 | 4-1924670-0 | 3-1924670-9 | 3-1924670-8 | 3-1924670-7 | 3-1924670-6 | 3-1924670-5 | 3-1924670-4 | 3-1924670-3 | 3-1924670-2 | 1924671-5 | 1924671-4 | 1924671-3 | 3-1924670-1 | 3-1924670-0 | 3-1924672-0 | 2-1924672-9 | 2-1924672-8 | 2-1924672-7 | 2-1924672-6 | 2-1924672-5 | 2-1924672-4 | 2-1924672-3 | 2-1924672-2 | 2-1924672-1 | 2-1924672-0 | 1-1924672-9 | 1-1924672-8 | 1-1924672-7 | 1-1924672-6 | 1-1924672-5 | 1-1924672-4 | 1-1924672-3 | 1-1924672-2 | 1-1924672-1 | 1-1924672-0 | 1924672-9 | 1924672-8 | 1924672-7 | 1924672-6 | 1924672-5 | 1924672-4 | 1924672-3 | 1924672-2 | 1924672-1 | 1924671-2 | 2-1924670-8 | 1924671-1 | 2-1924670-7 | 2-1924670-6 | 2-1924670-5 | 2-1924670-4 | 2-1924670-3 | 2-1924670-2 | 2-1924670-1 | 1-1924670-9 | 1-1924670-8 | 1-1924670-7 | 1-1924670-6 | 1-1924670-5 | 1-1924670-4 | 1-1924670-3 | 1-1924670-2 | 1-1924670-1 | 1-1924670-0 | 1924670-9 | 1924670-8 | 1924670-7 | 1924670-6 | 1924670-5 | 1924670-4 | 1924670-3 | 1924670-2 | 1924670-1 | ASSEMBLY PART NUMBER | ITEM | DESCRIPTION | MATERIAL | FINISH/COLOR |
|---|---|---|---|---|---

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
FX	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

ASSEMBLY PART NUMBER	ITEM	DESCRIPTION	MATERIAL	FINISH/COLOR	QUANTITY
6-1924670-6	7	CPA	PBT-GF15	RED	1
6-1924670-5	6	PERIMETER SEAL	SILICONE	GREEN	1
3-1924672-7	5	GROMMET	SILICONE	BROWN	1
3-1924672-6	4	SHORTING BAR	S.S.	SEE COMPONENT DRAWING	5
6-1924670-4	3	COVER	PA66 35% GF	BLACK	1
6-1924670-3	2	SPACER FOR SHORTING BAR APPLICATIONS	sPS 30% GF	NATURAL	1
6-1924670-2	1	PLUG WITH KEYING OPTION "D" AND 5 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
6-1924670-1		PLUG WITH KEYING OPTION "C" AND 5 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
6-1924670-0		PLUG WITH KEYING OPTION "B" AND 5 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
1924673-3 (7)		PLUG WITH KEYING OPTION "A" AND 5 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK	
1924673-2 (7)					
1924673-1 (7)					
5-1924670-9					1
5-1924670-8					1
5-1924670-7					1
1924671-8					1
1924671-7					1
1924671-6					1
5-1924670-6					1
5-1924670-5					1
5-1924670-4					1
5-1924670-3					1
5-1924670-2					1

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±0.3
2 PLC ±0.10
3 PLC ±-
4 PLC ±-
ANGLES ±3°

MATERIAL -
FINISH -

DWN R. VESTAL 23JUL2007
CHK W. WELLINSKY 23JUL2007
APVD W. WELLINSKY 23JUL2007
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

Tyco Electronics
Tyco Electronics
Harrisburg, PA 17105-3608

NAME
24 WAY ARM
PLUG ASSEMBLY WITH SHORTING BARS
CUSTOMER SPEC.

SIZE A1 | CAGE CODE 00779 | DRAWING NO C-1924670 | RESTRICTED TO -

CUSTOMER DRAWING | SCALE 3:1 | SHEET 2 OF 3 | REV D

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
FX	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

PIN-OUT CHART

| | | |

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.