

# ATC 800 R Series NPO Ceramic, High RF Power Lowest ESR Multilayer Capacitors

- Case R Size  
(.070" x .090")
- Rugged, reliable  
NPO dielectric
- Optimized for highest  
self resonant frequency
- Capacitance Range  
1 pF to 100 pF
- Optimized for lowest ESR  
and superior heat transfer
- Capable of highest  
RF Power
- RoHS Compliant / Lead-Free

ATC's 800 R Series offers superb performance in demanding high RF power applications requiring consistent and reliable operation. The combination of optimized case geometry, highly conductive electrode formulations and proprietary dielectrics, yields the lowest ESR and superior heat transfer. ATC's new NPO low loss rugged dielectrics are designed to provide superior heat transfer in high RF power applications. Ultra-low ESR and superior thermal performance ensure that the 800 R Series products are your best choice for high RF power applications from UHF through microwave frequencies.

Typical applications: WiMAX/LTE\*, Homeland Security/Public Safety Radio (APCO-25), Satellite Systems, Avionics, Digital HD FM Transmitters, Digital HDTV Transmitters, Microwave Communications and Medical Electronics.

Typical circuit applications: High RF Power Filter Networks, Combiners, Couplers, Matching Networks, Output Coupling, Antenna Coupling, and DC Blocking and Bypassing.

\* Long term evolution

## ENVIRONMENTAL TESTS

ATC 800 R Series Capacitors are designed and manufactured to meet and exceed the requirements of EIA-198, MIL-PRF-55681 and MIL-PRF-123.

### THERMAL SHOCK:

MIL-STD-202, Method 107, Condition A

### MOISTURE RESISTANCE:


MIL-STD-202, Method 106

### LOW VOLTAGE HUMIDITY:

MIL-STD-202, Method 103, Condition A, with 1.5 Volts D.C. applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours min.

### LIFE TEST:

MIL-STD-202, Method 108, for 2000 hours, at 125°C  
200% WVDC applied



## ELECTRICAL AND MECHANICAL SPECIFICATIONS

**QUALITY FACTOR (Q):** > 2,000 @ 1 MHz

**TEMPERATURE COEFFICIENT OF CAPACITANCE (TCC):**  
0 ±30 PPM/°C (-55°C to +125°C)

### INSULATION RESISTANCE (IR):

1 pF to 100 pF:  
10<sup>5</sup> Megohms min. @ +25°C at rated WVDC  
10<sup>4</sup> Megohms min. @ +125°C at rated WVDC

**WORKING VOLTAGE (WVDC):** 500 WVDC

### DIELECTRIC WITHSTANDING VOLTAGE (DWV):

Case R: 250% of rated WVDC for 5 secs

**AGING EFFECTS:** None

### PIEZOELECTRIC EFFECTS:

None  
(No capacitance variation with voltage or pressure)

**CAPACITANCE DRIFT:** ±(0.02% or 0.02 pF), whichever is greater

### OPERATING TEMPERATURE RANGE:

From -55°C to +125°C

### TERMINATION STYLES:

RoHS Compliant and Solder Plate  
See Mechanical Configurations, page 3

**TERMINAL STRENGTH:** Terminations for chips withstand a pull of 5 lbs. min., 15 lbs. typical, for 5 seconds in direction perpendicular to the termination surface of the capacitor. Test per MIL-STD-202, Method 211.



**AMERICAN**

ATC North America  
sales@atceramics.com

**TECHNICAL**

ATC Europe  
saleseur@atceramics.com

**CERAMICS**

ATC Asia  
sales@atceramics-asia.com



THE  
ENGINEERS'  
CHOICE®  
ISO 9001 REGISTERED  
COMPANY

**THE ENGINEERS' CHOICE™**

**www.atceramics.com**

ATC # 001-1029  
Rev. K; 9/14

# ATC 800 R Series NPO Ceramic Ultra-Low ESR Multilayer Capacitors


## ATC 800 R Capacitance Values

| CAP. CODE | CAP. (pF) | TOL.    | RATED WVDC | CAP. CODE | CAP. (pF) | TOL.             | RATED WVDC | CAP. CODE | CAP. (pF) | TOL.         | RATED WVDC |
|-----------|-----------|---------|------------|-----------|-----------|------------------|------------|-----------|-----------|--------------|------------|
| 1R0       | 1.0       | B, C, D | 500        | 3R9       | 3.9       | B, C, D          | 500        | 220       | 22        | G, J<br>K, M | 500        |
| 1R1       | 1.1       |         |            | 4R3       | 4.3       |                  |            | 240       | 24        |              |            |
| 1R2       | 1.2       |         |            | 4R7       | 4.7       |                  |            | 270       | 27        |              |            |
| 1R3       | 1.3       |         |            | 5R1       | 5.1       |                  |            | 300       | 30        |              |            |
| 1R4       | 1.4       |         |            | 5R6       | 5.6       |                  |            | 330       | 33        |              |            |
| 1R5       | 1.5       |         |            | 6R2       | 6.2       |                  |            | 360       | 36        |              |            |
| 1R6       | 1.6       |         |            | 6R8       | 6.8       | B, C, J,<br>K, M |            | 390       | 39        |              |            |
| 1R7       | 1.7       |         |            | 7R5       | 7.5       |                  |            | 430       | 43        |              |            |
| 1R8       | 1.8       |         |            | 8R2       | 8.2       |                  |            | 470       | 47        |              |            |
| 1R9       | 1.9       |         |            | 9R1       | 9.1       | G, J<br>K, M     |            | 510       | 51        |              |            |
| 2R0       | 2.0       |         |            | 100       | 10        |                  |            | 560       | 56        |              |            |
| 2R1       | 2.1       |         |            | 110       | 11        |                  |            | 620       | 62        |              |            |
| 2R2       | 2.2       |         |            | 120       | 12        |                  |            | 680       | 68        |              |            |
| 2R4       | 2.4       |         |            | 130       | 13        |                  |            | 750       | 75        |              |            |
| 2R7       | 2.7       |         |            | 150       | 15        |                  |            | 820       | 82        |              |            |
| 3R0       | 3.0       |         |            | 160       | 16        |                  |            | 910       | 91        |              |            |
| 3R3       | 3.3       |         |            | 180       | 18        |                  |            | 101       | 100       |              |            |
| 3R6       | 3.6       |         |            | 200       | 20        |                  |            |           |           |              |            |

$$V_{RMS} = 0.707 \times WVDC$$

SPECIAL VALUES, TOLERANCES, HIGHER WVDC AND MATCHING AVAILABLE. PLEASE CONSULT FACTORY.

### ATC PART NUMBER CODE



| CAPACITANCE TOLERANCE |         |          |         |     |     |      |      |
|-----------------------|---------|----------|---------|-----|-----|------|------|
| Code                  | B       | C        | D       | G   | J   | K    | M    |
| Tol.                  | ±0.1 pF | ±0.25 pF | ±0.5 pF | ±2% | ±5% | ±10% | ±20% |

The above part number refers to a 800 R Series (case size R) 10 pF capacitor, J tolerance (±5%), 500 WVDC, with T termination (Tin Plated over Nickel Barrier, RoHS Compliant), laser marked, and tape and reel packaging.

\*\*Laser Marking is optional.

ATC accepts orders for our parts using designations **with** or **without** the "ATC" prefix. Both methods of defining the part number are equivalent, i.e., part numbers referenced with the "ATC" prefix are interchangeable to parts referenced without the "ATC" prefix. Customers are free to use either in specifying or procuring parts from American Technical Ceramics.

For additional information and catalogs contact your ATC representative or call direct at (+1-631) 622-4700.

Consult factory for additional performance data.

A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America  
sales@atceramics.com



ATC Europe  
sales@atceramics.com

ATC Asia  
sales@atceramics-asia.com


www.atceramics.com

# ATC 800 R Series NPO Ceramic Ultra-Low ESR Multilayer Capacitors


## ATC 800 R Capacitors: Mechanical Configurations

| ATC SERIES & CASE SIZE | ATC TERM. CODE | CASE SIZE & TYPE               | OUTLINES<br>W/T IS A TERMINATION SURFACE                                          | BODY DIMENSIONS<br>Inches (mm) |                            |                        | LEAD AND TERMINATION<br>DIMENSIONS AND MATERIALS |                                                                        |
|------------------------|----------------|--------------------------------|-----------------------------------------------------------------------------------|--------------------------------|----------------------------|------------------------|--------------------------------------------------|------------------------------------------------------------------------|
|                        |                |                                |                                                                                   | LENGTH (L)                     | WIDTH (W)                  | THICKNESS (T)          | OVERLAP (Y)                                      | MATERIALS                                                              |
| 800R                   | T              | R<br>Solderable Nickel Barrier |  | .070 ±.015<br>(1.78 ±0.38)     | .090 ±.010<br>(2.29 ±0.25) | .115<br>(2.92)<br>max. | .010<br>+.010 - .005<br>(0.25<br>+.025 - 0.13)   | <b>RoHS Compliant</b><br>Tin Plated over<br>Nickel Barrier Termination |
| 800R                   | W              | R<br>Solder Plate              |  | .070 ±.015<br>(1.78 ±0.38)     | .090 ±.010<br>(2.29 ±0.25) | .115<br>(2.92)<br>max. | .010<br>+.010 - .005<br>(0.25<br>+.025 - 0.13)   | Tin/Lead, Solder Plated over<br>Nickel Barrier Termination             |

## ATC 800 R Non-Magnetic Capacitors: Mechanical Configurations

| ATC SERIES & CASE SIZE | ATC TERM. CODE | CASE SIZE & TYPE                   | OUTLINES<br>W/T IS A TERMINATION SURFACE                                            | BODY DIMENSIONS<br>Inches (mm) |                            |                        | LEAD AND TERMINATION<br>DIMENSIONS AND MATERIALS |                                                                              |
|------------------------|----------------|------------------------------------|-------------------------------------------------------------------------------------|--------------------------------|----------------------------|------------------------|--------------------------------------------------|------------------------------------------------------------------------------|
|                        |                |                                    |                                                                                     | LENGTH (L)                     | WIDTH (W)                  | THICKNESS (T)          | OVERLAP (Y)                                      | MATERIALS                                                                    |
| 800R                   | TN             | R<br>Non-Mag<br>Solderable Barrier |  | .070 ±.015<br>(1.78 ±0.38)     | .090 ±.010<br>(2.29 ±0.25) | .115<br>(2.92)<br>max. | .010<br>+.010 - .005<br>(0.25<br>+.025 - 0.13)   | <b>RoHS Compliant</b><br>Tin Plated over<br>Non-Magnetic Barrier Termination |

## Suggested Mounting Pad Dimensions



Horizontal Electrode Orientation

Vertical Electrode Orientation

Case R

|                  | Pad Size     | A Min. | B Min. | C Min. | D Min. |
|------------------|--------------|--------|--------|--------|--------|
| Vertical Mount   | Normal       | .125   | .050   | .030   | .130   |
|                  | High Density | .115   | .030   | .030   | .090   |
| Horizontal Mount | Normal       | .110   | .050   | .030   | .130   |
|                  | High Density | .090   | .030   | .030   | .090   |

Dimensions are in inches.

A M E R I C A N T E C H N I C A L C E R A M I C S



ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com

ATC Asia  
sales@atceramics-asia.com

www.atceramics.com

# ATC 800 R Series NPO Ceramic Ultra-Low ESR Multilayer Capacitors




**A M E R I C A N   T E C H N I C A L   C E R A M I C S**

ATC North America  
sales@atceramics.com

ATC Europe  
saleseur@atceramics.com

ATC Asia  
sales@atceramics-asia.com

# ATC 800 R Performance Data



Sales of ATC products are subject to the terms and conditions contained in American Technical Ceramics Corp. Terms and Conditions of Sale (ATC document #001-992 Rev. B; 12/05). Copies of these terms and conditions will be provided upon request. They may also be viewed on ATC's website at [www.atceramics.com/productfinder/default.asp](http://www.atceramics.com/productfinder/default.asp). Click on the link for Terms and Conditions of Sale.

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product without prior notice.

© 2006 American Technical Ceramics Corp. All Rights Reserved.

ATC # 001-1029 Rev. K, 9/14

**A M E R I C A N   T E C H N I C A L   C E R A M I C S**

**ATC North America**  
sales@atceramics.com

**ATC Europe**  
saleseur@atceramics.com

**ATC Asia**  
sales@atceramics-asia.com

[www.atceramics.com](http://www.atceramics.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.