

SURFACE-MOUNT FUSES

Fast-Acting Chip Fuses

Fast-acting chip fuses help provide overcurrent protection for systems using DC power sources up to 63V_{DC}. The fuse's monolithic, multilayer design helps provide the highest hold current in the smallest footprint, reduce diffusion-related aging, improve product reliability and resilience, and enhance high-temperature performance in a wide range of circuit designs.

These RoHS-compliant surface-mount devices offer strong arc suppression characteristics and help facilitate the development of more reliable, high-performance consumer electronics such as laptops, multimedia devices, cell phones and other portable electronics.



BENEFITS

- Small size with high current ratings
- Temperature stability
- High reliability and resilience
- Strong arc suppression characteristics

FEATURES

- Lead-free and RoHS compliant
- Halogen free
(refers to: Br≤900ppm, Cl≤900ppm, Br+Cl≤1500ppm)
- Monolithic, multilayer design
- High-temperature performance
- -55°C to +125°C operating temperature range

APPLICATIONS

- Laptops
- Digital cameras
- Cell phones
- Printers
- DVD players
- Portable electronics
- Game systems
- LCD monitors
- Scanners

Surface Mount Fuses

Fast-Acting Chip Fuses

Table FF1 – Clear Time Characteristics

| % of Rated Current | Clear Time at 25°C |
|--------------------|--------------------|
| 100% | 4 hrs (min) |
| 250% | 5 s (max) |
| 400% | 0.05 s (max) |


Table FF2 – Typical Electrical Characteristics, Dimensions and Recommended Pad Layout

0402 (1005mm) Fast-Acting Chip Fuses

Shape and Dimensions
in (mm)



Recommended Pad Layout
in (mm)




0603 (1608mm) Fast-Acting Chip Fuses

Shape and Dimensions
in (mm)



Recommended Pad Layout
in (mm)




1206 (3216mm) Fast-Acting Chip Fuses

Shape and Dimensions
in (mm)



Recommended Pad Layout
in (mm)



| Part Number | Typical Electrical Characteristics | | | Max Interrupt Ratings | |
|----------------|------------------------------------|-----------------------|--|----------------------------|-------------|
| | Rated Current (A) | Nominal Cold DCR (Ω)* | Nominal I ² t (A ² sec) [†] | Voltage (V _{DC}) | Current (A) |
| 0402SFF100F/24 | 1.00 | 0.120 | 0.0170 | 24 | 35 |
| 0402SFF150F/24 | 1.50 | 0.056 | 0.0490 | 24 | 35 |
| 0402SFF200F/24 | 2.00 | 0.035 | 0.0700 | 24 | 35 |
| 0402SFF300F/24 | 3.00 | 0.021 | 0.1250 | 24 | 35 |
| 0402SFF400F/24 | 4.00 | 0.014 | 0.2250 | 24 | 35 |

| Part Number | Typical Electrical Characteristics | | | Max Interrupt Ratings | |
|----------------|------------------------------------|-----------------------|--|----------------------------|-------------|
| | Rated Current (A) | Nominal Cold DCR (Ω)* | Nominal I ² t (A ² sec) [†] | Voltage (V _{DC}) | Current (A) |
| 0603SFF050F/32 | 0.50 | 0.485 | 0.0029 | 63 | 35 |
| 0603SFF075F/32 | 0.75 | 0.254 | 0.0064 | 63 | 35 |
| 0603SFF100F/32 | 1.00 | 0.147 | 0.0160 | 63 | 35 |
| 0603SFF150F/32 | 1.50 | 0.059 | 0.0300 | 63 | 35 |
| 0603SFF200F/32 | 2.00 | 0.044 | 0.0600 | 32 | 35 |
| 0603SFF250F/32 | 2.50 | 0.032 | 0.1150 | 32 | 35 |
| 0603SFF300F/32 | 3.00 | 0.025 | 0.1900 | 32 | 35 |
| 0603SFF350F/32 | 3.50 | 0.024 | 0.2950 | 32 | 35 |
| 0603SFF400F/32 | 4.00 | 0.018 | 0.4000 | 32 | 35 |
| 0603SFF500F/32 | 5.00 | 0.013 | 0.7000 | 32 | 35 |
| 0603SFF600F/24 | 6.00 | 0.010 | 1.1250 | 24 | 35 |

| Part Number | Typical Electrical Characteristics | | | Max Interrupt Ratings | |
|----------------|------------------------------------|-----------------------|--|----------------------------|-------------|
| | Rated Current (A) | Nominal Cold DCR (Ω)* | Nominal I ² t (A ² sec) [†] | Voltage (V _{DC}) | Current (A) |
| 1206SFF050F/63 | 0.50 | 0.730 | 0.0021 | 63 | 50 |
| 1206SFF075F/63 | 0.75 | 0.513 | 0.0052 | 63 | 50 |
| 1206SFF100F/63 | 1.00 | 0.220 | 0.0120 | 63 | 50 |
| 1206SFF150F/63 | 1.50 | 0.120 | 0.0250 | 63 | 50 |
| 1206SFF175F/63 | 1.75 | 0.100 | 0.0450 | 63 | 50 |
| 1206SFF200F/63 | 2.00 | 0.050 | 0.0700 | 63 | 50 |
| 1206SFF250F/32 | 2.50 | 0.035 | 0.1400 | 32 | 50 |
| 1206SFF300F/32 | 3.00 | 0.031 | 0.2200 | 32 | 50 |
| 1206SFF400F/32 | 4.00 | 0.022 | 0.3800 | 32 | 45 |
| 1206SFF500F/32 | 5.00 | 0.015 | 0.6000 | 32 | 45 |
| 1206SFF600F/32 | 6.00 | 0.013 | 1.0000 | 32 | 50 |
| 1206SFF700F/32 | 7.00 | 0.011 | 1.7500 | 32 | 50 |
| 1206SFF800F/32 | 8.00 | 0.008 | 2.5000 | 32 | 50 |
| 1206SFF600F/24 | 6.00 | 0.013 | 1.0000 | 24 | 45 |
| 1206SFF700F/24 | 7.00 | 0.011 | 1.7500 | 24 | 45 |
| 1206SFF800F/24 | 8.00 | 0.008 | 2.5000 | 24 | 45 |

* Measured at ≤10% of rated current and 25°C ambient temperature.

† Melting I²t at 0.001 sec clear time.

Surface Mount Fuses

Fast-Acting Chip Fuses

Figures FF1-FF6 — Family Performance Curves

Figure FF1

0402SFF Average Time Current Curves





Figure FF2

0402SFF I²t vs. t Curves



Note: Curves are nominal.

Figure FF3

0603SFF Average Time Current Curves





Figure FF4

0603SFF I²t vs. t Curves



Note: Curves are nominal.

Surface Mount Fuses

Fast-Acting Chip Fuses

Figures FF1-FF6 — Family Performance Curves

(Cont'd)



Notice:

Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.