


Low Noise, Rail-to-Rail Input/Output Dual Operational Amplifier

■ GENERAL DESCRIPTION


The NJM2737 is a Rail-to-Rail Input/Output single supply dual operational amplifier featuring low voltage operation, low power and low noise. It is designed to offer a low voltage operating from 1.8V with a $5\text{nV}/\sqrt{\text{Hz}}$ low noise of the conventional low noise operational amplifiers such as the NJM4580 and NJM 5532.

The Combination of Rail-to-Rail Input/Output, low voltage operation and low noise makes the NJM2737 well-suited for single supply low voltage operation applications such as PC audio, portable audio and others. The NJM2737 is available in a wide variety packages 8-lead DIP, and 8-lead surface-mount packages of SOP (DMP), SSOP and MSOP (TVSP).

■ PACKAGE OUTLINE



**NJM2737D
(DIP8)**



**NJM2737M
(DMP8)**



**NJM2737V
(SSOP8)**




**NJM2737RB1
(MSOP8 (TVSP8))**

■ FEATURES

- Operating Voltage 1.8 to 6V
- Low Input Voltage Noise $5\text{nV}/\sqrt{\text{Hz}}$ typ.
- Gain Band Width product 3.1MHz typ. (at $V^+=5\text{V}$, $R_L=2\text{k}\Omega$)
- Slew Rate $0.7\text{V}/\mu\text{s}$ typ. (at $V^+=5\text{V}$, $R_L=2\text{k}\Omega$)
- Offset Voltage 5mV max
- Rail-to-Rail Input $V_{\text{ICM}}=0$ to 5V (at $V^+=5\text{V}$)
- Maximum Output Voltage1 $V_{\text{OH1}} \geq 4.9\text{V}$ / $V_{\text{OL1}} \leq 0.15\text{V}$ (at $V^+=5\text{V}$, $R_L=20\text{k}\Omega$)
- Maximum Output Voltage2 $V_{\text{OH2}} \geq 4.75\text{V}$ / $V_{\text{OL2}} \leq 0.25\text{V}$ (at $V^+=5\text{V}$, $R_L=2\text{k}\Omega$)
- Bipolar Technology
- Package Outline DIP8, DMP8, SSOP8, MSOP8 (TVSP8) MEET JEDEC MO-187-DA / THIN TYPE

■ PIN CONFIGURATION



PIN CONFIGURATION

- 1.OUTPUT1
- 2.-INPUT1
- 3.+INPUT1
- 4.GND(V⁻)
- 5.+INPUT2
- 6.-INPUT2
- 7.OUTPUT2
- 8.V⁺

NJM2737

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V ⁺	7	V
Differential Input Voltage	V _{ID}	±1	V
Input Common Mode Voltage Range	V _{ICM}	0 to 7	V
Power Dissipation	P _D	500(DIP8) 300(DMP8) 250(SSOP8) 320(MSOP8 (TVSP8))	mW
Operating Temperature Range	Topr	-40 to 85	°C
Storage Temperature Range	Tstg	-40 to 125	°C

(Note1) If the supply voltage (V⁺) is less than 7V, the input voltage must not over the V⁺ level through 7V is limit specified.

■ RECOMMENDED OPERATING CONDITION

(Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Supply Voltage	V ⁺	1.8 to 6	V

■ ELECTRICAL CHARACTERISTICS

● DC CHARACTERISTICS

(V⁺=5V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Operating Current	I _{CC}	No Signal	-	1200	1600	μA
Input Offset Voltage	V _{IO}		-	1	5	mV
Input Bias Current	I _B		-	200	800	nA
Input Offset Current	I _{IO}		-	5	100	nA
Voltage Gain	A _V	R _L =2kΩ	60	85	-	dB
Common Mode Rejection Ratio	CMR	CMR+: 2.5V ≤ V _{CM} ≤ 5V, CMR-: 0 ≤ V _{CM} ≤ 2.5V(Note2)	55	70	-	dB
Supply Voltage Rejection Ratio	SVR	V ⁺ /GND = ±2 to ±3V	70	85	-	dB
Maximum Output Voltage1	V _{OH1}	R _L =20kΩ	4.9	4.95	-	V
	V _{OL1}	R _L =20kΩ	-	0.1	0.15	
Maximum Output Voltage 2	V _{OH2}	R _L =2kΩ	4.75	4.85	-	V
	V _{OL2}	R _L =2kΩ	-	0.15	0.25	
Input Common Mode Voltage Range	V _{ICM}	CMR > 55dB	0	-	5	V

(Note2) CMR is represented by either CMR+ or CMR- which has lower value.

CMR+ is measured with 2.5V ≤ V_{CM} ≤ 5V and CMR- is measured with 0V ≤ V_{CM} ≤ 2.5V .

● AC CHARACTERISTICS

(V⁺=5V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Gain Bandwidth Product	GBW	R _L =2kΩ	-	3.1	-	MHz
Phase Margin	Φ _M	R _L =2kΩ	-	85	-	Deg
Equivalent Input Noise Voltage	V _{NI}	f=1kHz	-	5	-	nV/√Hz

• TRANSIENT CHARACTERISTICS

(V⁺=5V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Slew Rate	SR	R _L =2kΩ	-	0.7	-	V/μs

• DC CHARACTERISTICS

(V⁺=3V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Operating Current	I _{CC}	No Signal	-	1000	1500	μA
Input Offset Voltage	V _{IO}		-	1	5	mV
Input Bias Current	I _B		-	200	800	nA
Input Offset Current	I _{IO}		-	5	100	nA
Voltage Gain	A _V	R _L =2kΩ	60	85	-	dB
Common Mode Rejection Ratio	CMR	CMR+: 1.5V ≤ V _{CM} ≤ 3V, CMR-: 0 ≤ V _{CM} ≤ 1.5V(Note3)	48	63	-	dB
Supply Voltage Rejection Ratio	SVR	V ⁺ /GND = ±1.2 to ±2V	68	83	-	dB
Maximum Output Voltage 1	V _{OH1}	R _L =20kΩ	2.9	2.95	-	V
	V _{OL1}	R _L =20kΩ	-	0.1	0.15	
Maximum Output Voltage 2	V _{OH2}	R _L =2kΩ	2.75	2.85	-	V
	V _{OL2}	R _L =2kΩ	-	0.15	0.25	
Input Common Mode Voltage Range	V _{ICM}	CMR > 48dB	0	-	3	V

(Note3) CMR is represented by either CMR+ or CMR- which has lower value.

CMR+ is measured with 1.5V ≤ V_{CM} ≤ 3V and CMR- is measured with 0V ≤ V_{CM} ≤ 1.5V .

• AC CHARACTERISTICS

(V⁺=3V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Gain Bandwidth Product	GBW	R _L =2kΩ	-	2.6	-	MHz
Phase Margin	Φ _M	R _L =2kΩ	-	85	-	Deg
Equivalent Input Noise Voltage	V _{NI}	f=1kHz	-	5	-	nV/√Hz

• TRANSIENT CHARACTERISTICS

(V⁺=3V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Slew Rate	SR	R _L =2kΩ	-	0.6	-	V/μs

NJM2737

• DC CHARACTERISTICS

(V⁺=1.8V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Operating Current	I _{CC}	No Signal	-	1000	1500	μA
Input Offset Voltage	V _{IO}		-	1	5	mV
Input Bias Current	I _B		-	200	800	nA
Input Offset Current	I _{IO}		-	5	100	nA
Voltage Gain	A _V	R _L =2kΩ	60	85	-	dB
Common Mode Rejection Ratio	CMR	CMR+: 0.9V ≤ V _{CM} ≤ 1.8V, CMR-: 0 ≤ V _{CM} ≤ 0.9V(Note4)	40	55	-	dB
Supply Voltage Rejection Ratio	SVR	V ⁺ /GND = ±0.9 to ±1.2V	65	80	-	dB
Maximum Output Voltage1	V _{OH1}	R _L =20kΩ	1.7	1.75	-	V
	V _{OL1}	R _L =20kΩ	-	0.1	0.15	
Maximum Output Voltage 2	V _{OH2}	R _L =2kΩ	1.6	1.65	-	V
	V _{OL2}	R _L =2kΩ	-	0.15	0.25	
Input Common Mode Voltage Range	V _{ICM}	CMR > 40dB	0	-	1.8	V

(Note4) CMR is represented by either CMR+ or CMR- which has lower value.

CMR+ is measured with 0.9V ≤ V_{CM} ≤ 1.8V and CMR- is measured with 0V ≤ V_{CM} ≤ 0.9V .

• AC CHARACTERISTICS

(V⁺=1.8V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Gain Bandwidth Product	GBW	R _L =2kΩ	-	2.3	-	MHz
Phase Margin	Φ _M	R _L =2kΩ	-	85	-	Deg
Equivalent Input Noise Voltage	V _{NI}	f=1kHz	-	5	-	nV/√Hz

• TRANSIENT CHARACTERISTICS

(V⁺=1.8V, Ta=25°C)


PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Slew Rate	SR	R _L =2kΩ	-	0.5	-	V/μs

■ TERMINAL CHARACTERISTICS


No.	Symbol	Equivalent Circuit	Typ.DC Voltage(V)	Function
3,5	+INPUT			non-inverting input
2,6	-INPUT			inverting input
1,7	VOUT			output

■ TYPICAL CHARACTERISTICS


Operating Current vs. Operating Voltage




Operating Current vs. Temperature




Input Offset Voltage vs. Temperature




Input Offset Voltage vs. Common Mode Input Voltage



Input Offset Current vs. Temperature




Input Bias Current vs. Temperature




Common Mode Rejection Ratio vs. Temperature

$V_{IC}=V^+, 0, V^-$




Supply Voltage Rejection Ratio vs. Temperature




Voltage Gain vs. Temperature

$R_L=2k\Omega$




Maximum Output Voltage vs. Load Resistance

$V^+/V^- = \pm 2.5V, OPEN LOOP$




Maximum Output Voltage vs. Temperature

$V^+/V^- = \pm 2.5V, G_v=OPEN$




Maximum Output Voltage vs. Supply Voltage


OPEN LOOP, $R_L=2k\Omega, T_a=25^\circ C$



Maximum Output Voltage vs. Output Current
 $V^+ / V^- = \pm 0.9V$, OPEN LOOP




Maximum Output Voltage vs. Output Current
 $V^+ / V^- = \pm 2.5V$, OPEN LOOP




Voltage Gain · Phase vs. Frequency

$V^+ / V^- = \pm 0.9V$, $G_V = 40dB$
 $R_F = 20\Omega$, $R_G = 2k\Omega$, $R_L = \infty$, $C_L = 0pF$




Voltage Gain · Phase vs. Frequency

$V^+ / V^- = \pm 1.5V$, $G_V = 40dB$
 $R_F = 20\Omega$, $R_G = 2k\Omega$, $R_L = \infty$, $C_L = 0pF$




Voltage Gain · Phase vs. Frequency

$V^+ / V^- = \pm 2.5V$, $G_V = 40dB$
 $R_F = 20\Omega$, $R_G = 2k\Omega$, $R_L = \infty$, $C_L = 0pF$




Peak Gain of Voltage Follower

$V^+ / V^- = \pm 2.5V$, $G_V = 0dB$
 $R_S = 50\Omega$, $R_L = 2k\Omega$, $T_a = +25^\circ C$




Input Voltage Noise Density vs. Frequency

$G_V=40\text{dB}, R_S=50\Omega, R_G=20\Omega,$
 $R_F=2\text{k}\Omega, C_L=0\text{pF}, T_a=25^\circ\text{C}$




TOTAL HARMONIC DISTORTION + NOISE vs OUTPUT AMPLITUDE

(Voltage Follower)
 $V^+/V^-=\pm 2.5\text{V}, G_V=20\text{dB}$
 $R_L=2\text{k}\Omega, T_a=25^\circ\text{C}$




TOTAL HARMONIC DISTORTION + NOISE vs OUTPUT AMPLITUDE


($\times 10$ Amplifier)
 $V^+/V^-=\pm 2.5\text{V}, G_V=20\text{dB}$
 $R_L=2\text{k}\Omega, T_a=25^\circ\text{C}$




Positive Transient Response
 $V^+ / V^- = \pm 0.9V, GV = 0dB, f = 10kHz, V_{IN} = 0.5V_{PP}$
 $R_S = 50\Omega, R_L = 2k\Omega, C_L = 0pF, T_a = +25^\circ C$




Negative Transient Response
 $V^+ / V^- = \pm 0.9V, GV = 0dB, f = 10kHz, V_{IN} = 0.5V_{PP}$
 $R_S = 50\Omega, R_L = 2k\Omega, C_L = 0pF, T_a = +25^\circ C$



Positive Transient Response
 $V^+ / V^- = \pm 1.5V, GV = 0dB, f = 10kHz, V_{IN} = 1V_{PP}$
 $R_S = 50\Omega, R_L = 2k\Omega, C_L = 0pF, T_a = +25^\circ C$



Negative Transient Response
 $V^+ / V^- = \pm 1.5V, GV = 0dB, f = 10kHz, V_{IN} = 1V_{PP}$
 $R_S = 50\Omega, R_L = 2k\Omega, C_L = 0pF, T_a = +25^\circ C$



[CAUTION]
 The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NJR:](#)

[NJM2737V-TE1](#) [NJM2737D](#) [NJM2737M](#) [NJM2737RB1-TE1](#) [NJM2737M-TE1](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.