



Main

| | |
|---------------------------|------------------|
| Range of product | 9007 |
| Series name | Miniature potted |
| Product or component type | Limit switch |
| Device short name | 9007MS/ML |
| Sensor design | Miniature |
| Body type | Fixed |
| Head type | Plunger head |
| Material | Metal |
| Body material | Cast zinc |
| Number of poles | 1 |

Complementary

| | |
|--|---|
| Fixing mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Spring return plunger stainless steel (-) |
| Type of approach | Vertical approach 1 direction |
| Switch actuation | On end |
| Contacts type and composition | NC-NO |
| Switch function | SPDT |
| Contact form | Form C |
| Contacts material | Gold flashed contacts |
| Contact operation | Snap action |
| Positive opening | Without |
| Electrical connection | Pre-wired cable bottom |
| Type of cable | SJTO cable (AWG 18), 3 ft, yellow |
| Terminals description ISO n°1 | (green-yellow)gnd (black)com (white)NO (red)NC |
| Wire insulation material | PVC |
| Maximum force for tripping | 80 ozf |
| [Ie] rated operational current | 100 mAat 125 V AC 30 mAat 28 V DC |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 V degree of pollution 3 conforming to UL 508 300 V degree of pollution 3 conforming to CSA C22.2 No 14 |
| Electrical durability | 100000 cycles |
| Mechanical durability | 10000000 cycles |
| Marking | CE CSA UL |
| Sale per indivisible quantity | 1 |
| Height | 1.75 in |
| Width | 1.56 in |
| Depth | 0.62 in |
| Product weight | 1.2 lb(US) |

Environment

| | |
|----------------------|--|
| shock resistance | 35 gn (duration = 9 ms) conforming to IEC 60068-2-27 |
| vibration resistance | 10 gn (f = 75...1200 Hz) conforming to IEC 60068-2-6 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------------------------|---|
| NEMA degree of protection | NEMA 1 conforming to Nema type 250 NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 6 conforming to Nema type 250 NEMA 6P conforming to Nema type 250 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| ambient air temperature for operation | -40...220 °F |
| ambient air temperature for storage | -40...220 °F |
| protective treatment | Epoxy powder coat |
| product certifications | CE CSA UL |
| standards | LR 25490 Class 32 11 03 E78403 |

Offer Sustainability

| | |
|--|--|
| Not Green Premium product | Not Green Premium product |
| Will not be Compliant | Will not be Compliant |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.