

AA SERIES PHOTOCONTROL

THERMAL, BUTTON STYLE, WIRE - IN DESIGN

KEY FEATURES

- 3/4in long threaded nipple
- 30 - 45 second time delay
- UL and CSA Listed
- Durable polycarbonate housing
- 1800 and 1200 watt load rating
- Fail mode is ON

TE Connectivity's (TE) AA Series offers a unique button style design for internal post fixtures or mounting applications. Common uses include decorative light fixtures, post lanterns, wall mount applications, and other commercial and residential uses. TE's innovative design with the wire leads exiting from the rear allow the control to be placed in tight locations while positioning the wiring for easy access.

The AA Series photocontrol is constructed of a high impact UV stabilized polycarbonate housing for superior quality. The 105W and 1068W controls include a brushed aluminum wall plate for installation in standard outlet boxes.


The 105M and 1068M are equipped with a 180 Joule Metal Oxide Varistor (MOV) and are designed to protect luminaries where transient voltage surges are a frequent and recurring problem.

The 105HA is a high ambient temperature photocontrol, designed specifically to last longer in today's hotter running HID luminaries. This unit incorporates insulation and heat sink to absorb the heat generated by the lamp and other components, significantly adding to the control's useful life.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.



TE's photocontrols can be used to safely control luminaries with incandescent, HID, LED, or compact fluorescent lamps.



Dimensions shown in inches (mm)

| PRODUCT SELECTION INFORMATION | | | | | | | | |
|-------------------------------|---------------------|-------------|---------------|------------------------------|--------------------------|---------------------------|--------------|--------------|
| Description | Product Information | Rated Volts | Range (Volts) | Load Rating Tungsten (Watts) | Load Rating Ballast (VA) | Surge Protection (Joules) | Turn ON (Fc) | OFF/ON Ratio |
| AA-105 | | 120 | 105 - 130 | 1800 | 1100 | | 1.5 | 4 : 1 |
| AA-105W | w/Wall Plate | 120 | 105 - 130 | 1800 | 1100 | | 1.5 | 4 : 1 |
| AA-1068 | | 208/240/277 | 185 - 305 | 1200 | 1100 | | 1.5 | 4 : 1 |
| AA-1068W | w/Wall Plate | 208/240/277 | 185 - 305 | 1200 | 1100 | | 1.5 | 4 : 1 |
| AA-305 | | 120 | 105 - 130 | 300 | 840 | | 1.5 | 4 : 1 |
| AA-105M | 15" Leads | 120 | 105 - 130 | 1800 | 1100 | 180 | 1.5 | 4 : 1 |
| AA-1068M | 15" Leads | 208/240/277 | 185 - 305 | 1200 | 1100 | 180 | 1.5 | 4 : 1 |
| AA-105HA | High Ambient | 120 | 105 - 130 | 1800 | 1100 | | 1.5 | 4 : 1 |

Note: 6" lead wires unless otherwise noted

| SPECIFICATION | |
|---------------|--|
| Physical | Dimensions: approx. 2.05" [51.94mm] dia. x 1.62" [41.21mm] high (Not including wiring) |
| | Enclosure: designed to meet ANSI C136.24, UL 773A |
| | Power consumption: less than 0.9 watts at 120 VAC |
| Temperature | Minus 40°C to plus 65°C at 96% RH |
| Control | Thermal State Switch Type |
| Light Sensor | Cadmium Sulfide Cell |

| TECHNICAL INFORMATION | |
|-----------------------|--|
| Switch | SPST thermal bi-metallic, exceeds 7,500 ON/OFF operations |
| Fail Mode | ON (contacts normally closed) |
| Housing | Polycarbonate with UV stabilized window |
| Lead Wires | 6", #18 AWG, rated 105°C (AA controls) 15", #18 AWG, rated 105°C (AA-M controls) 6", #18 AWG, rated 150°C (AA-HA controls) |
| Nipple | 3/8" pipe |
| Nut | 3/8" pipe, thermoplastic |
| Light Sensor | 1/2" Cadmium sulfide (Cds) cell |



te.com/energy

©2008, 2012, 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. 7-1773453-6 E328 10/2014

TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA: +1 800 327 6996
 France: +33 380 583 200
 UK: +44 0870 870 7500
 Germany: +49 896 089 903
 Spain: +34 916 630 400
 Benelux: +32 16 351 731
 Canada: +1 (905) 475-6222
 Mexico: +52 (0) 55-1106-0800
 Latin/S. America: +54 (0) 11-4733-2200
 China: +86 (0) 400-820-6015



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.