

3M™ BOARDMOUNT SOCKET, 1502 SERIES
 2.00MM X 2.00MM STRAIGHT AND SURFACE MOUNT, PLATED THROUGH HOLE



STRAIGHT
VERSION



SURFACE MOUNT
VERSION

2 PHYSICAL :

INSULATOR :
 MATERIAL : HIGH TEMP THERMOPLASTIC
 CONTACT :
 MATERIAL : COPPER ALLOY
 PLATING :
 UNDER PLATING : 1.27-3.8µm (50-150µ") NICKEL-OVERALL
 WIPING AREA : .76µm (30µ") GOLD
 SOLDER TAILS : 5.1µm (200µ") MATTE TIN (RIA E1 & C1 APPLY)
 MARKING : ORIENTATION DELTA AND 3M LOGO (EXCEPT SURFACE MOUNT)

2 ELECTRICAL :

CURRENT RATING : 1A
 VOLTAGE RATING : 150V_{AC} PER EIA-364-20
 INSULATION RESISTANCE : >1 X 10⁹ OHM AT 250V_{DC}
 WITHSTANDING VOLTAGE : 500V_{DC} AT SEA LEVEL

2 ENVIRONMENTAL :

TEMPERATURE RATING : -55° C TO 105° C
 PROCESS RATING : MAX. 260° C (PER J-STD-020C)
 MOISTURE SENSITIVITY LEVEL : 1 (PER J-STD-020C)

- NOTES
1. REGULATORY INFORMATION: ROHS COMPLIANT. SEE THE REGULATORY INFORMATION APPENDIX (RIA) IN THE "ROHS COMPLIANCE" SECTION OF WWW.3MCONNECTORS.COM FOR COMPLIANCE INFORMATION.
 2. IN THE EVENT OF CONFLICT BETWEEN THIS DATA AND THAT CONTAINED IN THE PRODUCT SPECIFICATION, THE PRODUCT SPECIFICATION TAKES PRECEDENT.
 3. TAPE & REEL INCLUDE VACUUM PICK-UP CAP FOR PICK 'N PLACE HANDLING EQUIPMENT.
 4. PARTS IN TRAY PACKAGING ARE SUPPLIED WITHOUT VACUUM CAP.
 5. POSITIONS PER ROW, SUBTRACT 1, MULTIPLY BY 2MM SPACING.
 6. OPTIONAL LOCATOR POSTS: POSITIONS PER ROW, MULTIPLY BY 2MM SPACING, THEN SUBTRACT 4MM. POSTS ARE ONLY AVAILABLE FOR POSITIONS 08 AND GREATER.

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
 INTERCONNECT SOLUTIONS
<http://www.3mconnectors.com>

3M IS A TRADEMARK OF 3M COMPANY.
 FOR TECHNICAL, SALES OR ORDERING
 INFORMATION CALL 800-225-5373

UL
 UL FILE NO: E68080

DIMENSIONS: MM (INCH)
 (INCH) FOR REF. ONLY

| | | | | | | |
|---------------------------------|--|---|---|--|-------------|------------------------|
| DESIGN REFERENCE | NEXT ASSEMBLY | REV | ECO | ISSUE DATE AND DESCRIPTION | DRFT | CHKD |
| 63282 | | | | SEP 03, 2015 REDRAWN & REMOVED RIGHT ANGLE | JNC | ARM |
| APPROVED | DATE | DATE | DATE | DATE | DATE | DATE |
| CASTIGLIONE | SEP 03, 2015 | MFG | | | | |
| CHKD | DATE | APPRV | DATE | DATE | DATE | DATE |
| | | G. MATHEWS | SEP 03, 2015 | | | |
| DIVISION | DIVISION CODE | © 3M COPYRIGHT 2017 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved. | | | | |
| DO NOT SCALE DRAWING | SCALE 6/1 | TOLERANCES EXCEPT AS NOTED | 3M 3M Center St. Paul, MN 55144 | | | |
| THIRD ANGLE PROJECTION | INCHES: .0 ± .1 .00 ± .01 .000 ± .005 .0000 ± .0002 | MILLIMETERS: 0 ± .2 .0 ± .13 .000 ± .005 | TITLE BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20 | | | |
| INTERPRET PER ASME Y14.5 - 2009 | MAX SURFACE ROUGHNESS | MARKED ONLY | CAGE NUMBER | SIZE | DRAWING NO. | REV. |
| | | | D | 78-5100-0519-8 | K | |
| | | | MODEL | 1502 | DET | ISTS YES NO SHT 1 OF 4 |

78-5100-0519-8
 DRAWING NUMBER
 K
 REVISION
 12/7/2017
 Standard Time
 12/7/2017
 UTC
 Offset

3M™ BOARDMOUNT SOCKET, 1502 SERIES
 2.00MM X 2.00MM STRAIGHT AND SURFACE MOUNT, PLATED THROUGH HOLE



| CONTACT QTY. | DIM. "A" |
|--------------|-----------------|
| 04 | 3.96 [.156] |
| 06 | 5.87 [.231] |
| 08 | 7.87 [.310] |
| 10 | 9.88 [.389] |
| 12 | 11.86 [.467] |
| 14 | 13.87 [.546] |
| 16 | 15.88 [.625] |
| 18 | 17.88 [.704] |
| 20 | 19.86 [.782] |
| 22 | 21.87 [.861] |
| 24 | 23.88 [.940] |
| 26 | 25.88 [1.019] |
| 28 | 27.86 [1.097] |
| 30 | 29.87 [1.176] |
| 32 | 31.88 [1.255] |
| 34 | 33.88 [1.334] |
| 36 | 35.86 [1.412] |
| 38 | 37.87 [1.491] |
| 40 | 39.88 [1.570] |
| 42 | 41.88 [1.649] |
| 44 | 43.87 [1.727] |
| 46 | 45.87 [1.806] |
| 48 | 47.88 [1.885] |
| 50 | 49.89 [1.964] |
| 52 | 51.87 [2.042] |
| 54 | 53.87 [2.121] |
| 56 | 55.88 [2.200] |
| 58 | 57.86 [2.278] |
| 60 | 59.87 [2.357] |

ORDERING INFORMATION
 STRAIGHT
 1502XX-600X-RB

CONTACT QTY.:
 SEE TABLE 1

SOLDER TAIL LENGTH:
 DIMENSION "B"
 1 = 1.4MM (SPECIAL ORDER)
 2 = 2.54MM (STANDARD)

| | | | | | | |
|---|---------------|---|--------------|---|------|------|
| DESIGN REFERENCE | NEXT ASSEMBLY | REV | ECO | ISSUE DATE AND DESCRIPTION | DRFT | CHKD |
| | | | | SEP 03, 2015 REDRAWN & REMOVED RIGHT ANGLE | JNC | ARM |
| APPROVED | DATE | APPROVED | DATE | © 3M COPYRIGHT 2017 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved. | | |
| APPROVED | SEP 03, 2015 | APPROVED | SEP 03, 2015 | | | |
| DO NOT SCALE DRAWING SCALE 6/1 TOLERANCES EXCEPT AS NOTED INCHES: .00 ±.01, .000 ±.005, .0000 ±.0002 MILLIMETERS: 0 ±.2, .00 ±.13, .000 ±.005 | | TITLE BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20 | | CAGE NUMBER D78-5100-0519-8 MODEL 1502 | | |
| INTERPRET PER ASME Y14.5 - 2009 MAX SURFACE ROUGHNESS SURFACES MARKED ONLY | | DIVISION CODE EMSD | | REV. NUMBER K | | |
| | | | | SHEET 2 OF 4 | | |

78-5100-0519-8
 DRAWING NUMBER
 K
 REVISION
 Standard Time 12/7/2017 UTC Offset
 Imaged: K.3 Central

3M™ BOARDMOUNT SOCKET, 1502 SERIES
 2.00MM X 2.00MM STRAIGHT AND SURFACE MOUNT, PLATED THROUGH HOLE



RECOMMENDED PAD PATTERN
 (AS VIEWED FROM CONNECTOR SIDE)

| CONTACT QTY. | DIM. "A" | TAPE WIDTH | ORDER CODE |
|--------------|-----------------|------------|------------|
| 04 | 3.96 [.156] | N/A | N/A |
| 06 | 5.87 [.231] | N/A | N/A |
| 08 | 7.87 [.310] | 24 MM | WB |
| 10 | 9.88 [.389] | 24 MM | WB |
| 12 | 11.86 [.467] | 24 MM | WB |
| 14 | 13.87 [.546] | 24 MM | WB |
| 16 | 15.88 [.625] | 24 MM | WB |
| 18 | 17.88 [.704] | 44 MM | WD |
| 20 | 19.86 [.782] | 44 MM | WD |
| 22 | 21.87 [.861] | 44 MM | WD |
| 24 | 23.88 [.940] | 44 MM | WD |
| 26 | 25.88 [1.019] | 44 MM | WD |
| 28 | 27.86 [1.097] | 44 MM | WD |
| 30 | 29.87 [1.176] | 44 MM | WD |
| 32 | 31.88 [1.255] | 56 MM | WE |
| 34 | 33.88 [1.334] | 56 MM | WE |
| 36 | 35.86 [1.412] | 56 MM | WE |
| 38 | 37.87 [1.491] | 56 MM | WE |
| 40 | 39.88 [1.570] | 56 MM | WE |
| 42 | 41.88 [1.649] | 56 MM | WE |
| 44 | 43.87 [1.727] | 72 MM | WF |
| 46 | 45.87 [1.806] | 72 MM | WF |
| 48 | 47.88 [1.885] | 72 MM | WF |
| 50 | 49.89 [1.964] | 72 MM | WF |
| 52 | 51.87 [2.042] | 72 MM | WF |
| 54 | 53.87 [2.121] | 72 MM | WF |
| 56 | 55.88 [2.200] | 72 MM | WF |
| 58 | 57.86 [2.278] | 88 MM | WG |
| 60 | 59.87 [2.357] | 88 MM | WG |

ORDERING INFORMATION
 SURFACE MOUNT
 1502XX-20X0-RB-XX

CONTACT QTY.:
 SEE TABLE 1

BOARD LOCATION POST:
 0 = NONE (STANDARD)
 2 = WITH BOARD LOCATION POSTS
 (SPECIAL ORDER)

PACKAGING STYLE:
 BLANK = TRAY PACKAGING
 WX = TAPE & REEL PACKAGING
 (SEE TABLE 1 FOR ORDERING CODE)

| | | | | | | |
|------------------------|---------------------------------|----------------------------|-----|---|------|-------------|
| DESIGN REFERENCE | NEXT ASSEMBLY | REV | ECO | ISSUE DATE AND DESCRIPTION | DRFT | CHKD |
| | | | | SEP 03, 2015 | | |
| DIVISION | | DIVISION CODE | | DATE | | |
| EMSD | | EMSD | | SEP 03, 2015 | | |
| DO NOT SCALE DRAWING | SCALE 6/1 | TOLERANCES EXCEPT AS NOTED | | © 3M COPYRIGHT 2017 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved. | | |
| THIRD ANGLE PROJECTION | INTERPRET PER ASME Y14.5 - 2009 | MILLIMETERS | | TITLE | | |
| | | 0 ±.2 | | BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20 | | |
| MAX SURFACE ROUGHNESS | MARKED ONLY | .00 ±.13 | | CAGE NUMBER | SIZE | DRAWING NO. |
| | | .000 ±.005 | | D78-5100-0519-8 | | REV. K |
| MODEL 1502 | | | | SHT 3 OF 4 | | |

78-5100-0519-8
 K
 REV. 1
 DATE SEP 03, 2015
 APPR. G. MATHEWS
 DATE SEP 03, 2015
 JNC ARM
 REDRAWN & REMOVED RIGHT ANGLE
 3M Center St. Paul, MN 55144
 © 3M COPYRIGHT 2017
 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.
 TITLED BOARDMOUNT SOCKET, 2MM X 2MM, STRAIGHT & SMT, PAC 20
 CAGE NUMBER D78-5100-0519-8
 SIZE
 DRAWING NO.
 REV. K
 SHT 3 OF 4



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.