




A Dimensions: [mm]












Scale - 8:1

Optical Properties:


Properties	Value
Chip Technology	InGaN
Emitting Color	Blue
Lens Type	Dome Lens Waterclear

B Recommended land pattern: [mm]



Scale - 8:1

C Schematic:





D Absolute Maximum Ratings (Ambient Temperature 25°C):

Properties	Test condi- tions		Value	Unit
Power dissipation		P _{Diss}	2.66	W
Peak Forward Current	duty/10 @1kHz	I _{F Peak}	1000	mA
Continuous Forward Current		ΙF	1000	mA
Reverse Voltage		V _{Rev}	5	V
ESD Threshold/ Human Body Modell		V_{ESD}	8000	V
Absolute thermal resistance junction to solder point		R _{0JS}	8	K/ W
Junction temperature		Tj	150	°C

E General information:

- •Operating temperature: -40°C to +125°C
- •Storage temperature (on tape & reel): -40°C to +125°C; 60% RH max.

				-1-	100
)-	
				Würth Elektronik eiSos Gmbl-	1 & Co. KG
				EMC & Inductive Solutions Max-Eyth-Str. 1	
				74638 Waldenburg	
1.1	2014-12-01	SSt	ZAn	Germany Tel. +49 (0) 79 42 945 - 0	
1 Ո	2014-10-28	SSt.	HOe	www.we-online.com	

CHECKED

eiSos@we-online.com

WL-SMDC Ceramic mono-color Highpower LED waterclear

Order.- No.

150353BS74500



SIZE A4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment only. This product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, strip control), transportation (automotive control, train control, strip control), transportation (automotive control, train control, strip control), transportation (automotive control, train control, trai the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

DATE




D Electrical & Optical Properties:

Properties	Test conditions			Value		Unit
Troportion	Tool contained		min.	typ.	max.	J
Peak Wavelength	350 mA	λ _{Peak}		455		nm
Dominant wavelength	350 mA	λ _{Dom}		460		nm
Luminous Flux	350 mA	Φ _V	20	25		lm
Forward Voltage	350 mA	V _F		3.2	3.8	V
Spectral Bandwidth	350 mA	Δλ		20		nm
Viewing Angle	350 mA	2 θ _{50%}		125		0






F1 Viewing Angle:




F2 Spectral:




				Projection		DESCRIPTION					
						WL-SMDC Ceramic mono-color High-					
				Würth Elektronik eiSos Gmbl- EMC & Inductive Solutions	H & Co. KG	power LED waterclear					
				Max-Eyth-Str. 1 74638 Waldenburg		Order No.	SIZE				
1.1	2014-12-01	SSt	ZAn	Germany Tel. +49 (0) 79 42 945 - 0		Rohs&Reach	OIZL				
1.0	2014-10-28	SSt	H0e	www.we-online.com eiSos@we-online.com		150353BS74500	A4				
REV	DATE	BY	CHECKED	CIOO3@WC OHIIIIC.COM		Size: 3535					



F3 Forward Current vs. Forward Voltage:




F4 Luminous Intensity vs. Forward Current:




				Projection ————————————————————————————————————		DESCRIPTION WL-SMDC Cerami	c mono-color High-	•			
				Würth Elektronik eiSos Gmbl EMC & Inductive Solutions Max-Eyth-Str. 1	H & Co. KG	power LED waterclear					
				74638 Waldenburg		Order No.	COMPLIANT	SIZF			
1.1	2014-12-01	SSt	ZAn	Germany Tel. +49 (0) 79 42 945 - 0		4500500074500	ROHS&REACH HALOGENFREE	OIZE			
1.0	2014-10-28	SSt	H0e	www.we-online.com eiSos@we-online.com		150353BS74500	2 TIMES GENTINE	A4			
REV	DATE	BY	CHECKED	- GIOGOSTIO OTIMICIONI		Size: 3535					



F5 Junction temperature vs. Dominant Wavelength:



F6 Junction temperature vs. Luminous Intensity:



				Projection -		DESCRIPTION WL-SMDC Cerami	c mono-color High-	•		
				Würth Elektronik eiSos Gmbł EMC & Inductive Solutions Max-Eyth-Str. 1	H & Co. KG	power LED waterclear				
				74638 Waldenburg		Order No.	COMPLIANT	SIZE		
1.1	2014-12-01	SSt	ZAn	Germany Tel. +49 (0) 79 42 945 - 0		4500500074500	ROHS&REACH HALOGENFREE	OIZE		
1.0	2014-10-28	SSt	H0e	www.we-online.com eiSos@we-online.com		150353BS74500	2	A4		
REV	DATE	BY	CHECKED	0.000@W0 OHIIIO.OOHI		Size: 3535				

COMPLIANT

RoHS&REACh


HALOGENFREE

SIZE

A4





F7 Derating Curve:






G Packaging Specification - Tape and Reel [mm]:







		Α0	В0	w	P1	Ţ	T1	Т2	D0	E1	E2	F	P0	P2	Tape	Packaging Unit
	tolerance	typ.	typ.	+0,3 -0,1	± 0,1	± 0,1	max.	typ.	+0,1 -0,0	± 0,1	min.	± 0,05	± 0,1	± 0,05		
i	Ceramic 3535	3,80	3,80	12,00	8,00	0,25	0,10	2,20	1,50	1,75	10,25	5,50	4,00	2,00	Polystyrene	1000




Packaging is referred to the international standard IEC 60286 -3:2007







		Α	В	С	D	N	W1	W2	W3	W3
tolerance		± 2,0	min.	± 0,8	min.	min.	+ 1,5	max.	min.	max.
Tape width	12 mm	178,00	1,50	13,00	20,20	50,00	12,40	18,40	11,90	15,40





Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com

eiSos@we-online.com

Projection

DESCRIPTION

WL-SMDC Ceramic mono-color Highpower LED waterclear

Order.- No.

Size: 3535

150353BS74500



SIZE A4


This electronic component has been designed and developed for usage in general electronic equipment only. This product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.

Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, ship control, transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

H Soldering Specifications:



H1: Classification Reflow Profile for SMT components:



H2: Classification Reflow Profile:

Profile Feature	Pb-Free Assembly	
Preheat - Temperature Min (T _{smin}) - Temperature Max (T _{smax}) - Time (t _s) from (T _{smin} to T _{smax})	150°C 200°C 120 seconds max.	
Ramp-up rate (T _L to T _P)	3°C/ second max.	
Liquidous temperature (T_L) Time (t_L) maintained above T_L	217°C 60 seconds max.	
Peak package body temperature (Tp)	250°C max.	
Time within 5°C of actual peak temperature (t _p)	10 seconds max.	
Ramp-down rate (T _P to T _L)	6°C/ second max.	
Time 25°C to peak temperature	220 seconds max.	
Applied cycles	2 cycles max.	

				Projection		DESCRIPTION					
				——————————————————————————————————————		WL-SMDC Ceramic mono-color High	1-				
				Würth Elektronik eiSos Gmbł EMC & Inductive Solutions	H & Co. KG	power LED waterclear					
				Max-Eyth-Str. 1 74638 Waldenburg		Order No.	SIZE				
1.1	2014-12-01	SSt	ZAn	Germany Tel. +49 (0) 79 42 945 - 0		ROHS&REACH HALOGENEREE	SIZE				
1.0	2014-10-28	SSt	H0e	www.we-online.com eiSos@we-online.com		150353BS74500	A4				
REV	DATE	BY	CHECKED	CIOOSSWC OHIIIIC.COM		Size: 3535					

SIZE

A4

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WL-SMDC of Würth Elektronik eiSos GmbH & Co. KG:

General:

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the component surface, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the LED body, pins or termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the LED body, pins or termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Washing varnish agent that is used during the production to clean the customer application might damage or change the characteristics of the LED body, pins or termination. The washing varnish agent could have a negative effect on the long term function of the product.

Direct mechanical impact to the product shall be prevented as the material of the LED body, pins or termination could flake or in the worst case it could break.

The standard deliveries include values in the range and limitation as defined in the Electrical & Optical Properties specified in the datasheet. On each reel, only one bin is sorted and taped. The bin is defined on intensity, chromaticity coordinate or wavelength and forward voltage. In order to ensure highest availability, the reel binning of standard deliveries can vary. A single bin cannot be ordered. Please contact us in advance, if you need a particular bin sorting before placing your order to clarify the lead time, MOQ and pricing.



Product specific:

Follow all instructions mentioned in the data sheet, especially:

- The soldering profile has to be complied with according to the technical reflow/ or wave soldering specification, otherwise this will void the
 warranty.
- •All products shall be used before the end of the period of 12 months based on the product date code, if not a 100% solderability can't be ensured.
- Violation of the technical product specifications such as exceeding the absolute maximum ratings will void the warranty.
- •It is also recommended to return the LEDs to the original moisture proof bag and reseal the moisture proof bag again.
- Certain LED surfaces consist of soft material. Pressure on the top surface has to be handeled carefully to prevent negative influence to the function and reliability of the LEDs.
- •ESD prevention methods need to be applicated for manual handling and processing by machinery.
- Resistors for protection are obligatory.
- •Luminaires in operation could harm human vision or skin on a photo-biological level, therefore direct light impact has to be avoided. All products are additionally certified as risk groups 0 to 2 according to DIN EN 62471:2008



COMPLIANT

RoHS&REACh

HALOGENFREE

SIZE

Α4

J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific. in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications.

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further gueries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.



6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Flektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов:
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001:
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина,

дом 2, корпус 4, литера А.