

### FEATURES

- ◆ Encapsulated compact AC-DC power supply
- ◆ Single-, Dual- and Triple Output Models
- ◆ Over Load and Over Voltage Protection
- ◆ 3 Mounting Package Versions:
  - Solder pins for direct PCB mount
  - Screw terminal block for chassis mount
  - DIN-Rail Mounting
- ◆ Universal Input voltage range 85-264 VAC, 47-440 Hz
- ◆ 3kVAC Isolation, Protection Class II level
- ◆ UL/UL/IEC/EN 60950-1 Certified , CE Marked
- ◆ UL508 Approval (Selective)
- ◆ Lead free, RoHs Compliant
- ◆ 3 Year Product Warranty



The AA15S/D/T series , isolated fully encapsulated 15W AC/DC power module with 3,000VAC isolation. With Universal input voltage 85-264VAC and International safety approvals, these power modules are ideal for applications in commercial and industrial electronic equipment. These isolated AC/DC converters are the latest offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc. With creative design technology and optimization of component placement, these converters possess outstanding electrical and thermal performance, as well as extremely high reliability under highly stressful operating conditions. industrial electronic equipment.

### Model List

| Model Number | Output Voltage | Output Current | Input Current       |                   | Max. capacitive Load | Efficiency (typ.) | UL60950-1 Approval | UL508 Approval |
|--------------|----------------|----------------|---------------------|-------------------|----------------------|-------------------|--------------------|----------------|
|              |                |                | 115VAC, 60Hz        |                   |                      |                   |                    |                |
|              | VDC            | Max. mA        | @Max. Load mA(typ.) | @No Load mA(typ.) | μF                   | @Max. Load %      |                    |                |
| AA15S0500A   | 5              | 3000           | 290                 | 30                | 3900                 | 75                | ○                  | ○              |
| AA15S1200A   | 12             | 1250           | 275                 | 30                | 2200                 | 79                | ○                  | ○              |
| AA15S1500A   | 15             | 1000           | 275                 | 30                | 2200                 | 79                | ○                  | ○              |
| AA15S2400A   | 24             | 625            | 275                 | 30                | 1000                 | 79                | ○                  | ○              |
| AA15S4800A   | 48             | 310            | 273                 | 30                | 680                  | 79                | ○                  | ○              |
| AA15D1212A   | ±12            | ±650           | 275                 | 30                | *1500                | 79                | ○                  | ○              |
| AA15D1515A   | ±15            | ±500           | 275                 | 30                | *1500                | 79                | ○                  | ○              |
| AA15D0512A   | 5              | 1500           | 302                 | 30                | 2000                 | 72                | ○                  |                |
|              | *12            | 625            |                     |                   | 1500                 |                   |                    |                |
| AA15T051212A | 5              | 2000           | 290                 | 30                | 2200                 | 74                | ○                  |                |
|              | *12            | 200            |                     |                   | 1500                 |                   |                    |                |
|              | *-12           | -200           |                     |                   | 1500                 |                   |                    |                |
|              | *5             | 2000           |                     |                   | 2200                 |                   |                    |                |
| AA15T051515A | *15            | 150            | 284                 | 30                | 2200                 | 74                | ○                  |                |
|              | *15            | 150            |                     |                   | 1500                 |                   |                    |                |
|              | *-15           | -150           |                     |                   | 1500                 |                   |                    |                |

\* Output voltage accuracy 4% max.

\* For each output



## Input Characteristics

| Parameter                           | Model      | Min. | Typ. | Max. | Unit |
|-------------------------------------|------------|------|------|------|------|
| Input Voltage Range                 | All Models | 85   | ---  | 264  | VAC  |
| Input Frequency Range               |            | 47   | ---  | 440  | Hz   |
| Input Voltage Range                 |            | 120  | ---  | 370  | VDC  |
| Inrush Current (Cold Start at 25°C) | 115VAC     | ---  | ---  | 15   | A    |
|                                     | 230VAC     | ---  | ---  | 30   | A    |

## Output Characteristics

| Parameter  | Conditions   | Min.   | Typ.  | Max.  | Unit                   |   |
|--|--|--|-------|-------|------------------------|---|
| Output Voltage Accuracy                                |  | ---  | ±1.0  | ±2.0  | %                      |   |
| Line Regulation  | Vin=Min. to Max.   | ---  | ±0.5  | ±1.0  | %                      |   |
| Load Regulation  | Iout=Min. to Max.  | Single Output Models   | ---   | ±0.5  | ±1.0                   | % |
|  |  | Dual/ Triple Output Models   | ---   | ±2.5  | ±5.0                   | % |
| Cross Regulation-<br>Dual Positives / Triple<br>Output | Vo1  | Measured output Io = 20% to 100% of rated load<br>Other output(s) set at 50% of rated load | ---   | ±1.0  | ---                    | % |
|  | Vo2  |  | ---   | ±2.5  | ---                    | % |
|  | Vo3  |  | ---   | ±2.5  | ---                    | % |
| Ripple & Noise (20MHz)                                 | 5VDC Output Models   | ---  | 1.5   | 1.8   | %V <sub>PP</sub> of Vo |   |
|  | Other Output Models  | ---  | 0.8   | 1.0   | %V <sub>PP</sub> of Vo |   |
| Minimum Load   |  | ---  | 10    | ---   | %Inom.                 |   |
| Over Voltage Protection                                | Zener diode clamp  | ---  | 120   | ---   | % of Vo                |   |
| Temperature Coefficient                                |  | ---  | ±0.01 | ±0.02 | %/°C                   |   |
| Overshoot  |  | ---  | ---   | 5     | % Vout                 |   |
| Current Limitation                                     | Foldback, auto-recovery<br>(long term overload condition may cause damage) | 105  | ---   | ---   | %Inom.                 |   |
| Short Circuit Protection                               | Hiccup mode, indefinite (automatic recovery)                               |  |       |       |                        |   |

## General Characteristics

| Parameter                             | Conditions                        | Min.  | Typ.                      | Max. | Unit                    |
|---------------------------------------|-----------------------------------|---|---------------------------|------|-------------------------|
| I/O Isolation Voltage                 | Input to Output, 60 Seconds       | 3000  | ---                       | ---  | VACrms                  |
| I/O Isolation Resistance              | 500 VDC                           | 100   | ---                       | ---  | MΩ                      |
| Switching Frequency                   |                                   | ---   | 100                       | ---  | KHz                     |
| Hold-up Time                          |                                   | ---   | 20                        | ---  | ms                      |
| MTBF (calculated)                     | MIL-HDBK-217F@25°C, Ground Benign | 280,000   | ---                       | ---  | Hours                   |
| Protection Class II                   | According IEC/EN 60536            |   |                           |      |                         |
| Safety Approvals                      | cUL/UL 60950-1, IEC/EN 60950-1    |   |                           |      |                         |
|                                       | UL508 for selective models        |   |                           |      |                         |
| EMC Emission                          | Conducted and radiated            | EN 55011 class B, EN 55032 class B, FCC part 15 class B |                           |      |                         |
| EMC Immunity according<br>EN61000-6-1 | Standard                          |   | Specification Requirement |      | Performance<br>Criteria |
|                                       | ESD                               | EN61000-4-2   | Air ±8KV Cont. ±4KV       |      | B                       |
|                                       | Radiated immunity                 | EN61000-4-3   | 10V/m                     |      | A                       |
|                                       | Fast transient                    | EN61000-4-4   | ±2KV,                     |      | B                       |
|                                       | Surge                             | EN61000-4-5   | ±1KV                      |      | B                       |
|                                       | Conducted immunity                | EN61000-4-6   | 10Vrms                    |      | B                       |
|                                       | PFMF                              | EN61000-4-8   | 30A/m                     |      | A                       |
|                                       | Dips                              | EN61000-4-11  | 30%, 10ms<br>>95%, 5000ms |      | B<br>C                  |



## Input Fuse

| All Models                  |                       |
|-----------------------------|-----------------------|
| Built-in Fuse               | 2A / 250VAC           |
| External Fuse (Recommended) | 1.5A Slow – Blow Type |

## Environmental Specifications

| Parameter                       | Conditions                       |   |             |
|---------------------------------|----------------------------------|---|-------------|
| Temperature Range (operational) | Ambient                          | -25°C                                   | +70°C       |
| Storage Temperature Range       |                                  | -40°C                                   | +85°C       |
| Over Temperature Protection     | Internal IC junction temperature | 140°C shutdown, 65°C automatic recovery |             |
| Cooling                         | Free-Air convection              |   |             |
| Humidity (non condensing)       |                                  | ---                                     | 95 % rel. H |

## Power Derating Curve



## Notes

- 1 All Specifications typical at  $T_a=+25^{\circ}\text{C}$ , resistive load, 115VAC, 60Hz input voltage and after warm-up time rated output current unless otherwise noted.
- 2 Ripple & Noise measurement bandwidth is 0-20 MHz
- 3 These power modules require a minimum output loading to maintain specified regulation, operation under no-load conditions will not damage the power supplies however they may not meet all listed specifications.
- 4 Specifications are subject to change anytime without notice

## Mechanical Drawing PCB Mount



**Pin Connections**

| Pin | Single             | Dual ( $\pm 12, \pm 15$ ) | Dual (0512) | Triple |
|-----|--------------------|---------------------------|-------------|--------|
| 1   | AC(N) – AC Neutral |                           |             |        |
| 2   | AC(L) – AC Line    |                           |             |        |
| 3   | No Pin             |                           |             | -Vout3 |
| 4   | -Vout              | -Vout                     | -Vout2      | Common |
| 5   | No Pin             | Common                    | +Vout2      | +Vout2 |
| 6   | +Vout              | +Vout                     | -Vout1      | -Vout1 |
| 7   | No Pin             |                           | +Vout1      | +Vout1 |

- ▶ All dimensions in mm (inches)
- ▶ Tolerance:  $\pm 0.5$  ( $\pm 0.02$ )
- ▶ Pin diameter  $\varnothing 1.0 \pm 0.1$  ( $0.04 \pm 0.004$ )

## Physical Outline

|               |   |
|---------------|---|
| Case Size     | : 74.0x54.0x19.5mm (2.91x2.13x0.77 inches)                    |
| Case Material | : Plastic resin + Fiberglass (flammability to UL 94V-0 rated) |
| Pin Material  | : Copper Alloy with Gold Plate Over Nickel Subplate           |
| Weight        | : 140g  |

## Mechanical Drawings Chassis Mount (Option code, suffix C)



**Connections**

| Terminal | Single             | Dual ( $\pm 12, \pm 15$ ) | Dual (0512) | Triple |
|----------|--------------------|---------------------------|-------------|--------|
| 1        | AC(N) – AC Neutral |                           |             |        |
| 2        | AC(L) – AC Line    |                           |             |        |
| 3        | NC                 |                           |             | -Vout3 |
| 4        | -Vout              | -Vout                     | -Vout2      | Common |
| 5        | NC                 | Common                    | +Vout2      | +Vout2 |
| 6        | +Vout              | +Vout                     | -Vout1      | -Vout1 |
| 7        | NC                 |                           | +Vout1      | +Vout1 |

NC: No Connection

- ▶ All dimensions in mm (inches)
- ▶ Tolerance:  $X.X \pm 0.5$  ( $X.XX \pm 0.02$ )  
 $X.XX \pm 0.25$  ( $X.XXX \pm 0.01$ )
- ▶ Pin pitch tolerance:  $\pm 0.25$  (0.01)

## Physical Outline

|               |   |
|---------------|---|
| Case Size     | : 96.0x54.0x23.3mm (3.78x2.13x0.92 inches)                    |
| Case Material | : Plastic resin + Fiberglass (flammability to UL 94V-0 rated) |
| Weight        | : 130g  |

## Mechanical Drawings Chassis Mounting with DIN Rail Kit (Option code, suffix D)

### Mechanical Dimensions



## Physical Outline

|               |   |
|---------------|---|
| Case Size     | : 96.0x54.0x23.3mm (3.78x2.13x0.92 inches)                    |
| Case Material | : Plastic resin + Fiberglass (flammability to UL 94V-0 rated) |
| Weight        | : 190g  |

## DIN-Rail Mounting Kit





## Part Numbering System

| A                  | A                      | 15      | T                 | 05               | 12                  | 12                 | A                               |
|--------------------|------------------------|---------|-------------------|------------------|---------------------|--------------------|---------------------------------|
| Product typ        | Family series          | Watt    | Number of Outputs | Output Voltage I | Output Voltage II   | Output Voltage III | Option Code                     |
| AC/DC Power Module | Industrial application | 15 -15W | S - Single        | 05 - 5V          | 00 - not applicable | 12 - 12V           | A - PCB Mount                   |
|                    |                        |         | D - Dual          | 12 - 12V         | 12 - 12V            | 15 - 15V           | C - Chassis Mount               |
|                    |                        |         | T - Triple        | 15 - 15V         | 15 - 15V            |                    | D -C code module + Din-rail kit |
|                    |                        |         |                   | 24 - 24V         |                     |                    |                                 |
|                    |                        |         |                   | 48 - 48V         |                     |                    |                                 |

**Website:** [www.deltaww.com/dcdc](http://www.deltaww.com/dcdc)

**Email:** [dcdc@deltaww.com](mailto:dcdc@deltaww.com)

**USA:**

Telephone:  
 East Coast: 978-656-3993  
 West Coast: 510-668-5100  
 Fax: (978) 656 3964

**Europe:**

Phone: +31-20-655-0967  
 Fax: +31-20-655-0999

**Asia & the rest of world:**

Telephone: +886 3 4526107  
 ext 6220~6224  
 Fax: +886 3 4513485

**WARRANTY**

Delta offers a three(3) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.