



Pin 1 –  $V_{IN}$   
 Pin 2 –  $V_{OUT}$   
 Case – Ground

**K Package – TO-3**



Pin 1 –  $V_{IN}$   
 Pin 2 –  $V_{OUT}$   
 Case – Ground


**R Package – TO-66**



Pin 1 –  $V_{IN}$   
 Pin 2 – Ground  
 Pin 3 –  $V_{OUT}$   
 Case – Ground\*

**G Package – TO-257**  
**IG Package – TO-257\***

\* isolated Case on IG package




**LCC4**  
**CERAMIC SURFACE MOUNT**

Pins 4,5 –  $V_{IN}$  .

Pins 6,7,8,9,10,11,12,13 –  $V_{OUT}$


Pins 15,16,17,18,1,2 – Ground



Pin 1 –  $V_{IN}$   
 Pin 2 – Ground  
 Pin 3 –  $V_{OUT}$

**SMD 1 PACKAGE**

Ceramic Surface Mount



Pin 1 –  $V_{IN}$   
 Pin 2 – Ground  
 Pin 3 –  $V_{OUT}$

**SMD 05 PACKAGE**

Ceramic Surface Mount

## 1 AMP POSITIVE VOLTAGE REGULATOR

### FEATURES

- OUTPUT CURRENT UP TO 1.0A
- OUTPUT VOLTAGES OF 5, 12, 15V
- 0.01% / V LINE REGULATION
- 0.3% / A LOAD REGULATION
- THERMAL OVERLOAD PROTECTION
- SHORT CIRCUIT PROTECTION
- OUTPUT TRANSISTOR SOA PROTECTION
- 1% VOLTAGE TOLERANCE (–A VERSIONS)

### DESCRIPTION

The IP140A / LM140 / IP7800A / IP7800 series of 3 terminal regulators is available with several fixed output voltage making them useful in a wide range of applications.

The A suffix devices are fully specified at 1A, provide 0.01% / V line regulation, 0.3% / A load regulation and  $\pm 1\%$  output voltage tolerance at room temperature.

Protection features include Safe Operating Area current limiting and thermal shutdown.

### ABSOLUTE MAXIMUM RATINGS ( $T_{case} = 25^{\circ}C$ unless otherwise stated)

$V_I$	DC Input Voltage (for $V_O = 5, 12, 15V$ )	35V
$P_D$	Power Dissipation	Internally limited <sup>1</sup>
$T_j$	Operating Junction Temperature Range	–55 to 150°C
$T_{stg}$	Storage Temperature	–65 to 150°C

Note 1. Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation  $P_{MAX}$  of 20W.  $I_{MAX} = 1.0A$ .

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.

Parameter	Test Conditions	IP7805A LM,IP140A-05			IP7805 LM,IP140-05			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V <sub>O</sub> Output Voltage	I <sub>O</sub> = 1A V <sub>IN</sub> = 10V	4.95	5	5.05	4.8	5	5.2	V
	I <sub>O</sub> = 5mA to I <sub>MAX</sub> P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = 7.5V to 20V T <sub>J</sub> = -55 to 150°C	4.85		5.15	4.75		5.25	
V <sub>O</sub> Low Supply	I <sub>O</sub> = 5mA to I <sub>MAX</sub> P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = 7V to 20V	4.75		5.15	4.75		5.25	V
ΔV <sub>O</sub> Line Regulation	I <sub>O</sub> = 0.5 I <sub>MAX</sub>	V <sub>IN</sub> = 7V to 25V	3	10			50	mV
		V <sub>IN</sub> = 7.5V to 25V T <sub>J</sub> = -55 to 150°C	3	10			50	
	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 7.3V to 20V	3	10			50		
	V <sub>IN</sub> = 8V to 12V	1	4			20		
		T <sub>J</sub> = -55 to 150°C	2	12			25	
ΔV <sub>O</sub> Load Regulation	V <sub>IN</sub> = 10V	I <sub>O</sub> = 5mA to 1.5A	10	25			50	mV
		I <sub>O</sub> = 250mA to 750mA	4	15			25	
	V <sub>IN</sub> = 10V	I <sub>O</sub> = 5mA to I <sub>MAX</sub> T <sub>J</sub> = -55 to 150°C	7	25			50	
I <sub>Q</sub> Quiescent Current	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 10V	T <sub>J</sub> = -55 to 150°C	4	6			6	mA
			4	6.5			7	
ΔI <sub>Q</sub> Quiescent Current Change	I <sub>O</sub> = 5mA to I <sub>MAX</sub>	V <sub>IN</sub> = 10V	0.2	0.5			0.5	mA
		V <sub>IN</sub> = 7.5V to 20V T <sub>J</sub> = -55 to 150°C	0.1	0.8			0.8	
	I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> V <sub>IN</sub> = 8V to 25V	0.1	0.8			0.8		
	I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> V <sub>IN</sub> = 7V to 25V T <sub>J</sub> = -55 to 150°C	0.2	1			1.0		
V <sub>N</sub> Output Noise Voltage	f = 10Hz to 100kHz V <sub>IN</sub> = 10V		40	200		40		μV
ΔV <sub>IN</sub> / ΔV <sub>O</sub> Ripple Rejection	f = 120Hz V <sub>IN</sub> = 8V to 18V	I <sub>O</sub> ≤ I <sub>MAX</sub>	68	80		68		dB
		I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> T <sub>J</sub> = -55 to 150°C	68	80		68		
Dropout Voltage	I <sub>O</sub> = I <sub>MAX</sub>		2	2.5		2		V
R <sub>O</sub> Output Resistance	f = 1 kHz		5			5		mΩ
I <sub>sc</sub> Short Circuit Current	V <sub>IN</sub> = 35V		0.6	1.2		0.6	1.2	A
I <sub>pk</sub> Peak Output Current	V <sub>IN</sub> = 10V		2.4	3.3		2.4	3.3	
Average Temperature Coefficient of V <sub>O</sub>	I <sub>O</sub> = 5mA		0.2	2		0.6		mV / °C
Input Voltage required to maintain line regulation	I <sub>O</sub> ≤ I <sub>MAX</sub>	7.3			7.3			V

- All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF. All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t<sub>p</sub> ≤ 10ms, δ ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.
- Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation P<sub>MAX</sub> of 20W, I<sub>MAX</sub> = 1.0A.
- T<sub>J</sub> = 25°C unless otherwise stated.

Parameter	Test Conditions	IP7812A LM,IP140A-12			IP7812 LM,IP140-12			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V <sub>O</sub> Output Voltage	I <sub>O</sub> = 1A V <sub>IN</sub> = 19V	11.88	12	12.12	11.5	12	12.5	V
	I <sub>O</sub> = 5mA to I <sub>MAX</sub> P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = 14.8V to 27V T <sub>J</sub> = -55 to 150°C	11.64		12.36	11.4		12.6	
V <sub>O</sub> Low Supply	I <sub>O</sub> = 5mA to I <sub>MAX</sub> P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = 14.5V to 27V	11.40		12.36	11.4		12.6	V
ΔV <sub>O</sub> Line Regulation	I <sub>O</sub> = 0.5 I <sub>MAX</sub>	V <sub>IN</sub> = 14.5V to 30V		4	18		120	mV
		V <sub>IN</sub> = 14.8V to 30V T <sub>J</sub> = -55 to 150°C		4	18		120	
	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 14.5V to 27V		4	18		120		
	V <sub>IN</sub> = 16V to 22V		2	9		50		
		T <sub>J</sub> = -55 to 150°C		4	30		60	
ΔV <sub>O</sub> Load Regulation	V <sub>IN</sub> = 19V	I <sub>O</sub> = 5mA to 1.5A		12	32		120	mV
		I <sub>O</sub> = 250mA to 750mA		4	19		60	
	V <sub>IN</sub> = 19V	I <sub>O</sub> = 5mA to I <sub>MAX</sub> T <sub>J</sub> = -55 to 150°C		8	60		120	
I <sub>Q</sub> Quiescent Current	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 19V	T <sub>J</sub> = -55 to 150°C		4	6		6	mA
				4	6.5		7	
ΔI <sub>Q</sub> Quiescent Current Change	I <sub>O</sub> = 5mA to I <sub>MAX</sub> V <sub>IN</sub> = 19V		0.2	0.5			0.5	mA
	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 14.8V to 27V T <sub>J</sub> = -55 to 150°C		0.1	0.8			0.8	
	I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> V <sub>IN</sub> = 15V to 30V		0.1	0.8			0.8	
	I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> V <sub>IN</sub> = 14.5V to 30V T <sub>J</sub> = -55 to 150°C		0.2	1			1	
V <sub>N</sub> Output Noise Voltage	f = 10Hz to 100kHz V <sub>IN</sub> = 19V		75	480		75		μV
ΔV <sub>IN</sub> / ΔV <sub>O</sub> Ripple Rejection	f = 120Hz V <sub>IN</sub> = 15V to 25V	I <sub>O</sub> ≤ I <sub>MAX</sub>	61	72		61		dB
		I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> T <sub>J</sub> = -55 to 150°C	61	72		61		
Dropout Voltage	I <sub>O</sub> = I <sub>MAX</sub>		2	2.5		2		V
R <sub>O</sub> Output Resistance	f = 1 kHz		8			8		mΩ
I <sub>sc</sub> Short Circuit Current	V <sub>IN</sub> = 35V		0.6	1.2		0.6	1.2	A
I <sub>pk</sub> Peak Output Current	V <sub>IN</sub> = 19V		2.4	3.3		2.4	3.3	
Average Temperature Coefficient of V <sub>O</sub>	I <sub>O</sub> = 5mA		0.5	4.8		1.5		mV / °C
Input Voltage required to maintain line regulation	I <sub>O</sub> ≤ I <sub>MAX</sub>	14.5				14.6		V

- All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF. All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t<sub>p</sub> ≤ 10ms, δ ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.
- Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation P<sub>MAX</sub> of 20W, I<sub>MAX</sub> = 1.0A.
- T<sub>J</sub> = 25°C unless otherwise stated.


Parameter	Test Conditions	IP7815A LM,IP140A-15			IP7815 LM,IP140-15			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V <sub>O</sub> Output Voltage	I <sub>O</sub> = 1A V <sub>IN</sub> = 23V	14.85	15	15.15	14.4	15	15.60	V
	I <sub>O</sub> = 5mA to I <sub>MAX</sub> P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = 17.9V to 30V T <sub>J</sub> = -55 to 150°C	14.55		15.45	14.25		15.75	
V <sub>O</sub> Low Supply	I <sub>O</sub> = 5mA to I <sub>MAX</sub> P <sub>D</sub> ≤ P <sub>MAX</sub> V <sub>IN</sub> = 17.5V to 30V	14.25		15.45	14.25		15.75	V
ΔV <sub>O</sub> Line Regulation	I <sub>O</sub> = 0.5 I <sub>MAX</sub>	V <sub>IN</sub> = 17.5V to 30V	4	22			150	mV
		V <sub>IN</sub> = 17.9V to 30V T <sub>J</sub> = -55 to 150°C	4	22			150	
	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 17.5V to 30V	4	22			150		
	V <sub>IN</sub> = 20V to 26V T <sub>J</sub> = -55 to 150°C	2	10			60		
ΔV <sub>O</sub> Load Regulation	V <sub>IN</sub> = 23V	I <sub>O</sub> = 5mA to 1.5A	12	35			150	mV
		I <sub>O</sub> = 250mA to 750mA	4	21			75	
	V <sub>IN</sub> = 23V I <sub>O</sub> = 5mA to I <sub>MAX</sub> T <sub>J</sub> = -55 to 150°C	9	75			150		
I <sub>Q</sub> Quiescent Current	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 23V	T <sub>J</sub> = -55 to 150°C	4	6			6	mA
			4	6.5			7	
ΔI <sub>Q</sub> Quiescent Current Change	I <sub>O</sub> = 5mA to I <sub>MAX</sub> V <sub>IN</sub> = 23V	0.2	0.5			0.5	mA	
	I <sub>O</sub> ≤ I <sub>MAX</sub> V <sub>IN</sub> = 17.9V to 30V T <sub>J</sub> = -55 to 150°C	0.1	0.8			0.8		
	I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> V <sub>IN</sub> = 18.5V to 30V	0.1	0.8			0.8		
	I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> V <sub>IN</sub> = 17.5V to 30V T <sub>J</sub> = -55 to 150°C	0.2	1			1		
V <sub>N</sub> Output Noise Voltage	f = 10Hz to 100kHz V <sub>IN</sub> = 23V	90	600		90		μV	
ΔV <sub>IN</sub> / ΔV <sub>O</sub> Ripple Rejection	f = 120Hz I <sub>O</sub> ≤ I <sub>MAX</sub>	60	70		60		dB	
	V <sub>IN</sub> = 18.5V to 28.5V I <sub>O</sub> ≤ 0.5 I <sub>MAX</sub> T <sub>J</sub> = -55 to 150°C	60	70		60			
Dropout Voltage	I <sub>O</sub> = I <sub>MAX</sub>	2	2.5		2		V	
R <sub>O</sub> Output Resistance	f = 1 kHz	9			9		mΩ	
I <sub>sc</sub> Short Circuit Current	V <sub>IN</sub> = 35V	0.6	1.2		0.6	1.2	A	
I <sub>pk</sub> Peak Output Current	V <sub>IN</sub> = 23V	2.4	3.3		2.4	3.3		
Average Temperature Coefficient of V <sub>O</sub>	I <sub>O</sub> = 5mA	0.6	6		1.8		mV / °C	
Input Voltage required to maintain line regulation	I <sub>O</sub> ≤ I <sub>MAX</sub>	17.5			17.7		V	

- All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF. All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t<sub>p</sub> ≤ 10ms, δ ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.
- Although power dissipation is internally limited, these specifications are applicable for maximum power dissipation P<sub>MAX</sub> of 20W, I<sub>MAX</sub> = 1.0A.
- T<sub>J</sub> = 25°C unless otherwise stated.


## THERMAL DATA

$R_{thj-case}$ Thermal Resistance Junction-case		<b>MAX</b>
	K-Pack	3°C/W
	R-Pack	7°C/W
	G/IG-Pack	5°C/W
	LCC4	13°C/W
	SMD	1.3°C/W


## APPLICATIONS INFORMATION



**Fixed Output Regulator**



**Adjustable Output Regulator**



**Current Regulator**

- \* Required if the regulator is located far from the power supply.
- \*\* Although no output capacitor is needed for stability, it does help transient response. (If needed, use 0.1µF ceramic disc)

$$V_{OUT} = 5V + \left( \frac{5V}{R1 + V} \right) R2$$

$$\left( \frac{5V}{R1} \right) > 3I_Q, \text{ Load Regulation } \approx$$

$$\left[ \frac{R1+R2}{R1} \right] (L_R \text{ of Regulator})$$

$$I_{OUT} = \left( \frac{V2 - V3}{R1} \right) + I_Q$$

$\Delta I_Q = 1.3\text{mA}$  over line and load changes

## Order Information

Part Number	K-Pack (TO-3)	R-Pack (TO-66)	G/IG-Pack (TO-257)	SMD 1 SMD 05	LCC4	Temp. Range	Note:
IP7800A	✓	✓	✓	✓	✓	-55 to +150°C	To order, add the package identifier to the part number. eg. IP7805AK IP140SMD-12
IP7800	✓	✓	✓	✓	✓	"	
IP140A	✓	✓	✓	✓	✓	"	
IP140	✓	✓	✓	✓	✓	"	
LM140	✓	✓	✓	✓	✓	"	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TT electronics:](#)

[IP7815AIG-DESC](#)

[TT Electronics:](#)

[LM140K-15-883B](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.