


**Features**

- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDTA)
- Built-In Biasing Resistor, R1 only
- **Lead Free/RoHS Compliant (Note 2)**
- **"Green" Device (Note 3 and 4)**

**Mechanical Data**

- Case: SOT-323
- Case Material: Molded Plastic, "Green" Molding Compound, Note 4. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Marking Information: See Diagrams & Page 3
- Type Code: See Table Below
- Ordering Information: See Page 3
- Weight: 0.006 grams (approximate)



| SOT-323              |              |      |
|----------------------|--------------|------|
| Dim                  | Min          | Max  |
| A                    | 0.25         | 0.40 |
| B                    | 1.15         | 1.35 |
| C                    | 2.00         | 2.20 |
| D                    | 0.65 Nominal |      |
| E                    | 0.30         | 0.40 |
| G                    | 1.20         | 1.40 |
| H                    | 1.80         | 2.20 |
| J                    | 0.0          | 0.10 |
| K                    | 0.90         | 1.00 |
| L                    | 0.25         | 0.40 |
| M                    | 0.10         | 0.18 |
| $\alpha$             | 0°           | 8°   |
| All Dimensions in mm |              |      |

SCHEMATIC DIAGRAM

| P/N        | R1 (NOM)      | Type Code |
|------------|---------------|-----------|
| DDTC113TUA | 1K $\Omega$   | N01       |
| DDTC123TUA | 2.2K $\Omega$ | N03       |
| DDTC143TUA | 4.7K $\Omega$ | N07       |
| DDTC114TUA | 10K $\Omega$  | N12       |
| DDTC124TUA | 22K $\Omega$  | N16       |
| DDTC144TUA | 47K $\Omega$  | N19       |
| DDTC115TUA | 100K $\Omega$ | N23       |
| DDTC125TUA | 200K $\Omega$ | N25       |

**Maximum Ratings** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                       | Symbol                            | Value       | Unit |
|--|-----------------------------------|-------------|------|
| Collector-Base Voltage                               | V <sub>CBO</sub>                  | 50          | V    |
| Collector-Emitter Voltage                            | V <sub>CEO</sub>                  | 50          | V    |
| Emitter-Base Voltage                                 | V <sub>EBO</sub>                  | 5           | V    |
| Collector Current                                    | I <sub>C</sub> (Max)              | 100         | mA   |
| Power Dissipation                                    | P <sub>d</sub>                    | 200         | mW   |
| Thermal Resistance, Junction to Ambient Air (Note 1) | R <sub>θJA</sub>                  | 833         | °C/W |
| Operating and Storage Temperature Range              | T <sub>j</sub> , T <sub>STG</sub> | -55 to +150 | °C   |





- Notes:
1. Mounted on FR4 PC Board with recommended pad layout as shown on Diodes Inc., suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>
  2. No purposefully added lead.
  3. Diodes Inc.'s "Green" Policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).
  4. Product manufactured with date code 0627 (week 27, 2006) and newer are built with Green Molding Compound. Product manufactured prior to date code 0627 are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants

## Electrical Characteristics @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                             | Symbol               | Min | Typ | Max | Unit | Test Condition  |
|--|----------------------|-----|-----|-----|------|---|
| Collector-Base Breakdown Voltage           | BV <sub>CBO</sub>    | 50  | —   | —   | V    | I <sub>C</sub> = 50μA   |
| Collector-Emitter Breakdown Voltage        | BV <sub>CEO</sub>    | 50  | —   | —   | V    | I <sub>C</sub> = 1mA  |
| Emitter-Base Breakdown Voltage             | BV <sub>EBO</sub>    | 5   | —   | —   | V    | I <sub>E</sub> = 50μA   |
| Collector Cutoff Current                   | I <sub>CB0</sub>     | —   | —   | 0.5 | μA   | V <sub>CB</sub> = 50V   |
| Emitter Cutoff Current                     | I <sub>E0</sub>      | —   | —   | 0.5 | μA   | V <sub>EB</sub> = 4V  |
| Collector-Emitter Saturation Voltage       | V <sub>CE(sat)</sub> | —   | —   | 0.3 | V    | I <sub>C</sub> /I <sub>B</sub> = 10mA/1mA DDTC113TUA<br>I <sub>C</sub> /I <sub>B</sub> = 5mA/0.5mA DDTC123TUA<br>I <sub>C</sub> /I <sub>B</sub> = 2.5mA/.25mA DDTC143TUA<br>I <sub>C</sub> /I <sub>B</sub> = 1mA/.1mA DDTC114TUA<br>I <sub>C</sub> /I <sub>B</sub> = 5mA/0.5mA DDTC124TUA<br>I <sub>C</sub> /I <sub>B</sub> = 2.5mA/.25mA DDTC144TUA<br>I <sub>C</sub> /I <sub>B</sub> = 1mA/0.1mA DDTC115TUA<br>I <sub>C</sub> /I <sub>B</sub> = .5mA/.05mA DDTC125TUA |
| DC Current Transfer Ratio                  | h <sub>FE</sub>      | 100 | 250 | 600 | —    | I <sub>C</sub> = 1mA, V <sub>CE</sub> = 5V  |
| Input Resistor (R <sub>1</sub> ) Tolerance | ΔR <sub>1</sub>      | -30 | —   | +30 | %    | —   |
| Gain-Bandwidth Product*                    | f <sub>T</sub>       | —   | 250 | —   | MHz  | V <sub>CE</sub> = 10V, I <sub>E</sub> = -5mA, f = 100MHz  |

\*Transistor - For Reference Only

## Typical Curves – DDTC114TUA






Fig. 5 Collector Current vs. Input Voltage





Fig. 6 Input Voltage vs. Collector Current

## Ordering Information (Note 4 & 5)

| Device          | Packaging | Shipping           |
|-----------------|-----------|--------------------|
| DDTC1xxTUA-7-F  | SOT-323   | 3000/Tape & Reel   |
| DDTC1xxTUA-13-F | SOT-323   | 10,000/Tape & Reel |

Notes: 5. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



XXX = Product Type Marking Code, See Table on Page 1  
 YM = Date Code Marking  
 Y = Year ex: T = 2006  
 M = Month ex: 9 = September

### Date Code Key

| Year | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|------|
| Code | T    | U    | V    | W    | X    | Y    | Z    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.