



Features

- Fast acting
- Balanced
- Stable breakdown throughout life
- Designed to operate with TBU® devices
- RoHS compliant* versions available

Applications

- Telecommunications
- Industrial electronics
- Avionics

2020 T-Series - Fast Acting 3-Electrode Miniature GDT

Characteristics

| Characteristic | Model No. | | |
|--|-----------|----------|----------|
| | 2020-15T | 2020-23T | 2020-42T |
| Minimum DC Sparkover (100 V/s) Throughout Service Life | 60 V | 180 V | 360 V |
| Maximum Impulse Sparkover (5k V 1.2/50 μ s) Throughout Service Life | 500 V | 650 V | 850 V |

| | | |
|--|--|-----------------------------------|
| Impulse Transverse Delay | 1000 V/ μ s | < 75 ns |
| Insulation Resistance (IR) | 50 V / 100 V | > 10 ⁹ Ω |
| Glow Voltage | 10 mA | ~ 70 V |
| Arc Voltage | >1 A | ~ 10 V |
| Glow-Arc Transition Current | | < 0.5 A |
| Capacitance..... | 1 MHz | < 1 pF |
| DC Holdover Voltage (Network Applied per ITU-T K.12) | | |
| 2020-15T | 52 V | < 150 ms |
| 2020-23T | 80 V | < 150 ms |
| 2020-42T | 135 V | < 150 ms |
| Service Life ¹ | 8/20 μ s, 10 kA..... | 1 operation |
| | 10/1000 μ s, 1 kV, 200 A..... | 100 operations ² |
| | 2/10 μ s, 6 kV, 2000 A..... | 10 operations ² |
| | 10/700 μ s, 6 kV, 300 A..... | 50 operations ² |
| | 8/20 μ s, 500 A, 1.2/50 μ s, 500 V | 150 operations ² |
| | 600 V, 10 Arms, 0.2 sec..... | 10 operations |
| | 600 Vrms, 0.5 A - 60 A..... | Fail-Short activates ³ |
| | 230 Vrms, 0.5 A-25 A..... | Fail-Short activates ³ |
| Operating and Storage Temperature | | -40 to +90 °C |
| Climatic Category (IEC 60068-1) | | 40 / 90 / 21 |

Notes:

- 1 The rated discharge current is the total current equally divided between each line to ground.
 - 2 Surge polarity should be reversed between consecutive surges (+,-,+,-)
 - 3 Applies only to GDT with optional Fail-Short. GDT operates and will survive with Fail-Short activation.
- At delivery AQL 0.65 Level II, DIN ISO 2859.

Applications

| Port Protection | GDT Device P/N | TBU® Device P/N |
|-----------------|----------------|----------------------------------|
| CanBus | 2020-23T | TBU-CA065-100-WH |
| RS232 | 2020-23T | TBU-CA065-200-WH |
| RS422 | 2020-23T | TBU-CA065-200-WH |
| RS485 | 2020-23T | TBU-CA065-200-WH |
| RS485 | 2020-42T | TBU-CA085-200-WH |
| SDI | 2020-23T | TBU-CA065-100-WH |
| VDSL | 2020-15T | TBU-CA050-500-WH |

"TBU" is a registered trademark of Bourns, Inc. in the United States and other countries.

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011. Specifications are subject to change without notice.


Customers should verify actual device performance in their specific applications.

2020 T-Series - Fast Acting 3-Electrode Miniature GDT


BOURNS®

Product Dimensions (additional lead form configurations available upon request)

2020-xxT-A1



2020-xxT-C4



**FAIL-SHORT
CONFIGURATION
2020-xxT-C2F SHOWN**



2020-xxT-C2




2020-xxT-C8




DIMENSIONS: MILLIMETERS

UNITS WITH LEADS ARE BASED ON THE 2020-xxT-A1 BODY.

2020-xxT-C3



**2020-xxT-C
1.0 mm dia. lead wire**



How to Order

2020 - xxT - x x F LF

Model Number

Designator

Voltage

15 = 60 V

23 = 180 V

42 = 360 V

Leads

A = None/Cassette Applications

C = 1 mm Dia. Leads/Through-hole

Lead Shape

(See Product Dimension Drawings)

Fail-Short Option

Blank = Standard Product

F = With Fail-Short Mechanism

RoHS Compliant Option

Blank = Standard Product

LF = RoHS Compliant Product

Model 2020-xxT ships in standard bulk pack, 100 pcs./tray.

2020 T-Series - Fast Acting 3-Electrode Miniature GDT

BOURNS®

Switch-Grade Fail-Short Device Shorting Curve 2020-xxT-XF



ELTGS = Each Line to Ground Simultaneously

NOTE: When using a GDT fail-short device, it is imperative that all components associated and connected to the GDT with failsafe be tested in their respective completely integrated environment (finished product) to assure desired operation.

REV. D 03/12

Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.