

# MINIATURE PRESSURE SENSORS

H-Grade  
Pressure Sensors



## Features

- 0 to 4" H<sub>2</sub>O to 0 to 100 PSI Pressure Ranges
- 0.5 % linearity...high accuracy version
- Temperature Compensated
- Calibrated Zero and Span

## Applications

- Medical Instrumentation
- Environmental Controls
- HVAC

## General Description

The Miniature series pressure sensors are based upon a proprietary technology to reduce the size of the sensor and yet maintain a high level of performance. This model provides a calibrated millivolt output with superior output offset characteristics. Output offset errors due to change in temperature, stability to warm-up, stability to long time period, and position sensitivity are all significantly reduced when compared to conventional compensation methods. In addition the sensor utilizes a silicon, micromachined, stress concentration enhanced structure to provide a very linear output to measured pressure.

These calibrated and temperature compensated sensors give an accurate and stable output over a wide temperature range. This series is intended for use with non-corrosive, non-ionic working fluids such as air, dry gases and the like. The H-GRADE is a high accuracy version of the millivolt output pressure sensors.

The output of the device is ratiometric to the supply voltage and operation from any D.C. supply voltage.

## Physical Dimensions



No Pressure Port




Single Pressure Port



Dual Pressure Port

Marking:  
right dot: gold: H-Grade  
left dot:  
L04: white  
L10: yellow  
0.3: pink  
L.0: green  
05: blue  
15: purple  
30: orange  
100: brown

## Equivalent Circuit



Input Resistance 5.0 k ohm

Output Resistance 3.0 k ohm

## Approvals

| MKT   | DATE | MFG   | DATE | ENG   | DATE | QA  | DATE |
|---|------|---|------|---|------|---|------|
| <input type="checkbox"/> As Is <input type="checkbox"/> With Change |      | <input type="checkbox"/> As Is <input type="checkbox"/> With Change |      | <input type="checkbox"/> As Is <input type="checkbox"/> With Change |      | <input type="checkbox"/> As Is <input type="checkbox"/> With Change |      |



## Pressure Sensor Characteristics Maximum Ratings

|  |         |
|--|---------|
| <b>Supply Voltage VS</b>                     | 16 Vdc  |
| <b>Common-mode pressure</b>                  | 50 psig |
| <b>Lead Temperature (soldering 2-4 sec.)</b> | 250°C   |

## Environmental Specifications

|                           |                                 |
|---------------------------|---------------------------------|
| <b>Temperature Ranges</b> |                                 |
| <b>Compensated</b>        | 0 to (50)70° C                  |
| <b>Operating</b>          | -25 to 85° C                    |
| <b>Storage</b>            | -40 to 125° C                   |
| <b>Humidity Limits</b>    | 0 to 95% RH<br>(non condensing) |

## Standard Pressure Ranges

| No Pressure Port      |                    | Single Pressure Port   |                       | Dual Pressure Port |  |
|-----------------------|--------------------|------------------------|-----------------------|--------------------|--|
| Part Number           | Operating Pressure | Part Number            | Part Number           | Proof Pressure     |  |
| 4 INCH-G-HGRADE-MINI  | 0 - 4 "H2O         | 4 INCH-GF-HGRADE-MINI  | 4 INCH-D-HGRADE-MINI  | 3 PSI              |  |
| 0.3 PSI-G-HGRADE-MINI | 0 - 0.3 PSI        | 0.3 PSI-GF-HGRADE-MINI | 0.3 PSI-D-HGRADE-MINI | 3 PSI              |  |
| 10 INCH-G-HGRADE-MINI | 0 - 10 "H2O        | 10 INCH-GF-HGRADE-MINI | 10 INCH-D-HGRADE-MINI | 5 PSI              |  |
| 1 PSI-G-HGRADE-MINI   | 0 - 1 PSI          | 1 PSI-GF-HGRADE-MINI   | 1 PSI-D-HGRADE-MINI   | 10 PSI             |  |
| 5 PSI-G-HGRADE-MINI   | 0 - 5 PSI          | 5 PSI-GF-HGRADE-MINI   | 5 PSI-D-HGRADE-MINI   | 20 PSI             |  |
| 15 PSI-A-HGRADE-MINI  | 0 - 15 PSIA        | 15 PSI-AF-HGRADE-MINI  |                       | 60 PSI             |  |
| 15 PSI-G-HGRADE-MINI  | 0-15 PSI           | 15 PSI-GF-HGRADE-MINI  | 15 PSI-D-HGRADE-MINI  | 60 PSI             |  |
| 30 PSI-A-HGRADE-MINI  | 0 -30 PSIA         | 30 PSI-AF-HGRADE-MINI  |                       | 60 PSI             |  |
| 30 PSI-G-HGRADE-MINI  | 0-30 PSI           | 30 PSI-GF-HGRADE-MINI  | 30 PSI-D-HGRADE-MINI  | 60 PSI             |  |
| 100 PSI-G-HGRADE-MINI | 0-100 PSI          | 100 PSI-GF-HGRADE-MINI |                       | 150 PSI            |  |

## Performance Characteristics for 4 INCH-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, differential pressure      | --      | 4.0     | --      | "H2O  |
| Output Span, note 5                         | 24      | 25      | 26      | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-50°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-50°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 10 INCH-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, differential pressure      | --      | 10.0    | --      | "H2O  |
| Output Span, note 5                         | 19      | 20      | 21      | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 0.3 PSI-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, differential pressure      | --      | 0.3     | --      | PSI   |
| Output Span, note 5                         | 19      | 20      | 21      | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 1 PSI-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, differential pressure      | --      | 1.0     | --      | PSI   |
| Output Span, note 5                         | 17.82   | 18.00   | 18.18   | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 5 PSI-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, differential pressure      | --      | 5.0     | --      | PSI   |
| Output Span, note 5                         | 59.4    | 60.0    | 60.6    | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 15 PSI-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, gage pressure              | --      | 15.0    | --      | PSI   |
| Output Span, note 5                         | 89.1    | 90.0    | 90.9    | mV    |
| Offset Voltage @ zero gage pressure         | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |



## Performance Characteristics for 15 PSI-A-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, absolute pressure          | --      | 15.0    | --      | PSIA  |
| Output Span, note 5                         | 89.1    | 90.0    | 90.9    | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 30 PSI-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, gage pressure              | --      | 30.0    | --      | PSI   |
| Output Span, note 5                         | 89.1    | 90.0    | 90.9    | mV    |
| Offset Voltage @ zero gage pressure         | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 30 PSI-A-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, absolute pressure          | --      | 30.0    | --      | PSIA  |
| Output Span, note 5                         | 89.1    | 90.0    | 90.9    | mV    |
| Offset Voltage @ zero differential pressure | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

## Performance Characteristics for 100 PSI-G-HGRADE-MINI

| Parameter, note 1                           | Minimum | Nominal | Maximum | Units |
|---|---------|---------|---------|-------|
| Operating Range, gage pressure              | --      | 100.0   | --      | PSI   |
| Output Span, note 5                         | 99.0    | 100.0   | 101.0   | mV    |
| Offset Voltage @ zero gage pressure         | --      | --      | ±0.5    | mV    |
| Offset Temperature Shift (0°C-70°C), note 2 | --      | --      | ±0.5    | mV    |
| Linearity, hysteresis error, note 4         | --      | 0.25    | 0.5     | %fs   |
| Span Shift (0°C-70°C), note 2               | --      | --      | ±1      | %fs   |

### Specification Notes

NOTE 1: ALL PARAMETERS ARE MEASURED AT 12.0 VOLT EXCITATION, FOR THE NOMINAL FULL SCALE PRESSURE AND ROOM TEMPERATURE UNLESS OTHERWISE SPECIFIED. PRESSURE MEASUREMENTS ARE WITH POSITIVE PRESSURE APPLIED TO PORT B.

NOTE 2: SHIFT IS RELATIVE TO 25°C.

NOTE 3: SHIFT IS WITHIN THE FIRST HOUR OF EXCITATION APPLIED TO THE DEVICE.

NOTE 4: MEASURED AT ONE-HALF FULL SCALE RATED PRESSURE USING BEST STRAIGHT LINE CURVE FIT.

NOTE 5: THE VOLTAGE ADDED TO THE OFFSET VOLTAGE AT FULL SCALE PRESSURE.

**Pressure Response: for any pressure applied the response time to get to 90% of pressure applied is typically less than 100 useconds.**

All Sensors reserves the right to make changes to any products herein. All Sensors does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.