

# ZXMN3A02X8

---

## 30V N-CANNEL ENHANCEMENT MODE MOSFET


---

### SUMMARY

$V_{(BR)DSS}=30V$ ;  $R_{DS(ON)}=0.025\Omega$   $I_D=6.7A$

### DESCRIPTION

This new generation of TRENCH MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.




### FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- Low profile SOIC package


### APPLICATIONS

- DC - DC Converters
- Power Management Functions
- Disconnect switches
- Motor control



### ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXMN3A02X8TA	7"	12mm	1000 units
ZXMN3A02X8TC	13"	12mm	4000 units



Top View

### DEVICE MARKING

- ZXMN  
3A02

# ZXMN3A02X8

## ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V <sub>DSS</sub>	30	V
Gate Source Voltage	V <sub>GS</sub>	±20	V
Continuous Drain Current V <sub>GS</sub> =10V; T <sub>A</sub> =25°C (b) V <sub>GS</sub> =10V; T <sub>A</sub> =70°C (b) V <sub>GS</sub> =10V; T <sub>A</sub> =25°C (a)	I <sub>D</sub>	6.7 5.4 5.3	A
Pulsed Drain Current (c)	I <sub>DM</sub>	24	A
Continuous Source Current (Body Diode) (b)	I <sub>S</sub>	3.2	A
Pulsed Source Current (Body Diode) (c)	I <sub>SM</sub>	24	A
Power Dissipation at T <sub>A</sub> =25°C (a) Linear Derating Factor	P <sub>D</sub>	1.1 8.8	W mW/°C
Power Dissipation at T <sub>A</sub> =25°C (b) Linear Derating Factor	P <sub>D</sub>	1.8 14.4	W mW/°C
Operating and Storage Temperature Range	T <sub>j</sub> :T <sub>stg</sub>	-55 to +150	°C

## THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient (a)	R <sub>θJA</sub>	113	°C/W
Junction to Ambient (b)	R <sub>θJA</sub>	70	°C/W

### NOTES

(a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions

(b) For a device surface mounted on FR4 PCB measured at t ≤ 10 secs.


(c) Repetitive rating 25mm x 25mm FR4 PCB, D = 0.05, pulse width 10μs - pulse width limited by maximum junction temperature.



ISSUE 1 - JANUARY 2002

# ZXMN3A02X8

## CHARACTERISTICS



\* For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.

# ZXMN3A02X8

**ELECTRICAL CHARACTERISTICS** (at  $T_A = 25^\circ\text{C}$  unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
<b>STATIC</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	30			V	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$
Zero Gate Voltage Drain Current	$I_{DSS}$			1	$\mu\text{A}$	$V_{DS}=30\text{V}, V_{GS}=0\text{V}$
Gate-Body Leakage	$I_{GSS}$			100	nA	$V_{GS}=\pm 20\text{V}, V_{DS}=0\text{V}$
Gate-Source Threshold Voltage	$V_{GS(th)}$	1			V	$I_D=250\mu\text{A}, V_{DS}=V_{GS}$
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$			0.025 0.035	$\Omega$ $\Omega$	$V_{GS}=10\text{V}, I_D=12\text{A}$ $V_{GS}=4.5\text{V}, I_D=10.2\text{A}$
Forward Transconductance (1)(3)	$g_{fs}$		22		S	$V_{DS}=10\text{V}, I_D=12\text{A}$
<b>DYNAMIC (3)</b>						
Input Capacitance	$C_{iss}$		1400		pF	$V_{DS}=25\text{V}, V_{GS}=0\text{V},$ $f=1\text{MHz}$
Output Capacitance	$C_{oss}$		209		pF	
Reverse Transfer Capacitance	$C_{rss}$		120		pF	
<b>SWITCHING(2) (3)</b>						
Turn-On Delay Time	$t_{d(on)}$		3.9		ns	$V_{DD}=15\text{V}, I_D=5.5\text{A}$ $R_G=6.2\Omega, V_{GS}=10\text{V}$ (refer to test circuit)
Rise Time	$t_r$		5.5		ns	
Turn-Off Delay Time	$t_{d(off)}$		35.0		ns	
Fall Time	$t_f$		7.6		ns	
Gate Charge	$Q_g$		14.5		nC	$V_{DS}=15\text{V}, V_{GS}=5\text{V},$ $I_D=5.5\text{A}$ (refer to test circuit)
Total Gate Charge	$Q_g$		26.8		nC	$V_{DS}=15\text{V}, V_{GS}=10\text{V},$ $I_D=5.5\text{A}$ (refer to test circuit)
Gate-Source Charge	$Q_{gs}$		4.7		nC	
Gate-Drain Charge	$Q_{gd}$		4.7		nC	
<b>SOURCE-DRAIN DIODE</b>						
Diode Forward Voltage (1)	$V_{SD}$			0.95	V	$T_J=25^\circ\text{C}, I_S=9\text{A},$ $V_{GS}=0\text{V}$
Reverse Recovery Time (3)	$t_{rr}$		17		ns	$T_J=25^\circ\text{C}, I_F=5.5\text{A},$ $di/dt= 100\text{A}/\mu\text{s}$
Reverse Recovery Charge (3)	$Q_{rr}$		8.3		nC	

## NOTES

(1) Measured under pulsed conditions. Width=300 $\mu\text{s}$ . Duty cycle  $\leq 2\%$ .

(2) Switching characteristics are independent of operating junction temperature.


(3) For design aid only, not subject to production testing.



ISSUE 1 - JANUARY 2002


# ZXMN3A02X8

## CHARACTERISTICS




# ZXMN3A02X8

## CHARACTERISTICS



# ZXMN3A02X8


## PACKAGE OUTLINE



## PACKAGE DIMENSION

DIM	Millimetres		Inches	
	MIN	MAX	MIN	MAX
A		1.10		0.043
A1	0.05	0.15	0.002	0.006
B	0.25	0.40	0.010	0.016
C	0.13	0.23	0.005	0.009
D	2.90	3.10	0.114	0.122
e	0.65	BSC	0.0256	BSC
E	2.90	3.10	0.114	0.122
H	4.90	BSC	0.193	BSC
L	0.40	0.70	0.016	0.028
$\theta^\circ$	0°	6°	0°	6°

## PAD LAYOUT



© Zetex plc 2001

Zetex plc  
Fields New Road  
Chadderton  
Oldham, OL9 8NP  
United Kingdom  
Telephone (44) 161 622 4422  
Fax: (44) 161 622 4420

Zetex GmbH  
Streitfeldstraße 19  
D-81673 München  
Germany  
Telefon: (49) 89 45 49 49 0  
Fax: (49) 89 45 49 49 49

Zetex Inc  
700 Veterans Memorial Hwy  
Hauppauge, NY11788  
USA  
Telephone: (631) 360 2222  
Fax: (631) 360 8222

Zetex (Asia) Ltd  
3701-04 Metroplaza, Tower 1  
Hing Fong Road  
Kwai Fong  
Hong Kong  
Telephone: (852) 26100 611  
Fax: (852) 24250 494

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to [www.zetex.com](http://www.zetex.com)

ISSUE 1 - JANUARY 2002

ZETEX



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.