

### Thermal Transfer Component Labels



- Use for identifying patch panels, faceplates, punchdown blocks and other network systems hardware
- Die-cut labels designed to provide maximum aesthetic quality and appearance
- Available in adhesive polyester and non-adhesive polyester materials
- Use with Panduit thermal transfer resin ribbons

Application Description	Typical Application Page	Code
Boxes – Surface Mount, Outlet, Hybrid	G.24	BX
Faceplates	G.2	FP
GP6™ Category 6 Punchdown Blocks	B.72	GP
Jack Modules	B.12	JM

Application Description	Typical Application Page	Code
Punchdown Blocks – 110	B.80	PB
Patch Panels	B.26 – B.27	PP
Racks and Cabinets	L.11	RK
Cable Marker Holder – SLCT	B.90	SL

Part Number	Part Description	Width		Height		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm		
C061X030YPT	White, adhesive polyester label, Mini-Com® 1-port identifier. Application codes: BX, FP, and PP.	0.61	15.5	0.30	7.6	2500	10000
C125X030YPT	White, adhesive polyester label, Mini-Com® 2-port identifier. Application codes: BX, FP, and PP.	1.25	31.8	0.30	7.6	2500	10000
C138X019YPT	White, adhesive polyester label, Mini-Com® module identifier. Application code: JM.	1.38	35.1	0.19	4.8	2500	10000
C138X019Y0T	Black, adhesive polyester label, Mini-Com® module identifier. Application code: JM.	1.38	35.1	0.19	4.8	2500	10000
C150X030Y1T	White, non-adhesive polyester label, Mini-Com® 3-port identifier. Application code: FP.	1.50	38.1	0.30	7.6	1000	5000
C188X030YPT	White, adhesive polyester label, Mini-Com® 3-port identifier. Application code: FP.	1.88	47.8	0.30	7.6	2500	10000
C195X040Y1T	White, non-adhesive polyester label, single gang faceplate. Application Code: FP.	1.95	49.5	0.40	10.2	2500	10000
C200X100YPT	White, adhesive polyester label, SLCT bundle marker identifier. Application code: SL and RK.	2.00	50.8	1.00	25.4	2500	10000
C200X100Y0T	Black, adhesive polyester label, SLCT bundle marker identifier. Application code: SL and RK.	2.00	50.8	1.00	25.4	2500	10000
C252X030YPT	White, adhesive polyester label, Mini-Com® 4-port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YPT-P*	White, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YQT-P*	Blue, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YRT-P*	Brown, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YST-P*	Green, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YTT-P*	Gray, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YUT-P*	Orange, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YVT-P*	Purple, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030YWT-P*	Red, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030Y0T-P*	Black, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.1	0.30	7.6	2500	10000
C252X030Y8T-P*	Yellow, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000
C252X030Y9T-P*	Gold, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	2500	10000

\*Label is perforated to be used in 1, 2, 3, or 4-position applications.

‡Label is perforated to be used in 1, 2, 3, 4, 5, or 6-position applications.

Order number of labels required in multiples of Std. Pkg. Qty.

Labels roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Table continues on next page

**Thermal Transfer Component Labels (continued)**

Part Number	Part Description	Width		Height		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm		
<b>C261X030YPT</b>	White, adhesive polyester label, Mini-Com <sup>®</sup> 4-port identifier. Application codes: FP and PP.	2.61	66.3	0.30	7.6	2500	10000
<b>C261X035Y1T</b>	White, non-adhesive polyester label, Mini-Com <sup>®</sup> 4-port identifier. Application codes: FP and PP.	2.61	66.3	0.35	8.9	2500	10000
<b>C275X125YPT</b>	White, adhesive polyester label, general identifier. Application code: RK.	2.75	69.9	1.25	31.8	2500	10000
<b>C275X125Y0T</b>	Black, adhesive polyester label, general identifier. Application code: RK.	2.75	69.9	1.25	31.8	2500	10000
<b>C288X030YPT</b>	White, adhesive polyester label, double gang faceplate identifier. Application code: FP.	2.88	73.2	0.30	7.6	2500	2500
<b>C288X040Y1T</b>	White, non-adhesive polyester label, Mini-Com <sup>®</sup> double-gang faceplate. Application code: FP.	2.88	73.2	0.40	10.2	1000	1000
<b>C315X030YPT</b>	White, adhesive polyester label, Mini-Com <sup>®</sup> 5-port identifier. Application code: FP.	3.15	80.0	0.30	7.6	2500	2500
<b>C379X030YPT</b>	White, adhesive polyester label, Mini-Com <sup>®</sup> 6-port identifier. Application code: FP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YPT-P‡</b>	White, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YQT-P‡</b>	Blue, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YRT-P‡</b>	Brown, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YST-P‡</b>	Green, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YTT-P‡</b>	Gray, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YUT-P‡</b>	Orange, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YVT-P‡</b>	Purple, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030YWT-P‡</b>	Red, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030Y0T-P‡</b>	Black, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030Y8T-P‡</b>	Yellow, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C379X030Y9T-P‡</b>	Gold, adhesive polyester label, Mini-Com <sup>®</sup> perforated port identifier. Application codes: BX, FP, and PP.	3.79	96.3	0.30	7.6	2500	10000
<b>C390X030Y1T</b>	White, non-adhesive polyester label, Mini-Com <sup>®</sup> 6-port identifier. Application code: PP.	3.90	99.1	0.30	7.6	2500	10000
<b>C750X050Y1T</b>	White, non-adhesive polyester label, 110 block identifier. Application code: PB.	7.50	190.5	0.50	12.7	2500	10000
<b>C788X050Y1T</b>	White, non-adhesive polyester label, GP6 System identifier. Application code: GP.	7.88	200.2	0.50	12.7	2500	10000

\*Label is perforated to be used in 1, 2, 3, or 4-position applications.

‡Label is perforated to be used in 1, 2, 3, 4, 5, or 6-position applications.

Order number of labels required in multiples of Std. Pkg. Qty.

Labels roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.