

Thermal Transfer Component Labels



- Use for identifying patch panels, faceplates, punchdown blocks and other network systems hardware
- Die-cut labels designed to provide maximum aesthetic quality and appearance
- Available in adhesive polyester and non-adhesive polyester materials
- Use with Panduit thermal transfer resin ribbons

| Application Description | Typical Application Page | Code |
|---------------------------------------|--------------------------|------|
| Boxes – Surface Mount, Outlet, Hybrid | G.24 | BX |
| Faceplates | G.2 | FP |
| GP6™ Category 6 Punchdown Blocks | B.72 | GP |
| Jack Modules | B.12 | JM |

| Application Description | Typical Application Page | Code |
|----------------------------|--------------------------|------|
| Punchdown Blocks – 110 | B.80 | PB |
| Patch Panels | B.26 – B.27 | PP |
| Racks and Cabinets | L.11 | RK |
| Cable Marker Holder – SLCT | B.90 | SL |

| Part Number | Part Description | Width | | Height | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|----------------|--|-------|------|--------|------|----------------|----------------|
| | | In. | mm | In. | mm | | |
| C061X030YPT | White, adhesive polyester label, Mini-Com® 1-port identifier. Application codes: BX, FP, and PP. | 0.61 | 15.5 | 0.30 | 7.6 | 2500 | 10000 |
| C125X030YPT | White, adhesive polyester label, Mini-Com® 2-port identifier. Application codes: BX, FP, and PP. | 1.25 | 31.8 | 0.30 | 7.6 | 2500 | 10000 |
| C138X019YPT | White, adhesive polyester label, Mini-Com® module identifier. Application code: JM. | 1.38 | 35.1 | 0.19 | 4.8 | 2500 | 10000 |
| C138X019Y0T | Black, adhesive polyester label, Mini-Com® module identifier. Application code: JM. | 1.38 | 35.1 | 0.19 | 4.8 | 2500 | 10000 |
| C150X030Y1T | White, non-adhesive polyester label, Mini-Com® 3-port identifier. Application code: FP. | 1.50 | 38.1 | 0.30 | 7.6 | 1000 | 5000 |
| C188X030YPT | White, adhesive polyester label, Mini-Com® 3-port identifier. Application code: FP. | 1.88 | 47.8 | 0.30 | 7.6 | 2500 | 10000 |
| C195X040Y1T | White, non-adhesive polyester label, single gang faceplate. Application Code: FP. | 1.95 | 49.5 | 0.40 | 10.2 | 2500 | 10000 |
| C200X100YPT | White, adhesive polyester label, SLCT bundle marker identifier. Application code: SL and RK. | 2.00 | 50.8 | 1.00 | 25.4 | 2500 | 10000 |
| C200X100Y0T | Black, adhesive polyester label, SLCT bundle marker identifier. Application code: SL and RK. | 2.00 | 50.8 | 1.00 | 25.4 | 2500 | 10000 |
| C252X030YPT | White, adhesive polyester label, Mini-Com® 4-port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YPT-P* | White, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YQT-P* | Blue, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YRT-P* | Brown, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YST-P* | Green, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YTT-P* | Gray, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YUT-P* | Orange, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YVT-P* | Purple, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030YWT-P* | Red, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030Y0T-P* | Black, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.1 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030Y8T-P* | Yellow, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |
| C252X030Y9T-P* | Gold, adhesive polyester label, Mini-Com® perforated port identifier. Application codes: BX, FP, and PP. | 2.52 | 64.0 | 0.30 | 7.6 | 2500 | 10000 |

*Label is perforated to be used in 1, 2, 3, or 4-position applications.

‡Label is perforated to be used in 1, 2, 3, 4, 5, or 6-position applications.

Order number of labels required in multiples of Std. Pkg. Qty.

Labels roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Table continues on next page

Thermal Transfer Component Labels (continued)

| Part Number | Part Description | Width | | Height | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-----------------------|--|-------|-------|--------|------|----------------|----------------|
| | | In. | mm | In. | mm | | |
| C261X030YPT | White, adhesive polyester label, Mini-Com [®] 4-port identifier. Application codes: FP and PP. | 2.61 | 66.3 | 0.30 | 7.6 | 2500 | 10000 |
| C261X035Y1T | White, non-adhesive polyester label, Mini-Com [®] 4-port identifier. Application codes: FP and PP. | 2.61 | 66.3 | 0.35 | 8.9 | 2500 | 10000 |
| C275X125YPT | White, adhesive polyester label, general identifier. Application code: RK. | 2.75 | 69.9 | 1.25 | 31.8 | 2500 | 10000 |
| C275X125Y0T | Black, adhesive polyester label, general identifier. Application code: RK. | 2.75 | 69.9 | 1.25 | 31.8 | 2500 | 10000 |
| C288X030YPT | White, adhesive polyester label, double gang faceplate identifier. Application code: FP. | 2.88 | 73.2 | 0.30 | 7.6 | 2500 | 2500 |
| C288X040Y1T | White, non-adhesive polyester label, Mini-Com [®] double-gang faceplate. Application code: FP. | 2.88 | 73.2 | 0.40 | 10.2 | 1000 | 1000 |
| C315X030YPT | White, adhesive polyester label, Mini-Com [®] 5-port identifier. Application code: FP. | 3.15 | 80.0 | 0.30 | 7.6 | 2500 | 2500 |
| C379X030YPT | White, adhesive polyester label, Mini-Com [®] 6-port identifier. Application code: FP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YPT-P‡ | White, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YQT-P‡ | Blue, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YRT-P‡ | Brown, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YST-P‡ | Green, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YTT-P‡ | Gray, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YUT-P‡ | Orange, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YVT-P‡ | Purple, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030YWT-P‡ | Red, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030Y0T-P‡ | Black, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030Y8T-P‡ | Yellow, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C379X030Y9T-P‡ | Gold, adhesive polyester label, Mini-Com [®] perforated port identifier. Application codes: BX, FP, and PP. | 3.79 | 96.3 | 0.30 | 7.6 | 2500 | 10000 |
| C390X030Y1T | White, non-adhesive polyester label, Mini-Com [®] 6-port identifier. Application code: PP. | 3.90 | 99.1 | 0.30 | 7.6 | 2500 | 10000 |
| C750X050Y1T | White, non-adhesive polyester label, 110 block identifier. Application code: PB. | 7.50 | 190.5 | 0.50 | 12.7 | 2500 | 10000 |
| C788X050Y1T | White, non-adhesive polyester label, GP6 System identifier. Application code: GP. | 7.88 | 200.2 | 0.50 | 12.7 | 2500 | 10000 |

*Label is perforated to be used in 1, 2, 3, or 4-position applications.

‡Label is perforated to be used in 1, 2, 3, 4, 5, or 6-position applications.

Order number of labels required in multiples of Std. Pkg. Qty.

Labels roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.