

## SERIES 88

Sealed, Flange Mounted


### FEATURES

- Sealed Keyboard
- Colorful Graphic Overlay
- Audible, Snap-Dome Contact
- User Legendable Styles
- 3,000,000 Operations per Button
- Optional Panel Seal Gasket to Protect Your Equipment




### DIMENSIONS In inches (and millimeters)

#### 3x4 Keyboard



### Termination In inches (and millimeters)

#### 3x4



### Code and Truth Table

Dots in the chart indicate connected terminals when switch is closed. Terminals are identified on the keyboard.

| 3x4             |    | CODES             |   |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  |   |
|-----------------|----|-------------------|---|---|---|---|---|---|---|------------------------|---|---|---|---|---|---|---|---|---|---|---|--|---|
|                 |    | Matrix            |   |   |   |   |   |   |   | Single Pole/Common Bus |   |   |   |   |   |   |   |   |   |   |   |  |   |
| BUTTON LOCATION | 1  | •                 |   |   |   | • |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 2  |                   | • |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 3  |                   |   | • |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 4  |                   | • |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 5  |                   |   | • |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 6  |                   |   |   | • |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 7  |                   | • |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 8  |                   |   | • |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 9  |                   |   |   | • |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 10 |                   | • |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 11 |                   |   | • |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 | 12 |                   |   |   | • |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  | • |
|                 |    | F                 | E | D | K | J | H | G | J | E                      | A | K | F | B | L | G | C | M | H | D | N |  |   |
|                 |    | TERMINAL LOCATION |   |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |  |   |

SINGLE POLE COMMON BUS TERMINAL


MATRIX TERMINAL PIN-OUT

## FEATURES


- Sealed Keyboard
- Colorful Graphic Overlay
- Audible, Snap-Dome Contact
- User Legendable Styles
- 3,000,000 Operations per Button
- Optional Panel Seal Gasket to Protect Your Equipment



### 4x4 Keyboard



### Code and Truth Table



Dots in the chart indicate connected terminals when switch is closed. Terminals are identified on the keyboard.

| 4x4             |    | CODES             |   |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
|-----------------|----|-------------------|---|---|---|---|---|---|---|------------------------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
|                 |    | Matrix            |   |   |   |   |   |   |   | Single Pole/Common Bus |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
| BUTTON LOCATION | 1  | ●                 |   |   |   | ● |   |   |   | ●                      |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 2  |                   | ● |   |   |   | ● |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 3  |                   |   | ● |   |   |   | ● |   |                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 4  |                   |   |   | ● |   |   |   | ● |                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 5  | ●                 |   |   |   |   |   |   |   |                        | ● |   |   |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 6  |                   | ● |   |   |   |   |   |   |                        |   | ● |   |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 7  |                   |   | ● |   |   |   |   |   |                        |   |   | ● |   |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 8  |                   |   |   | ● |   |   |   |   |                        |   |   |   | ● |   |   |   |   |   |   |   |   |   |   |   | ● |
|                 | 9  | ●                 |   |   |   |   |   |   |   |                        |   |   |   |   |   | ● |   |   |   |   |   |   |   |   |   | ● |
|                 | 10 |                   | ● |   |   |   |   |   |   |                        |   |   |   |   |   |   | ● |   |   |   |   |   |   |   |   | ● |
|                 | 11 |                   |   | ● |   |   |   |   |   |                        |   |   |   |   |   |   |   | ● |   |   |   |   |   |   |   | ● |
|                 | 12 |                   |   |   | ● |   |   |   |   |                        |   |   |   |   |   |   |   |   | ● |   |   |   |   |   |   | ● |
|                 | 13 | ●                 |   |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   | ● |   |   |   |   |   | ● |
|                 | 14 |                   | ● |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   | ● |   |   |   |   | ● |
|                 | 15 |                   |   | ● |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   | ● |   |   |   | ● |
|                 | 16 |                   |   |   | ● |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |   | ● |   |   | ● |
|                 |    | H                 | G | F | E | M | L | K | J |                        | P | J | E | A | R | L | F | B | S | M | H | C | T | N | G | D |
|                 |    | TERMINAL LOCATION |   |   |   |   |   |   |   |                        |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |

## SERIES 88

### Sealed, Flange Mounted


#### FEATURES

- Sealed Keyboard
- Colorful Graphic Overlay
- Audible, Snap-Dome Contact
- User Legendable Styles
- 3,000,000 Operations per Button
- Optional Panel Seal Gasket to Protect Your Equipment




#### DIMENSIONS In inches (and millimeters)

##### 5x4 Keyboard



#### Termination In inches (and millimeters)

##### 5x4 Keyboard



#### Code and Truth Table

Dots in the chart indicate connected terminals when switch is closed. Terminals are identified on the keyboard.

| 5x4             |    | CODES             |                                           |
|-----------------|----|-------------------|-------------------------------------------|
|                 |    | Matrix            | Single Pole/Common Bus                    |
| BUTTON LOCATION | 1  | •                 | •                                         |
|                 | 2  | •                 | •                                         |
|                 | 3  | •                 | •                                         |
|                 | 4  | •                 | •                                         |
|                 | 5  | •                 | •                                         |
|                 | 6  | •                 | •                                         |
|                 | 7  | •                 | •                                         |
|                 | 8  | •                 | •                                         |
|                 | 9  | •                 | •                                         |
|                 | 10 | •                 | •                                         |
|                 | 11 | •                 | •                                         |
|                 | 12 | •                 | •                                         |
|                 | 13 | •                 | •                                         |
|                 | 14 | •                 | •                                         |
|                 | 15 | •                 | •                                         |
|                 | 16 | •                 | •                                         |
|                 | 17 | •                 | •                                         |
|                 | 18 | •                 | •                                         |
|                 | 19 | •                 | •                                         |
|                 | 20 | •                 | •                                         |
|                 |    | P N K G F J L M H | T P M H D U Q L G C V R K F B W S J E A N |
|                 |    | TERMINAL LOCATION |                                           |

## SPECIFICATIONS

### Rating Criteria

**Rating at 24 Vdc:** 10 milliamps, resistive

**Contact Resistance:** Compatible with MOS, TTL and DTL (10 ohms maximum)

**Voltage Breakdown:** 250 Vac between mutually insulated parts

**Life Expectancy:** 3,000,000 operations per button

**Contact Bounce:** Less than 4 milliseconds at make, 10 milliseconds at break

**Temperature:** -40°C to +80°C

### Operating Features

**Button Travel:** 0.015"(0,38 mm) nominal total travel

**Typical Operating Force:** 350 grams

### Materials and Finishes

**Housing:** ABS polycarbonate, black

**Graphic Overlay:** Polyester

**Contact Dome:** Stainless steel, selectively gold-plated

**Terminals:** Phosphor bronze

## STANDARD LEGENDS

Colorful graphic overlays are polyester with a tough acrylic bond to provide maximum protection against dirt and moisture. Second surface printed, the overlay wipes clean and

continues to look bright and bold throughout the keyboard life. Available through distributors. For instant custom legends, order separate blank keyboards as indicated in the Ordering

Information section and choose one of the clear window overlays below; then order a sheet of legend inserts. Or, if you prefer, order the keyboard custom printed by Grayhill; see Ordering Information.



-143



-152



-172



-052



-072




-082



-252



-262




88-101

88AB2,  
88AC2



88-001

88BB2,  
88BC2



88-201

88JB2, 88JC2

## SEALING OF KEYBOARDS

The graphic legend is silk-screen printed on the second surface of a clear polyester film, providing maximum legend protection. It withstands high humidity, and it is resistant to scratching, marring, and dulling of the surface caused by fingernails, wiping cloths, and cleaning materials. It has excellent solvent resistance to water, petroleum oil, alcohols and aliphatic hydrocarbons.

These common liquids do not attack the overlay: 5% acetic acid, 5% citric acid, 2%

detergent solution, soapy water, 30% hydrogen peroxide, wine, beer, whiskey, coffee, cocoa, milk, tomato juice, lemon juice, etc. Hydrocarbons, ketones and freon do not affect the overlay. But, we recommend that you do not subject the keyboard to these chemicals, since they may affect the switch housing, which is ABS plastic. To discuss a particular solvent, contact Grayhill.

Protect your equipment in outdoor or harsh environmental conditions by sealing the

keyboard to the equipment panel. Use an optional gasket with the keyboard. There are two types of gaskets: one for mounting the keyboard beneath the panel, and one for mounting it above the equipment panel. See Panel Seal Gaskets.



The contact system is internally sealed by a special adhesive backed sheet that holds the domes in position on the PC board.

## PANEL SEAL GASKETS

Weatherproof and waterproof your subpanel and topside mounted keyboards with optional panel seal gaskets.

Subpanel keyboard gasket is .062" (1,57 mm) thick; topside keyboard gasket is .094" (2,39 mm).

Material is cellulose fiber, foam, nitrile rubber. Order gaskets separately from keyboard.



|              |                           |
|--------------|---------------------------|
| Subpanel 3x4 | <b>Part No. 88M2001-2</b> |
| Subpanel 4x4 | <b>Part No. 88M2009-2</b> |
| Subpanel 5x4 | <b>Part No. 88M2019-1</b> |
| Topside 3x4  | <b>Part No. 88M2012-1</b> |
| Topside 4x4  | <b>Part No. 88M2015-1</b> |
| Topside 5x4  | <b>Part No. 88M2018-1</b> |

| Size of Keyboard | Subpanel Mount                 |                                | Topside Mount                  |                                |
|------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
|                  | Dim. A                         | Dim. B                         | Dim. C                         | Dim. D                         |
| 3x4              | 2.010 ± .005<br>(51,05 ± 0,13) | 2.400 ± .005<br>(60,96 ± 0,13) | 1.800 ± .005<br>(45,72 ± 0,13) | 2.040 ± .005<br>(51,82 ± 0,13) |
| 4x4              | 2.510 ± .005<br>(63,75 ± 0,13) | 2.900 ± .005<br>(73,66 ± 0,13) | 2.300 ± .005<br>(58,42 ± 0,13) | 2.540 ± .005<br>(64,52 ± 0,13) |
| 5x4              | 3.010 ± .005<br>(76,45 ± 0,13) | 3.400 ± .005<br>(86,36 ± 0,13) | 2.800 ± .005<br>(71,12 ± 0,13) | 3.040 ± .005<br>(77,22 ± 0,13) |

## INSTANT CUSTOM LEGENDS

### Available through Distributors

Create your own legends using these 3 items: 1) a blank keyboard, 2) the clear window overlays shown on Standard Legend page and 3) a sheet of legend inserts.

### Blank Keyboards

The numbers below order blank keyboards for the user to legend. For description, refer to the part numbering scheme below. The keyboards and overlays are ordered separately.

|                |                       |
|----------------|-----------------------|
| 3x4 Matrix     | <b>Part No. 88AB2</b> |
| 3x4 SP/Com Bus | <b>Part No. 88AC2</b> |
| 4x4 Matrix     | <b>Part No. 88BB2</b> |
| 4x4 SP/Com Bus | <b>Part No. 88BC2</b> |
| 5x4 Matrix     | <b>Part No. 88JB2</b> |
| 5x4 SP/Com Bus | <b>Part No. 88JC2</b> |

### Legend Insert Sheet and Dry Transfers

Self-adhesive inserts are die-cut to fit the

button. Legends are printed in black on clear film in News Gothic Condensed type style. They include letters A through Z, numbers 0-9, telephone legends, commonly used words, symbols and blanks.

**Part No. 87AC2046**

Use matching dry transfer lettering on blank inserts of legend sheet: upper and lower case letters, 0-9, and common symbols.

|              |                                |
|--------------|--------------------------------|
| Small Print  | <b>Part No. 87-DT-2096-088</b> |
| Medium Print | <b>Part No. 87-DT-2096-125</b> |
| Large Print  | <b>Part No. 87-DT-2096-187</b> |

### Clear Window Overlays

Order separately from keyboards. See also ordering information.

|             |                        |
|-------------|------------------------|
| 3x4 Overlay | <b>Part No. 88-101</b> |
| 4x4 Overlay | <b>Part No. 88-001</b> |
| 5x4 Overlay | <b>Part No. 88-201</b> |

## PRINTED LEGENDS

**Not available through Distributors.** For medium volume applications, or where legends cannot be produced by the self legend method, you can order epoxy ink printed legends. Virtually anything which can be photographed can be printed. Grayhill will print your legend and then add the clear window overlay.

| Type I.D. No. | Simulated Style & Size | Character & Line Limitations * |
|---------------|------------------------|--------------------------------|
| 4GH088        | ABCDEFGH               | END DATA                       |
| 1GH125        | ABCDE                  | LAD                            |
| 3GH187        | ABCD                   | ON                             |
| 2GH250        | ABC                    | 15                             |

## ORDERING INFORMATION

|  |                                                 |
|--|-------------------------------------------------|
|  | <b>Grayhill Series Number</b>                   |
|  | <b>Size Option</b>                              |
|  | A = 3x4<br>B = 4x4<br>J = 5x4                   |
|  | <b>Circuitry Option</b>                         |
|  | B2 = Matrix code<br>C2 = Single pole/common bus |
|  | <b>Standard Legend Choices</b>                  |
|  | 3x4 Size: -143, -152, or -172                   |
|  | 4x4 Size: -052, -072 or -082                    |
|  | 5x4 Size: -252 or -262                          |

**Available from your local Grayhill Distributor.**

For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.