

## Description

The AP7315 is a low dropout regulator with high output voltage accuracy, low  $R_{DS(ON)}$ , high PSRR, low output noise and low quiescent current. This regulator is based on a CMOS process.

The AP7315 includes a voltage reference, error amplifier, current limit circuit and an enable input to turn it on and off. With the integrated resistor network fixed output voltage versions can be delivered.

With its low power consumption and line and load transient response, the AP7315 is well suited for low power handheld communication equipment.

The AP7315 is packaged in X2-DFN1010-4, SOT23 and SOT25 packages and allows for smallest footprint and dense PCB layout.


## Features

- Low  $V_{IN}$  and Wide  $V_{IN}$  Range: 1.7V to 5.25V
- Guarantee Output Current, 150mA
- $V_{OUT}$  Accuracy  $\pm 1\%$
- Ripple Rejection 75dB at 1kHz
- Low Output Noise, 60 $\mu$ Vrms from 10Hz to 100kHz
- Quiescent Current as Low as 35 $\mu$ A
- $V_{OUT}$  Fixed 1.1V to 3.3V
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free, Green Device (Note 3)**

## Applications


- Smart Phone/PAD
- RF Supply
- Cameras
- Portable Video
- Portable Media Player
- Wireless Adapter
- Wireless Communication

## Pin Assignments




Top View X2-DFN1010-4 Bottom View

Pin 1 –  $V_{OUT}$ , Pin 2 – GND, Pin 3 – EN, Pin 4 –  $V_{IN}$



SOT23 (SA)


SOT23 (SR)



SOT25

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


## Typical Applications Circuit



## Pin Descriptions

| Pin Name  | Pin Number   |       |            |            | Function                                                                                                                                                                                                     |
|-----------|--------------|-------|------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | X2-DFN1010-4 | SOT25 | SOT23 (SA) | SOT23 (SR) |                                                                                                                                                                                                              |
| $V_{OUT}$ | 1            | 5     | 2          | 2          | Power output pin                                                                                                                                                                                             |
| $GND$     | 2            | 2     | 3          | 1          | Ground                                                                                                                                                                                                       |
| $EN$      | 3            | —     | —          | —          | Enable pin. Active high                                                                                                                                                                                      |
| $V_{IN}$  | 4            | 1     | 1          | 3          | Power input pin                                                                                                                                                                                              |
| —         | Thermal PAD  | —     | —          | —          | In PCB layout, prefer to use large copper area to cover this pad for better thermal dissipation, then connect this area to $GND$ or leave it open. However, do not use it as $GND$ electrode function alone. |
| $EN/NC$   | —            | 3     | —          | —          | Enable pin. Active high/ NC, No connection                                                                                                                                                                   |
| $NC$      | —            | 4     | —          | —          | No connection                                                                                                                                                                                                |

## Functional Block Diagram



## Absolute Maximum Ratings (Note 4) (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Symbol           | Parameter                     | Ratings                      | Unit |
|------------------|-------------------------------|------------------------------|------|
| V <sub>IN</sub>  | Input Voltage                 | 6.0                          | V    |
| V <sub>EN</sub>  | Input Voltage EN              | 6.0                          | V    |
| V <sub>OUT</sub> | Output Voltage                | -0.3 to V <sub>IN</sub> +0.3 | V    |
| I <sub>OUT</sub> | Output Current                | 300                          | mA   |
| P <sub>D</sub>   | Power Dissipation             | 400                          | mW   |
| T <sub>A</sub>   | Operating Ambient Temperature | -40 to +85                   | °C   |
| T <sub>STG</sub> | Storage Temperature           | -55 to +125                  | °C   |

Note: 4. a). Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.  
b). Ratings apply to ambient temperature at +25°C. The JEDEC High-K board design used to derive this data is a 2in. x 2in. multi-layer board with 1oz. internal power and ground planes and 2oz. copper traces on the top and bottom of the board.

## Recommended Operating Conditions (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Symbol           | Parameter                     | Min | Max  | Unit |
|------------------|-------------------------------|-----|------|------|
| V <sub>IN</sub>  | Input Voltage                 | 1.7 | 5.25 | V    |
| I <sub>OUT</sub> | Output Current                | 0   | 150  | mA   |
| T <sub>A</sub>   | Operating Ambient Temperature | -40 | +85  | °C   |

# Electrical Characteristics

( $V_{EN} = V_{IN} = V_{OUT} + 1.0V$ ,  $C_{IN} = C_{OUT} = 0.47\mu F$ ,  $I_{OUT} = 1.0mA$  @  $T_A = +25^\circ C$ , unless otherwise specified.)


| Parameter                                                                 | Conditions                                                                                                            |                                | Min                     | Typ              | Max                     | Units  |
|---------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|--------------------------------|-------------------------|------------------|-------------------------|--------|
| Input Voltage                                                             | T <sub>A</sub> = -40°C to +85°C                                                                                       |                                | 1.7                     | —                | 5.25                    | V      |
| Output Voltage Accuracy (Note 11)                                         | V <sub>OUT</sub> ≥ 2.0V, V <sub>IN</sub> = V <sub>OUT</sub> +1V, T <sub>A</sub> = +25°C                               |                                | V <sub>OUT</sub> *0.99  | V <sub>OUT</sub> | V <sub>OUT</sub> *1.01  | V      |
|                                                                           | V <sub>OUT</sub> < 2.0V, V <sub>IN</sub> = V <sub>OUT</sub> +1V, T <sub>A</sub> = +25°C                               |                                | V <sub>OUT</sub> - 20mV | V <sub>OUT</sub> | V <sub>OUT</sub> + 20mV | V      |
| Line Regulation (dV <sub>OUT</sub> /dV <sub>IN</sub> /V <sub>OUT</sub> )  | V <sub>IN</sub> = (V <sub>OUT</sub> – N <sub>om</sub> + 1.0V) to 5.25V, I <sub>OUT</sub> = 1.0mA                      |                                | —                       | 0.02             | 0.1                     | %/V    |
| Load Regulation (dV <sub>OUT</sub> /V <sub>OUT</sub> /dI <sub>OUT</sub> ) | V <sub>IN</sub> = V <sub>OUT</sub> - N <sub>om</sub> + 1.0V, I <sub>OUT</sub> = 1mA to 150mA                          |                                | —                       | 0.5              | 1.0                     | %/A    |
| Quiescent Current (Note 6)                                                | I <sub>OUT</sub> = 0mA                                                                                                |                                | 20                      | 35               | 60                      | μA     |
|                                                                           | I <sub>OUT</sub> = 150mA                                                                                              |                                | 30                      | 60               | 100                     |        |
| I <sub>STANDBY</sub>                                                      | V <sub>EN</sub> = 0V (Disabled)                                                                                       |                                | —                       | 0.01             | 1.0                     | μA     |
| Output Current                                                            | —                                                                                                                     |                                | 150                     | —                | —                       | mA     |
| Fold-back Short Current (Note 7)                                          | V <sub>OUT</sub> Short to Ground                                                                                      |                                | —                       | 55               | —                       | mA     |
| PSRR (Note 8)                                                             | V <sub>IN</sub> = (V <sub>OUT</sub> +1V)V <sub>DC</sub> + 0.2Vp-pAC, V <sub>OUT</sub> ≥ 1.8V, I <sub>OUT</sub> = 30mA | f = 1kHz                       | —                       | 75               | —                       | dB     |
| Output Noise Voltage (Notes 8, 9)                                         | BW = 10Hz to 100kHz, I <sub>OUT</sub> = 30mA                                                                          |                                | —                       | 60               | —                       | μVrms  |
| Dropout Voltage (Note 5)                                                  | I <sub>OUT</sub> = 150mA                                                                                              | 1.1V ≤ V <sub>OUT</sub> < 1.5V | —                       | 0.50             | 0.64                    | V      |
|                                                                           |                                                                                                                       | 1.5V ≤ V <sub>OUT</sub> < 1.7V | —                       | 0.38             | 0.49                    |        |
|                                                                           |                                                                                                                       | 1.7V ≤ V <sub>OUT</sub> < 2.0V | —                       | 0.34             | 0.44                    |        |
|                                                                           |                                                                                                                       | 2.0V ≤ V <sub>OUT</sub> < 2.5V | —                       | 0.28             | 0.38                    |        |
|                                                                           |                                                                                                                       | 2.5V ≤ V <sub>OUT</sub> < 2.8V | —                       | 0.22             | 0.32                    |        |
|                                                                           |                                                                                                                       | 2.8V ≤ V <sub>OUT</sub> ≤ 3.3V | —                       | 0.21             | 0.29                    |        |
| Output Voltage Temperature Coefficient                                    | I <sub>OUT</sub> = 30mA, T <sub>A</sub> = -40°C to +85°C                                                              |                                | —                       | ±30              | —                       | ppm/°C |
| EN Input Low Voltage                                                      | —                                                                                                                     |                                | 0                       | —                | 0.5                     | V      |
| EN Input High Voltage                                                     | —                                                                                                                     |                                | 1.3                     | —                | 5.25                    | V      |
| EN Input Leakage                                                          | V <sub>EN</sub> = 0, V <sub>IN</sub> = 5.0V or V <sub>EN</sub> = 5.0V, V <sub>IN</sub> = 0V                           |                                | -1.0                    | —                | +1.0                    | μA     |
| On Resistance of N-channel for Auto-Discharge (Note 10)                   | V <sub>IN</sub> = 4.0V V <sub>EN</sub> = 0V (Disabled)                                                                |                                | —                       | 30               | —                       | Ω      |

- Notes:
- Dropout voltage is the voltage difference between the input and the output at which the output voltage drops 2% below its nominal value.
  - Quiescent current is defined here is the difference in current between the input and the output.
  - Short circuit current is measured with  $V_{OUT}$  pulled to GND.
  - This specification is guaranteed by design.
  - To make sure lowest environment noise minimizes the influence on noise measurement.
  - AP7315 has 2 options for output, built-in discharge and non-discharge.
  - Potential multiple grades based on following output voltage accuracy.

## Typical Characteristics


Output Voltage vs. Output Current

AP7315-18




Output Voltage vs. Output Current

AP7315-25




Output Voltage vs. Output Current

AP7315-33




Output Noise (AP7315-33)




Output Voltage vs. Input Voltage

AP7315-25



Output Voltage vs. Input Voltage

AP7315-33




**Typical Characteristics (Cont.)**

NEW PRODUCT


**Supply Current vs. Input Voltage**

AP7315-25




**Supply Current vs. Input Voltage**

AP7315-33




**Output Voltage vs. Temperature**

AP7315-25




**Output Voltage vs. Temperature**

AP7315-33




**Supply Current vs. Temperature**

AP7315-25



**Supply Current vs. Temperature**


AP7315-33




**Typical Characteristics (Cont.)**

NEW PRODUCT


**Dropout Voltage vs. Output Current**  
AP7315-25




**Dropout Voltage vs. Output Current**  
AP7315-33




**Dropout Voltage vs. Temperature**  
AP7315-25




**Dropout Voltage vs. Temperature**  
AP7315-33



**Ripple Rejection vs. Frequency**  
AP7315-18




**Ripple Rejection vs. Frequency**  
AP7315-25




# Typical Characteristics (Cont.)

## Ripple Rejection vs. Frequency


AP7315-33




AP7315-25




AP7315-33



AP7315-25  $V_{IN}=3.5V$   
 $tr=tf=0.5\mu s$









AP7315-33  $V_{IN}=4.3V$   
 $tr=tf=0.5\mu s$







**Typical Characteristics (Cont.)**

NEW PRODUCT



**Typical Characteristics (Cont.)**



## Application Information

### Output Capacitor

An output capacitor ( $C_{OUT}$ ) is needed to improve transient response and maintain stability. The AP7315 is stable with very small ceramic output capacitors. The ESR (equivalent series resistance) and capacitance drives the selection. If the application has large load variations, it is recommended to utilize low-ESR bulk capacitors. It is recommended to place ceramic capacitors as close as possible to the load and the ground pin and care should be taken to reduce the impedance in the layout.

### Input Capacitor

To prevent the input voltage from dropping during load steps it is recommended to utilize an input capacitor ( $C_{IN}$ ). A minimum  $0.47\mu\text{F}$  ceramic capacitor is recommended between  $V_{IN}$  and GND pins to decouple input power supply glitch. This input capacitor must be located as close as possible to the device to assure input stability and reduce noise. For PCB layout, a wide copper trace is required for both  $V_{IN}$  and GND pins.

### Enable Control

The AP7315 is turned on by setting the EN pin high, and is turned off by pulling it low. If this feature is not used, the EN pin should be tied to  $V_{IN}$  pin to keep the regulator output on at all time. To ensure proper operation, the signal source used to drive the EN pin must be able to swing above and below the specified turn-on/off voltage thresholds listed in the Electrical Characteristics section.

### Short Circuit Protection

When  $V_{OUT}$  pin is short-circuit to GND, short circuit protection will be triggered and clamp the output current to approximately 60mA. This feature protects the regulator from over-current and damage due to overheating.

### Layout Considerations



For good ground loop and stability, the input and output capacitors should be located close to the  $V_{IN}$ ,  $V_{OUT}$ , and GND pins of the device. The regulator GND pin should be connected to the external circuit ground to reduce voltage drop caused by trace impedance. Ground plane is generally used to reduce trace impedance. Wide trace should be used for large current paths from  $V_{IN}$  to  $V_{OUT}$ , and load circuit.


## ESR vs. Output Current

Ceramic type output capacitor is recommended for this series; however, the other output capacitors with low ESR also can be used. The relations between  $I_{OUT}$  (Output Current) and ESR of an output capacitor are shown below. The stable region is marked as the hatched area in the graph.

Measurement conditions:

Frequency Band: 10Hz to 2MHz, Temperature:  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$



**Ordering Information** (Note 12)



| Part Number       | Package Code | Packaging    | 7" Tape and Reel  |                    |
|-------------------|--------------|--------------|-------------------|--------------------|
|                   |              |              | Quantity          | Part Number Suffix |
| AP7315-XXXFS4-7B  | FS4          | X2-DFN1010-4 | 10000/Tape & Reel | -7B                |
| AP7315D-XXXFS4-7B | FS4          | X2-DFN1010-4 | 10000/Tape & Reel | -7B                |
| AP7315-XXXW5-7    | W5           | SOT25        | 3000/Tape & Reel  | -7                 |
| AP7315D-XXXW5-7   | W5           | SOT25        | 3000/Tape & Reel  | -7                 |
| AP7315-XXXSA-7    | SA           | SOT23        | 3000/Tape & Reel  | -7                 |
| AP7315-XXXSR-7    | SR           | SOT23        | 3000/Tape & Reel  | -7                 |

Note: 12. For packaging details, go to our website at <http://www.diodes.com/products/packages.html>.

## Marking Information

(1) X2-DFN1010-4

(Top View)



XXX : Identification Code


Y : Year : 0~9

W : Week : A~Z : 1~26 week;  
a~z : 27~52 week; z represents  
52 and 53 week

X : Internal Code

| Part Number       | Package      | Identification Code |
|-------------------|--------------|---------------------|
| AP7315-11FS4-7B   | X2-DFN1010-4 | 15A                 |
| AP7315-12FS4-7B   | X2-DFN1010-4 | 15B                 |
| AP7315-135FS4-7B  | X2-DFN1010-4 | 15C                 |
| AP7315-15FS4-7B   | X2-DFN1010-4 | 15D                 |
| AP7315-18FS4-7B   | X2-DFN1010-4 | 15E                 |
| AP7315-185FS4-7B  | X2-DFN1010-4 | 15F                 |
| AP7315-22FS4-7B   | X2-DFN1010-4 | 15G                 |
| AP7315-23FS4-7B   | X2-DFN1010-4 | 15H                 |
| AP7315-25FS4-7B   | X2-DFN1010-4 | 15J                 |
| AP7315-26FS4-7B   | X2-DFN1010-4 | 15K                 |
| AP7315-28FS4-7B   | X2-DFN1010-4 | 15M                 |
| AP7315-285FS4-7B  | X2-DFN1010-4 | 15N                 |
| AP7315-295FS4-7B  | X2-DFN1010-4 | 15P                 |
| AP7315-30FS4-7B   | X2-DFN1010-4 | 15R                 |
| AP7315-31FS4-7B   | X2-DFN1010-4 | 15S                 |
| AP7315-32FS4-7B   | X2-DFN1010-4 | 15T                 |
| AP7315-33FS4-7B   | X2-DFN1010-4 | 15U                 |
| AP7315D-11FS4-7B  | X2-DFN1010-4 | 5DA                 |
| AP7315D-12FS4-7B  | X2-DFN1010-4 | 5DB                 |
| AP7315D-135FS4-7B | X2-DFN1010-4 | 5DC                 |
| AP7315D-15FS4-7B  | X2-DFN1010-4 | 5DD                 |
| AP7315D-18FS4-7B  | X2-DFN1010-4 | 5DE                 |
| AP7315D-185FS4-7B | X2-DFN1010-4 | 5DF                 |
| AP7315D-22FS4-7B  | X2-DFN1010-4 | 5DG                 |
| AP7315D-23FS4-7B  | X2-DFN1010-4 | 5DH                 |
| AP7315D-25FS4-7B  | X2-DFN1010-4 | 5DJ                 |
| AP7315D-26FS4-7B  | X2-DFN1010-4 | 5DK                 |
| AP7315D-28FS4-7B  | X2-DFN1010-4 | 5DM                 |
| AP7315D-285FS4-7B | X2-DFN1010-4 | 5DN                 |
| AP7315D-29FS4-7B  | X2-DFN1010-4 | 5DP                 |
| AP7315D-295FS4-7B | X2-DFN1010-4 | 5DR                 |
| AP7315D-30FS4-7B  | X2-DFN1010-4 | 5DS                 |
| AP7315D-31FS4-7B  | X2-DFN1010-4 | 5DT                 |
| AP7315D-32FS4-7B  | X2-DFN1010-4 | 5DU                 |
| AP7315D-33FS4-7B  | X2-DFN1010-4 | 5DV                 |

**Marking Information** (Cont.)

**(2) SOT25**
**(Top View)**

XXX : Identification Code


Y : Year 0 to 9

W : Week : A to Z : 1 to 26 week;  
a to z : 27 to 52 week; z represents  
52 and 53 week

X : Internal Code

| Part Number     | Package | Identification Code |
|-----------------|---------|---------------------|
| AP7315-11W5-7   | SOT25   | 15A                 |
| AP7315-12W5-7   | SOT25   | 15B                 |
| AP7315-13W5-7   | SOT25   | 15C                 |
| AP7315-15W5-7   | SOT25   | 15D                 |
| AP7315-18W5-7   | SOT25   | 15E                 |
| AP7315-185W5-7  | SOT25   | 15F                 |
| AP7315-22W5-7   | SOT25   | 15G                 |
| AP7315-23W5-7   | SOT25   | 15H                 |
| AP7315-25W5-7   | SOT25   | 15J                 |
| AP7315-26W5-7   | SOT25   | 15K                 |
| AP7315-28W5-7   | SOT25   | 15M                 |
| AP7315-285W5-7  | SOT25   | 15N                 |
| AP7315-295W5-7  | SOT25   | 15P                 |
| AP7315-30W5-7   | SOT25   | 15R                 |
| AP7315-31W5-7   | SOT25   | 15S                 |
| AP7315-32W5-7   | SOT25   | 15T                 |
| AP7315-33W5-7   | SOT25   | 15U                 |
| AP7315D-11W5-7  | SOT25   | 5DA                 |
| AP7315D-12W5-7  | SOT25   | 5DB                 |
| AP7315D-13W5-7  | SOT25   | 5DC                 |
| AP7315D-15W5-7  | SOT25   | 5DD                 |
| AP7315D-18W5-7  | SOT25   | 5DE                 |
| AP7315D-185W5-7 | SOT25   | 5DF                 |
| AP7315D-22W5-7  | SOT25   | 5DG                 |
| AP7315D-23W5-7  | SOT25   | 5DH                 |
| AP7315D-25W5-7  | SOT25   | 5DJ                 |
| AP7315D-26W5-7  | SOT25   | 5DK                 |
| AP7315D-28W5-7  | SOT25   | 5DM                 |
| AP7315D-285W5-7 | SOT25   | 5DN                 |
| AP7315D-29W5-7  | SOT25   | 5DP                 |
| AP7315D-295W5-7 | SOT25   | 5DR                 |
| AP7315D-30W5-7  | SOT25   | 5DS                 |
| AP7315D-31W5-7  | SOT25   | 5DT                 |
| AP7315D-32W5-7  | SOT25   | 5DU                 |
| AP7315D-33W5-7  | SOT25   | 5DV                 |

**Marking Information** (Cont.)

**(3) SOT23**
**(Top View)**

XXX : Identification Code

Y : Year 0 to 9

W : Week : A to Z : 1 to 26 week;  
a to z : 27 to 52 week; z represents  
52 and 53 week


X : Internal Code

| Part Number    | Package | Identification Code |
|----------------|---------|---------------------|
| AP7315-11SA-7  | SOT23   | 15A                 |
| AP7315-12SA-7  | SOT23   | 15B                 |
| AP7315-135SA-7 | SOT23   | 15C                 |
| AP7315-15SA-7  | SOT23   | 15D                 |
| AP7315-18SA-7  | SOT23   | 15E                 |
| AP7315-185SA-7 | SOT23   | 15F                 |
| AP7315-22SA-7  | SOT23   | 15G                 |
| AP7315-23SA-7  | SOT23   | 15H                 |
| AP7315-25SA-7  | SOT23   | 15J                 |
| AP7315-26SA-7  | SOT23   | 15K                 |
| AP7315-28SA-7  | SOT23   | 15M                 |
| AP7315-285SA-7 | SOT23   | 15N                 |
| AP7315-295SA-7 | SOT23   | 15P                 |
| AP7315-30SA-7  | SOT23   | 15R                 |
| AP7315-31SA-7  | SOT23   | 15S                 |
| AP7315-32SA-7  | SOT23   | 15T                 |
| AP7315-33SA-7  | SOT23   | 15U                 |
| AP7315-11SR-7  | SOT23   | 5DA                 |
| AP7315-12SR-7  | SOT23   | 5DB                 |
| AP7315-135SR-7 | SOT23   | 5DC                 |
| AP7315-15SR-7  | SOT23   | 5DD                 |
| AP7315-18SR-7  | SOT23   | 5DE                 |
| AP7315-185SR7  | SOT23   | 5DF                 |
| AP7315-22SR-7  | SOT23   | 5DG                 |
| AP7315-23SR-7  | SOT23   | 5DH                 |
| AP7315-25SR-7  | SOT23   | 5DJ                 |
| AP7315-26SR-7  | SOT23   | 5DK                 |
| AP7315-28SR-7  | SOT23   | 5DM                 |
| AP7315-285SR-7 | SOT23   | 5DN                 |
| AP7315-295SR-7 | SOT23   | 5DR                 |
| AP7315-30SR-7  | SOT23   | 5DS                 |
| AP7315-31SR-7  | SOT23   | 5DT                 |
| AP7315-32SR-7  | SOT23   | 5DU                 |
| AP7315-33SR-7  | SOT23   | 5DV                 |

## Package Outline Dimensions


Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for the latest version.

### (1) Package Type: X2-DFN1010-4



| X2-DFN1010-4         |      |      |       |
|----------------------|------|------|-------|
| Dim                  | Min  | Max  | Typ   |
| A                    | -    | 0.40 | 0.39  |
| A1                   | 0.00 | 0.05 | 0.02  |
| A3                   | -    | -    | 0.13  |
| b                    | 0.20 | 0.30 | 0.25  |
| D                    | 0.95 | 1.05 | 1.00  |
| D2                   | 0.38 | 0.58 | 0.48  |
| E                    | 0.95 | 1.05 | 1.00  |
| E2                   | 0.38 | 0.58 | 0.48  |
| e                    | -    | -    | 0.65  |
| L                    | 0.20 | 0.30 | 0.25  |
| L1                   | 0.27 | 0.37 | 0.32  |
| L2                   | 0.02 | 0.12 | 0.07  |
| Z                    | -    | -    | 0.050 |
| All Dimensions in mm |      |      |       |


**Package Outline Dimensions** (All dimensions in mm.)

**(2) Package Type: SOT23**


NEW PRODUCT

**Package Outline Dimensions** (All dimensions in mm.)

(3) Package Type: SOT25




NEW PRODUCT

## Suggested Pad Layout

Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.


(1) Package Type: X2-DFN1010-4



| Dimensions | Value<br>(in mm) |
|------------|------------------|
| C          | 0.650            |
| X          | 0.250            |
| X1         | 0.480            |
| X2         | 0.900            |
| X3         | 0.070            |
| Y          | 0.400            |
| Y1         | 0.470            |
| Y2         | 0.220            |
| Y3         | 0.480            |
| Y4         | 1.300            |
| Y5         | 0.180            |

## Suggested Pad Layout (Cont.)


(2) Package Type: SOT23



| Dimensions | Z<br>(mm)/(inch) | G<br>(mm)/(inch) | X<br>(mm)/(inch) | Y<br>(mm)/(inch) | E<br>(mm)/(inch) |
|------------|------------------|------------------|------------------|------------------|------------------|
| Value      | 2.900/0.114      | 1.100/0.043      | 0.800/0.031      | 0.900/0.035      | 0.950/0.037      |

## Suggested Pad Layout (Cont.)



(3) Package Type: SOT25



| Dimensions | Z<br>(mm)/(inch) | G<br>(mm)/(inch) | X<br>(mm)/(inch) | Y<br>(mm)/(inch) | E1<br>(mm)/(inch) | E2<br>(mm)/(inch) |
|------------|------------------|------------------|------------------|------------------|-------------------|-------------------|
| Value      | 3.600/0.142      | 1.600/0.063      | 0.700/0.028      | 1.000/0.039      | 0.950/0.037       | 1.900/0.075       |

## Tape Orientation

For AP7315-XXXFS4-7B & AP7315D-XXXFS4-7B



Note: 13. The taping orientation of the other package type can be found on our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2015, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.