

SENCITY® Omni-S Thimble 1399.17.0224

Description

Broadband omnidirectional WiFi & Cellular antenna from 1710 MHz up to 7125 MHz
 WiFi-4, WiFi-5, WiFi-6, WiFi-6E
 4G and 5G frequencies band
 Small & robust outdoor stick antenna IP66 / IP68 / IP69K
 Direct mount on N type connector of wireless access points or clients



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	1710 - 2000	2000 - 2700	2700 - 4200	4900 - 5150
VSWR	2	2	2	2
Impedance (Ohm)	50	50	50	50
Gain (dBi)	1.5	2	1.5	2.5
3dB beamwidth (h) (°)	360	360	360	360
Composite power max (W)	200	160	120	120
Ambient temperature (°C)	25	25	25	25

	Band 5	Band 6
Frequency (MHz)	5150 - 5925	5925 - 7125
VSWR	2	2
Impedance (Ohm)	50	50
Gain (dBi)	2.5	3
3dB beamwidth (h) (°)	360	360
Composite power max (W)	120	120
Ambient temperature (°C)	25	25

Ports

	Port 1
Connector	N, plug (male)
Polarization	vertical
DC grounded	No

General Data

Mechanical Data

Dimensions (mm) 55 x 22 (Height x Diameter)
 Weight (kg) 0.05

Coupling nut torque: nominal 1Nm
 maximum 3Nm

Environmental Data

Environmental conditions outdoor
 Operation temperature (°C) -40 to 85
 Storage temperature (°C) -40 to 85
 Transport temperature (°C) -40 to 85
 IP rating IP66, IP68
 Flammability rating UL 94-HB
 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant
 Lead-free soldered not soldered
 WEEE 2012/19/EU special marking needed
 REACH 1907/2006/EC compliant

SENCITY® Omni-S Thimble 1399.17.0224

Ingress protection IP66, IP68 & IP69K (EN 60529)

Flammability rating EN 45545 DIN 5510-2

Temperature range (damp heat) EN 60068-2-30, Test Db, Variant 1 (40°C 6 cycles)

Temperature shock EN 60068-2-14, Test N, -45°C/85°C, 1h, 5 cycles

Vibration and shock EN 61373, category 1, class b (for railway carriage)

Material Data

Radome colour	RAL 7043 (dark grey)
Radome material	ASA (acrylic ester-styrene-acrylonitrile)

Related Documents

Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00248614
3D-model	DOC-0000424893

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[1399.17.0224](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.