

PART NUMBER EXAMPLE: **Q2-F-3/64-01-QB48IN-25**

PART NUMBER EXAMPLE:

X - X - X - X X - X

- (6) QUANTITY - QB (Q BAG) ONLY
- (5) LENGTH - SEE LIST BELOW
- (4) STANDARD PACKAGING CODES - SEE LIST BELOW
- (3) COLOR - SEE LIST BELOW
- (2) SIZE - SEE TABLE BELOW
- (1) TYPE - SEE SPEC SHEET(Q1, Q2-F, Q-150K, etc...)

NOTE: Table below represents information on individual spec sheet

- ④ **STANDARD PACKAGING CODES:**
MS - MINI SPOOL + LENGTH (FT or M)
QB - Q BAG (Polybag contains quantity specified)
QX - Q BOX + LENGTH (FT or M)
RK - REFILL BAG
SS - STANDARD SPOOL + LENGTH (FT or M)

- ③ **COLOR CODES:**
01 BLACK
02 CLEAR
03 WHITE
04 RED
05 BLUE
06 GREEN
07 YELLOW
08 YELLOW / GREEN
09 BROWN
10 ORANGE
11 ASSORTED COLORS
12 GRAY

- ⑤ **LENGTH:**
FT = FEET
M = METERS
IN = INCH
MM = MILLIMETERS

HEAT SHRINK THIN WALL TUBING Qualtek Electronics

Q2-F RoHS Compliant

FLEXIBLE, FLAME RETARDANT POLYOLEFIN TUBING
ENVIRONMENT FRIENDLY, HIGHLY FLAME RETARDANT
SHRINK RATIO 2:1

Features/Applications
 Provides both commercial and military applications electrical insulation and protects in-line components, disconnect terminals and splices with its high strength and excellent resilience. Bundles wires for very flexible light-duty harnesses. Identifies or color-codes wires, cables, terminals and components.

- Operating temperature: -55°C to +135°C
- Minimum shrink temperature: 70°C
- Full recovery temperature: 100°C
- Approval: **UL**, File No. E236137, **CS** 242540
- 125°C, VW-1, 600V
- Meets: SAE-AMS-DTL-2205/35 Class 1 & 3, Sony-SS-00259
- Material: No PBB's, PBBO's, PBBE's, Free of Cadmium & Lead
- Standard colors: Black, red, blue, yellow, green, white, clear (class 2)
- RoHS Compliant

Technical Data		
Property	Test Method	Typical Data
RoHS Status	ASTM D2011	RoHS
Exemption of Lead	ASTM D2011	RoHS
Temperature/Aging (100°C/168 hrs.)		50%
Flammability	UL 94V-0, SAE-AMS-DTL-2205/35	Pass
Thermal Shrink (100°C)	ASTM D2011	2:1 (max)
Color Retention (100°C/4 hrs.)	ASTM D2011	Non-bleeding
Dielectric Strength	ASTM D149	30KV/mm
Volume Resistance	ASTM D199	>10 ¹² Ohm-cm
Surface Resistance	UL 224	Pass
Water Absorption	ASTM D570	0.15%
Chemical Resistance	SAE-AMS-DTL-2205/35	Pass
Longitudinal Tensile	UL 224	5.2% Elong
Elongation	UL 224	>30%

Product Dimensions							
Size (Inch)	As Supplied (mm)			After Recovered (mm)			Standard Packaging
	Inside Diameter (min.)	Inside Diameter (max.)	Wall Thickness (min.)	Mini Spool (MS) (Feet)	Standard Spool (SS) (Feet)	Box Length (QX) (Feet)	Cut Length Pcs. Qty per bag
3/64	1.2	0.6	0.40	100	1000	50	48
1/16	1.6	0.8	0.40	100	1000	50	36
3/32	2.4	1.2	0.48	100	500	50	32
1/8	3.2	1.6	0.48	100	500	50	28
3/16	4.8	2.4	0.48	100	500	30	25
1/4	6.4	3.2	0.56	100	500	30	25
5/16	8.0	4.0	0.62	100	250	30	18
3/8	9.5	4.8	0.62	100	250	30	18
1/2	12.7	6.4	0.62	100	200	15	14
5/8	15.9	8.0	0.68	50	200	15	14
3/4	19.1	9.5	0.68	50	200	15	12
1	25.4	12.7	0.87	50	200	15	8
1 1/4	31.8	15.9	1.00	50	100	-	8
1 1/2	38.1	19.1	1.00	50	100	-	5
2	50.8	25.4	1.10	50	100	-	3
3	76.2	38.1	1.20	-	100	-	2
4	102.0	50.8	1.35	-	100	-	1
5	125.0	63.5	1.40	-	50	-	1
6	151.0	75.0	1.40	-	50	-	1

Notes:
 1. See page 8 - Part Number Guide for dimensional packaging codes.
 2. Cross Reference Guide located on page 10.
 3. Special color packaging, colors and cut pieces are available upon request.

ISO-9001 Company www.qualtekusa.com

SAMPLE TABLE: Q2-F

② **Product Dimensions**

Size (Inch)	As Supplied (mm)			After Recovered (mm)			Standard Packaging	
	Inside Diameter (min.)	Inside Diameter (max.)	Wall Thickness (min.)	Mini Spool *(MS) (Feet)	Standard Spool *(SS) (Feet)	Box Length *(QX) (Feet)	Cut to Length Pcs. *(QB) Qty per bag	
3/64	1.2	0.6	0.40	100	1000	50	6"	25
1/16	1.6	0.8	0.40	100	1000	50	40	25
3/32	2.4	1.2	0.48	100	500	50	36	25
1/8	3.2	1.6	0.48	100	500	50	32	25
3/16	4.8	2.4	0.48	100	500	30	28	25
1/4	6.4	3.2	0.56	100	500	30	24	25
5/16	8.0	4.0	0.62	100	250	30	20	25
3/8	9.5	4.8	0.62	100	250	30	18	25
1/2	12.7	6.4	0.62	100	200	15	16	25
5/8	15.9	8.0	0.68	50	200	15	14	5
3/4	19.1	9.5	0.68	50	200	15	14	5
1	25.4	12.7	0.87	50	200	15	12	5
1 1/4	31.8	15.9	1.00	50	100	-	8	5
1 1/2	38.1	19.1	1.00	50	100	-	8	5
2	50.8	25.4	1.10	50	100	-	5	5
3	76.2	38.1	1.20	-	100	-	3	5
4	102.0	50.8	1.35	-	100	-	2	2
5	125.0	63.5	1.40	-	50	-	2	2
6	151.0	75.0	1.40	-	50	-	1	2

⑥

ISO-9001 Company

www.qualtekusa.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.