

Mini Contactor Relays 4-pole J7KNA-AR

Main contactor

- AC & DC operated
- 4-, 6- and 8-pole versions in different configurations
- Mirror contacts
- Screw fixing and snap fitting (35 mm DIN rail)
- Rated current = 10A (I_{th})
- Suitable for electronic devices (DIN 19240)
- Finger proof (BGV A2)

Accessories

- 2- and 4-pole additional auxiliary contacts in different configurations



Approved Standards

| Standard | Guide No (US,C) |
|--------------|-----------------|
| UL | NKCR, NKCR7 |
| IEC 947-5-1 | see page 95 |
| VDE 0660 | |
| EN 60947-5-1 | |

Ordering Information

■ Model Number Legend

1. Mini Contactor Relays

J7KNA-□□-□□-□□□□

1 2 3 4

- 1) Mini Contactor
- 2) AR: Contactor Relay
- 3) Combination of NO / NC contacts
 - 22: 2 NO 2 NC
 - 31: 3 NO 1 NC
 - 40: 4 NO 0 NC
- 4) Coil voltage (AC operated)
 - 24: AC24V 50/60Hz
 - 48: AC48V 50Hz
 - 110: AC110-115V 50Hz, AC120-125V 60Hz
 - 230: AC220-230V 50Hz, AC240V 60Hz
 - 240: AC230-240V 50Hz
 - 400: AC380-400V 50Hz, AC440V 60Hz
 - 415: AC400-415V 50Hz
 - 550: AC525-550V 50Hz, AC600V 60Hz
 Coil voltage (DC operated)
 - 24D: DC24V
 - 48D: DC48V
 - 60D: DC60V
 - 110D: DC110V
 - 125D: DC125V
 - 24VS: DC24V with diode
 - 48VS: DC48V with diode
 - 110VS: DC110V with diode
 - 125VS: DC125V with diode

2. Aux. Contact Modules for Mini Motor Contactor Relays

J73KN-□□-□□-□

1 2 3 4

- 1) Auxiliary Contact Modules
- 2) A: for mini contactor relays
- 3) Combination of NO/NC contacts
 - 11: 1 NO 1 NC
 - 02: 0 NO 2 NC
 - 22: 2 NO 2 NC
 - 40: 4 NO 0 NC

■ System overview

Mini Contactor Relays 4-pole

AC Operated

| | Contacts | | Distinc. Number acc. to DIN EN 50011 | Ratings | | Thermal Rated Current I_{th} A | Type | Pack | Weight |
|---|------------------------------|----|--------------------------------------|-------------------|-----------|--|-----------------|------|--------|
| | NO | NC | | AC15 230V A | 400V A | | | | |
|  | 4-pole, With Screw Terminals | | | | | | | | |
| | 4 | - | 40E | 3 | 2 | 10 | J7KNA-AR-40 24 | 10 | 0,16 |
| | | | | | | | J7KNA-AR-40 230 | | |
| | 3 | 1 | 31E | 3 | 2 | 10 | J7KNA-AR-31 24 | 10 | 0,16 |
| | | | | | | | J7KNA-AR-31 230 | | |
| | 2 | 2 | 22E | 3 | 2 | 10 | J7KNA-AR-22 24 | 10 | 0,16 |
| | | | | | | | J7KNA-AR-22 230 | | |
| | | | | | | | | | |
| | | | | | | | | | |

1) Other coil voltages see page 10

DC Solenoid Operated

| | Contacts | | Distinc. Number acc. to DIN EN 50011 | Ratings | | Thermal Rated Current I_{th} A | Type | Pack | Weight |
|---|------------------------------|----|--------------------------------------|-------------------|-----------|--|-------------------------------------|------|--------|
| | NO | NC | | AC15 230V A | 400V A | | | | |
|  | 4-pole, With Screw Terminals | | | | | | | | |
| | 4 | - | 40E | 3 | 2 | 10 | J7KNA-AR-40 24D (-VS) ¹⁾ | 10 | 0,19 |
| | | | | | | | | | |
| | 3 | 1 | 31E | 3 | 2 | 10 | J7KNA-AR-31 24D (-VS) ¹⁾ | 10 | 0,19 |
| | | | | | | | | | |
| | 2 | 2 | 22E | 3 | 2 | 10 | J7KNA-AR-22 24D (-VS) ¹⁾ | 10 | 0,19 |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

1) with built-in coil suppressor (diode + zener diode)

Auxiliary Contact Blocks for Contactor Relays J7KNA-AR

| | Contacts | | Ratings | | Thermal Rated Current I_{th} A | Type | Pack | Weight |
|---|----------|----|-------------------|-----------|--|------------|------|--------|
| | NO | NC | AC15 230V A | 400V A | | | | |
|  | 1 | 1 | 3 | 2 | 10 | J73KN-A-11 | 10 | 0,04 |
| | - | 2 | 3 | 2 | 10 | J73KN-A-02 | 10 | 0,04 |
| | 4 | - | 3 | 2 | 10 | J73KN-A-40 | 10 | 0,04 |
| | 2 | 2 | 3 | 2 | 10 | J73KN-A-22 | 10 | 0,04 |

■ System overview

Mini Contactor Relays 4-pole

AC Operated

| Wiring Diagrams | Distinc. Number acc. to DIN EN 50011 | Auxiliary Contact Blocks | | Contactor Relay with Auxiliary Contact | | Contacts suitable for Electronic Circuits according to DIN 19240 for rated voltage 24V DC (test ratings 17V DC, 5mA) Mirror contacts | | |
|------------------------------|--------------------------------------|--------------------------|----|--|---|--|----|---|
| | | Type | NO | NC | Block Distinc. Number according to DIN EN 50011 | | NO | NC |
| 4-pole, With Screw Terminals | | | | | | | | |
| | 40E | J73KN-A-11 | 1 | 1 | 51E | 5 | 1 | Preferable combinations with distinctive letter „E“ according to DIN EN 50011 |
| | | J73KN-A-02 | 0 | 2 | 42E | 4 | 2 | |
| | | J73KN-A-40 | 4 | 0 | 80E | 8 | 0 | |
| | | J73KN-A-22 | 2 | 2 | 62E | 6 | 2 | |
| | 31E | J73KN-A-11 | 1 | 1 | 42Y | 4 | 2 | |
| | | J73KN-A-02 | 0 | 2 | 33Y | 3 | 3 | |
| | | J73KN-A-40 | 4 | 0 | 71Y | 7 | 1 | |
| | | J73KN-A-22 | 2 | 2 | 53Y | 5 | 3 | |
| | 22E | J73KN-A-11 | 1 | 1 | 33Y | 3 | 3 | |
| | | J73KN-A-02 | 0 | 2 | 24Y | 2 | 4 | |
| | | J73KN-A-40 | 4 | 0 | 62Y | 6 | 2 | |
| | | J73KN-A-22 | 2 | 2 | 44Y | 4 | 4 | |

DC Solenoid Operated

| Wiring Diagrams | Distinc. Number acc. to DIN EN 50011 | Auxiliary Contact Blocks | | Contactor Relay with Auxiliary Contact | | | | |
|------------------------------|--------------------------------------|--------------------------|----|--|---|---|----|---|
| | | Type | NO | NC | Block Distinc. Number according to DIN EN 50011 | | NO | NC |
| 4-pole, With Screw Terminals | | | | | | | | |
| | 40E | J73KN-A-11 | 1 | 1 | 51E | 5 | 1 | Preferable combinations with distinctive letter „E“ according to DIN EN 50011 |
| | | J73KN-A-02 | 0 | 2 | 42E | 4 | 2 | |
| | | J73KN-A-40 | 4 | 0 | 80E | 8 | 0 | |
| | | J73KN-A-22 | 2 | 2 | 62E | 6 | 2 | |
| | 31E | J73KN-A-11 | 1 | 1 | 42Y | 4 | 2 | |
| | | J73KN-A-02 | 0 | 2 | 33Y | 3 | 3 | |
| | | J73KN-A-40 | 4 | 0 | 71Y | 7 | 1 | |
| | | J73KN-A-22 | 2 | 2 | 53Y | 5 | 3 | |
| | 22E | J73KN-A-11 | 1 | 1 | 33Y | 3 | 3 | |
| | | J73KN-A-02 | 0 | 2 | 24Y | 2 | 4 | |
| | | J73KN-A-40 | 4 | 0 | 62Y | 6 | 2 | |
| | | J73KN-A-22 | 2 | 2 | 44Y | 4 | 4 | |

Auxiliary Contact Blocks for Contactor Relays J7KNA-AR

| Wiring diagrams | | | | Contacts suitable for Electronic Circuits according to DIN 19240 for rated voltage 24V DC (test ratings 17V DC, 5mA) Mirror contacts |
|-----------------|------------|------------|------------|--|
| J73KN-A-11 | J73KN-A-02 | J73KN-A-40 | J73KN-A-22 | |
| | | | | |

Specifications

■ Coil Voltages

| Suffix to contactor type e.g. J7KNA-AR-40-24 | Voltage Marking at the coil | | Rated Control Voltage U_s range for | | | |
|---|--------------------------------|---------------|--|-----------|-----------|-----------|
| | for 50Hz V | for 60Hz V | 50Hz | | 60Hz | |
| | | | min V. | max V. | min V. | max V. |
| 12 | 12 | 12 | 11 | 12 | 12 | 12 |
| 24 | 24 | 24 | 22 | 24 | 24 | 24 |
| 42 | 42 | 42 | 38.5 | 42 | 42 | 42 |
| 48 | 48-50 | 48 | 48 | 50 | 48 | 50 |
| 60 | 60 | 60 | 52 | 66 | 54 | 60 |
| 90 | 90-95 | 100-105 | 90 | 95 | 100 | 105 |
| 95 | 95-100 | 105-110 | 95 | 100 | 105 | 110 |
| 100 | 100 | 110-115 | 100 | 105 | 110 | 115 |
| 105 | 105-110 | 115-120 | 105 | 110 | 115 | 120 |
| 110 | 110-115 | 120-125 | 110 | 115 | 120 | 125 |
| 200 | 200 | 210-220 | 195 | 205 | 210 | 220 |

| Suffix to contactor type e.g. J7KNA-AR-40- 230 | Voltage Marking at the coil | | Rated Control Voltage U_s range for | | | |
|---|--------------------------------|---------------|--|------------|------------|------------|
| | for 50Hz V | for 60Hz V | 50Hz | | 60Hz | |
| | | | min V. | max V. | min V. | max V. |
| 210 | 205-215 | 220-230 | 205 | 215 | 220 | 230 |
| 220 | 210-220 | 230-240 | 210 | 220 | 230 | 240 |
| 230 | 220-230 | 240 | 220 | 230 | 240 | 250 |
| 240 | 230-240 | | 230 | 240 | 250 | 260 |
| 400 | 380-400 | 440 | 380 | 400 | 415 | 440 |
| 500 | 475-500 | 520-545 | 475 | 500 | 520 | 545 |
| 550 | 525-550 | 600 | 525 | 550 | 570 | 600 |

Standard voltages in bold type letters. Coil not exchangeable

Engineering data and Characteristics

Mini Contactor Relays

Data according to IEC 947-5-1, VDE 0660, EN 60947-5-1

| Auxiliary Contacts | | Type | AC J7KNA-AR... | DC J7KNA-AR...D | DC + Diode J7KNA-AR...VS | J73KN-A... |
|---|-----------------------------------|-----------------|--------------------------------|--------------------|-----------------------------|-------------------|
| Rated insulation voltage U_i | | V AC | 690 ^{*1} | 690 ^{*1} | 690 ^{*1} | 690 ^{*1} |
| Thermal rated current I_{th} to 690V | | | | | | |
| Ambient temperature | 40°C | A | 10 | 10 | 10 | 10 |
| | 60°C | A | 6 | 6 | 6 | 6 |
| Power loss per pole | at I_{th} | W | 0.5 | 0.5 | 0.5 | 0.5 |
| Utilization category AC15 | | | | | | |
| Rated operational current I_e | 220-240V | A | 3 | 3 | 3 | 3 |
| | 380-415V | A | 2 | 2 | 2 | 2 |
| | 440V | A | 1.6 | 1.6 | 1.6 | 1.6 |
| | 500V | A | 1.2 | 1.2 | 1.2 | 1.2 |
| | 660-690V | A | 0.6 | 0.6 | 0.6 | 0.6 |
| Utilization category DC13 | | | | | | |
| Rated operational current I_e | 60V | A | 2 | 2 | 2 | 2 |
| | 110V | A | 0.4 | 0.4 | 0.4 | 0.4 |
| | 220V | A | 0.1 | 0.1 | 0.1 | 0.1 |
| Maximum ambient temperature | | | | | | |
| Operation | open | °C | -40 to +60 (+90) ^{*2} | | | |
| | enclosed | °C | | | | |
| Storage | | °C | -40 to +90 | | | |
| Short circuit protection short-circuit current 1kA, contact welding not accepted | | | | | | |
| max. fuse size | gL (gG) | A | 20 | 20 | 20 | 20 |
| Power consumption of coils | | | | | | |
| AC operated | inrush | VA | 25 | - | - | - |
| | sealed | VA | 4 - 5 | - | - | - |
| | | W | 1.2 | - | - | - |
| DC operated | inrush | W | - | 2.5 | 2.5 | - |
| | sealed | W | - | 2.5 | 2.5 | - |
| Operation range of coils in multiples of control voltage U_s | | | 0.85 - 1.1 | 0.8 - 1.1 | 0.8 - 1.1 | - |
| Switching time at control voltage $U_c \pm 10\%$^{*3,*4} | | | | | | |
| AC operated | make time | ms | 15 - 25 | - | - | - |
| | release time | ms | 8 - 25 | - | - | - |
| | arc duration | ms | 10 - 15 | - | - | - |
| DC operated | make time | ms | - | 15 - 19 | 15 - 19 | - |
| | release time | ms | - | 8 - 25 | 8 - 25 | - |
| | arc duration | ms | - | 10 - 15 | 10 - 15 | - |
| Cable cross-section | | | | | | |
| all connectors | solid | mm ² | 0.75 - 2.5 | 0.75 - 2.5 | 0.75 - 2.5 | 0.75 - 2.5 |
| | flexible | mm ² | 0.75 - 2.5 | 0.75 - 2.5 | 0.75 - 2.5 | 0.75 - 2.5 |
| | flexible with multicore cable end | mm ² | 0.5 - 1.5 | 0.5 - 1.5 | 0.5 - 1.5 | 0.5 - 2.5 |
| Clamps per pole | | | 2 | 2 | 2 | 2 |
| | solid or stranded | AWG | 18 - 14 | 18 - 14 | 18 - 14 | 18 - 14 |

*1) Suitable at 690V for: earthed-neutral systems, overvoltage category I to IV, pollution degree 3 (standard-industry): $U_{imp} = 8kV$.
Data for other conditions on request.

*2) With reduced control voltage range 0.9 up to 1.0 x U_s and with reduced thermal rated current I_{th} to $I_e/AC15$

*3) Summary switching time = release time + arc duration

*4) Release time of NC make time of NO increase when suppressor units for voltage peak protection are used (Varistor, RC-units, Diode units).

Mini Contactor Relays for North America

Data according to UL508

| Main Contacts (cULus) | | Type | J7KNA-AR... | J73KN-A... |
|--|---------------------|------|-------------|------------|
| Rated operational current "General Use" | | A | 10 | 10 |
| Rated operational power of three-phase motors at 60Hz (3ph) | 115V | hp | - | - |
| | 200V | hp | - | - |
| | 230V | hp | - | - |
| | 460V | hp | - | - |
| | 575V | hp | - | - |
| Rated operational power of of AC motors at 60Hz (1ph) | 115V | hp | - | - |
| | 200V | hp | - | - |
| | 230V | hp | - | - |
| Fuses | | A | - | - |
| Suitable for use on a capability of delivering not more than rms | | A | - | - |
| | | V | - | - |
| | | V AC | 600 | 600 |
| Auxiliary Contacts (cULus) | | | | |
| | heavy pilot duty | AC | A600 | A600 |
| | standard pilot duty | DC | Q600 | Q600 |

■ Dimensions

AC and DC operated
with screw terminals

Auxiliary Contact Blocks

J7KNA-AR...

J73KN-A...



Do not use/install these products before having read the applicable precautions as listed in Cat. No. J09-EN-01 available from www.europe.omron.com or on request from OMRON local sales office.

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.