


# cPCI/PCI/LPCI-9112


16-CH 12-Bit 110 kS/s Multi-Function DAQ Card / Low-Profile DAQ Card



cPCI-9112



PCI-9112



LPCI-9112

## Features

- Supports a 3.3 V or 5 V PCI bus (PCI/LPCI-9112)
- 3U Eurocard form factor, CompactPCI compliant (PICMG 2.0 R2.1) (cPCI-9112)
- 12-bit A/D resolution
- Up to 110 kS/s sampling rate
- 16-CH single-ended or 8-CH differential inputs
- Bipolar or unipolar analog input ranges
- Programmable gains of x0.5, x1, x2, x4, x8
- Automatic analog inputs scanning
- Bus-mastering DMA for analog inputs
- 2-CH 12-bit multiplying analog outputs
- 16-CH TTL digital inputs and 16-CH TTL digital outputs
- 1-CH 16-bit general-purpose timer/counter
- Compact, half-size PCB (PCI-9112)
- Compact, low-profile PCI size PCB (LPCI-9112)
- Rear I/O available on cPCI-9112R

### Operating Systems

- Windows 7/Vista/XP/2000/2003 Server
- Linux
- Windows CE (call for availability)

### Recommended Software

- AD-Logger
- VB.NET/VC.NET/VB/VC+++/BCB/Delphi
- DAQBench

### Driver Support

- DAQPilot for Windows
- DAQPilot for LabVIEW™
- DAQ-MTLB for MATLAB®
- PCIS-DASK for Windows
- PCIS-DASK/X for Linux

## Introduction

ADLINK's cPCI/PCI/LPCI-9112 are 16-CH, 12-bit, 110 kS/s multi-function DAQ cards. The cPCI/PCI/LPCI-9112 devices features flexible configurations on analog inputs. They provides analog inputs with 4 programmable input ranges for both bipolar and unipolar inputs. The A/D on the cPCI/PCI/LPCI-9112 features a sampling rate up to 110 kS/s with resolution at 12 bits. These devices support automatic analog input scanning, and offers a differential mode for 8-CH analog inputs and maximum noise elimination, as well as single-ended modes for 16-CH analog inputs.

The cPCI/PCI/LPCI-9112 also feature 2-CH 12-bit analog outputs, 1-CH 16-bit general-purpose timer/counter, 16-CH TTL digital inputs, and 16-CH TTL digital outputs. The LPCI-9112 is the MD1 size, low-profile version of PCI-9112. The low-profile PCI card is especially suitable for the applications which have a space restriction on the size of peripheral cards.

The cPCI-9112R allows I/O connectivity to be routed through the backplane via J2/P2 allowing a rear I/O transition module to be inserted, which is capable of efficient trouble-shooting and maintenance.

## Specifications

### Analog Input

- Number of channels: 16 single-ended or 8 differential
- Resolution: 12 bits
- Conversion time: 8  $\mu$ s
- Maximum sampling rate: 110 kS/s
- Input signal ranges

Gain	Input Range	
	Bipolar	Unipolar
0.5	$\pm 10$ V	-
1	$\pm 5$ V	0 to 10 V
2	$\pm 2.5$ V	0 to 5 V
4	$\pm 1.25$ V	0 to 2.5 V
8	$\pm 0.625$ V	0 to 1.25 V

### Accuracy

Gain	Accuracy
0.5, 1	0.01% of FSR $\pm$ 1 LSB
2, 4	0.02% of FSR $\pm$ 1 LSB
8	0.04% of FSR $\pm$ 1 LSB

- Input coupling: DC
- Overvoltage protection: continuous  $\pm 3$  V
- Input impedance: 1 G $\Omega$
- Trigger modes: software
- Data transfers: programmed I/O, interrupt, bus-mastering DMA

### Analog Output

- Number of channels: 2 voltage outputs
- Resolution: 12 bits
- Output ranges (software programmable)

Output Range	
Unipolar	0 to 10 V, 0 to 5 V, 0 to EXTREF

- Output driving capacity:  $\pm 5$  mA max
- Settling time: 30  $\mu$ s to 0.5 LSB
- Data transfers: programmed I/O

### Digital I/O

- Number of channels: 16 inputs and 16 outputs
- Compatibility: 5 V/TTL
- Data transfers: programmed I/O

### General-Purpose Timer/Counter

- Number of channels: 1
- Resolution: 16 bits
- Compatibility: 5 V/TTL
- Base clock available: 2 MHz, external clock to 10 MHz

### General Specifications

- I/O connector: 37-pin D-sub female
- Operating temperature: 0°C to 60°C
- Storage temperature: -20°C to 80°C
- Relative humidity: 5% to 95%, non-condensing
- Power requirements

	+5 V	+12 V
cPCI-9112(R)	600 mA typical	20 mA typical
PCI-9112	460 mA typical	110 mA typical
LPCI-9112	500 mA typical	110 mA typical

- Dimensions (not including connectors)
  - 160 mm x 100 mm (cPCI-9112/9112R)
  - 175 mm x 107 mm (PCI-9112)
  - 120 mm x 65 mm (LPCI-9112)

## Terminal Boards & Cables

### For PCI-9112:

- **DIN-37D-01\***  
Terminal Board with One 37-pin D-sub Connector and DIN-Rail Mounting Section 12.)
- **DIN-20P-01\***  
Terminal Board with One 20-pin Ribbon Connector and DIN-Rail Mounting
- **ACLD-9137-01**  
General-Purpose Terminal Board with One 37-pin D-sub Male Connector
- **ACLD-9138-01\***  
General-Purpose Terminal Board with One 37-pin D-sub Connector
- **ACLD-9188-01\***  
General-Purpose Terminal Board with Two 20-pin Ribbon Connectors and One 37-pin D-sub Connector
- **ACLD-9182A-01\***  
Terminal Board with 16-CH Isolated Digital Inputs
- **ACLD-9185-01\***  
Terminal Board with 16-CH Isolated Digital Inputs

### For LPCI-9112:

- **DIN-68S-01\***  
Terminal Board with One 68-pin SCSI-II Connector and DIN-Rail Mounting

### For cPCI-9112:

- **DIN-100S-01**  
Terminal Board with One 100-pin SCSI-II Connector and DIN-Rail Mounting

\* Cables are not included. For information on mating cables, refer to P2-59/60.

## Ordering Information

- **PCI-9112**  
16-CH 12-Bit 110 kS/s Multi-Function DAQ Card
- **LPCI-9112**  
16-CH 12-Bit 110 kS/s Multi-Function Low-Profile DAQ Card
- **cPCI-9112**  
16-CH 12-Bit 110 kS/s Multi-Function DAQ Module
- **cPCI-9112R**  
16-CH 12-Bit 110 kS/s Multi-Function DAQ Module with rear I/O

## Pin Assignment

LPCI-9112			PCI-9112			cPCI-9112, cPCI-9112R					
DOUT0	1	35	DIN0	<b>CN3: Analog Input /Output &amp; Counter/Timer</b>			DOUT_0	1	51	GND	
DOUT1	2	36	DIN1	A10 (AIH0)	1	20	(AIL0) A18	DOUT_1	2	52	GND
DOUT2	3	37	DIN2	A11 (AIH1)	2	21	(AIL1) A19	DOUT_2	3	53	GND
DOUT3	4	38	DIN3	A12 (AIH2)	3	22	(AIL2) A110	DOUT_3	4	54	GND
DOUT4	5	39	DIN4	A13 (AIH3)	4	23	(AIL3) A111	DOUT_4	5	55	GND
DOUT5	6	40	DIN5	A14 (AIH4)	5	24	(AIL4) A112	DOUT_5	6	56	GND
DOUT6	7	41	DIN6	A15 (AIH5)	6	25	(AIL5) A113	DOUT_6	7	57	GND
DOUT7	8	42	DIN7	A16 (AIH6)	7	26	(AIL6) A114	DOUT_7	8	58	GND
DOUT8	9	43	DIN8	A17 (AIH7)	8	27	(AIL7) A115	DOUT_8	9	59	GND
DOUT9	10	44	DIN9	AGND	9	28	AGND	DOUT_9	10	60	GND
DOUT10	11	45	DIN10	AGND	10	29	AGND	DOUT_10	11	61	GND
DOUT11	12	46	DIN11	AGND	10	29	AGND	DOUT_11	12	62	GND
DOUT12	13	47	DIN12	V.REF	11	30	AO1	DOUT_12	13	63	GND
DOUT13	14	48	DIN13	ExtVref2	12	31	ExtVref1	DOUT_13	14	64	GND
DOUT14	15	49	DIN14	+12Vout	13	32	AO2	DOUT_14	15	65	+5Vout
DOUT15	16	50	DIN15	AGND	14	33	GATE0	DOUT_15	16	66	+5Vout
FCOUT0	17	51	EXTCLK	D.GND	15	34	GATE	DIN_0	17	67	GND
EXTTRG	18	52	GATE0	Cout0	16	35	Cout1	DIN_1	18	68	GND
FCOUT1	19	53	GATE	ExtTrg	17	36	N/C	DIN_2	19	69	GND
+12V	20	54	SGND	N/C	18	37	EXTCLK	DIN_3	20	70	GND
VCC	21	55	SGND	+5Vout	19	20		DIN_4	21	71	GND
AGND	22	56	AGND					DIN_5	22	72	GND
VREF	23	57	EXTVREF1					DIN_6	23	73	GND
EXTVREF2	24	58	DAOUT0					DIN_7	24	74	GND
AGND	25	59	DAOUT1					DIN_8	25	75	GND
AGND	26	60	AGND					DIN_9	26	76	GND
AIN0	27	61	AIN8					DIN_10	27	77	GND
AIN1	28	62	AIN9					DIN_11	28	78	GND
AIN2	29	63	AIN10					DIN_12	29	79	GND
AIN3	30	64	AIN11					DIN_13	30	80	GND
AIN4	31	65	AIN12					DIN_14	31	81	+5Vout
AIN5	32	66	AIN13					DIN_15	32	82	+5Vout
AIN6	33	67	AIN14					EXTCLK	33	83	GND
AIN7	34	68	AIN15					EXTTRG	34	84	GND
								COUT0	35	85	COUT1
								GATE0	36	86	GATE
								+12Vout	37	87	AGND
								ExtVref2	38	88	AGND
								ExtVref1	39	89	AGND
								REFout	40	90	AGND
								DA2	41	91	AGND
								DA1	42	92	AGND
								A17 (AIH7)	43	93	A115 (AIL7)
								A16 (AIH6)	44	94	A114 (AIL6)
								A15 (AIH5)	45	95	A113 (AIL5)
								A14 (AIH4)	46	96	A112 (AIL4)
								A13 (AIH3)	47	97	A111 (AIL3)
								A12 (AIH2)	48	98	A110 (AIL2)
								A11 (AIH1)	49	99	A19 (AIL1)
								A10 (AIH0)	50	100	A18 (AIL0)

### CN1: Digital Input

DI0	1	2	DI1
DI2	3	4	DI3
DI4	5	6	DI5
DI6	7	8	DI7
DI8	9	10	DI9
DI10	11	12	DI11
DI12	13	14	DI13
DI14	15	16	DI15
GND	17	18	GND
+5Vout	19	20	+12Vout

### CN2: Digital Output

DO0	1	2	DO1
DO2	3	4	DO3
DO4	5	6	DO5
DO6	7	8	DO7
DO8	9	10	DO9
DO10	11	12	DO11
DO12	13	14	DO13
DO14	15	16	DO15
GND	17	18	GND
+5Vout	19	20	+12Vout



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.