

# "High Frequency Ceramic Solutions"

## Dual Band 868-928 MHz/2.4 GHz Chip Antenna

P/N 0900AD47A2450

Detail Specification: 5/31/2017


Page 1 of 12

AEC-Q200 qualification available.

### General Specifications

Part Number	0900AD47A2450	
Frequency (MHz)	865 - 928	2400 - 2480
Avg. Rad Efficiency <sup>1</sup>	27%	56%
Peak Gain (dBi typ.)	-1.0 dBi typ. (XZ-Total)	2.5 dBi typ. (XZ-Total)
Average Gain (dBi typ.)	-4.5 dBi typ. (XZ-Total)	-0.5 dBi typ. (XZ-Total)
Return Loss (dB)	3 min.	6 min.
Impedance	50 Ω	
Input Power	2 Watts max. (CW)	

Separate Frequency Feeds! No diplexer needed.



Storage Period	18 months max.
Storage Temperature	-40 to +85°C
Operating Temperature	-40 to +85°C
Reel Quantity	1000

<sup>1</sup>Measured on a 30x40mm GND plane. Eval Board p/n 0900AD47A2450-EB1SMA (See pages 2-6 for details)

### Part Number Explanation

P/N Suffix	Packing Style	Bulk (loose)	Suffix = S	e.g. 0900AD47A2450S
		T & R	Suffix = E	e.g. 0900AD47A2450E
		100% Tin	Suffix = E or S	e.g. 0900AD47A2450(E or S)
Evaluation Board		0900AD47A2450-EB1SMA, 0900AD47A2450-EB2SMA, 0900AD47A2450-EB3SMA		

Need an EVB optimized for E.U. 868/2.4G or U.S./Americas/Japan 915/2.4G for improved performance on the Sub GHz band?



Evaluation Board Optimized for BOTH EU 868 & US/Americas/Japan and 2.4GHz: 0900AD47A2450-EB1SMA

Evaluation Board Optimized for US-Americas Japan 902-930MHz (max performance) only and 2.4GHz: 0900AD47A2450-EB2SMA

Evaluation Board Optimized for EU 868MHz (max performance) only and 2.4GHz: 0900AD47A2450-EB3SMA


### Mechanical Dimensions

	In	mm
L	0.39 ± 0.008	10.0 ± 0.2
W	0.13 ± 0.008	3.2 ± 0.2
T	0.06 ± 0.008	1.5 ± 0.2
a	0.03 ± 0.008	0.8 ± 0.2
b	0.11 ± 0.008	2.7 ± 0.2
c	0.04 ± 0.008	1.0 ± 0.2
d	0.01 +0.004/-0.008	0.3 +0.1/-0.2



### Terminal Configuration

No.	Function	No.	Function
1	2.4GHz Port	5	NC
2	NC	6	NC
3	NC	7	NC
4	<1GHz Port	8	NC



Even though pins 2, 3, 5, 6, 7, and 8 are NC ("No Connect"), they must be soldered down to the landing pad for proper operation

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 2.0

2017 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"


Dual Band 868-928 MHz/2.4 GHz Chip Antenna

P/N 0900AD47A2450

Detail Specification: 5/31/2017

Page 2 of 12

## Mounting Considerations 1: Evaluation Board p/n: 0900AD47A2450-EB1SMA



Evaluation Board p/n: 0900AD47A2450-EB1SMA/EB2SMA/EB3SMA

Units in mm

Frequency (GHz)	Total Radiated Efficiency (%)
0.896	27
2.4	56

To order a pre-tuned 50Ω EVB above with two female SMA connectors, click here:  
[www.johansontechnology.com/request-a-sample](http://www.johansontechnology.com/request-a-sample)

Reference p/n: 0900AD47A2450-EB1SMA (optimized for US/EU+2.4G), 0900AD47A2450-EB2SMA (optimized for US+2.4G), or 0900AD47A2450-EB3SMA (optimized for EU+2.4G)

Would you like the layout file of the above? Would you like us to tune the antenna for your on your PCB?

Please contact us if you have any questions regarding the implementation of this antenna in your PCB's layout. We'll be happy to guide you to maximize the antenna's performance.

Contact our RF Engineers at:

[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 2.0

2017 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

Dual Band 868-928 MHz/2.4 GHz Chip Antenna

P/N 0900AD47A2450


Detail Specification: 5/31/2017

Page 3 of 12

## Mounting Considerations 1: Evaluation Board p/n: 0900AD47A2450-EB1SMA/EB2.EB3 Antenna Footprint Detail

Mount these devices with brown mark facing up.

### PCB Layout (top)



The L/C values above ONLY apply to our EVB, yours will be different. If you need help finding out which values to use on your PCB, please read below:

Would you like the layout file of the above? Have antenna tuning issues?

Please contact us if you have any questions regarding the implementation of this antenna in your PCB's layout. We'll be happy to guide you to maximize the antenna's performance.

Contact our RF Engineers at:

[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

Johanson Technology, Inc. reserves the right to make design changes without notice.  
 All sales are subject to Johanson Technology, Inc. terms and conditions.



# "High Frequency Ceramic Solutions"

Dual Band 868-928 MHz/2.4 GHz Chip Antenna


P/N 0900AD47A2450

Detail Specification: 5/31/2017

Page 4 of 12

## Mounting Considerations 1: Typical Antenna response Performance (T=25°C)

Return Loss and Isolation



m1  
freq=2.400GHz  
dB(S(1,1))=-13.210

m5  
freq=896.0MHz  
dB(S(2,2))=-12.022

m9  
freq=2.480GHz  
dB(S(2,1))=-42.394

m2  
freq=2.440GHz  
dB(S(1,1))=-21.451

m6  
freq=928.0MHz  
dB(S(2,2))=-6.789

m10  
freq=868.0MHz  
dB(S(2,1))=-15.927

m3  
freq=2.480GHz  
dB(S(1,1))=-22.425

m7  
freq=2.400GHz  
dB(S(2,1))=-44.254

m11  
freq=896.0MHz  
dB(S(2,1))=-14.992

m4  
freq=868.0MHz  
dB(S(2,2))=-6.534

m8  
freq=2.440GHz  
dB(S(2,1))=-43.149

m12  
freq=928.0MHz  
dB(S(2,1))=-16.553

Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)


4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 2.0

2017 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

## Mounting Considerations 1: Typical EM Radiation Performance @900MHz Band (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.

# "High Frequency Ceramic Solutions"


Dual Band 868-928 MHz/2.4 GHz Chip Antenna

P/N 0900AD47A2450

Detail Specification: 5/31/2017

Page 6 of 12

## Mounting Considerations 1: Typical EM Radiation Performance @ 2.4GHz band (T=25°C)




Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



# "High Frequency Ceramic Solutions"

## Mounting Considerations 2: Larger Evaluation Board (Reference)



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.

# "High Frequency Ceramic Solutions"

Dual Band 868-928 MHz/2.4 GHz Chip Antenna


P/N 0900AD47A2450

Detail Specification: 5/31/2017

Page 8 of 12

## Mounting Considerations 2: Typical Antenna response Performance (T=25°C)

Return Loss



Would you like us to tune the antenna for your on your PCB?

Please contact us if you have any questions regarding the implementation of this antenna in your PCB's layout. We'll be happy to guide you to maximize the antenna's performance.

Contact our RF Engineers at:

[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)  
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821  
Ver. 2.0

2017 Johanson Technology, Inc. All Rights Reserved




# "High Frequency Ceramic Solutions"

**Dual Band 868-928 MHz/2.4 GHz Chip Antenna**  
 Detail Specification: 5/31/2017

**P/N 0900AD47A2450**  
 Page 9 of 12

## Mounting Considerations 2: Typical EM Radiation Performance @900MHz Band (T=25°C)




Johanson Technology, Inc. reserves the right to make design changes without notice.  
 All sales are subject to Johanson Technology, Inc. terms and conditions.

# "High Frequency Ceramic Solutions"

**Dual Band 868-928 MHz/2.4 GHz Chip Antenna**  
 Detail Specification: 5/31/2017

**P/N 0900AD47A2450**  
 Page 10 of 12

## Mounting Considerations 2: Typical EM Radiation Performance @ 2.4GHz band (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.  
 All sales are subject to Johanson Technology, Inc. terms and conditions.



# "High Frequency Ceramic Solutions"

Dual Band 868-928 MHz/2.4 GHz Chip Antenna

P/N 0900AD47A2450


Detail Specification: 5/31/2017

Page 11 of 12

## Single Feed Configuration with Diplexer Option

If there's a single 900/2.4G combined feed coming from the chipset, Johanson Technology offers a diplexer option to separate and filter the 900M and 2.4G signals. The recommended p/n is: 0900DP15A2450

Pairing a 900MHz low pass filter with a 2.4GHz high pass filter not only separates the two signals but provides harmonic attenuation to fulfill regulation qualification for industry standards.




0900DP15A2450

For more information about our diplexers go to:  
[www.johansontechnology.com/diplexers](http://www.johansontechnology.com/diplexers)

For assistance with PCB layout or general component inquiries, please go to:  
[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

"Dual Band  
900/2.4G,  
single channel  
chipset"



Mini chip  
diplexer  
footprint for  
reference only,  
please get the  
datasheet at:

[www.johansontechnology.com/diplexers](http://www.johansontechnology.com/diplexers)

Would you like the diplexer layout file? Please go to: [www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



Ver. 2.0

[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2017 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

Dual Band 868-928 MHz/2.4 GHz Chip Antenna

P/N 0900AD47A2450

Detail Specification: 5/31/2017

Page 12 of 12

## Antenna tuning, optimization, and validation services:

[www.johansontechnology.com/ipc-antenna-services](http://www.johansontechnology.com/ipc-antenna-services)

## For more antennas and to download measured S-parameters, go to:

[www.johansontechnology.com/antennas](http://www.johansontechnology.com/antennas)

## For more information about our diplexers:

[www.johansontechnology.com/diplexers](http://www.johansontechnology.com/diplexers)

## Soldering Information

[www.johansontechnology.com/ipcsoldering-profile](http://www.johansontechnology.com/ipcsoldering-profile)

## MSL Info

[www.johansontechnology.com/msl-rating](http://www.johansontechnology.com/msl-rating)

## Packaging information

[www.johansontechnology.com/tape-reel-packaging](http://www.johansontechnology.com/tape-reel-packaging)

## For layout review contact our Applications Team at:

[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

## RoHS Compliance

[www.johansontechnology.com/rohs-compliance](http://www.johansontechnology.com/rohs-compliance)

Need help designing the antenna in? Use our antenna design services!

[www.johansontechnology.com/ipc-antenna-services](http://www.johansontechnology.com/ipc-antenna-services)

2 free layout reviews and if you need us to tune and characterize the antenna on your product (inside anechoic chamber) we can do that too.

Small lab fee may apply for the latter.

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



[www.johansontechnology.com](http://www.johansontechnology.com)  
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821  
Ver. 2.0 2017 Johanson Technology, Inc. All Rights Reserved



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.