

## Potential distributors - PTRVB 4-FI - 3270158

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Potential distributors, Nom. voltage: 250 V, Nominal current: 17.5 A, Cross section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 12 - 26, Connection type: Push-in connection, Width: 8.3 mm, Length: 64 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15

### Product Features

- Bridgeable potential distributor with option to supply up to 6 mm<sup>2</sup>
- High contact quality thanks to push-in technology as a replacement for Wire-Wrap®, TERMI-POINT®, etc.
- Tool-free wiring in a confined space thanks to compact size



### Key Commercial Data

|                        |          |
|------------------------|----------|
| Packing unit           | 1 pc     |
| Minimum order quantity | 10 pc    |
| Custom tariff number   | 85369010 |
| Country of origin      | Poland   |

### Technical data

#### General

|  |   |
|--|---|
| Number of levels                       | 4   |
| Number of connections                  | 13  |
| Nominal cross section                  | 1.5 mm <sup>2</sup>   |
| Color                                  | gray  |
| Insulating material                    | PA  |
| Flammability rating according to UL 94 | V0  |
| Rated surge voltage                    | 4 kV  |
| Overvoltage category                   | III   |
| Insulating material group              | I   |
| Connection in acc. with standard       | IEC 60947-7-1   |
| Maximum load current                   | 32 A (The total current of the terminal block must not exceed 32 A) |

## Potential distributors - PTRVB 4-FI - 3270158

### Technical data

#### General

|   |   |
|---|---|
| Nominal current $I_N$   | 17.5 A (with 1.5 mm <sup>2</sup> conductor cross section) |
| Nominal voltage $U_N$   | 250 V   |
| Connection in acc. with standard  | IEC 60947-7-1   |
| Maximum load current  | 32 A (with 6 mm <sup>2</sup> conductor connection)        |
| Nominal current $I_N$   | 32 A (with 4 mm <sup>2</sup> conductor cross section)     |
| Nominal voltage $U_N$   | 250 V   |
| Open side panel   | Yes   |
| Shock protection test specification   | DIN EN 50274 (VDE 0660-514):2002-11                       |
| Back of the hand protection   | guaranteed  |
| Finger protection   | guaranteed  |
| Result of surge voltage test  | Test passed   |
| Surge voltage test setpoint   | 4.8 kV  |
| Result of power-frequency withstand voltage test  | Test passed   |
| Power frequency withstand voltage setpoint  | 1.5 kV  |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed   |
| Result of bending test  | Test passed   |
| Bending test rotation speed   | 10 rpm  |
| Bending test turns  | 135   |
| Bending test conductor cross section/weight   | 0.14 mm <sup>2</sup> / 0.2 kg                             |
|   | 1.5 mm <sup>2</sup> / 0.4 kg                              |
|   | 2.5 mm <sup>2</sup> / 0.7 kg                              |
|   | 0.2 mm <sup>2</sup> / 0.2 kg                              |
|   | 4 mm <sup>2</sup> / 0.9 kg                                |
|   | 6 mm <sup>2</sup> / 1.4 kg                                |
| Tensile test result   | Test passed   |
| Conductor cross section tensile test  | 0.14 mm <sup>2</sup>                                      |
| Tractive force setpoint   | 10 N  |
| Conductor cross section tensile test  | 1.5 mm <sup>2</sup>                                       |
| Tractive force setpoint   | 40 N  |
| Conductor cross section tensile test  | 2.5 mm <sup>2</sup>                                       |
| Tractive force setpoint   | 50 N  |
| Result of tight fit on support  | Test passed   |
| Tight fit on carrier  | NS 35   |
| Setpoint  | 1 N   |
| Result of voltage-drop test   | Test passed   |
| Requirements, voltage drop  | ≤ 3.2 mV  |

## Potential distributors - PTRVB 4-FI - 3270158

### Technical data

#### General

|   |                     |
|---|---------------------|
| Result of temperature-rise test   | Test passed         |
| Short circuit stability result  | Test passed         |
| Conductor cross section short circuit testing                           | 1.5 mm <sup>2</sup> |
| Short-time current  | 0.18 kA             |
| Conductor cross section short circuit testing                           | 2.5 mm <sup>2</sup> |
| Short-time current  | 0.3 kA              |
| Conductor cross section short circuit testing                           | 4 mm <sup>2</sup>   |
| Short-time current  | 0.48 kA             |
| Result of aging test  | Test passed         |
| Ageing test for screwless modular terminal block temperature cycles     | 192                 |
| Result of thermal test  | Test passed         |
| Proof of thermal characteristics (needle flame) effective duration      | 30 s                |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C              |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C              |
| Static insulating material application in cold                          | -60 °C              |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 8.3 mm  |
| Length           | 64 mm   |
| Height NS 35/7,5 | 55.5 mm |
| Height NS 35/15  | 63 mm   |

#### Connection data

|  |                      |
|--|----------------------|
| Connection method  | Push-in connection   |
| Connection in acc. with standard   | IEC 60947-7-1        |
| Conductor cross section solid min.   | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.   | 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.   | 26                   |
| Conductor cross section AWG max.   | 12                   |
| Conductor cross section flexible min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                      | 1.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible                                 | 26                   |
| Max. AWG conductor cross section, flexible                                 | 14                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 1.5 mm <sup>2</sup>  |
| Stripping length   | 8 mm ... 10 mm       |

## Potential distributors - PTRVB 4-FI - 3270158

### Technical data

#### Connection data

|  |   |
|--|---|
| Note   | Only the "CRIMPFOX 6" crimping pliers may be used for crimping with 6 mm <sup>2</sup> stranded and ferrule. |
| Connection in acc. with standard   | IEC 60947-7-1   |
| Conductor cross section solid min.   | 2.5 mm <sup>2</sup>   |
| Conductor cross section solid max.   | 6 mm <sup>2</sup>   |
| Conductor cross section AWG min.   | 12  |
| Conductor cross section AWG max.   | 8   |
| Conductor cross section flexible min.                                      | 2.5 mm <sup>2</sup>   |
| Conductor cross section flexible max.                                      | 6 mm <sup>2</sup>   |
| Min. AWG conductor cross section, flexible                                 | 12  |
| Max. AWG conductor cross section, flexible                                 | 8   |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 2.5 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 6 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 2.5 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 6 mm <sup>2</sup>   |
| Stripping length   | 12 mm   |

#### Standards and Regulations

|  |               |
|--|---------------|
| Connection in acc. with standard       | IEC 60947-7-1 |
|  | IEC 60947-7-1 |
| Flammability rating according to UL 94 | V0            |

### Classifications

#### eCl@ss


|            |          |
|------------|----------|
| eCl@ss 5.1 | 27141141 |
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000897 |
|----------|----------|

### Drawings

#### Circuit diagram







Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.