


Power MOSFET

| PRODUCT SUMMARY | |
|---------------------------------|----------------------------------|
| V _{DS} (V) | 500 |
| R _{DSD(on)} (Max.) (Ω) | V _{GS} = 10 V 1.40 |
| Q _g (Max.) (nC) | 24 |
| Q _{gs} (nC) | 6.3 |
| Q _{gd} (nC) | 11 |
| Configuration | Single |



FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- Low Gate Charge Q_g Results in Simple Drive Requirement
- Improved Gate, Avalanche and Dynamic dV/dt Ruggedness
- Fully Characterized Capacitance and Avalanche Voltage and Current
- Effective C_{oss} specified
- Compliant to RoHS Directive 2002/95/EC



RoHS*
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply
- High speed power switching

TYPICAL SMPS TOPOLOGIES

- Two Transistor Forward
- Half Bridge and Full Bridge

| ORDERING INFORMATION | | | |
|---------------------------------|-----------------------------|-------------------------------|-----------------------------|
| Package | D ² PAK (TO-263) | D ² PAK (TO-263) | I ² PAK (TO-262) |
| Lead (Pb)-free and Halogen-free | SiHF830AS-GE3 | SiHF830ASTRL-GE3 ^a | SiHF830AL-GE3 ^a |
| Lead (Pb)-free | IRF830ASPbF | IRF830ASTRLPbF ^a | IRF830ALPbF |
| | SiHF830AS-E3 | SiHF830ASTL-E3 ^a | SiHF830AL-E3 |

Note

a. See device orientation.

| ABSOLUTE MAXIMUM RATINGS (T _C = 25 °C, unless otherwise noted) | | | | |
|---|-------------------------|-----------------------------------|------------------|------|
| PARAMETER | | SYMBOL | LIMIT | UNIT |
| Drain-Source Voltage | | V _{DS} | 500 | V |
| Gate-Source Voltage | | V _{GS} | ± 30 | |
| Continuous Drain Current | V _{GS} at 10 V | T _C = 25 °C | 5.0 | A |
| | | T _C = 100 °C | 3.2 | |
| Pulsed Drain Current ^{a, e} | | I _{DM} | 20 | |
| Linear Derating Factor | | | 0.59 | W/°C |
| Single Pulse Avalanche Energy ^{b, e} | | E _{AS} | 230 | mJ |
| Avalanche Current ^a | | I _{AR} | 5.0 | A |
| Repetitive Avalanche Energy ^a | | E _{AR} | 7.4 | mJ |
| Maximum Power Dissipation | | T _A = 25 °C | 3.1 | W |
| | | T _C = 25 °C | 74 | |
| Peak Diode Recovery dV/dt ^{c, e} | | dV/dt | 5.3 | V/ns |
| Operating Junction and Storage Temperature Range | | T _J , T _{stg} | - 55 to + 150 | |
| Soldering Recommendations (Peak Temperature) | for 10 s | | 300 ^d | °C |

Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- Starting T_J = 25 °C, L = 18 mH, R_g = 25 Ω, I_{AS} = 5.0 A (see fig. 12).
- I_{SD} ≤ 5.0 A, dI/dt ≤ 370 A/μs, V_{DD} ≤ V_{DS}, T_J ≤ 150 °C.
- 1.6 mm from case.
- Uses SiHF830A data and test conditions.

* Pb containing terminations are not RoHS compliant, exemptions may apply

THERMAL RESISTANCE RATINGS

| PARAMETER | SYMBOL | TYP. | MAX. | UNIT |
|---|-------------------|------|------|------|
| Maximum Junction-to-Ambient (PCB Mounted, Steady-State) ^a | R _{thJA} | - | 40 | °C/W |
| Maximum Junction-to-Case (Drain) | R _{thJC} | - | 1.7 | |

Note


a. When mounted on 1" square PCB (FR-4 or G-10 material).

SPECIFICATIONS ($T_J = 25^\circ\text{C}$, unless otherwise noted)


| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT |
|--|----------------------------------|---|---|------|------|-------|------|
| Static | | | | | | | |
| Drain-Source Breakdown Voltage | V _{DS} | V _{GS} = 0, I _D = 250 μA | | 500 | - | - | V |
| V _{DS} Temperature Coefficient | ΔV _{DS} /T _J | Reference to 25 °C, I _D = 1 mA ^d | | - | 0.60 | - | V/°C |
| Gate-Source Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = 250 μA | | 2.0 | - | 4.5 | V |
| Gate-Source Leakage | I _{GSS} | V _{GS} = ± 30 V | | - | - | ± 100 | nA |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} = 500 V, V _{GS} = 0 V | | - | - | 25 | μA |
| | | V _{DS} = 400 V, V _{GS} = 0 V, T _J = 125 °C | | - | - | 250 | |
| Drain-Source On-State Resistance | R _{DS(on)} | V _{GS} = 10 V | I _D = 3.0 A ^b | - | - | 1.4 | Ω |
| Forward Transconductance | g _{fs} | V _{DS} = 50 V, I _D = 3.0 A ^d | | 2.8 | - | - | S |
| Dynamic | | | | | | | |
| Input Capacitance | C _{iss} | V _{GS} = 0 V, V _{DS} = 25 V, f = 1.0 MHz, see fig. 5 ^d | | - | 620 | - | pF |
| Output Capacitance | C _{oss} | | | - | 93 | - | |
| Reverse Transfer Capacitance | C _{rss} | | | - | 4.3 | - | |
| Output Capacitance | C _{oss} | V _{GS} = 0 V | V _{DS} = 1.0 V, f = 1.0 MHz | - | 886 | - | nC |
| | | | V _{DS} = 400 V, f = 1.0 MHz | - | 27 | - | |
| Effective Output Capacitance | C _{oss eff.} | | V _{DS} = 0 V to 400 V ^{c, d} | - | 39 | - | |
| Total Gate Charge | Q _g | V _{GS} = 10 V | I _D = 5.0 A, V _{DS} = 400 V, see fig. 6 and 13 ^{b, d} | - | - | 24 | ns |
| Gate-Source Charge | Q _{gs} | | | - | - | 6.3 | |
| Gate-Drain Charge | Q _{gd} | | | - | - | 11 | |
| Turn-On Delay Time | t _{d(on)} | | | - | 10 | - | |
| Rise Time | t _r | V _{DD} = 250 V, I _D = 5.0 A, R _g = 14 Ω, R _D = 49 Ω, see fig. 10 ^{b, d} | - | 21 | - | ns | |
| Turn-Off Delay Time | t _{d(off)} | | - | 21 | - | | |
| Fall Time | t _f | | - | 15 | - | | |
| Drain-Source Body Diode Characteristics | | | | | | | |
| Continuous Source-Drain Diode Current | I _S | MOSFET symbol showing the integral reverse p - n junction diode | I ^D | - | - | 5.0 | A |
| Pulsed Diode Forward Current ^a | I _{SM} | | I _S | - | - | 20 | |
| Body Diode Voltage | V _{SD} | T _J = 25 °C, I _S = 5.0 A, V _{GS} = 0 V ^b | | - | - | 1.5 | V |
| Body Diode Reverse Recovery Time | t _{rr} | T _J = 25 °C, I _F = 5.0 A, dI/dt = 100 A/μs ^{b, d} | | - | 430 | 650 | ns |
| Body Diode Reverse Recovery Charge | Q _{rr} | | | - | 2.0 | 3.0 | μC |
| Forward Turn-On Time | t _{on} | Intrinsic turn-on time is negligible (turn-on is dominated by L _S and L _D) | | | | | |

Notes


- a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- b. Pulse width ≤ 300 μs; duty cycle ≤ 2 %.
- c. C_{oss eff.} is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80 % V_{DS}.
- d. Uses SiHF830A data and test conditions.

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



91062_01

 V_{DS} , Drain-to-Source Voltage (V)**Fig. 1 - Typical Output Characteristics**

91062_03

 V_{GS} , Gate-to-Source Voltage (V)**Fig. 3 - Typical Transfer Characteristics**

91062_02

 V_{DS} , Drain-to-Source Voltage (V)**Fig. 2 - Typical Output Characteristics**

91062_04

 T_J , Junction Temperature (°C)**Fig. 4 - Normalized On-Resistance vs. Temperature**




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage










Fig. 8 - Maximum Safe Operating Area


Fig. 10a - Switching Time Test Circuit

Fig. 10b - Switching Time Waveforms

Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case

Fig. 12a - Unclamped Inductive Test Circuit

Fig. 12b - Unclamped Inductive Waveforms




Fig. 12c - Maximum Avalanche Energy vs. Drain Current




Fig. 12d - Basic Gate Charge Waveform




Fig. 13a - Maximum Avalanche Energy vs. Drain Current




Fig. 13b - Gate Charge Test Circuit




Fig. 14 - For N-Channel

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?91062.

TO-263AB (HIGH VOLTAGE)




| DIM. | MILLIMETERS | | INCHES | |
|------|-------------|------|--------|-------|
| | MIN. | MAX. | MIN. | MAX. |
| A | 4.06 | 4.83 | 0.160 | 0.190 |
| A1 | 0.00 | 0.25 | 0.000 | 0.010 |
| b | 0.51 | 0.99 | 0.020 | 0.039 |
| b1 | 0.51 | 0.89 | 0.020 | 0.035 |
| b2 | 1.14 | 1.78 | 0.045 | 0.070 |
| b3 | 1.14 | 1.73 | 0.045 | 0.068 |
| c | 0.38 | 0.74 | 0.015 | 0.029 |
| c1 | 0.38 | 0.58 | 0.015 | 0.023 |
| c2 | 1.14 | 1.65 | 0.045 | 0.065 |
| D | 8.38 | 9.65 | 0.330 | 0.380 |

ECN: S-82110-Rev. A, 15-Sep-08
DWG: 5970

Notes

- Dimensioning and tolerancing per ASME Y14.5M-1994.
- Dimensions are shown in millimeters (inches).
- Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body at datum A.
- Thermal PAD contour optional within dimension E, L1, D1 and E1.
- Dimension b1 and c1 apply to base metal only.
- Datum A and B to be determined at datum plane H.
- Outline conforms to JEDEC outline to TO-263AB.

RECOMMENDED MINIMUM PADS FOR D²PAK: 3-Lead

Recommended Minimum Pads
Dimensions in Inches/(mm)

[Return to Index](#)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.