

- **Function, Pinout, and Drive Compatible With FCT and F Logic**
- **Reduced $V_{OH}$ (Typically = 3.3 V) Versions of Equivalent FCT Functions**
- **Edge-Rate Control Circuitry for Significantly Improved Noise Characteristics**
- **$I_{off}$ Supports Partial-Power-Down Mode Operation**
- **ESD Protection Exceeds JESD 22**
  - **2000-V Human-Body Model (A114-A)**
  - **200-V Machine Model (A115-A)**
  - **1000-V Charged-Device Model (C101)**
- **Matched Rise and Fall Times**
- **Fully Compatible With TTL Input and Output Logic Levels**
- **CY54FCT245T**
  - **48-mA Output Sink Current**
    **12-mA Output Source Current**
- **CY74FCT245T**
  - **64-mA Output Sink Current**
    **32-mA Output Source Current**
- **3-State Outputs**

**CY54FCT245T . . . D PACKAGE**
**CY74FCT245T . . . P, Q, OR SO PACKAGE**
**(TOP VIEW)**




**CY54FCT245T . . . L PACKAGE**
**(TOP VIEW)**




## description

The ’FCT245T devices contain eight noninverting bidirectional buffers with 3-state outputs and are intended for bus-oriented applications.

The transmit/receive (T/$\overline{R}$) input determines the direction of data flow through these bidirectional transceivers. Transmit (active high) enables data from A ports to B ports. The output enable ($\overline{OE}$), when high, disables both the A and B ports by putting them in the high-impedance state.

These devices are fully specified for partial-power-down applications using $I_{off}$. The $I_{off}$ circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

**PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.**

Copyright © 2001, Texas Instruments Incorporated
**On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.**

## ORDERING INFORMATION

| $T_A$ | PACKAGE† | | SPEED (ns) | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|---|---|---|---|---|---|
| –40°C to 85°C | QSOP – Q | Tape and reel | 3.8 | CY74FCT245DTQCT | FCT245D |
| | QSOP – Q | Tape and reel | 4.1 | CY74FCT245CTQCT | FCT245C |
| | SOIC – SO | Tube | 4.1 | CY74FCT245CTSOC | FCT245C |
| | | Tape and reel | 4.1 | CY74FCT245CTSOCT | |
| | DIP – P | Tube | 4.6 | CY74FCT245ATPC | CY74FCT245ATPC |
| | QSOP – Q | Tape and reel | 4.6 | CY74FCT245ATQCT | FCT245A |
| | SOIC – SO | Tube | 4.6 | CY74FCT245ATSOC | FCT245A |
| | | Tape and reel | 4.6 | CY74FCT245ATSOCT | |
| | QSOP – Q | Tape and reel | 7 | CY74FCT245TQCT | FCT245 |
| | SOIC – SO | Tube | 7 | CY74FCT245TSOC | FCT245 |
| | | Tape and reel | 7 | CY74FCT245TSOCT | |
| –55°C to 125°C | CDIP – D | Tube | 4.5 | CY54FCT245CTDMB | |
| | LCC – L | Tube | 4.5 | CY54FCT245CTLMB | |
| | CDIP – D | Tube | 4.9 | CY54FCT245ATDMB | |
| | LCC – L | Tube | 4.9 | CY54FCT245ATLMB | |
| | CDIP – D | Tube | 7.5 | CY54FCT245TDMB | |
| | LCC – L | Tube | 7.5 | CY54FCT245TLMB | |


† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.

**FUNCTION TABLE**

| INPUTS | | OPERATION |
|---|---|---|
| $\overline{OE}$ | T/$\overline{R}$ | |
| L | L | B data to bus A |
| L | H | A data to bus B |
| H | X | Z |

H = High logic level, L = Low logic level, X = Don't care, Z = High-impedance state

## logic diagram (positive logic)



### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage range to ground potential . . . . . –0.5 V to 7 V
DC input voltage range . . . . . –0.5 V to 7 V
DC output voltage range . . . . . –0.5 V to 7 V
DC output current (maximum sink current/pin) . . . . . 120 mA
Package thermal impedance, $\theta_{JA}$ (see Note 1): P package . . . . . 69°C/W
Q package . . . . . 68°C/W
SO package . . . . . 58°C/W
Ambient temperature range with power applied, $T_A$ . . . . . –65°C to 135°C
Storage temperature range, $T_{stg}$ . . . . . –65°C to 150°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The package thermal impedance is calculated in accordance with JESD 51-7.

### recommended operating conditions (see Note 2)

| | | CY54FCT245T | | | CY74FCT245T<br>CY74FCT245AT<br>CY74FCT245CT<br>CY74FCT245DT | | | UNIT |
|---|---|---|---|---|---|---|---|---|
| | | MIN | NOM | MAX | MIN | NOM | MAX | |
| $V_{CC}$ | Supply voltage | 4.5 | 5 | 5.5 | 4.75 | 5 | 5.25 | V |
| $V_{IH}$ | High-level input voltage | 2 | | | 2 | | | V |
| $V_{IL}$ | Low-level input voltage | | | 0.8 | | | 0.8 | V |
| $I_{OH}$ | High-level output current | | | –12 | | | –32 | mA |
| $I_{OL}$ | Low-level output current | | | 48 | | | 64 | mA |
| $T_A$ | Operating free-air temperature | –55 | | 125 | –40 | | 85 | °C |

NOTE 2: All unused inputs of the device must be held at $V_{CC}$ or GND to ensure proper device operation.

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | CY54FCT245T | | | CY74FCT245T | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|
| | | | MIN | TYP† | MAX | MIN | TYP† | MAX | |
| $V_{IK}$ | $V_{CC}$ = 4.5 V, | $I_{IN}$ = –18 mA | | –0.7 | –1.2 | | | | V |
| | $V_{CC}$ = 4.75 V, | $I_{IN}$ = –18 mA | | | | | –0.7 | –1.2 | |
| $V_{OH}$ | $V_{CC}$ = 4.5 V, | $I_{OH}$ = –12 mA | 2.4 | 3.3 | | | | | V |
| | $V_{CC}$ = 4.75 V | $I_{OH}$ = –32 mA | | | | 2 | | | |
| | | $I_{OH}$ = –15 mA | | | | 2.4 | 3.3 | | |
| $V_{OL}$ | $V_{CC}$ = 4.5 V, | $I_{OL}$ = 48 mA | | 0.3 | 0.55 | | | | V |
| | $V_{CC}$ = 4.75 V, | $I_{OL}$ = 64 mA | | | | | 0.3 | 0.55 | |
| $V_{hys}$ | All inputs | | | 0.2 | | | 0.2 | | V |
| $I_I$ | $V_{CC}$ = 5.5 V, | $V_{IN}$ = $V_{CC}$ | | | 5 | | | | µA |
| | $V_{CC}$ = 5.25 V, | $V_{IN}$ = $V_{CC}$ | | | | | | 5 | |
| $I_{IH}$ | $V_{CC}$ = 5.5 V, | $V_{IN}$ = 2.7 V | | | ±1 | | | | µA |
| | $V_{CC}$ = 5.25 V, | $V_{IN}$ = 2.7 V | | | | | | ±1 | |
| $I_{IL}$ | $V_{CC}$ = 5.5 V, | $V_{IN}$ = 0.5 V | | | ±1 | | | | µA |
| | $V_{CC}$ = 5.25 V, | $V_{IN}$ = 0.5 V | | | | | | ±1 | |
| $I_{OZH}$ | $V_{CC}$ = 5.5 V, | $V_{OUT}$ = 2.7 V | | | 10 | | | | µA |
| | $V_{CC}$ = 5.25 V, | $V_{OUT}$ = 2.7 V | | | | | | 10 | |
| $I_{OZL}$ | $V_{CC}$ = 5.5 V, | $V_{OUT}$ = 0.5 V | | | –10 | | | | µA |
| | $V_{CC}$ = 5.25 V, | $V_{OUT}$ = 0.5 V | | | | | | –10 | |
| $I_{OS}$‡ | $V_{CC}$ = 5.5 V, | $V_{OUT}$ = 0 V | –60 | –120 | –225 | | | | mA |
| | $V_{CC}$ = 5.25 V, | $V_{OUT}$ = 0 V | | | | –60 | –120 | –225 | |
| $I_{off}$ | $V_{CC}$ = 0 V, | $V_{OUT}$ = 4.5 V | | | ±1 | | | ±1 | µA |
| $I_{CC}$ | $V_{CC}$ = 5.5 V, | $V_{IN}$ ≤ 0.2 V, $V_{IN}$ ≥ $V_{CC}$ – 0.2 V | | 0.1 | 0.2 | | | | mA |
| | $V_{CC}$ = 5.25 V, | $V_{IN}$ ≤ 0.2 V, $V_{IN}$ ≥ $V_{CC}$ – 0.2 V | | | | | 0.1 | 0.2 | |
| $\Delta I_{CC}$ | $V_{CC}$ = 5.5 V, $V_{IN}$ = 3.4 V§, $f_1$ = 0, Outputs open | | | 0.5 | 2 | | | | mA |
| | $V_{CC}$ = 5.25 V, $V_{IN}$ = 3.4 V§, $f_1$ = 0, Outputs open | | | | | | 0.5 | 2 | |
| $I_{CCD}$¶ | $V_{CC}$ = 5.5 V, One input switching at 50% duty cycle, Outputs open, T/$\overline{R}$ or $\overline{OE}$ = GND and $V_{IN}$ ≤ 0.2 V or $V_{IN}$ ≥ $V_{CC}$ – 0.2 V | | | 0.06 | 0.12 | | | | mA/ MHz |
| | $V_{CC}$ = 5.25 V, One input switching at 50% duty cycle, Outputs open, T/$\overline{R}$ or $\overline{OE}$ = GND and $V_{IN}$ ≤ 0.2 V or $V_{IN}$ ≥ $V_{CC}$ – 0.2 V | | | | | | 0.06 | 0.12 | |

† Typical values are at $V_{CC}$ = 5 V, $T_A$ = 25°C.

‡ Not more than one output should be shorted at a time. Duration of short should not exceed one second. The use of high-speed test apparatus and/or sample-and-hold techniques are preferable to minimize internal chip heating and more accurately reflect operational values. Otherwise, prolonged shorting of a high output can raise the chip temperature well above normal and cause invalid readings in other parametric tests. In any sequence of parameter tests, $I_{OS}$ tests should be performed last.

§ Per TTL-driven input ($V_{IN}$ = 3.4 V); all other inputs at $V_{CC}$ or GND

¶ This parameter is derived for use in total power-supply calculations.

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted) (continued)**

| PARAMETER | TEST CONDITIONS | | | CY54FCT245T | | | CY74FCT245T | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP† | MAX | MIN | TYP† | MAX | |
| $I_C$# | $V_{CC}$ = 5.5 V, Outputs open, T/$\overline{R}$ or $\overline{OE}$ = GND | One bit switching at $f_1$ = 10 MHz at 50% duty cycle | $V_{IN} \le 0.2$ V or $V_{IN} \ge V_{CC} - 0.2$ V | | 0.7 | 1.4 | | | | mA |
| | | | $V_{IN}$ = 3.4 V or GND | | 1.2 | 3.4 | | | | |
| | | Eight bits switching at $f_1$ = 2.5 MHz at 50% duty cycle | $V_{IN} \le 0.2$V or $V_{IN} \ge V_{CC} - 0.2$ V | | 1.3 | 2.6‖ | | | | |
| | | | $V_{IN}$ = 3.4 V or GND | | 3.3 | 10.6‖ | | | | |
| | $V_{CC}$ = 5.25 V, Outputs open, T/$\overline{R}$ or $\overline{OE}$ = GND | One bit switching at $f_1$ = 10 MHz at 50% duty cycle | $V_{IN} \le 0.2$ V or $V_{IN} \ge V_{CC} - 0.2$ V | | | | | 0.7 | 1.4 | |
| | | | $V_{IN}$ = 3.4 V or GND | | | | | 1.2 | 3.4 | |
| | | Eight bits switching at $f_1$ = 2.5 MHz at 50% duty cycle | $V_{IN} \le 0.2$V or $V_{IN} \ge V_{CC} - 0.2$ V | | | | | 1.3 | 2.6‖ | |
| | | | $V_{IN}$ = 3.4 V or GND | | | | | 3.3 | 10.6‖ | |
| $C_i$ | | | | | 5 | 10 | | 5 | 10 | pF |
| $C_o$ | | | | | 9 | 12 | | 9 | 12 | pF |

† Typical values are at $V_{CC}$ = 5 V, $T_A$ = 25°C.

# $I_C = I_{CC} + \Delta I_{CC} \times D_H \times N_T + I_{CCD} (f_0/2 + f_1 \times N_1)$

Where:

$I_C$ = Total supply current
$I_{CC}$ = Power-supply current with CMOS input levels
$\Delta I_{CC}$ = Power-supply current for a TTL high input ($V_{IN}$ = 3.4 V)
$D_H$ = Duty cycle for TTL inputs high
$N_T$ = Number of TTL inputs at $D_H$
$I_{CCD}$ = Dynamic current caused by an input transition pair (HLH or LHL)
$f_0$ = Clock frequency for registered devices, otherwise zero
$f_1$ = Input signal frequency
$N_1$ = Number of inputs changing at $f_1$

All currents are in milliamperes and all frequencies are in megahertz.

‖ Values for these conditions are examples of the $I_{CC}$ formula.


### switching characteristics over operating free-air temperature range (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | CY54FCT245T | | CY54FCT245AT | | CY54FCT245CT | | UNIT |
|---|---|---|---|---|---|---|---|---|---|
| | | | MIN | MAX | MIN | MAX | MIN | MAX | |
| $t_{PLH}$ | A or B | B or A | 1.5 | 7.5 | 1.5 | 4.9 | 1.5 | 4.5 | ns |
| $t_{PHL}$ | | | 1.5 | 7.5 | 1.5 | 4.9 | 1.5 | 4.5 | |
| $t_{PZH}$ | $\overline{OE}$ or T/$\overline{R}$ | A or B | 1.5 | 10 | 1.5 | 6.5 | 1.5 | 6.2 | ns |
| $t_{PZL}$ | | | 1.5 | 10 | 1.5 | 6.5 | 1.5 | 6.2 | |
| $t_{PHZ}$ | $\overline{OE}$ or T/$\overline{R}$ | A or B | 1.5 | 10 | 1.5 | 6 | 1.5 | 5.2 | ns |
| $t_{PLZ}$ | | | 1.5 | 10 | 1.5 | 6 | 1.5 | 5.2 | |


### switching characteristics over operating free-air temperature range (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | CY74FCT245T | | CY74FCT245AT | | CY74FCT245CT | | CY74FCT245DT | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | MIN | MAX | MIN | MAX | MIN | MAX | MIN | MAX | |
| $t_{PLH}$ | A or B | B or A | 1.5 | 7 | 1.5 | 4.6 | 1.5 | 4.1 | 1.5 | 3.8 | ns |
| $t_{PHL}$ | | | 1.5 | 7 | 1.5 | 4.6 | 1.5 | 4.1 | 1.5 | 3.8 | |
| $t_{PZH}$ | $\overline{OE}$ or T/$\overline{R}$ | A or B | 1.5 | 9.5 | 1.5 | 6.2 | 1.5 | 5.8 | 1.5 | 5 | ns |
| $t_{PZL}$ | | | 1.5 | 9.5 | 1.5 | 6.2 | 1.5 | 5.8 | 1.5 | 5 | |
| $t_{PHZ}$ | $\overline{OE}$ or T/$\overline{R}$ | A or B | 1.5 | 7.5 | 1.5 | 5 | 1.5 | 4.8 | 1.5 | 4.3 | ns |
| $t_{PLZ}$ | | | 1.5 | 7.5 | 1.5 | 5 | 1.5 | 4.8 | 1.5 | 4.3 | |

## PARAMETER MEASUREMENT INFORMATION





LOAD CIRCUIT FOR
TOTEM-POLE OUTPUTS





LOAD CIRCUIT FOR
3-STATE OUTPUTS


| TEST | S1 |
|---|---|
| $t_{PLH}/t_{PHL}$ | Open |
| $t_{PLZ}/t_{PZL}$ | 7 V |
| $t_{PHZ}/t_{PZH}$ | Open |





VOLTAGE WAVEFORMS
PULSE DURATION




VOLTAGE WAVEFORMS
SETUP AND HOLD TIMES




VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES
INVERTING AND NONINVERTING OUTPUTS




VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES
LOW- AND HIGH-LEVEL ENABLING

NOTES: A. $C_L$ includes probe and jig capacitance.
B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
C. The outputs are measured one at a time with one input transition per measurement.

**Figure 1. Load Circuit and Voltage Waveforms**

## PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish | MSL Peak Temp (3) |
|---|---|---|---|---|---|---|---|---|
| 5962-9221401M2A | ACTIVE | LCCC | FK | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| 5962-9221401MRA | ACTIVE | CDIP | J | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| 5962-9221403M2A | ACTIVE | LCCC | FK | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| 5962-9221403MRA | ACTIVE | CDIP | J | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| 5962-9221405M2A | ACTIVE | LCCC | FK | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| 5962-9221405MRA | ACTIVE | CDIP | J | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| CY54FCT245ATDMB | ACTIVE | CDIP | J | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| CY54FCT245CTLMB | ACTIVE | LCCC | FK | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| CY54FCT245TLMB | ACTIVE | LCCC | FK | 20 | 1 | None | Call TI | Level-NC-NC-NC |
| CY74FCT245ATPC | ACTIVE | PDIP | N | 20 | 20 | Pb-Free (RoHS) | CU NIPDAU | Level-NC-NC-NC |
| CY74FCT245ATQCT | ACTIVE | SSOP/ QSOP | DBQ | 20 | 2500 | Pb-Free (RoHS) | CU NIPDAU | Level-2-260C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245ATSOC | ACTIVE | SOIC | DW | 20 | 25 | Pb-Free (RoHS) | CU NIPDAU | Level-2-250C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245ATSOCT | ACTIVE | SOIC | DW | 20 | 2000 | Pb-Free (RoHS) | CU NIPDAU | Level-2-250C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245CTQCT | ACTIVE | SSOP/ QSOP | DBQ | 20 | 2500 | Pb-Free (RoHS) | CU NIPDAU | Level-2-260C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245CTSOC | ACTIVE | SOIC | DW | 20 | 25 | Pb-Free (RoHS) | CU NIPDAU | Level-2-250C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245CTSOCT | ACTIVE | SOIC | DW | 20 | 2000 | Pb-Free (RoHS) | CU NIPDAU | Level-2-250C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245DTQCT | ACTIVE | SSOP/ QSOP | DBQ | 20 | 2500 | Pb-Free (RoHS) | CU NIPDAU | Level-2-260C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245TQCT | ACTIVE | SSOP/ QSOP | DBQ | 20 | 2500 | Pb-Free (RoHS) | CU NIPDAU | Level-2-260C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245TSOC | ACTIVE | SOIC | DW | 20 | 25 | Pb-Free (RoHS) | CU NIPDAU | Level-2-250C-1 YEAR/ Level-1-235C-UNLIM |
| CY74FCT245TSOCT | ACTIVE | SOIC | DW | 20 | 2000 | Pb-Free (RoHS) | CU NIPDAU | Level-2-250C-1 YEAR/ Level-1-235C-UNLIM |

(1) The marketing status values are defined as follows:
**ACTIVE:** Product device recommended for new designs.
**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.
**OBSOLETE:** TI has discontinued the production of the device.

(2) Eco Plan - May not be currently available - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
**None:** Not yet available Lead (Pb-Free).
**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
**Green (RoHS & no Sb/Br):** TI defines "Green" to mean "Pb-Free" and in addition, uses package materials that do not contain halogens, including bromine (Br) or antimony (Sb) above 0.1% of total product weight.

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDECindustry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| **Products** | | **Applications** | |
|---|---|---|---|
| Amplifiers | amplifier.ti.com | Audio | www.ti.com/audio |
| Data Converters | dataconverter.ti.com | Automotive | www.ti.com/automotive |
| DSP | dsp.ti.com | Broadband | www.ti.com/broadband |
| Interface | interface.ti.com | Digital Control | www.ti.com/digitalcontrol |
| Logic | logic.ti.com | Military | www.ti.com/military |
| Power Mgmt | power.ti.com | Optical Networking | www.ti.com/opticalnetwork |
| Microcontrollers | microcontroller.ti.com | Security | www.ti.com/security |
| | | Telephony | www.ti.com/telephony |
| | | Video & Imaging | www.ti.com/video |
| | | Wireless | www.ti.com/wireless |

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.




**Как с нами связаться**

**Телефон:** 8 (812) 309 58 32 (многоканальный)
**Факс:** 8 (812) 320-02-42
**Электронная почта:** org@eplast1.ru
**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.