

## Surface Mount Type

Series: **SXV**



**OS-CON**

**UPGRADE**


### Features

- Super high voltage (100 V.DC max.)
- RoHS compliance, Halogen free


### Specifications

| Size code                  | E7   | F8  | E12            | F12             |
|----------------------------|--|---|----------------|-----------------|
| Category temp. range       | -55 °C to +125 °C                                |   |                |                 |
| Rated voltage range        | 63 V.DC to 100 V.DC                              |   |                |                 |
| Nominal cap.range          | 6.8 μF to 18 μF                                  | 15 μF to 39 μF                                      | 15 μF to 56 μF | 18 μF to 100 μF |
| Capacitance tolerance      | ±20 % (120 Hz / +20 °C)                          |   |                |                 |
| DC leakage current         | Please see the attached characteristics list     |   |                |                 |
| Dissipation factor (tan δ) | Please see the attached characteristics list     |   |                |                 |
| Endurance                  | +125 °C, 1000 h, rated voltage applied           |   |                |                 |
|                            | Capacitance change                               | Within ±20 % of the initial value                   |                |                 |
|                            | Dissipation factor (tanδ)                        | ≤ 200 % of the initial limit                        |                |                 |
|                            | DC leakage current                               | Within the initial limit                            |                |                 |
|                            | +60 °C, 90 % to 95 %, 1000 h, No-applied voltage |   |                |                 |
|                            | Capacitance change                               | Within ±20 % of the initial value                   |                |                 |
|                            | Dissipation factor (tanδ)                        | ≤ 150 % of the initial limit                        |                |                 |
|                            | DC leakage current                               | Within the initial limit (after voltage processing) |                |                 |

### Marking



### Dimensions (not to scale)



# Panasonic Conductive Polymer Aluminum Solid Capacitors

## Characteristics list

| Rated vol. (V.DC) | Rated cap. ( $\pm 20\%$ ) ( $\mu\text{F}$ ) | Case size (mm) |      | Size code | Specifications                           |  |  |                              |                                    | Standard (Reel size : $\phi 380$ ) |                           |     |
|-------------------|---|----------------|------|-----------|--|--|--|------------------------------|------------------------------------|------------------------------------|---------------------------|-----|
|                   |   | $\phi\text{D}$ | L    |           | Ripple current* <sup>1</sup> (mA r.m.s.) | Allowable ripple current* <sup>1</sup> (mA r.m.s.) | ESR* <sup>2</sup> ( $\text{m}\Omega$ ) | $\tan \delta$ * <sup>3</sup> | LC* <sup>4</sup> ( $\mu\text{A}$ ) | Part number                        | Min. Packaging Q'ty (pcs) |     |
| 63                | 18  | 8.0            | 6.9  | E7        | 340                                      | 1100   | 60                                     | 0.12                         | 56                                 | 63SXV18M                           | 1000                      |     |
|                   | 33  | 8.0            | 11.9 | E12       | 930                                      | 2950   | 25                                     | 0.12                         | 104                                | 63SXV33M                           | 400                       |     |
|                   | 39  | 8.0            | 11.9 | E12       | 930                                      | 2950   | 25                                     | 0.12                         | 122                                | 63SXV39M                           | 400                       |     |
|                   |   | 10.0           | 7.9  | F8        | 690                                      | 2190   | 50                                     | 0.12                         | 122                                | 63SXV39MX                          | 500                       |     |
|                   | <b>NEW</b>                                  | 56             | 8.0  | 11.9      | E12                                      | 930  | 2950                                   | 25                           | 0.12                               | 176                                | 63SXV56M                  | 400 |
|                   | 68  | 10.0           | 12.6 | F12       | 1030                                     | 3280   | 25                                     | 0.12                         | 214                                | 63SXV68M                           | 400                       |     |
| <b>NEW</b>        | 100   | 10.0           | 12.6 | F12       | 1030                                     | 3280   | 25                                     | 0.12                         | 315                                | 63SXV100M                          | 400                       |     |
| 80                | 12  | 8.0            | 6.9  | E7        | 340                                      | 1100   | 60                                     | 0.12                         | 48                                 | 80SXV12M                           | 1000                      |     |
|                   | 27  | 8.0            | 11.9 | E12       | 780                                      | 2490   | 35                                     | 0.12                         | 108                                | 80SXV27M                           | 400                       |     |
|                   |   | 10.0           | 7.9  | F8        | 660                                      | 2080   | 55                                     | 0.12                         | 108                                | 80SXV27MX                          | 500                       |     |
|                   | <b>NEW</b>                                  | 33             | 8.0  | 11.9      | E12                                      | 780  | 2490                                   | 35                           | 0.12                               | 132                                | 80SXV33M                  | 400 |
|                   | 47  | 10.0           | 12.6 | F12       | 980                                      | 3100   | 28                                     | 0.12                         | 980                                | 80SXV47M                           | 400                       |     |
| <b>NEW</b>        | 56  | 10.0           | 12.6 | F12       | 980                                      | 3100   | 28                                     | 0.12                         | 224                                | 80SXV56M                           | 400                       |     |
| 100               | 6.8   | 8.0            | 6.9  | E7        | 340                                      | 1100   | 60                                     | 0.12                         | 34                                 | 100SXV6R8M                         | 1000                      |     |
|                   | 15  | 10.0           | 7.9  | F8        | 630                                      | 2000   | 60                                     | 0.12                         | 75                                 | 100SXV15MX                         | 500                       |     |
|                   |   | 8.0            | 11.9 | E12       | 730                                      | 2350   | 40                                     | 0.12                         | 75                                 | 100SXV15M                          | 400                       |     |
|                   | 18  | 10.0           | 12.6 | F12       | 940                                      | 3000   | 30                                     | 0.12                         | 90                                 | 100SXV18M                          | 400                       |     |
|                   |   | <b>NEW</b>     | 8.0  | 11.9      | E12                                      | 730  | 2350                                   | 40                           | 0.12                               | 90                                 | 100SXV18MX                | 400 |
|                   | 22  | 10.0           | 12.6 | F12       | 940                                      | 3000   | 30                                     | 0.12                         | 110                                | 100SXV22M                          | 400                       |     |
| <b>NEW</b>        | 27  | 10.0           | 12.6 | F12       | 940                                      | 3000   | 30                                     | 0.12                         | 135                                | 100SXV27M                          | 400                       |     |

\*1: Ripple current (100 kHz /  $+105\text{ }^\circ\text{C} < \text{T}_x \leq +125\text{ }^\circ\text{C}$ ) / Allowable ripple current (100 kHz /  $\text{T}_x \leq +105\text{ }^\circ\text{C}$ )

\*2: ESR (100 kHz to 300 kHz /  $+20\text{ }^\circ\text{C}$ )

\*3:  $\tan \delta$  (120 Hz /  $+20\text{ }^\circ\text{C}$ )

\*4: After 2 minutes

• Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".

## Frequency correction factor for ripple current

| Frequency(f) | $120\text{ Hz} \leq f < 1\text{ kHz}$ | $1\text{ kHz} \leq f < 10\text{ kHz}$ | $10\text{ kHz} \leq f < 100\text{ kHz}$ | $100\text{ kHz} \leq f < 500\text{ kHz}$ |
|--------------|---------------------------------------|---------------------------------------|---|--|
| Coefficient  | 0.05                                  | 0.3                                   | 0.7                                     | 1  |

## Guidelines and precautions regarding the technical information and use of our products described in this online catalog.

- If you want to use our products described in this online catalog for applications requiring special qualities or reliability, or for applications where the failure or malfunction of the products may directly jeopardize human life or potentially cause personal injury (e.g. aircraft and aerospace equipment, traffic and transportation equipment, combustion equipment, medical equipment, accident prevention, anti-crime equipment, and/or safety equipment), it is necessary to verify whether the specifications of our products fit to such applications. Please ensure that you will ask and check with our inquiry desk as to whether the specifications of our products fit to such applications use before you use our products.
- The quality and performance of our products as described in this online catalog only apply to our products when used in isolation. Therefore, please ensure you evaluate and verify our products under the specific circumstances in which our products are assembled in your own products and in which our products will actually be used.
- If you use our products in equipment that requires a high degree of reliability, regardless of the application, it is recommended that you set up protection circuits and redundancy circuits in order to ensure safety of your equipment.
- The products and product specifications described in this online catalog are subject to change for improvement without prior notice. Therefore, please be sure to request and confirm the latest product specifications which explain the specifications of our products in detail, before you finalize the design of your applications, purchase, or use our products.
- The technical information in this online catalog provides examples of our products' typical operations and application circuits. We do not guarantee the non-infringement of third party's intellectual property rights and we do not grant any license, right, or interest in our intellectual property.
- If any of our products, product specifications and/or technical information in this online catalog is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially with regard to security and export control, shall be observed.

## <Regarding the Certificate of Compliance with the EU RoHS Directive/REACH Regulations>

- The switchover date for compliance with the RoHS Directive/REACH Regulations varies depending on the part number or series of our products.
- When you use the inventory of our products for which it is unclear whether those products are compliant with the RoHS Directive/REACH Regulation, please select "Sales Inquiry" in the website inquiry form and contact us.

**We do not take any responsibility for the use of our products outside the scope of the specifications, descriptions, guidelines and precautions described in this online catalog.**

---

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Panasonic:

[63SXV33M](#) [100SXV15M](#) [100SXV15MX](#) [100SXV22M](#) [100SXV6R8M](#) [100SXV18M](#) [80SXV47M](#) [63SXV18M](#)  
[63SXV39M](#) [63SXV68M](#) [80SXV27MX](#) [80SXV27M](#) [63SXV39MX](#) [80SXV12M](#) [80SXV33M](#) [80SXV56M](#) [100SXV18MX](#)  
[100SXV27M](#) [63SXV100M](#) [63SXV56M](#)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.