

## Features

- Low equivalent on resistance
- Extremely low leakage (typically 40µA @30V)
- High current capability ( $I_F = 2.2\text{ A}$ )
- Low  $V_F$ , fast switching Schottky
- ZLLS2000 complements low temperature equivalent ZHCS2000
- Package thermally rated to 150°C
- **Lead, Halogen, and Antimony Free/RoHS Compliant (Note 1)**
- **“Green” Device (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**

## Mechanical Data

- Case: SOT23-6
- Case material: molded Plastic. “Green” molding Compound.
- UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish
- Weight: 0.008 grams (Approximate)

## Applications


- DC – DC converters
- Strobes
- Mobile phones
- Charging circuits
- Motor control



SOT23-6



Device symbol




Top View  
Pin Out

## Ordering Information

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
ZLLS2000TA	LL20	7	8mm	3000 units
ZLLS2000TC	LL20	13	8mm	10000 units

Notes: 1. No purposefully added lead. Halogen and Antimony Free.  
2. Diodes Inc's "Green" Policy can be found on our website at <http://www.diodes.com>

## Marking Information



LL20 = Product Type Marking Code

**Maximum Ratings** @ $T_A = 25^\circ\text{C}$  unless otherwise specified



Characteristic	Symbol	Value	Unit
Continuous Reverse Voltage	$V_R$	40	V
Forward Current	$I_F$	2.2	A
Peak Repetitive Forward Current Rectangular Pulse Duty Cycle	$I_{FPK}$	3.55	A
Non Repetitive Forward Current	$I_{FSM}$	36	A
		12	A

$t \leq 100\mu\text{s}$   
 $t \leq 10\text{ms}$

**Thermal Characteristics**

Characteristic	Symbol	Value	Unit
Power Dissipation @ $T_A = 25^\circ\text{C}$ Single Die Continuous	$P_D$	1.1	W
Single Die Measured at $t < 5$ secs		1.71	W
Junction to Ambient (Note 3)	$R_{\theta JA}$	113	$^\circ\text{C/W}$
Junction to Ambient (Note 4)	$R_{\theta JA}$	73	$^\circ\text{C/W}$
Storage Temperature Range	$T_{STG}$	-55 to +150	$^\circ\text{C}$
Junction Temperature	$T_J$	150	$^\circ\text{C}$







Notes: 3. For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.  
4. For a device mounted on FRB PCB measured at  $t < 5$ secs.




**Electrical Characteristics** @ $T_A = 25^\circ\text{C}$  unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage	$V_{(BR)R}$	40	-	-	V	$I_R = 1\text{mA}$
Forward Voltage (Note 5)	$V_F$	-	285	-	mV	$I_F = 50\text{mA}$
		-	305	-		$I_F = 100\text{mA}$
		-	335	-		$I_F = 250\text{mA}$
		-	365	390		$I_F = 500\text{mA}$
		-	403	430		$I_F = 1\text{A}$
		-	433	490		$I_F = 1.5\text{A}$
		-	461	540		$I_F = 2\text{A}$
		-	509	600		$I_F = 3\text{A}$
		-	450	-		$I_F = 2\text{A}, T_A = 100^\circ\text{C}$
Reverse Current	$I_R$	-	10	40	$\mu\text{A}$	$V_R = 30\text{V}$
		-	0.6	-	mA	$V_R = 30\text{V}, T_A = 85^\circ\text{C}$
Diode Capacitance	$C_D$	-	65	-	pF	$f = 1\text{MHz}, V_R = 30\text{V}$
Reverse Recovery Time	$t_{rr}$	-	6	-	ns	Switched from $I_F = 500\text{mA}$ to $V_R = 5.5\text{V}$
Reverse Recovery Charge	$Q_{rr}$	-	685	-	nC	Measured @ $I_R = 50\text{mA}$ . $di/dt = 500\text{mA}/\text{ns}$ . $R_{source} = 6\Omega; R_{load} = 10\Omega$

Notes: 5. Measured under pulsed conditions. Pulse width = 300 $\mu\text{s}$ . Duty cycle < 2%




**Package Outline Dimensions**



SOT-26			
Dim	Min	Max	Typ
A	0.35	0.50	0.38
B	1.50	1.70	1.60
C	2.70	3.00	2.80
D	—	—	0.95
H	2.90	3.10	3.00
J	0.013	0.10	0.05
K	1.00	1.30	1.10
L	0.35	0.55	0.40
M	0.10	0.20	0.15
α	0°	8°	—
All Dimensions in mm			

**Suggested Pad Layout**



Dimensions	Value (in mm)
Z	3.20
G	1.60
X	0.55
Y	0.80
C1	2.40
C2	0.95

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2010, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.