

Features

- Epitaxial Planar Die Construction
- Complementary PNP Type Available (DSS5140V)
- Low Collector-Emitter Saturation Voltage, $V_{CE(SAT)}$
- Surface Mount Package Suited for Automated Assembly
- Ultra-Small Surface Mount Package
- **Lead Free/RoHS Compliant (Note 1)**
- **"Green Device" (Note 2)**

Mechanical Data


- Case: SOT-563
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Finish — Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Marking Information: See Page 4
- Ordering Information: See Page 4
- Weight: 0.003 grams (approximate)




Top View



Bottom View



Device Schematic



Pin Out Configuration

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|--------------------------------------------|-----------|-------|------|
| Collector-Base Voltage | V_{CBO} | 40 | V |
| Collector-Emitter Voltage | V_{CEO} | 40 | V |
| Emitter-Base Voltage | V_{EBO} | 5 | V |
| Collector Current - Continuous | I_C | 1 | A |
| Repetitive Peak Collector Current (Note 3) | I_{CRP} | 2 | A |
| Peak Pulse Collector Current | I_{CM} | 3 | A |
| Base Current (DC) | I_B | 300 | mA |
| Peak Base Current | I_{BM} | 1 | A |

Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|-----------------------------------------------------------------------------|-----------------|-------------|---------------------------|
| Power Dissipation (Note 4) @ $T_A = 25^\circ\text{C}$ | P_D | 600 | mW |
| Thermal Resistance, Junction to Ambient (Note 4) @ $T_A = 25^\circ\text{C}$ | $R_{\theta JA}$ | 208 | $^\circ\text{C}/\text{W}$ |
| Operating and Storage Temperature Range | T_J, T_{STG} | -55 to +150 | $^\circ\text{C}$ |

- Notes:
1. No purposefully added lead.
 2. Diode's Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
 3. Operated under pulsed conditions: Pulse width $\leq 30\text{ms}$; duty cycle ≤ 0.2 .
 4. Device mounted on FR-4 PCB with minimum recommended pad layout.

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|----------------------------------------------|---------------|-------------------------|------------------|-------------------------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OFF CHARACTERISTICS | | | | | | |
| Collector-Base Breakdown Voltage | $V_{(BR)CBO}$ | 40 | — | — | V | $I_C = 100\mu\text{A}, I_E = 0$ |
| Collector-Emitter Breakdown Voltage (Note 5) | $V_{(BR)CEO}$ | 40 | — | — | V | $I_C = 10\text{mA}, I_B = 0$ |
| Emitter-Base Breakdown Voltage | $V_{(BR)EBO}$ | 5 | — | — | V | $I_E = 100\mu\text{A}, I_C = 0$ |
| Collector Cutoff Current | I_{CBO} | — | — | 100 | nA | $V_{CB} = 40\text{V}, I_E = 0$ |
| Collector Cutoff Current | I_{CES} | — | — | 100 | nA | $V_{CE} = 40\text{V}, V_{BE} = 0$ |
| Emitter Cutoff Current | I_{EBO} | — | — | 100 | nA | $V_{EB} = 5\text{V}, I_C = 0$ |
| ON CHARACTERISTICS (Note 5) | | | | | | |
| DC Current Gain | h_{FE} | 300 300 200 75 | — — — — | — 900 — — | — | $V_{CE} = 5\text{V}, I_C = 1\text{mA}$ $V_{CE} = 5\text{V}, I_C = 500\text{mA}$ $V_{CE} = 5\text{V}, I_C = 1\text{A}$ $V_{CE} = 5\text{V}, I_C = 2\text{A}$ |
| Collector-Emitter Saturation Voltage | $V_{CE(SAT)}$ | — — — — | — — — — | 80 110 190 440 | mV | $I_C = 100\text{mA}, I_B = 1\text{mA}$ $I_C = 500\text{mA}, I_B = 50\text{mA}$ $I_C = 1\text{A}, I_B = 100\text{mA}$ $I_C = 2\text{A}, I_B = 200\text{mA}$ |
| Collector-Emitter Saturation Resistance | $R_{CE(SAT)}$ | — | — | 190 | m Ω | $I_C = 1\text{A}, I_B = 100\text{mA}$ |
| Base-Emitter Saturation Voltage | $V_{BE(SAT)}$ | — | — | 1.2 | V | $I_C = 1\text{A}, I_B = 100\text{mA}$ |
| Base-Emitter Turn On Voltage | $V_{BE(ON)}$ | — | — | 1.1 | V | $V_{CE} = 5\text{V}, I_C = 1\text{A}$ |
| SMALL SIGNAL CHARACTERISTICS | | | | | | |
| Output Capacitance | C_{obo} | — | — | 10 | pF | $V_{CB} = 10\text{V}, f = 1.0\text{MHz}$ |
| Current Gain-Bandwidth Product | f_T | 150 | — | — | MHz | $V_{CE} = 10\text{V}, I_C = 50\text{mA}, f = 100\text{MHz}$ |
| SWITCHING CHARACTERISTICS | | | | | | |
| Turn-On Time | t_{on} | — | 58 | — | ns | $V_{CC} = 10\text{V}$ $I_C = 0.5\text{A}, I_{B1} = I_{B2} = 25\text{mA}$ |
| Delay Time | t_d | — | 30 | — | ns | |
| Rise Time | t_r | — | 28 | — | ns | |
| Turn-Off Time | t_{off} | — | 375 | — | ns | |
| Storage Time | t_s | — | 350 | — | ns | |
| Fall Time | t_f | — | 25 | — | ns | |


 Notes: 5. Measured under pulsed conditions. Pulse width = 300 μs . Duty cycle $\leq 2\%$.


Fig. 1 Power Dissipation vs. Ambient Temperature (Note 4)




Fig. 2 Typical Collector Current vs. Collector-Emitter Voltage (Note 4)




Fig. 3 Typical DC Current Gain vs. Collector Current




Fig. 4 Typical Collector-Emitter Saturation Voltage vs. Collector Current




Fig. 5 Typical Base-Emitter Turn-On Voltage vs. Collector Current




Fig. 6 Typical Base-Emitter Saturation Voltage vs. Collector Current




Fig. 7 Typical Capacitance Characteristics





Fig. 8 Transient Thermal Response (Note 4)

Ordering Information (Note 6)

| Part Number | Case | Packaging |
|-------------|---------|------------------|
| DSS4140V-7 | SOT-563 | 3000/Tape & Reel |

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information




ZN6 = Product Type Marking Code
YM = Date Code Marking
Y = Year (ex: V = 2008)
M = Month (ex: 9 = September)

Date Code Key

| Year | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 | 2015 |
|------|------|------|------|------|------|------|------|------|
| Code | V | W | X | Y | Z | A | B | C |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |


Package Outline Dimensions



| SOT-563 | | | |
|---------|------|------|------|
| Dim | Min | Max | Typ |
| A | 0.15 | 0.30 | 0.20 |
| B | 1.10 | 1.25 | 1.20 |
| C | 1.55 | 1.70 | 1.60 |
| D | - | - | 0.50 |
| G | 0.90 | 1.10 | 1.00 |
| H | 1.50 | 1.70 | 1.60 |
| K | 0.55 | 0.60 | 0.60 |
| L | 0.10 | 0.30 | 0.20 |
| M | 0.10 | 0.18 | 0.11 |

All Dimensions in mm

Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z | 2.2 |
| G | 1.2 |
| X | 0.375 |
| Y | 0.5 |
| C1 | 1.7 |
| C2 | 0.5 |

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.