

# CD4054B, CD4055B, CD4056B Types

## CMOS Liquid-Crystal Display Drivers

High-Voltage Types (20-Volt Rating)

**CD4054B – 4-Segment Display Driver**

**CD4055B – BCD to 7-Segment Decoder/Driver with “Display-Frequency” Output**

**CD4056B – BCD to 7-Segment Decoder/Driver with Strobed-Latch Function**

■ CD4055B and CD4056B types are single-digit BCD-to-7-segment decoder/driver circuits that provide level-shifting functions on the chip. This feature permits the BCD input-signal swings ( $V_{DD}$  to  $V_{SS}$ ) to be the same as or different from the 7-segment output-signal swings ( $V_{DD}$  to  $V_{EE}$ ). For example, the BCD input-signal swings ( $V_{DD}$  to  $V_{SS}$ ) may be as small as 0 to –3 V, whereas the output-display drive-signal swing ( $V_{DD}$  to  $V_{EE}$ ) may be as large as from 0 to –15 V. If  $V_{DD}$  to  $V_{EE}$  exceeds 15 V,  $V_{DD}$  to  $V_{SS}$  should be at least 4 V (0 to –4 V).

The 7-segment outputs are controlled by the DISPLAY-FREQUENCY (DF) input which causes the selected segment outputs to be low, high, or a square-wave output (for liquid-crystal displays). When the DF input is low the output segments will be high when selected by the BCD inputs. When the DF input is high, the output segments will be low when selected by the BCD inputs. When a square-wave is present at the DF input, the selected segments will have a square-wave output that is 180° out of phase with the DF input. Those segments which are not selected will have a square-wave output that is in phase with the input. DF square-wave repetition rates for liquid-crystal displays usually range from 30 Hz (well above flicker rate) to 200 Hz (well below the upper limit of the liquid-crystal frequency response). The CD4055B provides a level-shifted high-amplitude DF output which is required for driving the common electrode in liquid-crystal displays. The CD4056B provides a strobed-latch function at the BCD inputs. Decoding of all input combinations on the CD4055B and CD4056B provides displays of 0 to 9 as well as L, P, H, A, –, and a blank position.

The CD4054B provides level shifting similar to the CD4055B and CD4056B independently strobed latches, and common DF control on 4 signal lines. The CD4054B is intended to provide drive-signal compatibility with the CD4055B and CD4056B 7-segment decoder types for the decimal point, colon, polarity, and similar display lines. A level-shifted high-amplitude DF output can be obtained from any CD4054B output line by connect-

### Features:




- Operation of liquid crystals with CMOS circuits provides ultra-low-power displays
- Equivalent ac output drive for liquid-crystal displays – no external capacitor required
- Voltage doubling across display, e.g.  $V_{DD} - V_{EE} = 18\text{ V}$  results in effective 36 V p-p drive across selected display segments
- Low- or high-output level dc drive for other types of displays
- On-chip logic-level conversion for different input- and output-level swings
- Full decoding of all input combinations: 0-9, L, H, P, A, –, and blank positions
- Strobed-latch function—CD4054B Series and CD4056B Series
- DISPLAY-FREQUENCY (DF) output for liquid-crystal common-line drive signal—CD4055B Series (CD4054B Series also: see introductory text)
- 100% tested for quiescent current at 20 V
- Maximum input current of 1  $\mu\text{A}$  at 18 V over full package temperature range; 100 nA at 18 V and 25°C
- Noise margin (over full package temperature range):
  - 1 V at  $V_{DD} = 5\text{ V}$
  - 2 V at  $V_{DD} = 10\text{ V}$
  - 2.5 V at  $V_{DD} = 15\text{ V}$
- 5-V, 10-V, and 15-V parametric ratings

### Applications

- General-purpose displays
- Calculators and meters
- Wall and table clocks
- Industrial control panels
- Portable lab instruments
- Panel meters
- Auto dashboard displays
- Appliance control panels

ing the corresponding input and strobe lines to a low and high level, respectively and applying a square wave to DFIN. The CD4054B may also be utilized for logic-level “up conversion” or “down conversion”. For example, input-signal swings ( $V_{DD}$  to  $V_{SS}$ ) from +5 to 0 V can be converted to output-signal swings ( $V_{DD}$  to  $V_{EE}$ ) of +5 to –5 V. The level-shifting function on all three types permits the use of different input- and output-signal swings. The input swings from a low level of  $V_{SS}$  to a high level of  $V_{DD}$  while the output swings from a low level of  $V_{EE}$  to the same high level of  $V_{DD}$ . Thus, the input and output swings can be selected independently of each other over a 3-to-18 V range.  $V_{SS}$  may be connected to  $V_{EE}$  when no level-shift function is required.

For the CD4054B and CD4056B, data are



transferred from input to output by placing a high voltage level at the strobe input. A low voltage level at the strobe input latches the data input and the corresponding output segments remain selected (or non-selected) while the strobe is low.

Whenever the level-shifting function is required, the CD4055B can be used by itself to drive a liquid-crystal display (Fig.16 and Fig.20). The CD4056B, however, must be used together with a CD4054B to provide the common DF output (Fig.19). The capability of extending the voltage swing on the negative end (this voltage cannot be extended on the positive end) can be used to advantage in the setup of Fig.18. Fig.17 is common to all three types.

The CD4054B-, CD4055B-, and CD4056B-series types are supplied in 16-lead dual-in-line plastic packages (E suffix), 16-lead small-outline packages (M, M96, MT, and NSR suffixes), and 16-lead thin shrink small-outline packages (PW and PWR suffixes). The CD4054B- and CD4056B-series types also are supplied in 16-lead hermetic dual-in-line ceramic packages (F3A suffix).

# CD4054B, CD4055B, CD4056B Types




Fig. 1 - CD4054B functional diagram.



Fig. 2 - CD4055B functional diagram.



Fig. 3 - CD4056B functional diagram.

## CD4054B TRUTH TABLE

| DF | IN | ST | OUT |
|----|----|----|-----|
| 0  | 0  | 1  | 0   |
| 1  | 0  | 1  | 1   |
| 0  | 1  | 1  | 1   |
| 1  | 1  | 1  | 0   |
| X  | X  | 0  | *   |

X = Don't Care.

\*Depends upon the input mode previously applied when ST = 1.

## TRUTH TABLE FOR CD4055B and CD4056B

| INPUT CODE     |                |                |                | OUTPUT STATE |   |   |   |   |   |   | DISPLAY CHARAC-TER |
|----------------|----------------|----------------|----------------|--------------|---|---|---|---|---|---|--------------------|
| 2 <sup>3</sup> | 2 <sup>2</sup> | 2 <sup>1</sup> | 2 <sup>0</sup> | a            | b | c | d | e | f | g |                    |
| 0              | 0              | 0              | 0              | 1            | 1 | 1 | 1 | 1 | 1 | 0 |                    |
| 0              | 0              | 0              | 1              | 0            | 1 | 1 | 0 | 0 | 0 | 0 |                    |
| 0              | 0              | 1              | 0              | 1            | 1 | 0 | 1 | 1 | 0 | 1 |                    |
| 0              | 0              | 1              | 1              | 1            | 1 | 1 | 1 | 0 | 0 | 1 |                    |
| 0              | 1              | 0              | 0              | 0            | 1 | 1 | 0 | 0 | 1 | 1 |                    |
| 0              | 1              | 0              | 1              | 1            | 0 | 1 | 1 | 0 | 1 | 1 |                    |
| 0              | 1              | 1              | 0              | 1            | 0 | 1 | 1 | 1 | 1 | 1 |                    |
| 0              | 1              | 1              | 1              | 1            | 1 | 1 | 0 | 0 | 0 | 0 |                    |
| 1              | 0              | 0              | 0              | 1            | 1 | 1 | 1 | 1 | 1 | 1 |                    |
| 1              | 0              | 0              | 1              | 1            | 1 | 1 | 1 | 0 | 1 | 1 |                    |
| 1              | 0              | 1              | 0              | 0            | 0 | 0 | 1 | 1 | 1 | 0 |                    |
| 1              | 0              | 1              | 1              | 0            | 1 | 1 | 0 | 1 | 1 | 1 |                    |
| 1              | 1              | 0              | 0              | 1            | 1 | 0 | 0 | 1 | 1 | 1 |                    |
| 1              | 1              | 0              | 1              | 1            | 1 | 1 | 0 | 1 | 1 | 1 |                    |
| 1              | 1              | 1              | 0              | 0            | 0 | 0 | 0 | 0 | 0 | 1 |                    |
| 1              | 1              | 1              | 1              | 0            | 0 | 0 | 0 | 0 | 0 | 0 | BLANK              |




Fig. 4 - Typical propagation delay time vs. load capacitance for CD4054B.




Fig. 5 - Typical propagation delay time vs. load capacitance for CD4055 and CD4056B.




Fig. 6 - Typical transition time vs. load capacitance.




Fig. 7 - Typical input clock frequency vs. power dissipation.

# CD4054B, CD4055B, CD4056B Types

## MAXIMUM RATINGS, Absolute-Maximum Values:

DC SUPPLY-VOLTAGE RANGE, ( $V_{DD}$ )

Voltages referenced to  $V_{SS}$  Terminal)

INPUT VOLTAGE RANGE, ALL INPUTS

DC INPUT CURRENT, ANY ONE INPUT

POWER DISSIPATION PER PACKAGE ( $P_D$ ):

For  $T_A = -55^\circ\text{C}$  to  $+100^\circ\text{C}$

For  $T_A = +100^\circ\text{C}$  to  $+125^\circ\text{C}$

DEVICE DISSIPATION PER OUTPUT TRANSISTOR

FOR  $T_A = \text{FULL PACKAGE-TEMPERATURE RANGE (All Package Types)}$

OPERATING-TEMPERATURE RANGE ( $T_A$ )

STORAGE TEMPERATURE RANGE ( $T_{stg}$ )

LEAD TEMPERATURE (DURING SOLDERING):

At distance  $1/16 \pm 1/32$  inch ( $1.59 \pm 0.79\text{mm}$ ) from case for 10s max

## STATIC ELECTRICAL CHARACTERISTICS

| Characteristic                                 | CONDITIONS             |                        |                       |                        |                        | LIMITS AT INDICATED TEMPERATURES (°C) |       |       |       |       |                   |      | Unit |
|------------------------------------------------|------------------------|------------------------|-----------------------|------------------------|------------------------|---------------------------------------|-------|-------|-------|-------|-------------------|------|------|
|                                                | V <sub>EE</sub><br>(V) | V <sub>SS</sub><br>(V) | V <sub>O</sub><br>(V) | V <sub>IN</sub><br>(V) | V <sub>DD</sub><br>(V) | -55°                                  | -40°  | +85°  | +125° | +25°C |                   |      |      |
|                                                |                        |                        |                       |                        |                        |                                       |       |       |       | Min.  | Typ.              | Max. |      |
| Quiescent Device Current, I <sub>DD</sub> MAX. | -5                     | 0                      |                       |                        | 5                      | 5                                     |       | 150   | 150   | —     | 0.04              | 5    | μA   |
|                                                | 0                      | 0                      |                       |                        | 10                     | 10                                    |       | 300   | 300   | —     | 0.04              | 10   |      |
|                                                | 0                      | 0                      |                       |                        | 15                     | 20                                    |       | 600   | 600   | —     | 0.04              | 20   |      |
|                                                | 0                      | 0                      |                       |                        | 20                     | 100                                   |       | 3000  | 3000  | —     | 0.08              | 100  |      |
| Output Voltage:                                |                        |                        |                       |                        |                        |                                       |       |       |       |       |                   |      |      |
|                                                | 0                      | 0                      |                       | 0.5                    | 5                      |                                       | 0.05  |       |       | —     | 0                 | 0.05 |      |
| Low Level, V <sub>OL</sub> MAX.                | 0                      | 0                      |                       | 0.10                   | 10                     |                                       | 0.05  |       |       | —     | 0                 | 0.05 |      |
|                                                | 0                      | 0                      |                       | 0.15                   | 15                     |                                       | 0.05  |       |       | —     | 0                 | 0.05 | V    |
|                                                | 0                      | 0                      |                       | 0.5                    | 5                      |                                       | 4.95  |       |       | 4.95  | 5                 | —    |      |
| High Level, V <sub>OH</sub> MIN.               | 0                      | 0                      |                       | 0.10                   | 10                     |                                       | 9.95  |       |       | 9.95  | 10                | —    |      |
|                                                | 0                      | 0                      |                       | 0.15                   | 15                     |                                       | 14.95 |       |       | 14.95 | 15                | —    |      |
| Input Low Voltage, V <sub>IL</sub> MAX.        | 0                      | 0                      | 0.5, 4.5              |                        | 5                      |                                       | 1.5   |       |       | —     | —                 | 1.5  |      |
|                                                | 0                      | 0                      | 1.9                   |                        | 10                     |                                       | 3     |       |       | —     | —                 | 3    |      |
|                                                | 0                      | 0                      | 1.5, 13.5             |                        | 15                     |                                       | 4     |       |       | —     | —                 | 4    | V    |
| Input High Voltage, V <sub>IH</sub> MIN.       | -5                     | 0                      | 0.5, 4.5              |                        | 5                      |                                       | 3.5   |       |       | 3.5   | —                 | —    |      |
|                                                | 0                      | 0                      | 1.9                   |                        | 10                     |                                       | 7     |       |       | 7     | —                 | —    |      |
|                                                | 0                      | 0                      | 1.5, 13.5             |                        | 15                     |                                       | 11    |       |       | 11    | —                 | —    |      |
| Output Low (Sink) Current, I <sub>OL</sub>     | -5                     | 0                      | -4.5                  |                        | 5                      | 0.98                                  | 0.92  | 0.67  | 0.55  | 0.8   | 1.6               | —    |      |
|                                                | 0                      | 0                      | 0.5                   |                        | 10                     | 0.98                                  | 0.92  | 0.67  | 0.55  | 0.8   | 1.6               | —    |      |
|                                                | 0                      | 0                      | 1.5                   |                        | 15                     | 3.6                                   | 3.4   | 2.4   | 2     | 2.9   | 5.8               | —    |      |
| Output High (Source) Current, I <sub>OH</sub>  | -5                     | 0                      | 4.5                   |                        | 5                      | -0.6                                  | -0.55 | -0.35 | 0.3   | -0.45 | -0.9              | —    |      |
|                                                | 0                      | 0                      | 9.5                   |                        | 10                     | -0.6                                  | -0.55 | -0.35 | -0.3  | -0.45 | -0.9              | —    |      |
|                                                | 0                      | 0                      | 13.5                  |                        | 15                     | -1.9                                  | -1.8  | -1.2  | -1.1  | -1.5  | -3                | —    |      |
| Input Current, I <sub>IN</sub>                 | 0                      | 0                      | —                     | 0.18                   | 18                     | ±0.1                                  | ±0.1  | ±1    | ±1    | —     | ±10 <sup>-5</sup> | ±0.1 | μA   |




Fig. 11 - Quiescent-device-current test circuit.




Fig. 12 - Input-voltage test circuit.




Fig. 8 - Typical n-channel output low (sink) current characteristics.




Fig. 9 - Minimum n-channel output low (sink) current characteristics.




Fig. 10 - Typical p-channel output high (source) current characteristics.




Fig. 13 - Minimum p-channel output high (source) current characteristics.

## CD4054B, CD4055B, CD4056B Types

DYNAMIC ELECTRICAL CHARACTERISTICS at  $T_A = 25^\circ\text{C}$ ,  $C_L = 50\text{ pF}$ , Input  $t_r, t_f = 20\text{ ns}$ ,  
 $R_L = 200\text{ k}\Omega$

| CHARACTERISTIC                                                                             | CONDITIONS             |                        |                        | LIMITS            |      |               |      | UNITS |
|--------------------------------------------------------------------------------------------|------------------------|------------------------|------------------------|-------------------|------|---------------|------|-------|
|                                                                                            | V <sub>EE</sub><br>(V) | V <sub>SS</sub><br>(V) | V <sub>DD</sub><br>(V) | ALL PACKAGE TYPES |      |               |      |       |
|                                                                                            |                        |                        |                        | CD4054            |      | CD4055,CD4056 |      |       |
|                                                                                            |                        |                        |                        | Typ.              | Max. | Typ.          | Max. |       |
| Propagation Delay Time,<br>t <sub>PHL</sub> ,t <sub>PLH</sub><br>(Any Input to Any Output) | -5                     | 0                      | 5                      | 400               | 800  | 650           | 1300 | ns    |
|                                                                                            | 0                      | 0                      | 10                     | 340               | 680  | 575           | 1150 |       |
|                                                                                            | 0                      | 0                      | 15                     | 250               | 500  | 375           | 750  |       |
| Transition Time, t <sub>THL</sub> , t <sub>TLH</sub><br>(Any Output)                       | -5                     | 0                      | 5                      | 100               | 200  | 100           | 200  | ns    |
|                                                                                            | 0                      | 0                      | 10                     | 100               | 200  | 100           | 200  |       |
|                                                                                            | 0                      | 0                      | 15                     | 75                | 150  | 75            | 150  |       |
| Minimum Data Setup<br>Time, t <sub>S</sub> *                                               | -5                     | 0                      | 5                      | 110               | 220  | 110           | 220  | ns    |
|                                                                                            | 0                      | 0                      | 10                     | 50                | 100  | 50            | 100  |       |
|                                                                                            |                        |                        | 15                     | 35                | 70   | 35            | 70   |       |
| Minimum Strobe Pulse<br>Width, t <sub>W</sub> *                                            | -5                     | 0                      | 5                      | 110               | 220  | 110           | 220  | ns    |
|                                                                                            | 0                      | 0                      | 10                     | 50                | 100  | 50            | 100  |       |
|                                                                                            | 0                      | 0                      | 15                     | 35                | 70   | 35            | 70   |       |
| Input Capacitance, C <sub>IN</sub><br>(Any Input)                                          | —                      | —                      | —                      | 5                 | 7.5  | 5             | 7.5  | pF    |

\* CD4054 and CD4056 only.

RECOMMENDED OPERATING CONDITIONS at  $T_A = 25^\circ\text{C}$  (Unless otherwise specified)  
 For maximum reliability, nominal operating conditions should be selected so that operation  
 is always within the following ranges.

| CHARACTERISTIC                                                          | V <sub>EE</sub><br>(V) | V <sub>SS</sub><br>(V) | V <sub>DD</sub><br>(V) | LIMITS |      | UNITS |
|-------------------------------------------------------------------------|------------------------|------------------------|------------------------|--------|------|-------|
|                                                                         |                        |                        |                        | Min.   | Max. |       |
| Supply Voltage Range:<br>(At $T_A$ = Full Package<br>Temperature Range) |                        |                        |                        | 3      | 18   | V     |
| Setup Time ( $t_S$ ) <sup>*</sup>                                       | -5                     | 0                      | 5                      | 220    | —    | ns    |
|                                                                         | 0                      | 0                      | 10                     | 100    | —    |       |
|                                                                         | 0                      | 0                      | 15                     | 70     | —    |       |
| Strobe Pulse Width ( $t_W$ ) <sup>*</sup>                               | -5                     | 0                      | 5                      | 220    | —    | ns    |
|                                                                         | 0                      | 0                      | 10                     | 100    | —    |       |
|                                                                         | 0                      | 0                      | 15                     | 70     | —    |       |

\* For CD4054 and CD4056 only.




Fig. 16 - Clock display:  $V_{DD} = 0\text{ V}$ ,  $V_{SS} = -5\text{ V}$ ,  $V_{EE} = -15\text{ V}$ ,  $DF_{IN} = 30\text{ Hz}$  square wave.




Fig. 14 - Input-current test circuit.




Fig. 15 - Data setup time and strobe pulse duration.




Fig. 17 - Display-driver circuit for one segment line and waveforms.

## CD4054B, CD4055B, CD4056B Types




Fig. 18 - Digital (0 to +5 V) to bidirectional analog control (+5 to -5 V) level shifter.




Fig. 20 - Single-digit liquid-crystal display.




Fig. 19 - Typical 3 1/2-digit liquid-crystal display:  
VDD = +5 V, VSS = 0 V, VEE = -10 V,  
DFIN = 30 Hz square wave.





Fig. 21 - Conversion of "H" display to "F" display.

In addition to the letters L, H, P, and A (See the truth table), five other letters can be displayed through the use of simple logic circuits preceding and following the CD4055B or CD4056B devices. Fig. 21 is an example of a circuit that converts an "H" display (code 1011) to an "F" display. One condition that must be met is that VEE = VSS. If VEE ≠ VSS, the CD4054B must be used to level shift in the appropriate places.


In a similar manner the letters C, E, J, and U can be displayed. These circuits can also be used to drive LED displays provided the exclusive-OR gates have sufficient output-current drive.

The letters B, D, G, I, O, and S may be represented by the codes for numbers 8, 0, 6, 1, 0, and 5, respectively, when there is pre-knowledge that only letters are to be displayed.


Dimensions in parentheses are in millimeters and are derived from the basic inch dimensions as indicated. Grid graduations are in mils (10<sup>-3</sup> inch).



Dimensions and pad layout for CD4054BH.



Dimensions and pad layout for CD4055BH



Dimensions and pad layout for CD4056BH

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| CD4054BE         | ACTIVE        | PDIP         | N                  | 16   | 25             | Pb-Free<br>(RoHS)          | CU NIPDAU               | N / A for Pkg Type   | -55 to 125   | CD4054BE                | <a href="#">Samples</a> |
| CD4054BF3A       | ACTIVE        | CDIP         | J                  | 16   | 1              | TBD                        | A42                     | N / A for Pkg Type   | -55 to 125   | CD4054BF3A              | <a href="#">Samples</a> |
| CD4054BM         | ACTIVE        | SOIC         | D                  | 16   | 40             | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4054BM                | <a href="#">Samples</a> |
| CD4054BM96       | ACTIVE        | SOIC         | D                  | 16   | 2500           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4054BM                | <a href="#">Samples</a> |
| CD4054BPW        | ACTIVE        | TSSOP        | PW                 | 16   | 90             | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CM054B                  | <a href="#">Samples</a> |
| CD4055BE         | ACTIVE        | PDIP         | N                  | 16   | 25             | Pb-Free<br>(RoHS)          | CU NIPDAU               | N / A for Pkg Type   | -55 to 125   | CD4055BE                | <a href="#">Samples</a> |
| CD4055BEE4       | ACTIVE        | PDIP         | N                  | 16   | 25             | Pb-Free<br>(RoHS)          | CU NIPDAU               | N / A for Pkg Type   | -55 to 125   | CD4055BE                | <a href="#">Samples</a> |
| CD4055BM         | ACTIVE        | SOIC         | D                  | 16   | 40             | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4055BM                | <a href="#">Samples</a> |
| CD4055BPW        | ACTIVE        | TSSOP        | PW                 | 16   | 90             | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CM055B                  | <a href="#">Samples</a> |
| CD4056BE         | ACTIVE        | PDIP         | N                  | 16   | 25             | Pb-Free<br>(RoHS)          | CU NIPDAU               | N / A for Pkg Type   | -55 to 125   | CD4056BE                | <a href="#">Samples</a> |
| CD4056BEE4       | ACTIVE        | PDIP         | N                  | 16   | 25             | Pb-Free<br>(RoHS)          | CU NIPDAU               | N / A for Pkg Type   | -55 to 125   | CD4056BE                | <a href="#">Samples</a> |
| CD4056BF3A       | ACTIVE        | CDIP         | J                  | 16   | 1              | TBD                        | A42                     | N / A for Pkg Type   | -55 to 125   | CD4056BF3A              | <a href="#">Samples</a> |
| CD4056BM         | ACTIVE        | SOIC         | D                  | 16   | 40             | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |
| CD4056BM96       | ACTIVE        | SOIC         | D                  | 16   | 2500           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |
| CD4056BM96E4     | ACTIVE        | SOIC         | D                  | 16   | 2500           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |
| CD4056BM96G4     | ACTIVE        | SOIC         | D                  | 16   | 2500           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |
| CD4056BME4       | ACTIVE        | SOIC         | D                  | 16   | 40             | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)         | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|-------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| CD4056BMG4       | ACTIVE        | SOIC         | D               | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |
| CD4056BMT        | ACTIVE        | SOIC         | D               | 16   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CD4056BM                | <a href="#">Samples</a> |
| CD4056BPW        | ACTIVE        | TSSOP        | PW              | 16   | 90          | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -55 to 125   | CM056B                  | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF CD4054B, CD4054B-MIL, CD4056B, CD4056B-MIL :**

- Catalog: [CD4054B](#), [CD4056B](#)
- Military: [CD4054B-MIL](#), [CD4056B-MIL](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device     | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CD4054BM96 | SOIC         | D               | 16   | 2500 | 330.0              | 16.4               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |
| CD4056BM96 | SOIC         | D               | 16   | 2500 | 330.0              | 16.4               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device     | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CD4054BM96 | SOIC         | D               | 16   | 2500 | 333.2       | 345.9      | 28.6        |
| CD4056BM96 | SOIC         | D               | 16   | 2500 | 333.2       | 345.9      | 28.6        |

J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |



4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - D. The 20 pin end lead shoulder width is a vendor option, either half or full width.

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE



4040047-6/M 06/11

NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AC.

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PW (R-PDSO-G16)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G16)

PLASTIC SMALL OUTLINE



4211284-3/F 12/12

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

### Products

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| Audio                        | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers                   | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters              | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products                | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                          | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers            | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface                    | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                        | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt                   | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers             | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                         | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Applications Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity        | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

### TI E2E Community

[e2e.ti.com](http://e2e.ti.com)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.