Differential current monitoring - RCM-A-SCT-105 - 2806087

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Differential current converter for type A differential current monitor.

Product Features

- Residual current detection characteristics type A (50/60 Hz)
- Detects pulsating DC and AC residual currents
- Adjustable residual response current of 30 mA to 3 A
- Adjustable pre-alarm threshold and delay time
- Actual residual current can be read via LED display
- Remote signaling for main and pre-alarm
- Residual current monitoring devices act as a form of fire prevention

Key commercial data

Packing unit	1 pc
Custom tariff number	85043180
Country of origin	Germany

Technical data

Dimensions

Height	170 mm
Width	33 mm
Depth	146 mm
Diameter converter	105.00 mm
Outside diameter of cables max.	70.00 mm

Ambient conditions

Degree of protection	IP20 (terminal blocks)
	IP45 (housing)

Differential current monitoring - RCM-A-SCT-105 - 2806087

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

General

Housing material	Polycarbonate
Mounting type	Screw mounting

Common characteristics

Rated current I_n	250 A
Rated response differential current I_{dyn}	3 A
Differential current acquisition characteristic	Type A (50 / 60 Hz)
Response differential current $I_{\Delta n}$	0.03 A ... 3 A
Thermal permanent differential current I_{cth}	1.5 x I_n
Thermal rated short-time differential current I_{th}	10 x I_n (for 1 s)
Rated surge voltage resistance U_{imp}	8 kV
Surge voltage category	IV
Rated voltage U_n	690 V
Pollution degree	2
Max. overcurrent as regards the non-resolution	6 x I_n
Rated differential short-circuit current $I_{\Delta c}$	10 kA
Rated surge differential current I_{dyn}	25 x I_n

Connections

Connection method	Screw terminal blocks
Number of connections	2
Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm²
Conductor cross section stranded max.	2.5 mm²
Conductor cross section solid min.	0.2 mm²
Conductor cross section solid max.	4 mm²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Cable/line name	Converter supply line
Maximum cable length	10 m
Cross section	0.5 mm²
Cable type	LiY

Standards and Regulations

Standards/specifications	DIN EN 62020

Differential current monitoring - RCM-A-SCT-105 - 2806087

Technical data

Standards and Regulations

	VDE 0663
	DIN EN 60044-1
	VDE 0414

Classifications

eCl@ss

eCl@ss 4.0	27210902
eCl@ss 4.1	27210902
eCl@ss 5.0	27210902
eCl@ss 5.1	27210902
eCl@ss 6.0	27210902
eCl@ss 7.0	27210902
eCl@ss 8.0	27210902

ETIM

ETIM 2.0	EC001505
ETIM 3.0	EC001505
ETIM 4.0	EC002048
ETIM 5.0	EC002048

UNSPSC

UNSPSC 6.01	30211501
UNSPSC 7.0901	39121019
UNSPSC 11	39121006
UNSPSC 12.01	39121006
UNSPSC 13.2	39121006

Approvals

Approvals

Approvals

VDE Zeichengenehmigung

Ex Approvals

Differential current monitoring - RCM-A-SCT-105 - 2806087

Approvals

Approvals submitted

Approval details

VDE Zeichengenehmigung

Drawings

Circuit diagram



Phoenix Contact 2014 © - all rights reserved
http://www.phoenixcontact.com


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.