

Datasheet for 76650-0191

General Information

Part Number:	76650-0191
Manufacturer:	Molex / Waldom
Title:	TDP Connector Kit
Description:	SMT Right Angle Plug and Receptacle and Backshell Assemblies
Product Family:	TDP®
Certificates:	(Molex Parts within this kit) - EU RoHS Compliant, UL and CSA
Country of Origin:	Kit assembled in U.S.A.

Specifications

Design

Configuration:	Wire-to-Board
Pitch:	1.27mm (.050")
Connector Type:	Receptacles and Plugs
Mounting	
Orientation:	Right Angle
Circuit Sizes:	18 and 48
Current Rating:	1.5 Amps (per circuit)
Voltage:	40 VoltsAC(RMS)

Product Highlights

The innovative TDP (Triad Differential Pair) family uses a "triad" design of differential signal and ground lines to achieve bandwidths up to 5.0Gbps and beyond. The shielded, dual row, cable-to-board interface offers high speed and controlled impedance. It is comprised of a fully shielded receptacle and plug to provide maximum EMI/RFI protection. The inline SMT receptacle optimizes PCB routing and the low 7.67mm (.301") profile makes TDP an excellent choice where height considerations are a factor.

TDP utilizes a high-cycle-life (5000 cycles min.) Low Force Helix™ (LFH) contact design, providing long term performance and reliability. The recessed contacts protect signal lines from ESD, support mating alignment and provide added contact protection during operator handling. The TDP family is available in 18, 28 and 48 circuits. TDP cable plugs feature jackscrews for mating retention.

Datasheet for 76650-0191

Features and Benefits	Applications
• The shielded, dual row interface offers high-speed and 100-ohm controlled impedance with data rates up to 5 Gbs • Inline SMT leads on 0.64mm (.025") pitch provide direct PCB routing • High cycle LFH™ shrouded contact system provides 2 points of contact for optimal signal integrity • Jackposts with 4-40 threads for use with jackscrews for positive mating retention • First-mate/last-break pins 9 and 10 prevent damage when "hot plug" mating • LFH™ contact design provides shallow mating angle, reducing insertion forces • Terminates to (24-32)AWG wire through soldering or resistance welding • Contains 2-piece diecast shell and two jackscrews for TDP Cable Plug Connector • Lead-free process compatible, meets future manufacturing requirements • 5,000 mating cycles with 15µ" Gold (Au), high reliability • 1.5A continuous current per pin, allows for higher power throughput	• High Resolution Cameras • Audio, Video Editing and Storage • Printers • Medical Devices • LVDS Servers • Routers • Switches • Storage Devices • Multiple High-Speed, Differential-Pair Signal Applications • Military Data Communications and Video Equipment (cots)

Bill of Materials for Part No. 76650-0191

Molex Part No.	Country of Origin	Description	Quantity in Kit
74960-3018	USA	1.27mm (.050") Pitch TDP® Triad Differential Pair SMT Right Angle Receptacle, China RoHS, Lead-Free, 18 Circuits	1
74960-3048	USA	1.27mm (.050") Pitch TDP® Triad Differential Pair SMT Right Angle Receptacle, China RoHS, Lead-Free, 48 Circuits	1
75000-1018	Mexico	1.27mm (.050") Pitch TDP® Triad Differential Pair Plug Assembly, China RoHS, Lead-Free, 18 Circuits	1
75000-1048	Mexico	1.27mm (.050") Pitch TDP® Triad Differential Pair Plug Assembly, China RoHS, Lead-Free, 48 Circuits	1
75115-0018	USA	1.27mm (.050") Pitch TDP® Triad Differential Pair Die Cast Backshell, China 50 (Pb), 18 Circuits	1
75115-0048	USA	1.27mm (.050") Pitch TDP® Triad Differential Pair Die Cast Backshell, China 50 (Pb), 48 Circuits	1
74962-0001	Taiwan	TDP™ 3/16" Hex Jackpost (4-40 UNC-2B), China 50 (Pb)	4

No Recommended Molex Tool for Part No. 76650-0191

For additional Molex / Waldom Design and Solution Kits please go to www.molexkits.com



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.