

SmartOnline 208/240 & 120V 12kVA 8.4kW Double-Conversion UPS, 8U, Extended Run, Network Card Slot, USB, DB9, Bypass, NEMA

MODEL NUMBER: **SU12000RT4U**



Description

Tripp Lite 12kVA SmartOnline Hot-Swappable Modular Rack/Tower UPS offers 12,000 VA on-line, double-conversion UPS support for server, network and telecommunications equipment. Maintains battery-derived AC output during blackouts with active, full-time power conditioning. Fault-tolerant auto-bypass prevents unexpected service interruptions during overload or internal fault conditions. 4U power module and 4U external battery pack installs in 8 rack spaces (8U). Upright tower installation supported with optional accessories. Maintains full-time sine wave output within 3% of selectable 208/120 or 240/120V AC. Corrects brownouts and overvoltages from 65V to 140V (L-N). Expandable runtime with optional external battery packs. Converts raw input from AC to DC, then resynthesizes output power back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Highly efficient operation in optional economy mode setting, saving BTU heat output and energy costs. Network-grade AC surge and noise suppression. Network management interfaces include combination **DB9** RS-232 enabled and dry contact serial port, enhanced USB port and slot for network management card options. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all 3 network interfaces. PowerAlert UPS monitoring software is available via free download. Supports Emergency Power Off (EPO) via built-in interface. Front panel LEDs and LCD readout with scroll controls support visual monitoring of all major UPS functions. LED/LCD display panel easily rotates for viewing in rackmount or tower configurations. Split phase 4 conductor hardwire input and output supported. UPS supported outlets include two L6-30R, six C19 and 5 low voltage 5-15/20R. Output connections are mounted on a detachable backplate with manual bypass switch to enable hot-swappable UPS replacement without powering off connected equipment. External battery packs are field replaceable and hot swappable. Attractive all-black color scheme. \$250,000 Ultimate

Highlights

- 12kVA / 12,000VA / 8400W on-line double-conversion UPS
- 208/120V or 240/120V +/-3% output at 60Hz, 94% Efficient Economy-mode option
- 8U Rack / Tower compatible; Hot-swappable power and battery modules
- USB, RS232 & EPO ports; slot for Network Management Card options
- Front panel LEDs with detailed LCD monitoring and control screen
- Expandable runtime with optional external battery packs
- Hardwire input (4 wire split phase); L6-30R, C19 & 5-15/20R outlets

Package Includes

- SU12000RT4UPM 4u UPS Power Module
- BP192V18-4U External battery pack
- SUPDMB16K Detachable PDU with manual bypass switch
- 4 post rackmount installation brackets

Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- True online, double-conversion UPS provides pure, full-time sine wave AC output free of surges, voltage fluctuations and line noise
- 12,000 VA / 8400 watt output power capacity with dual voltage output of 208/120 or 240/120V
- 4U high power density power module and 4U external battery pack supports rackmount installation in 8 rack spaces
- Dual conversion UPS actively converts raw input from AC to DC, then back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types
- Hardwire input terminals and output receptacles are mounted on a detachable back plate with manual bypass switch to enable hot-swappable UPS replacement without powering off connected equipment
- Provides perfectly regulated, sine wave output power free of line noise, transient surges and frequency variation for the most efficient operation of critical servers, networking and telecommunications equipment
- Maintains output within 3% of selected 208/120 or 240/120V nominal voltage during brownouts and overvoltages
- Supports connected equipment during blackouts for 20/7 minutes at half/full load levels, runtime is further expandable with optional external [BP192V18-4U](#) battery packs
- Some external battery configurations require the use of Tripp Lite's External Battery Configuration Software (see manual)
- Intelligent battery management system extends battery life
- Network interfaces support simultaneous communications via [DB9](#) port, USB port and slot for network management card option
- Compatible with Tripp Lite UPS management card options [WEBCARDLX](#), [SNMPWEBCARD](#), [MODBUSCARD](#) and [RELAYIOCARD](#)
- [DB9](#) port supports RS-232 and dry contact messaging. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X.
- USB & Serial ports enable data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from www.tripplite.com/poweralert
- Built-in Emergency Power Off (EPO) interface with cable
- Includes 13 output receptacles (2 L6-30R, 6 C19, 5 NEMA 5-15/20R) plus hardwire output, all of which are available for simultaneous use
- Split phase, 4 conductor hardwire input connection (featured on included detachable PDU).
- Front panel LEDs and LCD readout with scroll button enables visual confirmation of all major UPS functions and current site electrical conditions
- Front panel switches enable power on/off control, self-test and alarm cancel functions



- Included adjustable mounting rails support installation in 4 post 19 inch rack enclosures
- Optional [2-9U STAND](#) set of tower stands supports upright tower installation
- Optional [2POSTRMKITHD](#) enables installation in 2 post racks (2 required)
- Fault tolerant electronic bypass maintains utility output during a variety of UPS fault conditions
- \$250,000 [Ultimate Lifetime Insurance](#) (U.S., Canada, and Puerto Rico only)

Specifications

| OUTPUT | |
|---|--|
| Output Volt Amp Capacity (VA) | 12000 |
| Output kVA Capacity (kVA) | 12 |
| Output Watt Capacity (Watts) | 8400 |
| Output kW Capacity (kW) | 8.4 |
| Output Capacity Details | 12,000VA, 8400W (240V) / 10,395VA, 8400W (208V); Supports up to 105% load continuously in double conversion mode, 106 to 125% for 3 minutes, 126 to 150% for 30 seconds; Loads over 150% trigger immediate bypass mode operation to support equipment directly from mains power; Double conversion mode is automatically restored as the overload is cleared |
| Power Factor | 0.7 |
| Crest Factor | 3:1 |
| Nominal Output Voltage(s) Supported | 120V; 208V; 240V |
| Nominal Voltage Details | 240/120V or 208/120V split phase output |
| Frequency Compatibility | 60 Hz |
| Output Voltage Regulation (Line Mode) | +/- 3% |
| Output Voltage Regulation (Economy Line Mode) | +/- 10% |
| Output Voltage Regulation (Battery Mode) | +/- 3% |
| Output Receptacles | (5) 5-15/20R; (2) L6-30R; (6) C19; Hardwire |
| Output Receptacle Details | Supports North American 208/120V or 240/120V split-phase hardwire output (L1, L2, N, G) |
| Output Circuit Breakers | 20A branch rated double pole breakers (x3) protect 2 C19 and 1 5-15/20R outlets each, 30A branch rated double pole breakers (x2) protect 1 L6-30R outlet each, 20A single pole breakers (x2) protect one 5-15/20R outlet each |
| Output AC Waveform (AC Mode) | Pure Sine wave |
| Output AC Waveform (Battery Mode) | Pure Sine wave |
| INPUT | |
| Rated input current (Maximum Load) | 50A |



| | |
|--|--|
| Nominal Input Voltage(s) Supported | 120/208V (Split phase L1,L2,N,G); 120/240V (Split phase L1,L2,N,G) |
| UPS Input Connection Type | Hardwire |
| UPS Input Connection Description | 4 wire split-phase input (L1, L2, N, G) |
| Recommended Electrical Service | 50A 208/240-120 Split Phase (L1, L2, N, G); 6 AWG wiring recommended |
| Input Phase | Single-Phase |
| BATTERY | |
| Full Load Runtime (min.) | 7 min. (8400w) |
| Half Load Runtime (min.) | 20 min. (4200w) |
| Expandable Battery Runtime | Supports extended runtime with optional external battery packs |
| External Battery Pack Compatibility | <u>BP192V18-4U</u> ; <u>BP192V557C-16K</u> ; <u>BP192V787C-16K</u> ; <u>BP192V1037C-16K</u> ; <u>BP192V1407C-16K</u> |
| DC System Voltage (VDC) | 192 |
| Battery Recharge Rate (Included Batteries) | Less than 6 hours from 10% to 80% (typical, full load discharge) |
| Battery Replacement Description | Hot-swappable, user replaceable batteries |
| Expandable Runtime | Yes |
| VOLTAGE REGULATION | |
| Voltage Regulation Description | +/-3% output voltage regulation in online, double-conversion mode |
| Overvoltage Correction | Corrects overvoltages to 140 (measured L1-N : L2-N) |
| Undervoltage Correction | Corrects undervoltages to 65V (measured L1-N : L2-N) |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LCD Display | Selectable LCD display with scroll and selection buttons enables UPS control and detailed monitoring options; LED/LCD panel rotates for viewing in rack/tower formats |
| Switches | 2 Switches control off/on power status and alarm-cancel/self-test operation; 2 additional switches support set and execute scrolling LCD functions; bundled PDU includes bypass switch to enable hot-swap UPS power module replacement |
| Alarm Cancel Operation | Alarm cancel switch |
| Audible Alarm | Unique audible alarms for all major UPS, environmental and power conditions (see manual) |
| LED Indicators | 6 LEDs indicate line power, online mode, economy/bypass mode, on-battery, charger and AC output status; LCD screen offers additional information and control options |
| SURGE / NOISE SUPPRESSION | |
| UPS AC Suppression Response Time | Instantaneous |
| EMI / RFI AC Noise Suppression | Yes |
| PHYSICAL | |



| | |
|---|---|
| Included Mounting Accessory Description | 2 sets of adjustable 4 post rack rails included |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount (2POSTRMKITHD); Tower (2-9USTAND) |
| Optional Mounting Accessory Notes | 2 sets of 2POSTRMKITHD required for 2 post rackmount installation |
| Primary Form Factor | Rackmount |
| UPS Power Module Dimensions (hwd, in.) | 7 x 17.5 x 27.8 |
| UPS Power Module Dimensions (hwd, cm) | 17.78 x 44.45 x 70.61 |
| Rack Height (U Spaces) | 8 |
| Maximum Device Depth (in.) | 34 |
| Minimum Required Rack Depth (inches) | 40 |
| Maximum Device Depth (cm) | 86.36 |
| Minimum Required Rack Depth (cm) | 101.60 |
| UPS Power Module Weight (lbs.) | 86 |
| UPS Power Module Weight (kg) | 39.01 |
| UPS Dimensions Details | Includes 4U battery pack, 4U UPS/power module and detachable bypass PDU; MAXIMUM DEVICE DEPTH specification refers to the whole UPS installed depth with bypass PDU installed |
| Included Battery Pack Dimensions (hwd / in.) | 7 x 17.5 x 27.8 |
| Included Battery Pack Weight (lbs.) | 239 |
| Included Battery Pack Weight (kg) | 108.41 |
| UPS Shipping Dimensions (hwd / in.) | 45.5 x 23.5 x 34.3 |
| UPS Shipping Dimensions (hwd / cm) | 115.57 x 59.69 x 87.12 |
| Shipping Weight (lbs.) | 448.8 |
| Shipping Weight (kg) | 203.8 |
| Cooling Method | Fan |
| UPS Housing Material | Steel |
| Maximum Device Depth (mm) | 864 |
| Minimum Required Rack Depth (mm) | 1016 |
| Primary UPS Height (mm) | 178 |
| Primary UPS Width (mm) | 444 |
| Primary UPS Depth (mm) | 706 |



| | |
|---|--|
| Shipping Height (mm) | 1156 |
| Shipping Width (mm) | 597 |
| Shipping Depth (mm) | 871 |
| ENVIRONMENTAL | |
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius. |
| Storage Temperature Range | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius. |
| Relative Humidity | 0 to 95%, non-condensing |
| AC Mode BTU / Hr. (Full Load) | 4286 |
| AC Economy Mode BTU / Hr. (Full Load) | 1829 |
| Battery Mode BTU / Hr. (Full Load) | 3187 |
| AC Mode Efficiency Rating (100% Load) | 87% |
| AC Economy Mode Efficiency Rating (100% Load) | 94% |
| Operating Elevation (ft.) | 0-3000m (0 to 10,000 ft.) |
| Audible Noise | 60 dBA at front side 1 meter |
| Operating Elevation (m) | 0-3000 m |
| COMMUNICATIONS | |
| Communications Interface | USB (HID enabled); DB9 Serial; Contact closure; EPO (emergency power off); Slot for SNMP/Web interface |
| Network Management Cards | SNMPWEBCARD; WEBCARDLX; MODBUSCARD; RELAYIOCARD |
| Network Monitoring Port Description | RS232 and contact closure communications are supported on one DB9 port |
| PowerAlert Software | For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at http://www.tripplite.com/poweralert |
| Communications Cable | USB and DB9 cabling included |
| LINE / BATTERY TRANSFER | |
| Transfer Time | No transfer time (0 ms.) in online, double-conversion mode |
| Transfer Time (Economy Mode) | 2 milliseconds typical in optional economy mode |
| Low Voltage Transfer to Battery Power (Setpoint) | 65V (L1-N:L2-N) |
| High Voltage Transfer to Battery Power (Setpoint) | 140V (L1-N:L2-N) |
| SPECIAL FEATURES | |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--|--|
| High Availability UPS Features | Automatic inverter bypass; Hot swappable batteries; Hot swappable UPS power module; Manual bypass switch |
| Green Energy-Saving Features | High efficiency economy mode operation; Schedulable daily hours of economy mode operation |
| CERTIFICATIONS | |
| UPS Certifications | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 <u>Ultimate Lifetime Insurance</u> |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.