
MODEL 22

3 mm Single Turn Sealed Surface Mount Cermet Trimming Potentiometer



MODELS AVAILABLE

J Hook	22A
Side Mount	22S

ELECTRICAL[1]

Resistance Range	10 Ohm to 2 Megohms
Standard Resistance Tolerance	± 20%
Input Voltage, Maximum	200 Vdc or rms, not to exceed power rating
Power rating, Watts	0.125 @ 70°C, derating to 0 @ 125°C
End Resistance, Maximum	1% or 3 Ohms, whichever is greater
Actual Electrical Travel, Nominal	220°
Dielectric Strength	500 V rms
Insulation Resistance, Minimum	100 Megohms
Resolution	Essentially infinite
Contact Resistance Variation, Maximum	3% or 3 Ohms, whichever is greater
Temperature Coefficient of Resistance	±100 ppm/°C (less than 100 ohms: ±150 ppm/°C)

MECHANICAL

Mechanical Stop	Solid
Static Stop Strength	1.3 in. oz.
Torque, Maximum	0.65 in. oz.
Weight, Nominal	0.002 oz.
Wiper Position	Approx. 50%

[1] *Specifications subject to change without notice.*


BI Technologies Corporation
4200 Bonita Place, Fullerton, CA 92835 USA
Phone: 714 447 2345 Website: www.bitechnologies.com

TT electronics
BI technologies

ENVIRONMENTAL

Seal	85°C Fluorinert®
Operating Temperature Range	-55°C to +125°C
Thermal Shock, 5 cycles, -55°C to +125°C	2% ΔR, 1% ΔV Ratio max.
Moisture Resistance, Ten 24 Hour Cycles	3% ΔR
Shock, 6 ms Sawtooth 100G's	1% ΔR, 1% ΔV Ratio max.
Vibration, 20G's to 2000 Hz	1% ΔR, 1% ΔV Ratio max.
High Temperature Exposure, 250 Hours @ 125°C	2% ΔR, 2% ΔV Ratio max.
Rotational Life, 100 Cycles	3% ΔR
Load Life, 0.125W, 100 Hours, 70°C	3% ΔR, 2% ΔV Ratio max.
Resistance to Solder Heat	260°C for 5 sec.

ORDERING INFORMATION[2]



PACKAGING – TAPE & REEL

	Model 22A	Model 22S
Tape Width	12 mm	16 mm
Sprocket Pitch	4 mm	4 mm
Reel Diameter	7 inches	7 inches
Quantity per Reel	1000 units	200 units


STANDARD RESISTANCE VALUES, OHMS

10	100	1K	10K	100K	1 Meg
20	200	2K	20K	200K	2 Meg
50	500	5K	50K	500K	


[2] *Contact our customer service for custom designs and features.*

OUTLINE DRAWING[3]


Model 22A



Model 22S



CIRCUIT DIAGRAM



[3] *Dimensions are Inches (mm), Tolerances are ±.01 inch (±.025 mm) unless otherwise stated.*


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.