




# ECONOMY POWER 2.5 CONNECTORS

## Quick Reference Guide

The Economy Power 2.5 (EP 2.5) connector is a single row or dual row crimp connector system. Based on a 2.5mm (0.098") centerline pitch, it is a very compact solution. EP 2.5 connectors provide a comprehensive connectivity solution with vertical and right angle headers, optional TPA retainers, wire-to-wire and wire-to-board options and a range of resin materials that include types meeting Glow Wire Test and UL 94 V-0 standards, as well as packaging to support automated board assembly. Additionally, EP 2.5 connectors are intermateable with similar products available in the market, facilitating simple retrofitting.

With board space increasingly at a premium, the EP 2.5 connector series offers an ideal interconnection solution for densely packed printed circuit boards. EP 2.5 housings and contacts were designed to help workers on the shop floor. The terminals have an asymmetrical shape. This means they can only be loaded into the housing cavity one way—the right way. Ideal for household appliances, HVAC and industrial machinery, EP 2.5 connectors offers this extensive portfolio for all design needs and challenges.

### FEATURES & BENEFITS

- Housing locking latch
- Polarization tabs
- Asymmetrical terminals can only be loaded into housing one way
- Standard or low insertion force (LIF) terminals
- Anti-fretting contact lubricant
- Offering includes vertical and right angle headers in single and dual row configurations
- Includes products compliant with Glow Wire test required by IEC/EN 60335-1 5th edition: Household and Similar Appliances-Safety and UL 94 V-0

### SPECIFICATIONS

- Product specification: [108-2418](#)
- Application specification: [114-13315](#)

### STANDARDS

- UL Recognized (U.S. and Canada) E28476
- VDE approval is being sought

### MATERIALS

- Housings: UL 94 V-0 rated Nylon (UL 94 V-0 rated PBT for headers on tape in ammo box packaging)
- Contacts: Copper alloy, tin plated
- Colored housings available upon request
- Glow Wire material and UL 94 V-0 option available

### ELECTRICAL

- Voltage rating: 250VAC
- Current rating: 4.2A max. (single row)

### MECHANICAL

- Positions: 2 to 15, single row, wire-to-wire; 2 to 20, single row, wire-to-board; 8 to 40, dual row, all types
- Wire size: 0.13 to 0.56mm<sup>2</sup> (26 to 20 AWG)
- Centerline pitch: 2.5mm (0.098")
- Operating temperature: -55 to 105°C
- Selectively loaded headers available upon request

# Economy Power 2.5 Connectors

## Quick Reference Guide

### SINGLE ROW PLUG HOUSING

| Style                        |           | Position    | 2   | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10   | 11   | 12   | 13   | 14   | 15   | 16   | 17   | 18   | 19   | 20   |
|------------------------------|-----------|-------------|-----|----|----|----|----|----|----|----|------|------|------|------|------|------|------|------|------|------|------|
| Free Hanging/<br>Panel Mount | UL 94 V-O | x-1969442-y | -2† | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |

### SINGLE ROW RECEPTACLE HOUSING

| Style        | Flammability                       | Position    | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10   | 11   | 12   | 13   | 14   | 15   |
|--------------|------------------------------------|-------------|----|----|----|----|----|----|----|----|------|------|------|------|------|------|
| Free Hanging | UL-94 V-O                          | x-1969588-y | -2 | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 |
|              | GWT acc. IEC 60335-1 and UL 94 V-O | x-1969589-y | -2 | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 |
| Panel Mount  | UL-94 V-O                          | x-1969590-y | -2 | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 |
|              | GWT acc.IEC 60335-1 and UL 94 V-O  | x-1969591-y | -2 | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 |

### TPA

| Style         |           | Position    | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10   | 11   | 12   | 13   | 14   | 15   | 16   | 17   | 18   | 19   | 20   |
|---------------|-----------|-------------|----|----|----|----|----|----|----|----|------|------|------|------|------|------|------|------|------|------|------|
| Locking Plate | UL 94 V-O | X-1969443-y | -2 | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |

### SINGLE ROW HEADERS

| Style                                                 |                                    | Position    | 2              | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10   | 11   | 12   | 13   | 14   | 15   | 16   | 17   | 18   | 19   | 20   |
|-------------------------------------------------------|------------------------------------|-------------|----------------|----|----|----|----|----|----|----|------|------|------|------|------|------|------|------|------|------|------|
| Vertical with Boss                                    | UL 94 V-O                          | x-1969730-y | -2             | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |
|                                                       | GWT acc. IEC 60335-1 and UL 94 V-O | x-1744418-y | -2             | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |
| Vertical without Boss                                 | UL 94 V-O, loose packaging         | x-2132415-y | -2             | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |
|                                                       | GWT acc.IEC 60335-1 and UL 94 V-O  | x-1744439-y | -2             | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |
| Vertical without Boss with Tape in Ammo Box Packaging | UL 94 V-O                          | x-2299683-y | ††<br>-1<br>-2 | -3 | -4 | -5 | -6 | -7 | -8 | -  | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    | -    |
| Right Angle                                           | UL-94 V-O                          | x-1744426-y | -2             | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |
|                                                       | GWT acc.IEC 60335-1 and UL 94 V-O  | x-1744446-y | -2             | -3 | -4 | -5 | -6 | -7 | -8 | -9 | 1- 0 | 1- 1 | 1- 2 | 1- 3 | 1- 4 | 1- 5 | 1- 6 | 1- 7 | 1- 8 | 1- 9 | 2- 0 |

Notes: **Configurations available in various color options. Please contact TE sales representative for more information or visit [TE.com](http://TE.com)**

† 1969442-2 is designed to mate with the full range of EP 2.5 2-position headers. Another 2-position plug, 2301559-2, with a modified latch is available to mate with a competitive manufacturer's 2-position header of a similar design or with new TE EP 2.5 2-position header 2299683-3 with a narrow (0.85 mm wide) latch.

†† 2299683-1 has a narrow (0.85 mm wide) latch to readily mate with a competitive manufacturer's 2-position plug of a similar design or with new TE EP 2.5 2-position plug 2301559-2. 2299683-2 has a 1.6 mm wide latch to readily mate with TE EP 2.5 2-position plug 1969442-2.

## Economy Power 2.5 Connectors

### Quick Reference Guide

#### DUAL ROW PLUG HOUSING

| Style         |                                    | Position    | 8  | 10    | 12    | 14    | 16    | 18    | 20    | 22    | 24    | 26    | 28    | 30    | 32    | 34    | 36    | 38    | 40    |
|---------------|------------------------------------|-------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| For all types | UL 94 V-0                          | x-1969540-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
|               | GWT acc. IEC 60335-1 and UL 94 V-0 | x-1969567-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |

#### DUAL ROW RECEPTACLE HOUSING

| Style        |                                    | Position    | 8  | 10    | 12    | 14    | 16    | 18    | 20    | 22    | 24    | 26    | 28    | 30    | 32    | 34    | 36    | 38    | 40    |
|--------------|------------------------------------|-------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Free Hanging | UL 94 V-0                          | x-1969540-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
|              | GWT acc. IEC 60335-1 and UL 94 V-0 | x-1969567-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
| Panel Mount  | UL 94 V-0                          | x-1969594-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
|              | GWT acc. IEC 60335-1 and UL 94 V-0 | x-1969595-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |

#### DUAL ROW TPA

| Style         |           | Position    | 8  | 10    | 12    | 14    | 16    | 18    | 20    | 22    | 24    | 26    | 28    | 30    | 32    | 34    | 36    | 38    | 40    |
|---------------|-----------|-------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Locking Plate | UL 94 V-0 | x-1969541-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |

#### DUAL ROW VERTICAL ROW HEADERS

| Style        |                                    | Position    | 8  | 10    | 12    | 14    | 16    | 18    | 20    | 22    | 24    | 26    | 28    | 30    | 32    | 34    | 36    | 38    | 40    |
|--------------|------------------------------------|-------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| With Boss    | UL 94 V-0                          | x-1969543-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
|              | GWT acc. IEC 60335-1 and UL 94 V-0 | x-1969570-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
| Without Boss | UL 94 V-0                          | x-1969582-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
|              | GWT acc. IEC 60335-1 and UL 94 V-0 | x-1969584-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |

#### DUAL ROW RIGHT ANGLE HEADER

| Style       |                                    | Position    | 8  | 10    | 12    | 14    | 16    | 18    | 20    | 22    | 24    | 26    | 28    | 30    | 32    | 34    | 36    | 38    | 40    |
|-------------|------------------------------------|-------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Right Angle | UL 94 V-0                          | x-1969572-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |
|             | GWT acc. IEC 60335-1 and UL 94 V-0 | x-1969574-y | -8 | 1- -0 | 1- -2 | 1- -4 | 1- -6 | 1- -8 | 2- -0 | 2- -2 | 2- -4 | 2- -6 | 2- -8 | 3- -0 | 3- -2 | 3- -4 | 3- -6 | 3- -8 | 4- -0 |

Note: **Configurations available in various color options. Please contact TE sales representative for more information or visit [TE.com](https://www.te.com)**

## Economy Power 2.5 Connectors

### Quick Reference Guide

#### TERMINALS

| Style                                            | Material            | Wire Range                  | Part Number |
|--------------------------------------------------|---------------------|-----------------------------|-------------|
| Standard Insertion Force<br>Socket (Receptacle)  | Plated Copper Alloy | 22-26 AWG (0.13 to 0.36mm²) | 2110989-1   |
|                                                  |                     | 20-24 AWG (0.20 to 0.56mm²) | 1744423-1   |
| Standard Insertion<br>Force Pin, Lanceless       |                     | 22-26 AWG (0.13 to 0.36mm²) | 2238007-1   |
|                                                  |                     | 20-24 AWG (0.20 to 0.56mm²) | 2238008-1   |
| Low Insertion Force (LIF)<br>Socket (Receptacle) |                     | 22-26 AWG (0.13 to 0.36mm²) | 2232905-1   |
|                                                  |                     | 20-24 AWG (0.20 to 0.56mm²) | 2232983-1   |

LIF sockets reduce insertion force about 60% from that of standard sockets. Maximum insertion force is 3.5 N for the new LIF sockets, versus maximum insertion force of 8.9 N for standard sockets.

#### APPLICATION TOOLING

Both the tab and receptacle contact can be applied to wire using OCEAN application for automatic and semi-automatic applications. For low volume production and prototype work, a hand-tool is available to crimp the contacts to wire.

| Part Number  | Description                                 |
|--------------|---------------------------------------------|
| 1590232- [ ] | HDI Quick Change Miniature Applicator       |
| 1725950- [ ] | AMP 3/K-40 Press                            |
| 1725900- [ ] | AMP 5/K Press                               |
| 1530232-3    | AMP-O-LECTRIC Model "G" Termination Machine |
| 1530232-2    | AMP-O-LECTRIC Model "K" Termination Machine |
| 1530232-1    | Lead Making Machine                         |
| 354500- [ ]  | AMP-O-LECTRIC Model "G" Terminating Machine |
| 528324- [ ]  | Komax Gamma 333 PC                          |
| 2217074-1    | Hand tool for 22-26 AWG                     |
| 2161958-1    | Pin Extraction Tool                         |



#### TE TECHNICAL SUPPORT CENTER

|                  |                       |
|------------------|-----------------------|
| USA:             | +1 (800) 522-6752     |
| Canada:          | +1 (905) 475-6222     |
| Mexico:          | +52 (0) 55-1106-0800  |
| Latin/S. America | +54 (0) 11-4733-2200  |
| Germany:         | +49 (0) 6251-133-1999 |
| UK:              | +44 (0) 800-267666    |
| France:          | +33 (0) 1-3420-8686   |
| Netherlands:     | +31 (0) 73-6246-999   |
| China:           | +86 (0) 400-820-6015  |

#### te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2018 TE Connectivity Ltd. family of companies All Rights Reserved.

7-1773461-66 APP 03/18



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.