- **Low Noise**
  - **10 Hz . . . 15 nV/√Hz**
  - **1 kHz . . . 10.5 nV/√Hz**
- **10000-pF Load Capability**
- **20-mA Min Short-Circuit Output Current**
- **27-V/μs Min Slew Rate**
- **High Gain-Bandwidth Product . . . 5.9 MHz**
- **Low V_{IO} . . . 500 μV Max at 25°C**
- **Single or Split Supply . . . 4 V to 44 V**
- **Fast Settling Time**
  - **340 ns to 0.1%**
  - **400 ns to 0.01%**
- **Saturation Recovery . . . 150 ns**
- **Large Output Swing**
  - **V_{CC-} +0.1 V to V_{CC+} – 1 V**

description

The TLE214x and TLE214xA devices are high-performance, internally compensated operational amplifiers built using Texas Instruments complementary bipolar Excalibur process. The TLE214xA is a tighter offset voltage grade of the TLE214x. Both are pin-compatible upgrades to standard industry products.

The design incorporates an input stage that simultaneously achieves low audio-band noise of 10.5 nV/√Hz with a 10-Hz 1/f corner and symmetrical 40-V/μs slew rate typically with loads up to 800 pF. The resulting low distortion and high power bandwidth are important in high-fidelity audio applications. A fast settling time of 340 ns to 0.1% of a 10-V step with a 2-kΩ/100-pF load is useful in fast actuator/positioning drivers. Under similar test conditions, settling time to 0.01% is 400 ns.

The devices are stable with capacitive loads up to 10 nF, although the 6-MHz bandwidth decreases to 1.8 MHz at this high loading level. As such, the TLE214x and TLE214xA are useful for low-droop sample-and-holds and direct buffering of long cables, including 4-mA to 20-mA current loops.

The special design also exhibits an improved insensitivity to inherent integrated circuit component mismatches as is evidenced by a 500-μV maximum offset voltage and 1.7-μV/°C typical drift. Minimum common-mode rejection ratio and supply-voltage rejection ratio are 85 dB and 90 dB, respectively.

Device performance is relatively independent of supply voltage over the ±2-V to ±22-V range. Inputs can operate between V_{CC-} – 0.3 to V_{CC+} – 1.8 V without inducing phase reversal, although excessive input current may flow out of each input exceeding the lower common-mode input range. The all-npn output stage provides a nearly rail-to-rail output swing of V_{CC-} – 0.1 to V_{CC+} – 1 V under light current-loading conditions. The device can sustain shorts to either supply since output current is internally limited, but care must be taken to ensure that maximum package power dissipation is not exceeded.

Both versions can also be used as comparators. Differential inputs of $V_{CC±}$ can be maintained without damage to the device. Open-loop propagation delay with TTL supply levels is typically 200 ns. This gives a good indication as to output stage saturation recovery when the device is driven beyond the limits of recommended output swing.

Both the TLE214x and TLE214xA are available in a wide variety of packages, including both the industry-standard 8-pin small-outline version and chip form for high-density system applications. The C-suffix devices are characterized for operation from 0°C to 70°C, I-suffix devices from –40°C to 105°C, and M-suffix devices over the full military temperature range of –55°C to 125°C.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1997 – 2006, Texas Instruments Incorporated

TLE2141 AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	PACKAGED DEVICES		
		SMALL OUTLINE† (D)	CERAMIC DIP (JG)	PLASTIC DIP (P)
0°C to 70°C	500 μV	TLE2141ACD	—	TLE2141ACP
	900 μV	TLE2141CD		TLE2141CP
–40°C to 105°C	500 μV	TLE2141AID	—	TLE2141AIP
	900 μV	TLE2141ID		TLE2141IP
–55°C to 125°C	500 μV	—	TLE2141AMJG	—
	900 μV	TLE2141MD	TLE2141MJG	—

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLE2141ACDR).

TLE2142 AVAILABLE OPTIONS

		PACKAGED DEVICES					
T_A	V_{IO}max AT 25°C	SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	TSSOP‡ (PW)	CERAMIC FLAT PACK (U)
0°C to 70°C	750 μV	TLE2142ACD	—	—	TLE2142ACP	—	—
	1200 μV	TLE2142CD	—	—	TLE2142CP	TLE2142CPWLE	—
–40°C to 105°C	750 μV	TLE2142AID	—	—	TLC2142AIP	—	—
	1200 μV	TLE2142ID	—	—	TLC2142IP	—	—
–55°C to 125°C	750 μV	TLE2142AMD	TLE2142AMFK	TLE2142AMJG	—	—	TLE2142AMU
	1200 μV	TLE2142MD	TLE2142MFK	TLE2142MJG	—	—	TLE2142MU

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLC2142ACDR).
‡ The PW packages are available left-ended taped and reeled. Add LE the suffix to device type (e.g., TLC2142CPWLE).

TLE2144 AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	PACKAGED DEVICES			
		SMALL OUTLINE† (DW)	CHIP CARRIER (FK)	CERAMIC DIP (J)	PLASTIC DIP (N)
0°C to 70°C	1.5 mV	—	—	—	TLE2144ACN
	2.4 mV	TLE2144CDW	—	—	TLE2144CN
–40°C to 105°C	1.5 mV	—	—	—	TLE2144AIN
	2.4 mV	TLE2144IDW	—	—	TLE2144IN
–55°C to 125°C	1.5 mV	—	TLE2144AMFK	TLE2144AMJ	—
	2.5 mV	TLE2144MDW	TLE2144MFK	TLE2144MJ	—

† The DW packages are available taped and reeled. Add R suffix to device type (e.g., TLE2144CDWR).

symbol



NOTES: A. OFFSET N1 AND OFFSET N2 are only availiable on the TLE2241x devices.

TLE2141
D, JG, OR P PACKAGE
(TOP VIEW)



TLE2142
PW PACKAGE
(TOP VIEW)



TLE2142
D, JG, OR P PACKAGE
(TOP VIEW)



TLE2141
FK PACKAGE
(TOP VIEW)



TLE2142
U PACKAGE
(TOP VIEW)



TLE2142
FK PACKAGE
(TOP VIEW)



TLE2144
DW PACKAGE
(TOP VIEW)



NC – No internal connection

TLE2144
J OR N PACKAGE
(TOP VIEW)



TLE2144
FK PACKAGE
(TOP VIEW)



equivalent schematic



NOTE A: OFFSET N1 AND OFFSET N2 are only availiable on the TLE2141x devices.

ACTUAL DEVICE COMPONENT COUNT			
COMPONENT	TLE2141	TLE2142	TLE2144
Transistors	46	65	130
Resistors	24	43	86
Diodes	8	14	28
Capacitors	4	8	16
Epi-FET	1	1	2

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{CC+} (see Note 1) . . . . . 22 V
Supply voltage, V_{CC-} . . . . . −22 V
Differential input voltage, V_{ID} (see Note 2) . . . . . ±44 V
Input voltage range, V_I (any input) . . . . . V_{CC+} to V_{CC-} − 0.3 V
Input current, I_I (each input) . . . . . ±1 mA
Output current, I_O . . . . . ±80 mA
Total current into V_{CC+} . . . . . 80 mA
Total current out of V_{CC-} . . . . . 80 mA
Duration of short-circuit current at (or below) 25°C (see Note 3) . . . . . unlimited
Package thermal impedance, θ_{JA} (see Notes 4 and 5): D package . . . . . 97.1°C/W
DW package . . . . . 57.3°C/W
N package . . . . . 79.7°C/W
P package . . . . . 84.6°C/W
PW package . . . . . 108.4°C/W
Package thermal impedance, θ_{JC} (see Notes 4 and 5): FK package . . . . . 5.6°C/W
J package . . . . . 15.1°C/W
JG package . . . . . 14.5°C/W
U package . . . . . 14.7°C/W
Operating free-air temperature range, T_A: C suffix . . . . . 0°C to 70°C
I suffix . . . . . −40°C to 105°C
M suffix . . . . . −55°C to 125°C
Storage temperature range . . . . . −65°C to 150°C
Case temperature for 60 seconds: FK package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D, DW, N, P, or PW package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: J or JG package . . . . . 300°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values, except differential voltages, are with respect to the midpoint between V_{CC+} and V_{CC-}.
2. Differential voltages are at IN+ with respect to IN−. Excessive current flows, if input, are brought below V_{CC-} − 0.3 V.
3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.
4. Maximum power dissipation is a function of $T_J(max)$, θ_{JA}, and T_A. The maximum allowable power dissipation at any allowable ambient temperature is $P_D = (T_J(max) - T_A)/\theta_{JA}$. Operating at the absolute maximum T_J of 150°C can affect reliability.
5. The package thermal impedance is calculated in accordance with JESD 51-7 (plastic) or MIL-STD-883 Method 1012 (ceramic).

recommended operating conditions

		C SUFFIX		I SUFFIX		M SUFFIX		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
Supply voltage, $V_{CC\pm}$		±2	±22	±2	±22	±2	±22	V
Common-mode input voltage, V_{IC}	V_{CC} = 5 V	0	2.9	0	2.7	0	2.7	V
	$V_{CC\pm}$ = ±15 V	−15	12.9	−15	12.7	−15	12.7	
Operating free-air temperature, T_A		0	70	−40	105	−55	125	°C

TLE2141C electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2141C			TLE2141AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, V_{IC} = 2.5 V, R_S = 50 Ω	25°C		225	1400		200	1000	μV
			Full range			1700			1300	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			150			150	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.1			−2.1	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.9			0 to 2.9			
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
			Full range	3.8			3.8			
		I_{OH} = −1.5 mA	25°C	3.8	4		3.8	4		
			Full range	3.7			3.7			
		I_{OH} = −15 mA	25°C	3.2	3.7		3.2	3.7		
			Full range	3.2			3.2			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
			Full range			150			150	
		I_{OL} = 1.5 mA	25°C		150	225		150	225	
			Full range			250			250	
		I_{OL} = 15 mA	25°C		1.2	1.6		1.2	1.6	V
			Full range			1.7			1.7	
A_{VD}	Large-signal differential voltage amplification	V_{CC} = ±2.5 V, R_L = 2 kΩ, V_O = 1 V to −1.5 V	25°C	50	220		50	220		V/mV
			Full range	25			25			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		3.4	4.4		3.4	4.4	mA
			Full range			4.6			4.6	

† Full range is 0°C to 70°C.

TLE2141C operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2141C			TLE2141AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF†,	R_L = 2 kΩ,†		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF†		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF†,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF†		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF†		57°			57°		

† R_L and C_L terminated to 2.5 V.

TLE2141C electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2141C			TLE2141AC			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0	R_S = 50 Ω,	25°C		200	900		175	500	μV
				Full range			1300			800	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			150			150	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	μA
				Full range			−1.6			−1.6	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.9	−15.3 to 13.1		−15 to 12.9	−15.3 to 13.1		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		25°C	13.8	14.1		13.8	14.1		V
				Full range	13.7			13.7			
		I_O = −1.5 mA		25°C	13.7	14		13.7	14		
				Full range	13.6			13.6			
		I_O = −15 mA		25°C	13.1	13.7		13.1	13.7		
				Full range	13			13			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		25°C	−14.7	−14.9		−14.7	−14.9		V
				Full range	−14.6			−14.6			
		I_O = 1.5 mA		25°C	−14.5	−14.8		−14.5	−14.8		
				Full range	−14.4			−14.4			
		I_O = 15 mA		25°C	−13.4	−13.8		−13.4	−13.8		
				Full range	−13.3			−13.3			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V		25°C	100	450		100	450		V/mV
				Full range	75			75			
r_i	Input resistance	R_L = 2 kΩ		25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0,	No load	25°C		3.5	4.5		3.5	4.5	mA
				Full range			4.7			4.7	

† Full range is 0°C to 70°C.

TLE2141C operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2141C			TLE2141AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2142C electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2142C			TLE2142AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		220	1900		200	1500	μV
			Full range			2200			1800	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			150			150	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.1			−2.1	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.9			0 to 2.9			
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
			Full range	3.8			3.8			
		I_{OH} = −1.5 mA	25°C	3.8	4		3.8	4		
			Full range	3.7			3.7			
		I_{OH} = −15 mA	25°C	3.4	3.7		3.4	3.7		
			Full range	3.4			3.4			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
			Full range			150			150	
		I_{OL} = 1.5 mA	25°C		150	225		150	225	
			Full range			250			250	
		I_{OL} = 15 mA	25°C		1.2	1.4		1.2	1.4	V
			Full range			1.5			1.5	
A_{VD}	Large-signal differential voltage amplification	V_{CC} = ±2.5 V, R_L = 2 kΩ, V_O = 1 V to −1.5 V	25°C	50	220		50	220		V/mV
			Full range	25			25			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		6.6	8.8		6.6	8.8	mA
			Full range			9.2			9.2	

† Full range is 0°C to 70°C.

TLE2142C operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142C			TLE2142AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF		57°			57°		

† R_L terminates at 2.5 V.

TLE2142C electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2142C			TLE2142AC			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0	R_S = 50 Ω,	25°C		290	1200		275	750	μV
				Full range			1600			1200	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			150			150	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	μA
				Full range			−1.6			−1.6	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.9	−15.3 to 13.1		−15 to 12.9	−15.3 to 13.1		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		25°C	13.8	14.1		13.8	14.1		V
				Full range	13.7			13.7			
		I_O = −1.5 mA		25°C	13.7	14		13.7	14		
				Full range	13.6			13.6			
		I_O = −15 mA		25°C	13.3	13.7		13.3	13.7		
				Full range	13.2			13.2			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		25°C	−14.7	−14.9		−14.7	−14.9		V
				Full range	−14.6			−14.6			
		I_O = 1.5 mA		25°C	−14.5	−14.8		−14.5	−14.8		
				Full range	−14.4			−14.4			
		I_O = 15 mA		25°C	−13.4	−13.8		−13.4	−13.8		
				Full range	−13.3			−13.3			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V		25°C	100	450		100	450		V/mV
				Full range	75			75			
r_i	Input resistance	R_L = 2 kΩ		25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω		25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ± 2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0,	No load	25°C		6.9	9		6.9	9	mA
				Full range			9.4			9.4	

† Full range is 0°C to 70°C.

TLE2142C operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142C			TLE2142AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ,, f =100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2144C electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2144C			TLE2144AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, V_{IC} = 2.5 V, R_S = 50 Ω	25°C		0.5	3.8		0.5	3	mV
			Full range			4.4			3.6	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			150			150	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.1			−2.1	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.9			0 to 2.9			
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
			Full range	3.8			3.8			
		I_{OH} = −1.5 mA	25°C	3.8	4		3.8	4		
			Full range	3.7			3.7			
		I_{OH} = −15 mA	25°C	3.4	3.7		3.4	3.7		
			Full range	3.4			3.4			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
			Full range			150			150	
		I_{OL} = 1.5 mA	25°C		150	225		150	225	
			Full range			250			250	
		I_{OL} = 15 mA	25°C		1.2	1.6		1.2	1.6	V
			Full range			1.7			1.7	
A_{VD}	Large-signal differential voltage amplification	V_{CC} = ±2.5 V, V_O = 1 V to −1.5 V, R_L = 2 kΩ,	25°C	50	95		50	95		V/mV
			Full range	25			25			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, V_{IC} = 2.5 V, No load,	25°C		13.2	17.6		13.2	17.6	mA
			Full range			18.5			18.5	

† Full range is 0°C to 70°C.

TLE2144C operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2144C			TLE2144AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF		57°			57°		

† R_L terminates at 2.5 V

TLE2144C electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2144C			TLE2144AC			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0	R_S = 50 Ω,	25°C		0.6	2.4		0.5	1.5	mV
				Full range			3.2			2.4	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		µV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			150			150	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	µA
				Full range			−1.6			−1.6	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.9	−15.3 to 13.1		−15 to 12.9	−15 to 13.1		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 µA		25°C	13.8	14.1		13.8	14.1		V
				Full range	13.7			13.7			
		I_O = −1.5 mA		25°C	13.7	14		13.7	14		
				Full range	13.6			13.6			
		I_O = −15 mA		25°C	13.1	13.7		13.1	13.7		
				Full range	13			13			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 µA		25°C	−14.7	−14.9		−14.7	−14.9		V
				Full range	−14.6			−14.6			
		I_O = 1.5 mA		25°C	−14.5	−14.8		−14.5	−14.8		
				Full range	−14.4			−14.4			
		I_O = 15 mA		25°C	−13.4	−13.8		−13.4	−13.8		
				Full range	−13.3			−13.3			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V		25°C	100	170		100	170		V/mV
				Full range	75			75			
r_i	Input resistance	R_L = 2 kΩ		25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0,	No load	25°C		13.8	18		13.8	18	mA
				Full range			18.8			18.8	

† Full range is 0°C to 70°C.

TLE2144C operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2144C			TLE2144AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2141I electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2141I			TLE2141AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		225	1400		200	1000	μV
			Full range			1900			1500	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			200			200	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.2			−2.2	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.7	−0.3 to 2.9		0 to 2.7	−0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
		I_{OH} = −1.5 mA		3.8	4		3.8	4		
		I_{OH} = −15 mA		3.2	3.7		3.2	3.7		
		I_{OH} = −100 μA	Full range	3.8			3.8			
		I_{OH} = −1 mA		3.7			3.7			
		I_{OH} = −10 mA		3.3			3.3			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
		I_{OL} = 1.5 μA			150	225		150	225	
		I_{OL} = 15 mA			1.2	1.6		1.2	1.6	V
		I_{OL} = 100 μA	Full range			175			175	mV
		I_{OL} = 1 mA				225			225	
		I_{OL} = 10 mA				1.4			1.4	V
A_{VD}	Large-signal differential voltage amplification	V_{CC} = ±2.5 V, R_L = 2 kΩ, V_O = 1 V to −1.5 V	25°C	50	220		50	220		V/mV
			Full range	10			10			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		3.4	4.4		3.4	4.4	mA
			Full range			4.6			4.6	

† Full range is −40°C to 105°C.

TLE2141I operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2141I			TLE2141AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF†		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ† f = 100 kHz	C_L = 100 pF†,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF†		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF†		57°			57°		

† R_L and C_L terminated to 2.5 V.

TLE2141I electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2141I			TLE2141AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0	R_S = 50 Ω,	25°C		200	900		175	500	μV
				Full range			1500			1000	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			200			200	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	μA
				Full range			−1.7			−1.7	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.7	−15.3 to 12.9		−15 to 12.7	−15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		25°C	13.8	14.1		13.8	14.1		V
		I_O = −1.5 mA			13.7	14		13.7	14		
		I_O = −15 mA			13.1	13.7		13.1	13.7		
		I_O = −100 μA		Full range	13.7			13.7			
		I_O = −1 mA			13.6			13.6			
		I_O = −10 mA			13.1			13.1			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		25°C	−14.7	−14.9		−14.7	−14.9		V
		I_O = 1.5 mA			−14.5	−14.8		−14.5	−14.8		
		I_O = 15 mA			−13.4	−13.8		−13.4	−13.8		
		I_O = 100 μA		Full range	−14.6			−14.6			
		I_O = 1 mA			−14.5			−14.5			
		I_O = 10 mA			−13.4			−13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	25°C	100	450		100	450		V/mV
				Full range	40			40			
r_i	Input resistance			25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω		25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0,	No load	25°C		3.5	4.5		3.5	4.5	mA
				Full range			4.7			4.7	

† Full range is −40°C to 105°C.

TLE2141I operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2141I			TLE2141AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2142I electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2142I			TLE2142AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, V_{IC} = 2.5 V	R_S = 50 Ω,	25°C		220	1900		220	1500	μV
				Full range			2400			2000	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		8	100		8	100	nA
				Full range			200			200	
I_{IB}	Input bias current			25°C		−0.8	−2		−0.8	−2	μA
				Full range			−2.2			−2.2	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
				Full range	0 to 2.7	−0.3 to 2.9		0 to 2.7	−0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = −150 μA		25°C	3.9	4.1		3.9	4.1		V
		I_{OH} = −1.5 mA			3.8	4		3.8	4		
		I_{OH} = −15 mA			3.4	3.7		3.4	3.7		
		I_{OH} = 100 μA		Full range	3.8			3.8			
		I_{OH} = 1 mA			3.7			3.7			
		I_{OH} = 10 mA			3.5			3.5			
V_{OL}	Low-level output voltage	I_{OI} = 150 μA		25°C		75	125		75	125	mV
		I_{OL} = 1.5 mA				150	225		150	225	
		I_{OL} = 15 mA				1.2	1.4		1.2	1.4	V
		I_{OL} = 100 μA		Full range			175			175	mV
		I_{OL} = 1 mA					225			225	
		I_{OL} = 10 mA					1.2			1.2	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = ±2.5 V, V_O = 1 V to −1.5 V	R_L = 2 kΩ,	25°C	50	220		50	220		V/mV
				Full range	10			10			
r_i	Input resistance			25°C		70			70		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	25°C	85	118		85	118		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, V_{IC} = 2.5 V	No load,	25°C		6.6	8.8		6.6	8.8	mA
				Full range			9.2			9.2	

† Full range is − 40°C to 105°C.

TLE2142I operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142I			TLE2142AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF		57°			57°		

† R_L terminates at 2.5 V.

TLE2142I electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2142I			TLE2142I			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0, R_S = 50 Ω		25°C		290	1200		275	750	μV
				Full range			1800			1400	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			200			200	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	μA
				Full range			−1.7			−1.7	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.7	−15.3 to 12.9		−15 to 12.7	−15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		25°C	13.8	14.1		13.8	14.1		V
		I_O = −1.5 mA			13.7	14		13.7	14		
		I_O = −15 mA			13.3	13.7		13.3	13.7		
		I_O = −100 μA		Full range	13.7			13.7			
		I_O = −1 mA			13.6			13.6			
		I_O = −10 mA			13.3			13.3			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		25°C	−14.7	−14.9		−14.7	−14.9		V
		I_O = 1.5 mA			−14.5	−14.8		−14.5	−14.8		
		I_O = 15 mA			−13.4	−13.8		−13.4	−13.8		
		I_O = 100 μA		Full range	−14.6			−14.6			
		I_O = 1 mA			−14.5			−14.5			
		I_O = 10 mA			−13.4			−13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V, R_L = 2 kΩ		25°C	100	450		100	450		V/mV
				Full range	40			40			
r_i	Input resistance			25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min		25°C	85	108		85	108		dB
		R_S = 50 Ω		Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0,	No load	25°C		6.9	9		6.9	9	mA
				Full range			9.4			9.4	

† Full range is −40°C to 105°C.

TLE2142I operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142I			TLE2142AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ,	30	45		30	45		V/μs
SR–	Negative slew rate			30	42		30	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f =100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2144I electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2144I			TLE2144AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0, R_S = 50 Ω	25°C		0.5	3.8		0.5	3	mV
			Full range			4.8			4	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			200			200	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.2			−2.2	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.7	−0.3 to 2.9		0 to 2.7	−0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
		I_{OH} = −1.5 mA		3.8	4		3.8	4		
		I_{OH} = −15 mA		3.4	3.7		3.4	3.7		
		I_{OH} = 100 μA	Full range	3.8			3.8			
		I_{OH} = 1 mA		3.7			3.7			
		I_{OH} = 10 mA		3.5			3.5			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
		I_{OL} = 1.5 μA			150	225		150	225	
		I_{OL} = 15 mA			1.2	1.6		1.2	1.6	V
		I_{OL} = 100 μA	Full range			175			175	mV
		I_{OL} = 1 mA				225			225	
		I_{OL} = 10 mA				1.4			1.4	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = ±2.5 V, V_O = 1 V to −1.5 V, R_L = 2 kΩ,	25°C	50	95		50	95		V/mV
			Full range	10			10			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, V_{IC} = 2.5 V, No load,	25°C		13.2	17.6		13.2	17.6	mA
			Full range			18.4			18.4	

† Full range is −40°C to 105°C.

TLE2144I operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2144I			TLE2144AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 10 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF		57°			57°		

† R_L terminates at 2.5 V

TLE2144I electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2144I			TLE2144AI			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0	R_S = 50 Ω,	25°C		0.6	2.4		0.5	1.5	mV
				Full range			3.2			2.8	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		µV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			200			200	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	µA
				Full range			−1.7			−1.7	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.7	−15.3 to 12.9		−15 to 12.7	−15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 µA		25°C	13.8	14.1		13.8	14.1		V
		I_O = −1.5 mA			13.7	14		13.7	14		
		I_O = −15 mA			13.1	13.7		13.1	13.7		
		I_O = −100 µA		Full range	13.7			13.7			
		I_O = −1 mA			13.6			13.6			
		I_O = −10 mA			13.1			13.1			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 µA		25°C	−14.7	−14.9		−14.7	−14.9		V
		I_O = 1.5 mA			−14.5	−14.8		−14.5	−14.8		
		I_O = 15 mA			−13.4	−13.8		−13.4	−13.8		
		I_O = 100 µA		Full range	−14.6			−14.6			
		I_O = 1 mA			−14.5			−14.5			
		I_O = 10 mA			−13.4			−13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	25°C	100	170		100	170		V/mV
				Full range	40			40			
r_i	Input resistance			25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0,	No load	25°C		13.8	18		13.8	18	mA
				Full range			18.8			18.8	

† Full range is −40°C to 105°C.

TLE2144I operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2144I			TLE2144AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2141M electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2141M			TLE2141AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		225	1400		200	1000	μV
			Full range			2100			1700	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			250			250	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.3			−2.3	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.7	−0.3 to 2.9		0 to 2.7	−0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
		I_{OH} = −1.5 mA		3.8	4		3.8	4		
		I_{OH} = −15 mA		3.2	3.7		3.2	3.7		
		I_{OH} = −100 μA	Full range	3.75			3.75			
		I_{OH} = −1 mA		3.65			3.65			
		I_{OH} = −10 mA		3.25			3.25			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
		I_{OL} = 1.5 μA			150	225		150	225	
		I_{OL} = 15 mA			1.2	1.4		1.2	1.4	V
		I_{OL} = 100 μA	Full range			200			200	mV
		I_{OL} = 1 mA				250			225	
		I_{OL} = 10 mA				1.25			1.25	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = ±2.5 V, R_L = 2 kΩ, V_O = 1 V to −1.5 V	25°C	50	220		50	220		V/mV
			Full range	5			5			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		3.4	4.4		3.4	4.4	mA
			Full range			4.6			4.6	

† Full range is −55°C to 125°C.

TLE2141M operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2141M			TLE2141AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF†		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF†,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1	R_L = 2 kΩ†,		660			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ†,	C_L = 100 pF†		57°			57°		

† R_L and C_L terminated to 2.5 V.

TLE2141M electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2141M			TLE2141AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0,	R_S = 50 Ω	25°C		200	900		175	500	μV
				Full range			1700			1200	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			250			250	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	μA
				Full range			−1.8			−1.8	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.7	−15.3 to 12.9		−15 to 12.7	−15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		25°C	13.8	14.1		13.8	14.1		V
		I_O = −1.5 mA			13.7	14		13.7	14		
		I_O = −15 mA			13.1	13.7		13.1	13.7		
		I_O = −100 μA		Full range	13.7			13.7			
		I_O = −1 mA			13.6			13.6			
		I_O = −10 mA			13.1			13.1			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		25°C	−14.7	−14.9		−14.7	−14.9		V
		I_O = 1.5 mA			−14.5	−14.8		−14.5	−14.8		
		I_O = 15 mA			−13.4	−13.8		−13.4	−13.8		
		I_O = 100 μA		Full range	−14.6			−14.6			
		I_O = 1 mA			−14.5			−14.5			
		I_O = 10 mA			−13.4			−13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	25°C	100	450		100	450		V/mV
				Full range	20			20			
r_i	Input resistance			25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0, V_{IC} = 2.5 V	No load,	25°C		3.5	4.5		3.5	4.5	mA
				Full range			4.7			4.7	

† Full range is −55°C to 125°C.

TLE2141M operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2141M			TLE2141AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 100 pF	R_L = 2 kΩ,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2142M electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2142M			TLE2142AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		220	1900		200	1500	μV
			Full range			2600			2200	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			200			200	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.3			−2.3	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.7	−0.3 to 2.9		0 to 2.7	−0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
		I_{OH} = −1.5 mA		3.8	4		3.8	4		
		I_{OH} = −15 mA		3.4	3.7		3.4	3.7		
		I_{OH} = 100 μA	Full range	3.75			3.75			
		I_{OH} = 1 mA		3.65			3.65			
		I_{OH} = 10 mA		3.45			3.45			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
		I_{OL} = 1.5 mA			150	225		150	225	
		I_{OL} = 15 mA			1.2	1.4		1.2	1.4	V
		I_{OL} = 100 μA	Full range			200			200	mV
		I_{OL} = 1 mA				250			250	
		I_{OL} = 10 mA				1.25			1.25	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = ±2.5 V, R_L = 2 kΩ, V_O = 1 V to −1.5 V	25°C	50	220		50	220		V/mV
			Full range	5			5			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		6.6	8.8		6.6	8.8	mA
			Full range			9.2			9.2	

† Full range is − 55°C to 125°C.

TLE2142M operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142M			TLE2142AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1,	R_L = 2 kΩ†, C_L = 100 pF		660			660		kHz
ϕ_m	Phase margin	R_L = 2 kΩ†,	C_L = 100 pF		57°			57°		

† R_L terminates at 2.5 V.

TLE2142M electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2142M			TLE2142AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0,	R_S = 50 Ω	25°C		290	1200		275	750	µV
				Full range			2000			1600	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		µV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			250			250	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	µA
				Full range			−1.8			−1.8	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.7	−15.3 to 12.9		−15 to 12.7	−15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 µA		25°C	13.8	14.1		13.8	14.1		V
		I_O = −1.5 mA			13.7	14		13.7	14		
		I_O = −15 mA			13.3	13.7		13.3	13.7		
		I_O = −100 µA		Full range	13.7			13.7			
		I_O = −1 mA			13.6			13.6			
		I_O = −10 mA			13.3			13.3			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 µA		25°C	−14.7	−14.9		−14.7	−14.9		V
		I_O = 1.5 mA			−14.5	−14.8		−14.5	−14.8		
		I_O = 15 mA			−13.4	−13.8		−13.4	−13.8		
		I_O = 100 µA		Full range	−14.6			−14.6			
		I_O = 1 mA			−14.5			−14.5			
		I_O = 10 mA			−13.4			−13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	25°C	100	450		100	450		V/mV
				Full range	20			20			
r_i	Input resistance			25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω		25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0, V_{IC} = 2.5 V	No load,	25°C		6.9	9		6.9	9	mA
				Full range			9.4			9.4	

† Full range is −55°C to 125°C.

TLE2142M operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142M			TLE2142AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	R_L = 2 kΩ, C_L = 100 pF	A_{VD} = –1,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		0.4			0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 1 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2144M electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE2144M			TLE2144AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		0.5	3.8		0.5	3	mV
			Full range			5.2			4.4	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current		25°C		8	100		8	100	nA
			Full range			250			250	
I_{IB}	Input bias current		25°C		−0.8	−2		−0.8	−2	μA
			Full range			−2.3			−2.3	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	−0.3 to 3.2		0 to 3	−0.3 to 3.2		V
			Full range	0 to 2.7	−0.3 to 2.9		0 to 2.7	−0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = −150 μA	25°C	3.9	4.1		3.9	4.1		V
		I_{OH} = −1.5 mA		3.8	4		3.8	4		
		I_{OH} = −15 mA		3.4	3.7		3.4	3.7		
		I_{OH} = 100 μA	Full range	3.75			3.75			
		I_{OH} = 1 mA		3.65			3.65			
		I_{OH} = 10 mA		3.45			3.45			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125		75	125	mV
		I_{OL} = 1.5 μA			150	225		150	225	
		I_{OL} = 15 mA			1.2	1.6		1.2	1.6	V
		I_{OL} = 100 μA	Full range			200			200	mV
		I_{OL} = 1 mA				250			250	
		I_{OL} = 10 mA				1.45			1.45	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = ±2.5 V, R_L = 2 kΩ, V_O = 1 V to −1.5 V	25°C	50	95		50	95		V/mV
			Full range	5			5			
r_i	Input resistance		25°C		70			70		MΩ
c_i	Input capacitance		25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	85	118		85	118		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		90	106		dB
			Full range	85			85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		13.2	17.6		13.2	17.6	mA
			Full range			18.4			18.4	

† Full range is −55°C to 125°C.

TLE2144M operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2144M			TLE2144AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, C_L = 500 pF	R_L = 2 kΩ†,		45			45		V/μs
SR–	Negative slew rate				42			42		
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16			0.16		μs
			To 0.01%		0.22			0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92			1.92		pA/√Hz
		f = 1 kHz			0.5			0.5		
THD + N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, A_{VD} = 2,	R_L = 2 kΩ†, f = 10 kHz		0.0052%			0.0052%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ†,	C_L = 100 pF		5.9			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ†, f = 100 kHz	C_L = 100 pF,		5.8			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, A_{VD} = 1	R_L = 2 kΩ†,		660			660		kHz
ϕ_m	Phase margin	R_L = 2 kΩ†,	C_L = 100 pF		57°			57°		

† R_L terminates at 2.5 V

TLE2144M electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLE2144M			TLE2144AM			UNIT
					MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0,	R_S = 50 Ω	25°C		0.6	2.4		0.5	1.5	mV
				Full range			4			3.2	
α_{VIO}	Temperature coefficient of input offset voltage			Full range		1.7			1.7		μV/°C
I_{IO}	Input offset current			25°C		7	100		7	100	nA
				Full range			250			250	
I_{IB}	Input bias current			25°C		−0.7	−1.5		−0.7	−1.5	μA
				Full range			−1.8			−1.8	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	−15 to 13	−15.3 to 13.2		−15 to 13	−15.3 to 13.2		V
				Full range	−15 to 12.7	−15.3 to 12.9		−15 to 12.7	−15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		25°C	13.8	14.1		13.8	14.1		V
		I_O = −1.5 mA			13.7	14		13.7	14		
		I_O = −15 mA			13.1	13.7		13.1	13.7		
		I_O = −100 μA		Full range	13.7			13.7			
		I_O = −1 mA			13.6			13.6			
		I_O = −10 mA			13.1			13.1			
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		25°C	−14.7	−14.9		−14.7	−14.9		V
		I_O = 1.5 mA			−14.5	−14.8		−14.5	−14.8		
		I_O = 15 mA			−13.4	−13.8		−13.4	−13.8		
		I_O = 100 μA		Full range	−14.6			−14.6			
		I_O = 1 mA			−14.5			−14.5			
		I_O = 10 mA			−13.4			−13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	25°C	100	170		100	170		V/mV
				Full range	20			20			
r_i	Input resistance			25°C		65			65		MΩ
c_i	Input capacitance			25°C		2.5			2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	25°C	85	108		85	108		dB
				Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		90	106		dB
				Full range	85			85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	−25	−50		−25	−50		mA
			V_{ID} = −1 V		20	31		20	31		
I_{CC}	Supply current	V_O = 0, V_{IC} = 2.5 V	No load,	25°C		13.8	18		13.8	18	mA
				Full range			18.8			18.8	

† Full range is −55°C to 125°C

TLE2144M operating characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2144M			TLE2144AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	R_L = 2 kΩ, C_L = 100 pF	A_{VD} = –1,	27	45		27	45		V/μs
SR–	Negative slew rate			27	42		27	42		
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34			0.34		μs
			To 0.01%		.4			.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω,	f = 10 Hz		15			15		nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48			0.48		μV
		f = 0.1 Hz to 10 Hz			0.51			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89			1.89		pA/√Hz
		f = 10 kHz			0.47			0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, A_{VD} = 10,	R_L = 2 kΩ, f = 10 kHz		0.01%			0.01%		
B_1	Unity-gain bandwidth	R_L = 2 kΩ,	C_L = 100 pF		6			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, f = 100 kHz	C_L = 100 pF,		5.9			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1,	R_L = 2 kΩ, C_L = 100 pF		668			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ,	C_L = 100 pF		58°			58°		

TLE2141Y electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2141Y			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0	R_S = 50 Ω,		200	1000	μV
I_{IO}	Input offset current				7	100	nA
I_{IB}	Input bias current				−0.7	−1.5	μA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		−15 to 13	−15.3 to 13.2		V
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		13.8	14.1		V
		I_O = −1.5 mA		13.7	14		
		I_O = −15 mA		13.3	13.7		
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		−14.7	−14.9		V
		I_O = 1.5 mA		−14.5	−14.8		
		I_O = 15 mA		−13.4	−13.8		
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	100	450		V/mV
r_i	Input resistance				65		MΩ
c_i	Input capacitance				2.5		pF
z_o	Open-loop output impedance	f = 1 MHz			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	80	108		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		85	106		dB
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	−25	−50		mA
			V_{ID} = −1 V	20	31		
I_{CC}	Supply current	V_O = 0,	No load		3.5	4.5	mA

TLE2142Y electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLE2142Y			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0, R_S = 50 Ω,			150	875	μV
I_{IO}	Input offset current				7	100	nA
I_{IB}	Input bias current				−0.7	−1.5	μA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		−15 to 13	−15.3 to 13.2		V
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		13.8	14.1		V
		I_O = −1.5 mA		13.7	14		
		I_O = −15 mA		13.3	13.7		
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		−14.7	−14.9		V
		I_O = 1.5 mA		−14.5	−14.8		
		I_O = 15 mA		−13.4	−13.8		
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V, R_L = 2 kΩ		100	450		V/mV
r_i	Input resistance				65		MΩ
c_i	Input capacitance				2.5		pF
z_o	Open-loop output impedance	f = 1 MHz			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω		80	108		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω		85	106		dB
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	−25	−50		mA
			V_{ID} = −1 V	20	31		
I_{CC}	Supply current	V_O = 0, No load			6.9	9	mA

TLE2144Y electrical characteristics at $V_{CC\pm}$ = ±15 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2144Y			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, V_O = 0, R_S = 50 Ω,			0.3	1.8	mV
I_{IO}	Input offset current				7	100	nA
I_{IB}	Input bias current				−0.7	−1.5	μA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		−15 to 13	−15.3 to 13.2		V
V_{OM+}	Maximum positive peak output voltage swing	I_O = −150 μA		13.8	14.1		V
		I_O = −1.5 mA		13.7	14		
		I_O = −15 mA		13.3	13.7		
V_{OM-}	Maximum negative peak output voltage swing	I_O = 150 μA		−14.7	−14.9		V
		I_O = 1.5 mA		−14.5	−14.8		
		I_O = 15 mA		−13.4	−13.8		
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V,	R_L = 2 kΩ	100	450		V/mV
r_i	Input resistance				65		MΩ
c_i	Input capacitance				2.5		pF
z_o	Open-loop output impedance	f = 1 MHz			30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min,	R_S = 50 Ω	80	108		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V,	R_S = 50 Ω	85	106		dB
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	−25	−50		mA
			V_{ID} = −1 V	20	31		
I_{CC}	Supply current	V_O = 0,	No load		13.8	18	mA

TYPICAL CHARACTERISTICS

Table of Graphs

				FIGURE
V_{IO}	Input offset voltage		Distribution	1, 2, 3
I_{IO}	Input offset current		vs Free-air temperature	4
I_{IB}	Input bias current		vs Common-mode input voltage vs Free-air temperature	5 6
V_{OM+}	Maximum positive peak output voltage		vs Supply voltage vs Free-air temperature vs Output current vs Settling time	7 8 9 11
V_{OM-}	Maximum negative peak output voltage		vs Supply voltage vs Free-air temperature vs Output current vs Settling time	7 8 10 11
$V_{O(PP)}$	Maximum peak-to-peak output voltage		vs Frequency	12
V_{OH}	High-level output voltage		vs Output current	13
V_{OL}	Low-level output voltage		vs Output current	14
A_{VD}	Large-signal differential voltage amplification		vs Frequency vs Free-air temperature	15 16
z_o	Closed-loop output impedance		vs Frequency	17
I_{OS}	Short-circuit output current		vs Free-air temperature	18
CMRR	Common-mode rejection ratio		vs Frequency vs Free-air temperature	19 20
k_{SVR}	Supply-voltage rejection ratio		vs Frequency vs Free-air temperature	21 22
I_{CC}	Supply current		vs Supply voltage vs Free-air temperature	23 24
V_n	Equivalent input noise voltage		vs Frequency	25
V_n	Input noise voltage		Over a 10-second period	26
I_n	Noise current		vs Frequency	27
THD + N	Total harmonic distortion plus noise		vs Frequency	28
SR	Slew rate		vs Free-air temperature vs Load capacitance	29 30
	Pulse response	Noninverting large signal	vs Time	31
		Inverting large signal	vs Time	32
		Small signal	vs Time	33
B_1	Unity-gain bandwidth		vs Load capacitance	34
	Gain margin		vs Load capacitance	35
ϕ_m	Phase margin		vs Load capacitance	36
	Phase shift		vs Frequency	15

TYPICAL CHARACTERISTICS

TLE2141
DISTRIBUTION OF
INPUT OFFSET VOLTAGE



Figure 1

TLE2142
DISTRIBUTION OF
INPUT OFFSET VOLTAGE



Figure 2

TLE2144
DISTRIBUTION OF
INPUT OFFSET VOLTAGE



Figure 3

INPUT OFFSET CURRENT†
vs
FREE-AIR TEMPERATURE



Figure 4

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

INPUT BIAS CURRENT† vs COMMON-MODE INPUT VOLTAGE



Figure 5

INPUT BIAS CURRENT† vs FREE-AIR TEMPERATURE



Figure 6

MAXIMUM PEAK OUTPUT VOLTAGE vs SUPPLY VOLTAGE



Figure 7

MAXIMUM PEAK OUTPUT VOLTAGE vs FREE-AIR TEMPERATURE



Figure 8

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

MAXIMUM POSITIVE PEAK OUTPUT VOLTAGE† vs OUTPUT CURRENT



Figure 9

MAXIMUM NEGATIVE PEAK OUTPUT VOLTAGE† vs OUTPUT CURRENT



Figure 10

MAXIMUM PEAK OUTPUT VOLTAGE vs SETTLING TIME



Figure 11

MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE† vs FREQUENCY



Figure 12

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

HIGH-LEVEL OUTPUT VOLTAGE† vs OUTPUT CURRENT



Figure 13

LOW-LEVEL OUTPUT VOLTAGE† vs OUTPUT CURRENT



Figure 14

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY



Figure 15

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION† vs FREE-AIR TEMPERATURE



Figure 16

CLOSED-LOOP OUTPUT IMPEDANCE vs FREQUENCY



Figure 17

SHORT-CIRCUIT OUTPUT CURRENT† vs FREE-AIR TEMPERATURE



Figure 18

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

COMMON-MODE REJECTION RATIO vs FREQUENCY



Figure 19

COMMON-MODE REJECTION RATIO† vs FREE-AIR TEMPERATURE



Figure 20

SUPPLY-VOLTAGE REJECTION RATIO vs FREQUENCY



Figure 21

SUPPLY-VOLTAGE REJECTION RATIO† vs FREE-AIR TEMPERATURE



Figure 22

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

SUPPLY CURRENT† vs SUPPLY VOLTAGE



Figure 23

SUPPLY CURRENT† vs FREE-AIR TEMPERATURE



Figure 24

EQUIVALENT INPUT NOISE VOLTAGE† vs FREQUENCY



Figure 25

INPUT NOISE VOLTAGE OVER A 10-SECOND PERIOD



Figure 26

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

NOISE CURRENT† vs FREQUENCY



Figure 27

TOTAL HARMONIC DISTORTION PLUS NOISE vs FREQUENCY



Figure 28

SLEW RATE† vs FREE-AIR TEMPERATURE



Figure 29

SLEW RATE vs LOAD CAPACITANCE



Figure 30

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

NONINVERTING LARGE-SIGNAL PULSE RESPONSE†



Figure 31

INVERTING LARGE-SIGNAL PULSE RESPONSE†



Figure 32

SMALL-SIGNAL PULSE RESPONSE



Figure 33

UNITY-GAIN BANDWIDTH† vs LOAD CAPACITANCE



Figure 34

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

GAIN MARGIN† vs LOAD CAPACITANCE



Figure 35

PHASE MARGIN† vs LOAD CAPACITANCE



Figure 36

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

APPLICATION INFORMATION

input offset voltage nulling

The TLE2141 series offers external null pins that can be used to further reduce the input offset voltage. If this feature is desired, connect the circuit of Figure 37 as shown. If external nulling is not needed, the null pins may be left unconnected.



Figure 37. Input Offset Voltage Null Circuit

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
5962-9321603Q2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Call TI	-55 to 125	5962-9321603Q2A TLE2142MFKB	Samples
5962-9321603QHA	ACTIVE	CFP	U	10	1	TBD	Call TI	Call TI	-55 to 125	9321603QHA TLE2142M	Samples
5962-9321603QPA	ACTIVE	CDIP	JG	8	1	TBD	Call TI	Call TI	-55 to 125	9321603QPA TLE2142M	Samples
5962-9321604Q2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Call TI	-55 to 125	5962-9321604Q2A TLE2142 AMFKB	Samples
5962-9321604QHA	ACTIVE	CFP	U	10	1	TBD	Call TI	Call TI	-55 to 125	9321604QHA TLE2142AM	Samples
5962-9321604QPA	ACTIVE	CDIP	JG	8	1	TBD	Call TI	Call TI	-55 to 125	9321604QPA TLE2142AM	Samples
5962-9321605Q2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Call TI	-55 to 125	5962-9321605Q2A TLE2144MFKB	Samples
5962-9321605QCA	ACTIVE	CDIP	J	14	1	TBD	Call TI	Call TI	-55 to 125	5962-9321605QCA TLE2144MJB	Samples
5962-9321606Q2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Call TI	-55 to 125	5962-9321606Q2A TLE2144 AMFKB	Samples
5962-9321606QCA	ACTIVE	CDIP	J	14	1	TBD	Call TI	Call TI	-55 to 125	5962-9321606QCA TLE2144AMJB	Samples
TLE2141ACD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141AC	Samples
TLE2141ACDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141AC	Samples
TLE2141ACP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2141AC	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
TLE2141ACPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2141AC	Samples
TLE2141AID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141AI	Samples
TLE2141AIDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141AI	Samples
TLE2141AIDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141AI	Samples
TLE2141AIDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141AI	Samples
TLE2141AIP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type	0 to 70	TLE2141AI	Samples
TLE2141AIPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type	0 to 70	TLE2141AI	Samples
TLE2141CD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141C	Samples
TLE2141CDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141C	Samples
TLE2141CDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141C	Samples
TLE2141CDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141C	Samples
TLE2141CP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2141CP	Samples
TLE2141CPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2141CP	Samples
TLE2141ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141I	Samples
TLE2141IDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141I	Samples
TLE2141IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141I	Samples
TLE2141IDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2141I	Samples
TLE2141IP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2141IP	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
TLE2141IPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2141IP	Samples
TLE2141MD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	2141M	Samples
TLE2141MDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	2141M	Samples
TLE2142ACD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AC	Samples
TLE2142ACDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AC	Samples
TLE2142ACDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AC	Samples
TLE2142ACDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AC	Samples
TLE2142ACP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	0 to 70		
TLE2142AID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AI	Samples
TLE2142AIDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AI	Samples
TLE2142AIDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AI	Samples
TLE2142AIDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142AI	Samples
TLE2142AIP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI			
TLE2142AMD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	E2142A	Samples
TLE2142AMDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		E2142A	Samples
TLE2142AMDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	E2142A	Samples
TLE2142AMDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		E2142A	Samples
TLE2142AMFKB	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type	-55 to 125	5962-9321604Q2A TLE2142 AMFKB	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
TLE2142AMJG	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type		TLE2142AMJG	Samples
TLE2142AMJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9321604QPA TLE2142AM	Samples
TLE2142AMUB	ACTIVE	CFP	U	10	1	TBD	A42	N / A for Pkg Type	-55 to 125	9321604QHA TLE2142AM	Samples
TLE2142CD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142C	Samples
TLE2142CDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142C	Samples
TLE2142CDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142C	Samples
TLE2142CDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142C	Samples
TLE2142CP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2142CP	Samples
TLE2142CPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2142CP	Samples
TLE2142CPWLE	OBSOLETE	TSSOP	PW	16		TBD	Call TI	Call TI			
TLE2142CPWR	ACTIVE	TSSOP	PW	16	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		Q2142	Samples
TLE2142CPWRG4	ACTIVE	TSSOP	PW	16	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		Q2142	Samples
TLE2142ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142I	Samples
TLE2142IDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142I	Samples
TLE2142IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142I	Samples
TLE2142IDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142I	Samples
TLE2142IP	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2142IP	Samples
TLE2142IPE4	ACTIVE	PDIP	P	8	50	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2142IP	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
TLE2142MD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	2142M	Samples
TLE2142MDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142M	Samples
TLE2142MDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	2142M	Samples
TLE2142MDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		2142M	Samples
TLE2142MFKB	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type	-55 to 125	5962-9321603Q2A TLE2142MFKB	Samples
TLE2142MJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	-55 to 125	9321603QPA TLE2142M	Samples
TLE2142MUB	ACTIVE	CFP	U	10	1	TBD	A42	N / A for Pkg Type	-55 to 125	9321603QHA TLE2142M	Samples
TLE2144ACN	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144ACN	Samples
TLE2144ACNE4	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144ACN	Samples
TLE2144AIN	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144AIN	Samples
TLE2144AINE4	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144AIN	Samples
TLE2144AMFKB	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type	-55 to 125	5962-9321606Q2A TLE2144 AMFKB	Samples
TLE2144AMJB	ACTIVE	CDIP	J	14	1	TBD	A42	N / A for Pkg Type	-55 to 125	5962-9321606QCA TLE2144AMJB	Samples
TLE2144CDW	ACTIVE	SOIC	DW	16	40	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144C	Samples
TLE2144CDWG4	ACTIVE	SOIC	DW	16	40	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144C	Samples
TLE2144CDWR	ACTIVE	SOIC	DW	16	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144C	Samples

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
TLE2144CDWRG4	ACTIVE	SOIC	DW	16	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144C	Samples
TLE2144CN	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144CN	Samples
TLE2144CNE4	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144CN	Samples
TLE2144IDW	ACTIVE	SOIC	DW	16	40	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144I	Samples
TLE2144IDWG4	ACTIVE	SOIC	DW	16	40	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144I	Samples
TLE2144IDWR	ACTIVE	SOIC	DW	16	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144I	Samples
TLE2144IDWRG4	ACTIVE	SOIC	DW	16	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144I	Samples
TLE2144IN	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144IN	Samples
TLE2144INE4	ACTIVE	PDIP	N	14	25	Pb-Free (RoHS)	CU NIPDAU	N / A for Pkg Type		TLE2144IN	Samples
TLE2144MDW	ACTIVE	SOIC	DW	16	40	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-55 to 125	TLE2144M	Samples
TLE2144MDWG4	ACTIVE	SOIC	DW	16	40	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		TLE2144M	Samples
TLE2144MFKB	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type	-55 to 125	5962-9321605Q2A TLE2144MFKB	Samples
TLE2144MJB	ACTIVE	CDIP	J	14	1	TBD	A42	N / A for Pkg Type	-55 to 125	5962-9321605QCA TLE2144MJB	Samples
TLE2144MN	OBSOLETE	PDIP	N	14		TBD	Call TI	Call TI	-55 to 125		

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) Only one of markings shown within the brackets will appear on the physical device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TLE2141, TLE2141A, TLE2142, TLE2142A, TLE2142AM, TLE2142M, TLE2144, TLE2144A, TLE2144AM, TLE2144M :

- Catalog: TLE2142A, TLE2142, TLE2144A, TLE2144
- Automotive: TLE2141-Q1, TLE2142-Q1, TLE2142-Q1
- Enhanced Product: TLE2141-EP, TLE2144-EP, TLE2144-EP
- Military: TLE2141M, TLE2141AM, TLE2142M, TLE2142AM, TLE2144M, TLE2144AM

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications

- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLE2141AIDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2141CDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2141IDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2141MDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142ACDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142AIDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142AMDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142AMDRG4	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142CDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142CPWR	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
TLE2142IDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142MDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2142MDRG4	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2144CDWR	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
TLE2144IDWR	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLE2141AIDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2141CDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2141IDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2141MDR	SOIC	D	8	2500	367.0	367.0	35.0
TLE2142ACDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2142AIDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2142AMDR	SOIC	D	8	2500	367.0	367.0	35.0
TLE2142AMDRG4	SOIC	D	8	2500	367.0	367.0	35.0
TLE2142CDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2142CPWR	TSSOP	PW	16	2000	367.0	367.0	35.0
TLE2142IDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2142MDR	SOIC	D	8	2500	367.0	367.0	35.0
TLE2142MDRG4	SOIC	D	8	2500	367.0	367.0	35.0
TLE2144CDWR	SOIC	DW	16	2000	367.0	367.0	38.0
TLE2144IDWR	SOIC	DW	16	2000	367.0	367.0	38.0

MCER001A – JANUARY 1995 – REVISED JANUARY 1997

JG (R-GDIP-T8) **CERAMIC DUAL-IN-LINE**



NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification.
E. Falls within MIL STD 1835 GDIP1-T8

J (R–GDIP–T**)

14 LEADS SHOWN

CERAMIC DUAL IN–LINE PACKAGE



DIM \ PINS **	14	16	18	20
A	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC
B MAX	0.785 (19,94)	.840 (21,34)	0.960 (24,38)	1.060 (26,92)
B MIN	—	—	—	—
C MAX	0.300 (7,62)	0.300 (7,62)	0.310 (7,87)	0.300 (7,62)
C MIN	0.245 (6,22)	0.245 (6,22)	0.220 (5,59)	0.245 (6,22)



4040083/F 03/03

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package is hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
E. Falls within MIL STD 1835 GDIP1–T14, GDIP1–T16, GDIP1–T18 and GDIP1–T20.

U (S–GDFP–F10) CERAMIC DUAL FLATPACK



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only.
E. Falls within MIL STD 1835 GDFP1–F10 and JEDEC MO–092AA

FK (S–CQCC–N**) LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN



NO. OF TERMINALS **	A		B	
	MIN	MAX	MIN	MAX
20	0.342 (8,69)	0.358 (9,09)	0.307 (7,80)	0.358 (9,09)
28	0.442 (11,23)	0.458 (11,63)	0.406 (10,31)	0.458 (11,63)
44	0.640 (16,26)	0.660 (16,76)	0.495 (12,58)	0.560 (14,22)
52	0.740 (18,78)	0.761 (19,32)	0.495 (12,58)	0.560 (14,22)
68	0.938 (23,83)	0.962 (24,43)	0.850 (21,6)	0.858 (21,8)
84	1.141 (28,99)	1.165 (29,59)	1.047 (26,6)	1.063 (27,0)



4040140/D 01/11

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a metal lid.
D. Falls within JEDEC MS–004

P (R–PDIP–T8) PLASTIC DUAL–IN–LINE PACKAGE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001 variation BA.

PW (R–PDSO–G16) PLASTIC SMALL OUTLINE



4040064–4/G 02/11

NOTES:
A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M–1994.
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
E. Falls within JEDEC MO–153

PW (R–PDSO–G16) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Publication IPC–7351 is recommended for alternate designs.
D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC–7525 for other stencil recommendations.
E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

D (R–PDSO–G8) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
E. Reference JEDEC MS–012 variation AA.

D (R–PDSO–G8) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Publication IPC–7351 is recommended for alternate designs.
D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC–7525 for other stencil recommendations.
E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

DW (R–PDSO–G16) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M–1994.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
D. Falls within JEDEC MS–013 variation AA.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as “components”) are sold subject to TI’s terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI’s terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers’ products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers’ products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI’s goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or “enhanced plastic” are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have ***not*** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products		**Applications**	
Audio	www.ti.com/audio	Automotive and Transportation	www.ti.com/automotive
Amplifiers	amplifier.ti.com	Communications and Telecom	www.ti.com/communications
Data Converters	dataconverter.ti.com	Computers and Peripherals	www.ti.com/computers
DLP® Products	www.dlp.com	Consumer Electronics	www.ti.com/consumer-apps
DSP	dsp.ti.com	Energy and Lighting	www.ti.com/energy
Clocks and Timers	www.ti.com/clocks	Industrial	www.ti.com/industrial
Interface	interface.ti.com	Medical	www.ti.com/medical
Logic	logic.ti.com	Security	www.ti.com/security
Power Mgmt	power.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Applications Processors	www.ti.com/omap	**TI E2E Community**	e2e.ti.com
Wireless Connectivity	www.ti.com/wirelessconnectivity		

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2013, Texas Instruments Incorporated

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.