

G3VM-□AY□/□DY□

MOS FET Relays Small DIP4 package with High dielectric strength type

Small DIP4 package with Dielectric Strength of 5,000 VAC between I/O

- Load voltage 40V/60V/200V/350V/400V/600V
- Standard type: Trigger LED forward current 3mA (max.)
- High sensitive type: Trigger LED forward current 2mA (max.)



NEW

Note: The actual product is marked differently from the image shown here.


RoHS Compliant

Refer to "Common Precautions".

Application Examples

- Electrical power unit
- Security equipment
- Medical equipment
- Test & measurement equipment
- Industrial equipment

Package (Unit : mm, Average)



Note: The actual product is marked differently from the image shown here.

Model Number Legend

G3VM-□□□□□
1 2 3 4 5

1. Load Voltage

- 4: 40V
- 6: 60V
- 20: 200V
- 35: 350V
- 40: 400V
- 60: 600V

2. Contact form

- 1: 1a (SPST-NO)

3. Package type

- A: DIP4 pin PCB terminals
- D: DIP4 pin Surface-mounting Terminals

4. Additional functions

- Y: Dielectric strength between I/O above 2,500V type

5. Other informations

When specifications overlap, serial code is added in the recorded order.

Ordering Information

Standard type

Package type	Contact form	Load voltage (peak value) *	Continuous load current (peak value) *	Packing/Tube		Packing/Tape & reel		
				Model		Minimum package quantity	Model	
				PCB terminals	Surface-mounting Terminals		Surface-mounting Terminals	Minimum package quantity
DIP4	1a	40V	2000mA	G3VM-41AY1	G3VM-41DY1	100 pcs.	G3VM-41DY1(TR05)	500 pcs.
		60V	500mA	G3VM-61AY1	G3VM-61DY1		G3VM-61DY1(TR05)	
		200V	250mA	G3VM-201AY1	G3VM-201DY1		G3VM-201DY1(TR05)	
		350V	100mA	G3VM-351AY1	G3VM-351DY1		G3VM-351DY1(TR05)	
		400V	120mA	G3VM-401AY1	G3VM-401DY1		G3VM-401DY1(TR05)	
		600V	90mA	G3VM-601AY1	G3VM-601DY1		G3VM-601DY1(TR05)	

* The AC peak and DC value are given for the load voltage and continuous load current.

High sensitive type

Package type	Contact form	Load voltage (peak value) *	Continuous load current (peak value) *	Packing/Tube		Packing/Tape & reel		
				Model		Minimum package quantity	Model	
				PCB terminals	Surface-mounting Terminals		Surface-mounting Terminals	Minimum package quantity
DIP4	1a	40V	2000mA	G3VM-41AY	G3VM-41DY	100 pcs.	G3VM-41DY(TR)	1,500 pcs.
		60V	500mA	G3VM-61AY	G3VM-61DY		G3VM-61DY(TR)	
		200V	250mA	G3VM-201AY	G3VM-201DY		G3VM-201DY(TR)	
		350V	100mA	G3VM-351AY	G3VM-351DY		G3VM-351DY(TR)	
		400V	120mA	G3VM-401AY	G3VM-401DY		G3VM-401DY(TR)	
		600V	90mA	G3VM-601AY	G3VM-601DY		G3VM-601DY(TR)	

* The AC peak and DC value are given for the load voltage and continuous load current.

■ Absolute Maximum Ratings (Ta = 25°C)

● Standard type, High sensitive type

Item	Symbol	G3VM-41AY1	G3VM-61AY1	G3VM-201AY1	G3VM-351AY1	G3VM-401AY1	G3VM-601AY1	Unit	Measurement conditions		
		G3VM-41DY1	G3VM-61DY1	G3VM-201DY1	G3VM-351DY1	G3VM-401DY1	G3VM-601DY1				
Input	LED forward current	IF						30	mA		
	Repetitive peak LED forward current	IFP						1	A	100 μs pulses, 100 pps	
	LED forward current reduction rate	ΔIF/°C						-0.3	mA/°C	Ta≥25°C	
	LED reverse voltage	VR						5	V		
	Connection temperature	TJ						125	°C		
Output	Load voltage (AC peak/DC)	VOFF		40	60	200	350	400	600	V	
	Continuous load current (AC peak/DC)	Io		2,000	500	250	100	120	90	mA	
	ON current reduction rate	ΔIo/°C		-20	-5	-2.5	-1	-1.2	-0.9	mA/°C	Ta≥25°C
	Pulse ON current	Iop		6	1.5	0.75	0.3	0.36	0.27	A	t=100ms, Duty=1/10
	Connection temperature	TJ						125	°C		
Dielectric strength between I/O (See note 1.)	VI-o		5,000					Vrms	AC for 1 min		
Ambient operating temperature	Ta		-40~+85					°C	With no icing or condensation		
Ambient storage temperature	Tstg		-55~+125					°C			
Soldering temperature	-		260					°C	10s		

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

■Electrical Characteristics (Ta = 25°C)


●Standard type

Item	Symbol	Model								Unit	Measurement conditions		
		G3VM-41AY1 G3VM-41DY1	G3VM-61AY1 G3VM-61DY1	G3VM-201AY1 G3VM-201DY1	G3VM-351AY1 G3VM-351DY1	G3VM-401AY1 G3VM-401DY1	G3VM-601AY1 G3VM-601DY1						
Input	LED forward voltage	V _F	Minimum								V	I _F =10mA	
		1.1											
		Typical											
	1.27												
	Maximum												
1.4													
Reverse current	I _R	Maximum								μA	V _R =5V		
Capacity between terminals	C _T	Typical								pF	V=0, f=1MHz		
Trigger LED forward current	I _{FT}	Minimum		0.5				0.6		0.5		mA	G3VM-41AY1/DY1 : I _o =1A Others : I _o =Continuous load current ratings
		Maximum								3			
Release LED forward current	I _{FC}	Minimum								mA	I _{OFF} =10μA		
Maximum resistance with output ON	R _{ON}	Typical		0.09(0.06)	0.6	5	35(25)	22(17)	45(30)	Ω	I _F =5mA, I _o =Continuous load current ratings (value at t<1s)		
		Maximum		0.15(0.10)	2	8	50(35)	35(28)	60(40)				
Current leakage when the relay is open	I _{LEAK}	Maximum								μA	V _{OFF} =Load voltage ratings		
Capacity between terminals	C _{OFF}	Typical								pF	V=0, f=1MHz		
Capacity between I/O terminals	C _{I-O}	Typical								pF	f=1MHz, V _S =0V		
Insulation resistance between I/O terminals	R _{I-O}	Minimum								MΩ	V _{I-O} =500VDC, R _{oH} ≤60%		
		Typical								10 ⁸			
Turn-ON time	t _{ON}	Typical		2.8	1	0.3	0.6	0.5		ms	G3VM-41AY1/DY1 : R _L =200Ω, I _F =10mA, V _{DD} =20V G3VM-601AY1/DY1 : R _L =200Ω, I _F =5mA, V _{DD} =10V Others : R _L =200Ω, I _F =5mA, V _{DD} =20V (See note 2.)		
		Maximum		5	3	2							
Turn-OFF time	t _{OFF}	Typical		0.3	0.2	0.1	0.2		ms	G3VM-41AY1/DY1 : R _L =200Ω, I _F =10mA, V _{DD} =20V G3VM-601AY1/DY1 : R _L =200Ω, I _F =5mA, V _{DD} =10V Others : R _L =200Ω, I _F =5mA, V _{DD} =20V (See note 2.)			
		Maximum		1									

●High sensitive type

Item	Symbol	Model								Unit	Measurement conditions	
		G3VM-41AY G3VM-41DY	G3VM-61AY G3VM-61DY	G3VM-201AY G3VM-201DY	G3VM-351AY G3VM-351DY	G3VM-401AY G3VM-401DY	G3VM-601AY G3VM-601DY					
Input	LED forward voltage	V _F	Minimum								V	I _F =10mA
		1.45										
		Typical										
	1.63											
	Maximum								1.75			
Reverse current	I _R	Maximum								μA	V _R =5V	
Capacity between terminals	C _T	Typical								pF	V=0, f=1MHz	
Trigger LED forward current	I _{FT}	Minimum								mA	G3VM-41AY/DY : I _o =1A Others : I _o =Continuous load current ratings	
		0.3										
Release LED forward current	I _{FC}	Maximum								mA	I _{OFF} =10μA	
		0.1										
Maximum resistance with output ON	R _{ON}	Typical		0.09(0.06)	0.6	5	35(25)	22(17)	45(30)	Ω	I _F =5mA, I _o =Continuous load current ratings (value at t<1s)	
		Maximum		0.15(0.10)	2	8	50(35)	35(28)	60(40)			
Current leakage when the relay is open	I _{LEAK}	Maximum								μA	V _{OFF} =Load voltage ratings	
Capacity between terminals	C _{OFF}	Typical								pF	V=0, f=1MHz	
Capacity between I/O terminals	C _{I-O}	Typical								pF	f=1MHz, V _S =0V	
Insulation resistance between I/O terminals	R _{I-O}	Minimum								MΩ	V _{I-O} =500VDC, R _{oH} ≤60%	
		Typical								10 ⁸		
Turn-ON time	t _{ON}	Typical		2	0.5	0.1	0.2		ms	G3VM-601AY/DY : R _L =200Ω, I _F =5mA, V _{DD} =10V Others : R _L =200Ω, I _F =5mA, V _{DD} =20V (See note 2.)		
		Maximum		5	1							
Turn-OFF time	t _{OFF}	Typical		0.3	0.2					ms	G3VM-601AY/DY : R _L =200Ω, I _F =5mA, V _{DD} =10V Others : R _L =200Ω, I _F =5mA, V _{DD} =20V (See note 2.)	
		Maximum		1								

Note: 2. Turn-ON and Turn-OFF Times



Recommended Operating Conditions

For usage with high reliability, Recommended Operation Conditions is a measure that takes into account the derating of Absolute Maximum Ratings and Electrical Characteristics.

Each item on this list is an independent condition, so it is not simultaneously satisfy several conditions.

Standard type

Item	Symbol		G3VM-41AY1	G3VM-61AY1	G3VM-201AY1	G3VM-351AY1	G3VM-401AY1	G3VM-601AY1	Unit
			G3VM-41DY1	G3VM-61DY1	G3VM-201DY1	G3VM-351DY1	G3VM-401DY1	G3VM-601DY1	
Load voltage (AC peak/DC)	V _{DD}	Maximum	32	48	160	280	320	480	V
		Minimum	5						
Operating LED forward current	I _F	Typical	7.5						mA
		Maximum	25						
		Maximum	2000	500	250	100	120	90	
Continuous load current (AC peak/DC)	I _o	Maximum	2000	500	250	100	120	90	
Ambient operating temperature	T _a	Minimum	-20						°C
		Maximum	65						

High sensitive type

Item	Symbol		G3VM-41AY	G3VM-61AY	G3VM-201AY	G3VM-351AY	G3VM-401AY	G3VM-601AY	Unit
			G3VM-41DY	G3VM-61DY	G3VM-201DY	G3VM-351DY	G3VM-401DY	G3VM-601DY	
Load voltage (AC peak/DC)	V _{DD}	Maximum	32	48	160	280	320	480	V
		Minimum	3						
Operating LED forward current	I _F	Typical	5						mA
		Maximum	15		20				
		Maximum	2000	500	250	100	120	90	
Continuous load current (AC peak/DC)	I _o	Maximum	2000	500	250	100	120	90	
Ambient operating temperature	T _a	Minimum	-20						°C
		Maximum	65						

Spacing and Insulation

Standard type and High sensitive type


Item	Standard	Unit
Creepage distances	Minimum 7.0	mm
Clearance distances	Minimum 7.0	
Internal isolation thickness	Minimum 0.4	

Engineering Data


DIP

G3VM-□AY□/□DY□

LED forward current vs. Ambient temperature




LED forward current vs. LED forward voltage




Continuous load current vs. Ambient temperature


G3VM-41AY/DY/AY1/DY1



G3VM-61AY/DY/AY1/DY1
G3VM-201AY/DY/AY1/DY1




G3VM-351AY/DY/AY1/DY1
G3VM-401AY/DY/AY1/DY1
G3VM-601AY/DY/AY1/DY1




Continuous load current vs. On-state voltage


G3VM-41AY/DY/AY1/DY1



G3VM-61AY/DY/AY1/DY1
G3VM-201AY/DY/AY1/DY1




G3VM-351AY/DY/AY1/DY1
G3VM-401AY/DY/AY1/DY1
G3VM-601AY/DY/AY1/DY1




On-state resistance vs. Ambient temperature


G3VM-41AY/DY/AY1/DY1



G3VM-61AY/DY/AY1/DY1
G3VM-201AY/DY/AY1/DY1




G3VM-351AY/DY/AY1/DY1
G3VM-401AY/DY/AY1/DY1
G3VM-601AY/DY/AY1/DY1




Engineering Data

Trigger LED forward current vs. Ambient temperature


G3VM-41AY/DY/AY1/DY1
G3VM-61AY/DY/AY1/DY1



G3VM-201AY/DY/AY1/DY1
G3VM-351AY/DY/AY1/DY1




G3VM-401AY/DY/AY1/DY1
G3VM-601AY/DY/AY1/DY1




Turn ON, Turn OFF time vs. LED forward current


G3VM-41AY1/DY1
G3VM-61AY1/DY1




G3VM-201AY1/DY1
G3VM-351AY1/DY1




G3VM-401AY1/DY1
G3VM-601AY1/DY1




G3VM-41AY/DY
G3VM-61AY/DY



G3VM-201AY/DY
G3VM-351AY/DY




G3VM-401AY/DY
G3VM-601AY/DY




Turn ON, Turn OFF time vs. Ambient temperature


G3VM-41AY1/DY1
G3VM-61AY1/DY1



G3VM-201AY1/DY1
G3VM-351AY1/DY1



G3VM-401AY1/DY1
G3VM-601AY1/DY1




DIP G3VM-□AY□/□DY□


Engineering Data

● Turn ON, Turn OFF time vs. Ambient temperature


G3VM-41AY1/DY1
G3VM-61AY1/DY1



G3VM-201AY/DY
G3VM-351AY/DY




G3VM-401AY/DY
G3VM-601AY/DY




● Current leakage vs. Ambient temperature


G3VM-41AY/DY/AY1/DY1
G3VM-61AY/DY/AY1/DY1



G3VM-201AY/DY/AY1/DY1
G3VM-351AY/DY/AY1/DY1



G3VM-401AY/DY/AY1/DY1
G3VM-601AY/DY/AY1/DY1



DIP


G3VM-□AY□/□DY□

■ Appearance/Terminal Arrangement/Internal Connections

■ Appearance

DIP (Dual Inline Package)


DIP4




Note: The actual product is marked differently from the image shown here.

* The indentation in the corner diagonally opposite from the pin 1 mark is from a pin on the mold.

■ Terminal Arrangement/Internal Connections




■ Dimensions (Unit: mm)




PCB Terminals

Weight: 0.25 g




Surface-mounting Terminals

Weight: 0.25 g




PCB Dimensions (BOTTOM VIEW)



Actual Mounting Pad Dimensions

(Recommended Value, TOP VIEW)



Note: The actual product is marked differently from the image shown here.

■ Approved Standards

UL recognized

● Standard type and High sensitive type

Approved Standards	Contact form	File No.
UL recognized	1a (SPST-NO)	E80555

■ Safety Precautions

• Refer to "Common Precautions" for all G3VM models.

• Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
 • Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

OMRON Corporation

Electronic and Mechanical Components Company

Contact: www.omron.com/ecb

Cat. No. K275-E1-02
0215(0115)(O)

DIP

G3VM-□AY□/□DY□



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.