

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

AUG ,2006.

© COPYRIGHT

BY TYCO ELECTRONICS CORPORATION.

ALL RIGHTS RESERVED.

LOC DW	DIST —	REVISIONS							
		P	LTR	DESCRIPTION			DATE	DWN	APVD
			G	REVISED PER ECR-16-003830			14MAR16	FL	SY

D

8.7	GEN II & GEN III	 PA9T	2.30	71.35	70	73.15	89	71.65	164	BLACK	30u"	4-1734774-8
5.45				38.35	37	40.15	56	38.65	98	WHITE		4-1734774-7
3.85				21.35	20	23.15	39	21.65	64	BLACK		4-1734774-6
2.55				7.35	6	9.15	25	7.65	36	WHITE		4-1734774-5
8.7				71.35	70	73.15	89	71.65	164	BLACK		4-1734774-4
										WHITE		4-1734774-3
5.45				38.35	37	40.15	56	38.65	98	BLACK	4-1734774-2	
										WHITE	4-1734774-1	
3.85				21.35	20	23.15	39	21.65	64	BLACK	3-1734774-9	
										WHITE	3-1734774-8	
2.55				7.35	6	9.15	25	7.65	36	BLACK	3-1734774-7	
										WHITE	3-1734774-6	
8.7				71.35	70	73.15	89	71.65	164	BLACK	3-1734774-5	
										WHITE	3-1734774-4	
5.45				38.35	37	40.15	56	38.65	98	BLACK	3-1734774-3	
										WHITE	3-1734774-2	
3.85				21.35	20	23.15	39	21.65	64	BLACK	3-1734774-1	
										WHITE	3-1734774-0	
2.55				7.35	6	9.15	25	7.65	36	BLACK	2-1734774-9	
										WHITE	2-1734774-8	
8.7				71.35	70	73.15	89	71.65	164	BLACK	2-1734774-7	
										WHITE	2-1734774-6	
5.45				38.35	37	40.15	56	38.65	98	BLACK	2-1734774-5	
										WHITE	2-1734774-4	
3.85	21.35	20	23.15	39	21.65	64	BLACK	2-1734774-3				
							WHITE	2-1734774-2				
2.55	7.35	6	9.15	25	7.65	36	BLACK	2-1734774-1				
							WHITE	2-1734774-0				
WEIGHT(g)	PCI-E COMPLIANCE	HOUSING MATERIAL	DIM. L	DIM. E	DIM. D	DIM. C	DIM. B	DIM. A	POS.	HOUSING COLOR	MIN. GOLD THICKNESS	PART NUMBER

D

C

8.8	GEN II	PA46	2.30	71.35	70	73.15	89	71.65	164	BLACK	30u"	9-1734774-7
5.5				38.35	37	40.15	56	38.65	98	WHITE		9-1734774-6
3.9				21.35	20	23.15	39	21.65	64	BLACK		9-1734774-5
2.55				7.35	6	9.15	25	7.65	36	WHITE		9-1734774-4
										BLACK		9-1734774-3
8.8				71.35	70	73.15	89	71.65	164	WHITE		9-1734774-2
										BLACK		9-1734774-1
5.5				38.35	37	40.15	56	38.65	98	G/F		9-1734774-0
										WHITE	8-1734774-9	
3.9				21.35	20	23.15	39	21.65	64	G/F	8-1734774-8	
										BLACK	8-1734774-7	
2.55				7.35	6	9.15	25	7.65	36	WHITE	8-1734774-6	
										BLACK	8-1734774-5	
8.8				71.35	70	73.15	89	71.65	164	G/F	8-1734774-4	
										WHITE	8-1734774-3	
5.5				38.35	37	40.15	56	38.65	98	BLACK	8-1734774-2	
										WHITE	8-1734774-1	
3.9				21.35	20	23.15	39	21.65	64	G/F	8-1734774-0	
										BLACK	7-1734774-9	
2.55				7.35	6	9.15	25	7.65	36	G/F	7-1734774-8	
			WHITE							7-1734774-7		
8.8			71.35	70	73.15	89	71.65	164	BLACK	7-1734774-6		
									WHITE	7-1734774-5		
5.5			38.35	37	40.15	56	38.65	98	G/F	7-1734774-4		
	BLACK	7-1734774-3										
3.9	21.35	20	23.15	39	21.65	64	WHITE	7-1734774-2				
							BLACK	7-1734774-1				
2.55	7.35	6	9.15	25	7.65	36	G/F	7-1734774-0				
							WHITE	6-1734774-9				
8.8	71.35	70	73.15	89	71.65	164	BLACK	6-1734774-8				
							WHITE	6-1734774-7				
5.5	38.35	37	40.15	56	38.65	98	BLACK	6-1734774-6				
							WHITE	6-1734774-5				
3.9	21.35	20	23.15	39	21.65	64	G/F	6-1734774-4				
							BLACK	6-1734774-3				
2.55	7.35	6	9.15	25	7.65	36	WHITE	6-1734774-2				
							BLACK	6-1734774-1				
8.8	71.35	70	73.15	89	71.65	164	G/F	6-1734774-0				
							WHITE	5-1734774-9				
5.5	38.35	37	40.15	56	38.65	98	BLACK	5-1734774-8				
							WHITE	5-1734774-7				
3.9	21.35	20	23.15	39	21.65	64	G/F	5-1734774-6				
							BLACK	5-1734774-5				
2.55	7.35	6	9.15	25	7.65	36	WHITE	5-1734774-4				
							BLACK	5-1734774-3				
8.8	71.35	70	73.15	89	71.65	164	G/F	5-1734774-2				
							WHITE	5-1734774-1				
5.5	38.35	37	40.15	56	38.65	98	BLACK	5-1734774-0				
							WHITE	4-1734774-9				
3.9	21.35	20	23.15	39	21.65	64	G/F	4-1734774-8				
							BLACK	4-1734774-7				
2.55	7.35	6	9.15	25	7.65	36	WHITE	4-1734774-6				
							BLACK	4-1734774-5				
8.8	71.35	70	73.15	89	71.65	164	G/F	4-1734774-4				
							WHITE	4-1734774-3				
5.5	38.35	37	40.15	56	38.65	98	BLACK	4-1734774-2				
							WHITE	4-1734774-1				
3.9	21.35	20	23.15	39	21.65	64	G/F	4-1734774-0				
							BLACK	3-1734774-9				
2.55	7.35	6	9.15	25	7.65	36	WHITE	3-1734774-8				
							BLACK	3-1734774-7				
8.8	71.35	70	73.15	89	71.65	164	G/F	3-1734774-6				
							WHITE	3-1734774-5				
5.5	38.35	37	40.15	56	38.65	98	BLACK	3-1734774-4				
							WHITE	3-1734774-3				
3.9	21.35	20	23.15	39	21.65	64	G/F	3-1734774-2				
							BLACK	3-1734774-1				
2.55	7.35	6	9.15	25	7.65	36	WHITE	3-1734774-0				
							BLACK	2-1734774-9				
8.8	71.35	70	73.15	89	71.65	164	G/F	2-1734774-8				
							WHITE	2-1734774-7				
5.5	38.35	37	40.15	56	38.65	98	BLACK	2-1734774-6				
							WHITE	2-1734774-5				
3.9	21.35	20	23.15	39	21.65	64	G/F	2-1734774-4				
							BLACK	2-1734774-3				
2.55	7.35	6	9.15	25	7.65	36	WHITE	2-1734774-2				
							BLACK	2-1734774-1				
8.8	71.35	70	73.15	89	71.65	164	G/F	2-1734774-0				
							WHITE	1-1734774-9				
5.5	38.35	37	40.15	56	38.65	98	BLACK	1-1734774-8				
							WHITE	1-1734774-7				
3.9	21.35	20	23.15	39	21.65	64	G/F	1-1734774-6				
							BLACK	1-1734774-5				
2.55	7.35	6	9.15	25	7.65	36	WHITE	1-1734774-4				
							BLACK	1-1734774-3				
8.8	71.35	70	73.15	89	71.65	164	G/F	1-1734774-2				
							WHITE	1-1734774-1				
5.5	38.35	37	40.15	56	38.65	98	BLACK	1-1734774-0				
							WHITE	0-1734774-9				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-8				
							BLACK	0-1734774-7				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-6				
							BLACK	0-1734774-5				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-4				
							WHITE	0-1734774-3				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-2				
							WHITE	0-1734774-1				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-0				
							BLACK	0-1734774-9				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-8				
							BLACK	0-1734774-7				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-6				
							WHITE	0-1734774-5				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-4				
							WHITE	0-1734774-3				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-2				
							BLACK	0-1734774-1				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-0				
							BLACK	0-1734774-9				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-8				
							WHITE	0-1734774-7				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-6				
							WHITE	0-1734774-5				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-4				
							BLACK	0-1734774-3				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-2				
							BLACK	0-1734774-1				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-0				
							WHITE	0-1734774-9				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-8				
							WHITE	0-1734774-7				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-6				
							BLACK	0-1734774-5				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-4				
							BLACK	0-1734774-3				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-2				
							WHITE	0-1734774-1				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-0				
							WHITE	0-1734774-9				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-8				
							BLACK	0-1734774-7				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-6				
							BLACK	0-1734774-5				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-4				
							WHITE	0-1734774-3				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-2				
							WHITE	0-1734774-1				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-0				
							BLACK	0-1734774-9				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-8				
							BLACK	0-1734774-7				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-6				
							WHITE	0-1734774-5				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-4				
							WHITE	0-1734774-3				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-2				
							BLACK	0-1734774-1				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-0				
							BLACK	0-1734774-9				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-8				
							WHITE	0-1734774-7				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-6				
							WHITE	0-1734774-5				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-4				
							BLACK	0-1734774-3				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-2				
							BLACK	0-1734774-1				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-0				
							WHITE	0-1734774-9				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-8				
							WHITE	0-1734774-7				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-6				
							BLACK	0-1734774-5				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-4				
							BLACK	0-1734774-3				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-2				
							WHITE	0-1734774-1				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-0				
							WHITE	0-1734774-9				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-8				
							BLACK	0-1734774-7				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-6				
							BLACK	0-1734774-5				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-4				
							WHITE	0-1734774-3				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-2				
							WHITE	0-1734774-1				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-0				
							BLACK	0-1734774-9				
2.55	7.35	6	9.15	25	7.65	36	WHITE	0-1734774-8				
							BLACK	0-1734774-7				
8.8	71.35	70	73.15	89	71.65	164	G/F	0-1734774-6				
							WHITE	0-1734774-5				
5.5	38.35	37	40.15	56	38.65	98	BLACK	0-1734774-4				
							WHITE	0-1734774-3				
3.9	21.35	20	23.15	39	21.65	64	G/F	0-1734774-2				
							BLACK					

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

AUG ,2006.



COPYRIGHT

-

BY TYCO ELECTRONICS CORPORATION.

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

DW

P

LTR

DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1

NOTES:

1. MATERIAL:

1.1 HOUSING: 1.PA46 WITH 40% G.F, UL94 V-0, COLOR: SEE TABLE.

2.PA9T WITH 30% GF, UL94 V-0, COLOR: SEE TABLE.

1.2 CONTACT: PHOSPHOR BRONZE

2. FINISH:

CONTACT: (SEE TABLE) GOLD PLATING ON CONTACT AREA.

2.54um [100u"] MIN. MATTE-TIN PALTING ON SOLDER TAIL AREA.

1.27um [50u"] MIN. NICKEL UNDERPLATING OVERALL.

3. CONNECTOR HAS MET THE REQUIREMENTS






PER PCI EXPRESS GEN 2 TECHNICAL DOCUMENT.

4. WEIGHT:


36 POS.: 2.55 GRAMS; 64 POS.: 3.90 GRAMS

98 POS.: 5.50 GRAMS; 164 POS.: 8.80 GRAMS

5. WAVE SOLDER CAPABLE TO 265°C PER TEST SPEC. 109-202 CONDITION B.

6. REFLOW SOLDER CAPABLE TO 260°C PER TEST SPEC. 109-201 CONDITION B.
(REFLOW SOLDERING PLEASE USE PN : 1734774-1 TO 4-1734774-8)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
MM

MATERIAL

SEE NOTE

TOLERANCES UNLESS
OTHERWISE SPECIFIED:0 PLC ± -
1 PLC ± 0.3
2 PLC ± 0.2
3 PLC ± 0.15
4 PLC ± -
ANGLES ± 3°

FINISH

SEE NOTE

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING



TE Connectivity

NAME

PCI EXPRESS CARD EDGE CONNECTOR
VERTICAL, DIP TYPE, 3GIO

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1734774


SCALE

SHEET

2 OF 5

REV

G



4

3

2

1


LOC	DIST	REVISIONS				
DW		P	LTR	DESCRIPTION	DATE	APVD
				SEE SHEET 1.		

D

D


ADD-IN CARD EDGE-FINGER DIMENSIONS

NOTES:
CHAMFER EDGE MUST BE FREE OF CUTTING BURRS



RECOMMENDED PCB LAYOUT


TOLERANCE: ±0.05
FOR DIM.L=3.1mm PCB THICKNESS: 2.4mm
FOR DIM.L=2.3mm PCB THICKNESS: 1.6mm





164	70.0	73.15	72.15	A1, B17, B31, B48, B81
98	37.0	40.15	39.15	A1, B17, B31, B48
64	20.0	23.15	22.15	A1, B17, B31
36	6.0	9.15	8.15	A1, B17
POS.	DIM. F	DIM. G	DIM. H	"K"

A


A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN —		 TE Connectivity	
DIMENSIONS: MM		CHK —			
		APVD —		NAME PCI EXPRESS CARD EDGE CONNECTOR VERTICAL, DIP TYPE, 3GIO	
		PRODUCT SPEC —			
		APPLICATION SPEC —			
		WEIGHT —			
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± — 4 PLC ± — ANGLES ± —		CUSTOMER DRAWING		SIZE CAGE CODE DRAWING NO RESTRICTED TO A300779C=1734774 —	
MATERIAL —		FINISH —		SCALE —	
				SHEET 4 OF 5 REV G	

LOC		DIST		REVISIONS				
P	LTR	DESCRIPTION			DATE	DWN	APVD	
		SEE SHEET 1.						



- NOTES :
- MATERIAL :
TRAY : PVC, COLOR: TRANSPARENT.
CARTON: CORRUGATED FIBER
BOX: CORRUGATED FIBER
 - DIMENSION :
TRAY: SEE DRAWING
CARTON: SEE DRAWING
BOX : SEE DRAWING
 - QUANTITY : SEE TABLE
 - WEIGHT : SEE TABLE



10.2 Kg	8.2 Kg	30	10	3	900	164
9.0 Kg	7.0 Kg	40	10	3	1200	98
8.5 Kg	6.5 Kg	60	10	3	1800	64
7.6 Kg	5.6 Kg	70	10	3	2100	36
GROSS WEIGHT	NET WEIGHT	PCS/ TRAY	TRAY/ CARTON	CARTON/ BOX	PCS/ BOX	POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM

MATERIAL

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME

PCI EXPRESS CARD EDGE CONNECTOR
VERTICAL, DIP TYPE, 3GIO

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C=1734774

SCALE

SHEET 5 OF 5

REV G



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.