

**FEATURES**

**Gain: 21 dB typical**  
**Noise figure: 3.6 dB typical**  
**Output power for 1 dB compression: 13 dBm typical**  
**Input third-order intercept at maximum gain: 1 dBm typical**  
**Output third-order intercept at maximum gain: 22 dBm typical**  
**Saturated output power: 17 dBm typical**  
**Input return loss: 15 dB typical**  
**Output return loss: 17 dB dB typical**  
**Die size: 2.844 mm × 0.999 mm × 0.05 mm**

**APPLICATIONS**

**E-band communication systems**  
**High capacity wireless backhauls**  
**Test and measurement**

**GENERAL DESCRIPTION**

The [HMC8325](#) is an integrated E-band gallium arsenide (GaAs), monolithic microwave integrated circuit (MMIC), low noise amplifier (LNA) chip that operates from 71 GHz to 86 GHz. The [HMC8325](#) provides 21 dB of gain, 13 dBm of output P1dB, 22 dBm of OIP3, and 17 dBm of  $P_{SAT}$  while requiring only 50 mA from a 3 V power supply. The [HMC8325](#) exhibits excellent linearity and is optimized for E-band communications and high capacity, wireless backhaul radio systems. All data is taken with the chip in a 50  $\Omega$  test fixture connected via a 3 mil wide × 0.5 mil thick × 7 mil long ribbon on each port.




Figure 1.

14692-001

Rev. 0

[Document Feedback](#)

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.  
 Tel: 781.329.4700 ©2017 Analog Devices, Inc. All rights reserved.  
[Technical Support](#) [www.analog.com](http://www.analog.com)

## TABLE OF CONTENTS

Features .....	1	Typical Performance Characteristics .....	6
Applications.....	1	Theory of Operation .....	12
General Description .....	1	Application Information.....	13
Functional Block Diagram .....	1	Mounting and Bonding Techniques for Millimeterwave GaAs MMICs.....	14
Revision History .....	2	Handling Precautions .....	14
Specifications.....	3	Mounting.....	14
Absolute Maximum Ratings.....	4	Wire Bonding.....	14
Thermal Resistance .....	4	Assembly Diagram .....	15
ESD Caution.....	4	Outline Dimensions .....	16
Pin Configuration and Function Descriptions.....	5	Ordering Guide .....	16
Interface Schematics.....	5		

## REVISION HISTORY

2/2017—Revision 0: Initial Version

## SPECIFICATIONS

$T_A = 25^\circ\text{C}$ ,  $V_{Dx}$  ( $V_{D1}$  and  $V_{D2}$  to  $V_{D3}$  and  $V_{D4}$ ) = 3 V, unless otherwise noted.

Table 1.

Parameter	Min	Typ	Max	Unit
<b>OPERATING CONDITIONS</b>				
Radio Frequency (RF) Range	71		86	GHz
<b>PERFORMANCE</b>				
Gain	19.5	21		dB
Gain Variation over Temperature		0.02		dB/°C
Output Power for 1 dB Compression (P1dB)		13		dBm
Saturated Output Power ( $P_{SAT}$ )		17		dBm
Input Third-Order Intercept (IIP3) at Maximum Gain <sup>1</sup>		1		dBm
Output Third-Order Intercept (OIP3) at Maximum Gain <sup>1</sup>		22		dBm
Noise Figure		3.6	4.5	dB
Return Loss				
Input		15		dB
Output		17		dB
<b>POWER SUPPLY</b>				
Total Drain Current ( $I_{Dx}$ ) <sup>2</sup>		50		mA

<sup>1</sup> Data taken at power output ( $P_{OUT}$ ) = 5 dBm/tone, 1 MHz spacing.

<sup>2</sup> Adjust  $V_{G1}$  and  $V_{G2}$  to  $V_{G3}$  and  $V_{G4}$  from -2 V to 0 V to achieve a total drain current ( $I_{Dx}$ ) = 50 mA.

## ABSOLUTE MAXIMUM RATINGS

Table 2.

Parameter	Rating
Drain Bias Voltage ( $V_{D1}$ to $V_{D4}$ )	4.5 V
Gate Bias Voltage ( $V_{G1}$ to $V_{G4}$ )	-3 V to 0 V
Maximum Junction Temperature (to Maintain 1 Million Hours Mean Time to Failure (MTTF))	175°C
Storage Temperature Range	-65°C to +150°C
Operating Temperature Range	-55°C to +85°C
ESD Sensitivity, Human Body Model (HBM)	Class 0 (150 V)

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

## THERMAL RESISTANCE

Thermal performance is directly linked to printed circuit board (PCB) design and operating environment. Careful attention to PCB thermal design is required.

Table 3. Thermal Resistance

Package Type	$\theta_{JC}$ <sup>1</sup>	Unit
C-22-1 <sup>2</sup>	225	°C/W

<sup>1</sup> Based on ABLEBOND® 84-1LMIT as die attach epoxy.

<sup>2</sup> Test Condition: Thermal impedance simulated values are based on JEDEC 252P thermal test board with four thermal vias. See JEDEC JESD51.

## ESD CAUTION



### ESD (electrostatic discharge) sensitive device.

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

# PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 2. Pin Configuration

Table 4. Pin Function Descriptions

Pad No.	Mnemonic	Description
1, 3, 4, 6, 8, 10, 12, 14, 16, 18, 20, 22	GND	Ground Connection.
2	RF <sub>IN</sub>	RF Input. AC couple RF <sub>IN</sub> and match it to 50 Ω.
5, 9, 13, 17	V <sub>G1</sub> to V <sub>G4</sub>	Gate Bias Voltage for the Low Noise Amplifier.
7, 11, 15, 19	V <sub>D1</sub> to V <sub>D4</sub>	Drain Bias Voltage for the Low Noise Amplifier.
21	RF <sub>OUT</sub>	RF Output. AC couple RF <sub>OUT</sub> and match it to 50 Ω.
Die Bottom	GND	Ground. Die bottom must be connected to the RF/dc ground.

## INTERFACE SCHEMATICS



Figure 3. GND Interface Schematic




Figure 4. RF<sub>IN</sub> Interface Schematic




Figure 5. V<sub>G1</sub> to V<sub>G4</sub> Interface Schematic




Figure 6. V<sub>D1</sub> to V<sub>D4</sub> Interface Schematic




Figure 7. RF<sub>OUT</sub> Interface Schematic

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 8. Gain and Return Loss vs. Frequency,  $V_{Dx} = 3 V$ ,  $I_{Dx} = 57 mA$




Figure 11. Noise Figure vs. Frequency over Temperature,  $V_{Dx} = 3 V$ ,  $I_{Dx} = 50 mA$




Figure 9. Output P1dB vs. Frequency over Temperature,  $V_{Dx} = 3 V$ ,  $I_{Dx} = 50 mA$




Figure 12. Saturated Output Power ( $P_{SAT}$ ) vs. Frequency over Temperature,  $V_{Dx} = 3 V$ ,  $I_{Dx} = 50 mA$




Figure 10. Input Third-Order Intercept (IP3) vs. Frequency over Temperatures,  $P_{OUT} = 5 dBm/Tone$ ,  $V_{Dx} = 3 V$ ,  $I_{Dx} = 50 mA$




Figure 13. Reverse Isolation vs. Frequency over Temperature,  $V_{Dx} = 3 V$ ,  $I_{Dx} = 57 mA$




Figure 14. Gain vs. Frequency over Temperature,  $V_{Dx} = 3\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$

14692-014




Figure 17. Gain vs. Frequency over Temperature,  $V_{Dx} = 4\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$

14692-017




Figure 15. Gain vs. Frequency over Drain Current,  $V_{Dx} = 3\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept

14692-015




Figure 18. Gain vs. Frequency over Drain Current,  $V_{Dx} = 4\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept

14692-018




Figure 16. Gain vs. Frequency over Drain Current,  $V_{D1}$  and  $V_{D2} = 2\text{ V}$ ,  $V_{D3}$  and  $V_{D4} = 4\text{ V}$

14692-016




Figure 19. Reverse Isolation vs. Frequency over Temperature,  $V_{Dx} = 4\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$

14692-019




Figure 20. Input Return Loss vs. Frequency over Temperature,  $V_{Dx} = 3\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$




Figure 23. Input Return Loss vs. Frequency over Temperature,  $V_{Dx} = 4\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$




Figure 21. Output Return Loss vs. Frequency over Temperature,  $V_{Dx} = 3\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$




Figure 24. Output Return Loss vs. Frequency over Temperature,  $V_{Dx} = 4\text{ V}$ ,  $I_{Dx} = 57\text{ mA}$




Figure 22. Noise Figure vs. Frequency over Temperature,  $V_{Dx} = 4\text{ V}$ ,  $I_{Dx} = 50\text{ mA}$




Figure 25. Noise Figure vs. Frequency over Drain Current,  $V_{Dx} = 3\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept






Figure 26. Noise Figure vs. Frequency over Drain Current,  $V_{Dx} = 4 V$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 29. Noise Figure vs. Frequency over Drain Current,  $V_{D1}$  and  $V_{D2} = 2 V$ ,  $V_{D3}$  and  $V_{D4} = 4 V$




Figure 27. Output P1dB vs. Frequency over Temperature,  $V_{Dx} = 4 V$ ,  $I_{Dx} = 50 mA$




Figure 30. Saturated Output Power ( $P_{SAT}$ ) vs. Frequency over Temperature,  $V_{Dx} = 4 V$ ,  $I_{Dx} = 50 mA$




Figure 28. Output P1dB vs. Frequency over Drain Current,  $V_{Dx} = 3 V$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 31. Saturated Output Power ( $P_{SAT}$ ) vs. Frequency over Drain Current,  $V_{Dx} = 3 V$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 32. Output P1dB vs. Frequency over Drain Current,  $V_{Dx} = 4 V$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 35. Saturated Output Power ( $P_{SAT}$ ) vs. Frequency over Drain Current,  $V_{Dx} = 4 V$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 33. Output P1dB vs. Frequency over Drain Current,  $V_{D1}$  and  $V_{D2} = 2 V$ ,  $V_{D3}$  and  $V_{D4} = 4 V$




Figure 36. Saturated Output Power ( $P_{SAT}$ ) vs. Frequency over Drain Current,  $V_{D1}$  and  $V_{D2} = 2 V$ ,  $V_{D3}$  and  $V_{D4} = 4 V$




Figure 34. Input Third-Order Intercept ( $IP3$ ) vs. Frequency over Temperature,  $V_{Dx} = 4 V$ ,  $I_{Dx} = 50 mA$




Figure 37. Output Third-Order Intercept ( $IP3$ ) vs. Frequency over Temperature,  $V_{Dx} = 4 V$ ,  $I_{Dx} = 50 mA$




Figure 38. Input Third-Order Intercept (IP3) vs. Frequency over Drain Current,  $V_{Dx} = 3\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 41. Output Third-Order Intercept (IP3) vs. Frequency over Drain Current,  $V_{Dx} = 3\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 39. Input Third-Order Intercept (IP3) vs. Frequency over Drain Current,  $V_{Dx} = 4\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 42. Output Third-Order Intercept (IP3) vs. Frequency over Drain Current,  $V_{Dx} = 4\text{ V}$ ,  $V_{G1}$  and  $V_{G2}$  Fixed at 20 mA,  $V_{G3}$  and  $V_{G4}$  Swept




Figure 40. Input Third-Order Intercept (IP3) vs. Frequency over Drain Current,  $V_{D1}$  and  $V_{D2} = 2\text{ V}$ ,  $V_{D3}$  and  $V_{D4} = 4\text{ V}$




Figure 43. Output Third-Order Intercept (IP3) vs. Frequency over Drain Current,  $V_{D1}$  and  $V_{D2} = 2\text{ V}$ ,  $V_{D3}$  and  $V_{D4} = 4\text{ V}$

## THEORY OF OPERATION

The circuit architecture of the HMC8325 low noise amplifier is shown in Figure 44. The HMC8325 uses four cascaded gain stages to form an amplifier with a combined gain of 21 dB (typical), a noise figure of 3.6 dB (typical), and 1 dBm (typical) input IP3 across the 71 GHz to 86 GHz frequency range. Stage 1 and Stage 2 can be biased separately from Stage 3 and Stage 4. Operating at  $V_{D1} = V_{D2} = 2\text{ V}$  and  $V_{D3} = V_{D4} = 4\text{ V}$  improves gain and noise figure compared to  $V_{D1} = V_{D2} = V_{D3} = V_{D4} = 4\text{ V}$ .

The input IP3 is slightly lower for the  $V_{D1} = V_{D2} = 2\text{ V}$  and  $V_{D3} = V_{D4} = 4\text{ V}$  case. A compromise bias voltage between the gain noise figure vs. the input IP3 is  $V_{D1} = V_{D2} = V_{D3} = V_{D4} = 3\text{ V}$ . Gain control can be achieved by down biasing Stage 3 and Stage 4. By lowering the drain current of  $I_{D3}$  and  $I_{D4}$ , a 12 dB reduction in gain can be achieved with a small degradation in the noise figure. Refer to Figure 45 for further details on biasing arrangements for the different stages.




Figure 44. Circuit Architecture

## APPLICATION INFORMATION

The typical application circuit shown in Figure 45 shows the HMC8325 chip with all of its required bypassing components. Bypass all supply connections with adequate bypassing capacitors is recommended. Use single-layer chip capacitors with a very high, self-resonant frequency close to the HMC8325 chip. Typically, 120 pF chip capacitors are recommended, followed by 0.01  $\mu$ F and 4.7  $\mu$ F surface-mount capacitors. Supply lines can be combined into single drain and single gate bias sources to minimize external component count and simplify power supply routing. The recommended single power supply source is 3 V ( $V_{Dx} = V_{D1}/V_{D2}$  and  $V_{D3}/V_{D4} = 3$  V). Alternatively, 2 V and 4 V power supply sources can be used for  $V_{D1}/V_{D2}$  and  $V_{D3}/V_{D4}$ , respectively.

The HMC8325 uses several amplifier stages. All stages use depletion mode, pseudomorphic high electron mobility transfer (pHEMT) transistors. Therefore, follow the following recommended bias sequence during power-up of the devices to ensure that damage does not occur.

1. Apply  $-2$  V bias to  $V_{Gx}$  ( $V_{G1}$  and  $V_{G2}$  to  $V_{G3}$  and  $V_{G4}$ ).
2. Apply 3 V bias to  $V_{Dx}$  ( $V_{D1}$  and  $V_{D2}$  to  $V_{D3}$  and  $V_{D4}$ ).
3. Adjust  $V_{G1}/V_{G2}$  to  $V_{G3}/V_{G4}$  between  $-2$  V and 0 V to achieve a total drain current ( $I_{Dx}$ ) of 50 mA.
4. Apply the RF input signal.

The recommended bias sequence during power-down of the device is as follows:

1. Turn off the RF input signal.
2. Turn off the  $V_{Dx}$  ( $V_{D1}$  and  $V_{D2}$  to  $V_{D3}$  and  $V_{D4}$ ) voltage supply or set it to 0 V.
3. Turn off the  $V_{Gx}$  ( $V_{G1}$  and  $V_{G2}$  to  $V_{G3}$  and  $V_{G4}$ ) voltage supply.




Figure 45. Typical Application Circuit (Two Power Supply Source Configuration)

14682-045

## MOUNTING AND BONDING TECHNIQUES FOR MILLIMETERWAVE GAAS MMICs

Attach the die directly to the ground plane eutectically or with conductive epoxy.

To bring RF to and from the chip, use 50  $\Omega$  microstrip transmission lines on 0.127 mm (0.005") thick, alumina thin film substrates (see Figure 46).




Figure 46. Routing RF Signals

To minimize bond wire length, place microstrip substrates as close to the die as possible. Typical die to substrate spacing is 0.076 mm to 0.152 mm (0.003" to 0.006").

## HANDLING PRECAUTIONS

To avoid permanent damage, adhere to the following storage, cleanliness, static sensitivity, transient, and general handling precautions.

### Storage

All bare die ship in either waffle or gel-based ESD protective containers, sealed in an ESD protective bag. After opening the sealed ESD protective bag, all die must be stored in a dry nitrogen environment.

### Cleanliness

Handle the chips in a clean environment. Never use liquid cleaning systems to clean the chip.

### Static Sensitivity

Follow ESD precautions to protect against ESD strikes.

## Transients

Suppress instrument and bias supply transients while bias is applied. To minimize inductive pickup, use shielded signal and bias cables.

## General Handling

Handle the chip on the edges only using a vacuum collet or with a sharp pair of bent tweezers. Because the surface of the chip has fragile air bridges, never touch the surface of the chip with a vacuum collet, tweezers, or fingers.

## MOUNTING

The chip is back metallized and can be die mounted with gold/tin (AuSn) eutectic preforms or with electrically conductive epoxy. The mounting surface must be clean and flat.

### Eutectic Die Attach

It is best to use an 80% gold/20% tin preform with a work surface temperature of 255°C and a tool temperature of 265°C. When hot 90% nitrogen/10% hydrogen gas is applied, maintain a tool tip temperature of 290°C. Do not expose the chip to a temperature greater than 320°C for more than 20 sec. No more than 3 sec of scrubbing is required for attachment.

### Epoxy Die Attach

The ABLEBOND 84-1LMIT is recommended for die attachment. Apply a minimum amount of epoxy to the mounting surface so that a thin epoxy fillet is observed around the perimeter of the chip after placing it into position. Cure the epoxy per the schedule provided by the manufacturer.

## WIRE BONDING

RF bonds made with 3 mil (0.0762 mm)  $\times$  0.5 mil (0.0127 mm) gold ribbon are recommended. Thermosonically bond these bonds with a force of 40 grams to 60 grams. DC bonds of 1 mil (0.0254 mm) diameter, thermosonically bonded, are recommended. Create ball bonds with a force of 40 grams to 50 grams and wedge bonds with a force of 18 grams to 22 grams. Create all bonds with a nominal stage temperature of 150°C. Apply a minimum amount of ultrasonic energy to achieve reliable bonds. Keep all bonds as short as possible, less than 12 mil (0.31 mm).

ASSEMBLY DIAGRAM





Figure 47. Assembly Diagram

14682-047

OUTLINE DIMENSIONS



05-03-2016-A

Figure 48. 22-Pad Bare Die [CHIP]  
(C-22-1)  
Dimensions shown in millimeters

ORDERING GUIDE

Model <sup>1</sup>	Temperature Range	Package Description	Package Option <sup>2</sup>
HMC8325	-55°C to +85°C	22-Pad Bare Die [CHIP]	C-22-1
HMC8325-SX	-55°C to +85°C	22-Pad Bare Die [CHIP]	C-22-1

<sup>1</sup> The HMC8325-SX is two pairs of the die in a gel pack for the sample orders.  
<sup>2</sup> This is a waffle pack option; contact Analog Devices, Inc., for additional packaging options.





Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.