






DETAIL A
KEY SLOTS #2 & #4 SHOWN
SCALE 2:1




spec ref	---			dr	Stu Stoner	2008/02/05	projection	MM	size A3 / scale 1:1
tolerance std --- ---	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Tommy Lin	2012/12/19			
				chr	-	-			ecn no ELX-N-13705-1
				appr	Roger Cheng	2012/12/24	product family	MiniSAS/SATA	rel level Released
surface -	linear	0.X	±0.3	FCI	title	FINAL CABLE ASSEMBLY-ALTERNATE CABLE		dwg no 10084749	rev G
		0.XX	±0.10			Mini SAS 2.0/SATA (CRKT)			
		0.XXX	±0.050						
---	angular	0°	±2°	www.fci.com	cat. no.	-	Product - Customer Drw		sheet 1 of 6


Copyright FCI.



KEY SLOT 2,4 & 6
◯ ◇ UNVERSIAL PORT



KEY SLOT 2 & 4
◇ OUT PORT



KEY SLOT 4 & 6
◯ IN PORT

MINI SAS 2.0

PRODUCT NUMBER SEE NOTE 4	DESCRIPTION	GAUGE	"DIM L" LENGTH	END P1 KEY SLOT	END P2 KEY SLOT	IDENTIFIER
10084749-M060002LF	X4 SAS CABLE ASSEMBLY	24 AWG	6M	4, 6	4, 6	SUBTRACTIVE ROUTING (IN PORT), SAS
10084749-N040002LF	X4 SAS CABLE ASSEMBLY	26 AWG	4M	4, 6	4, 6	
10084749-N050002LF	X4 SAS CABLE ASSEMBLY	26 AWG	5M	4, 6	4, 6	
10084749-P010002LF	X4 SAS CABLE ASSEMBLY	28 AWG	1M	4, 6	4, 6	
10084749-P020002LF	X4 SAS CABLE ASSEMBLY	28 AWG	2M	4, 6	4, 6	
10084749-P030002LF	X4 SAS CABLE ASSEMBLY	28 AWG	3M	4, 6	4, 6	
10084749-M060003LF	X4 SAS CABLE ASSEMBLY	24 AWG	6M	2, 4, 6	2, 4, 6	UNIVERSAL KEY, SAS
G 10084749-N030003LF	X4 SAS CABLE ASSEMBLY	26 AWG	3M	2, 4, 6	2, 4, 6	
10084749-N040003LF	X4 SAS CABLE ASSEMBLY	26 AWG	4M	2, 4, 6	2, 4, 6	
10084749-N050003LF	X4 SAS CABLE ASSEMBLY	26 AWG	5M	2, 4, 6	2, 4, 6	
10084749-P002503LF	X4 SAS CABLE ASSEMBLY	28 AWG	0.25M	2, 4, 6	2, 4, 6	
10084749-P010003LF	X4 SAS CABLE ASSEMBLY	28 AWG	1M	2, 4, 6	2, 4, 6	
10084749-P015003LF	X4 SAS CABLE ASSEMBLY	28 AWG	1.5M	2, 4, 6	2, 4, 6	
10084749-P020003LF	X4 SAS CABLE ASSEMBLY	28 AWG	2M	2, 4, 6	2, 4, 6	
10084749-P025003LF	X4 SAS CABLE ASSEMBLY	28 AWG	2.5M	2, 4, 6	2, 4, 6	
10084749-P030003LF	X4 SAS CABLE ASSEMBLY	28 AWG	3M	2, 4, 6	2, 4, 6	
10084749-M060006LF	X4 SAS CABLE ASSEMBLY	24 AWG	6M	2, 4	4, 6	SAS, TABLE ROUTING (OUT PORT), TO SUBTRACTIVE ROUTING (IN PORT)
10084749-N010006LF	X4 SAS CABLE ASSEMBLY	26 AWG	1M	2, 4	4, 6	
10084749-N030006LF	X4 SAS CABLE ASSEMBLY	26 AWG	3M	2, 4	4, 6	
10084749-N040006LF	X4 SAS CABLE ASSEMBLY	26 AWG	4M	2, 4	4, 6	
10084749-N050006LF	X4 SAS CABLE ASSEMBLY	26 AWG	5M	2, 4	4, 6	
10084749-P010006LF	X4 SAS CABLE ASSEMBLY	28 AWG	1M	2, 4	4, 6	
10084749-P020006LF	X4 SAS CABLE ASSEMBLY	28 AWG	2M	2, 4	4, 6	
10084749-P030006LF	X4 SAS CABLE ASSEMBLY	28 AWG	3M	2, 4	4, 6	

MINI SAS 2.0 KEYING OPTIONS

Copyright FCI.

spec ref	---		dr	Stu Stoner	2008/02/05	projection	MM
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Tommy Lin	2012/12/19	size A3	scale 1:1
---			chr	-	-	ecn no	ELX-N-13705-1
---			appr	Roger Cheng	2012/12/24	product family	MiniSAS/SATA
surface -	linear	0.X ±0.3				rel level	Released
		0.XX ±0.10					
		0.XXX ±0.050					
---	angular	0° ±2°°					

FCI www.fci.com

title: FINAL CABLE ASSEMBLY-ALTERNATE CABLE
Mini SAS 2.0/SATA (CRKT)


dwg no: 10084749 rev: G

cat. no. - Product - Customer Drw sheet 2 of 6

Pro/E File - REV C - 2009-06-09


PDS: Rev :G STATUS:Released Printed: Dec 24, 2012

SATA						
PRODUCT NUMBER SEE NOTE 4	DESCRIPTION	GAUGE	"DIM L" LENGTH	END P1 KEY SLOT	END P2 KEY SLOT	IDENTIFIER
10084749-M060004LF	X4 SATA CABLE ASSEMBLY	24 AWG	6M	1,4	1,4	X CABLE, SATA
10084749-N020004LF	X4 SATA CABLE ASSEMBLY	26 AWG	2M	1,4	1,4	
10084749-N040004LF	X4 SATA CABLE ASSEMBLY	26 AWG	4M	1,4	1,4	
10084749-N050004LF	X4 SATA CABLE ASSEMBLY	26 AWG	5M	1,4	1,4	
10084749-P010004LF	X4 SATA CABLE ASSEMBLY	28 AWG	1M	1,4	1,4	
10084749-P030004LF	X4 SATA CABLE ASSEMBLY	28 AWG	3M	1,4	1,4	
10084749-M060005LF	X4 SATA CABLE ASSEMBLY	24 AWG	6M	7	7	M CABLE, SATA
10084749-N020005LF	X4 SATA CABLE ASSEMBLY	26 AWG	2M	7	7	
10084749-N040005LF	X4 SATA CABLE ASSEMBLY	26 AWG	4M	7	7	
10084749-N050005LF	X4 SATA CABLE ASSEMBLY	26 AWG	5M	7	7	
10084749-P010005LF	X4 SATA CABLE ASSEMBLY	28 AWG	1M	7	7	
10084749-P030005LF	X4 SATA CABLE ASSEMBLY	28 AWG	3M	7	7	




BEND RADIUS
(24 AWG SHOWN)

TABLE 1		
CABLE	DIM "A"	DIM "B"
24 AWG	(R46.9)	(Ø9.5mm)
26 AWG	(R41.7)	(Ø8.3mm)
28 AWG	(R37.7)	(Ø7.6mm)



KEY SLOT 1 & 4
X CABLE, SATA



KEY SLOT 7
M CABLE, SATA


SATA KEYING OPTIONS

Copyright FCI.

spec ref	---			dr	Stu Stoner	2008/02/05	projection	MM
tolerance std --- ---	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Tommy Lin	2012/12/19		
				chr	-	-		
				appr	Roger Cheng	2012/12/24	product family	MiniSAS/SATA
surface - ---	linear	0.X	±0.3	FCI	title	FINAL CABLE ASSEMBLY-ALTERNATE CABLE	dwg no	10084749
		0.XX	±0.10			Mini SAS 2.0/SATA (CRKT)		
		0.XXX	±0.050					
	angular	0°	±2°°	www.fci.com	cat. no.	-	Product - Customer Drw	

size	scale	rev
A3	1:1	G

ecn no ELX-N-13705-1
rel level Released
sheet 3 of 6



WIRING LIST SEE NOTE 7

P1						P2
	GND	A1	—	B1	GND	
	Rx 0+	A2	←	B2	Tx 0+	
	Rx 0-	A3	←	B3	Tx 0-	
	GND	A4	—	B4	GND	
	Rx 1+	A5	←	B5	Tx 1+	
	Rx 1-	A6	←	B6	Tx 1-	
	GND	A7	—	B7	GND	
	Rx 2+	A8	←	B8	Tx 2+	
	Rx 2-	A9	←	B9	Tx 2-	
	GND	A10	—	B10	GND	
	Rx 3+	A11	←	B11	Tx 3+	
	Rx 3-	A12	←	B12	Tx 3-	
	GND	A13	—	B13	GND	
	GND	B1	—	A1	GND	
	Tx 0+	B2	→	A2	Rx 0+	
	Tx 0-	B3	→	A3	Rx 0-	
	GND	B4	—	A4	GND	
	Tx 1+	B5	→	A5	Rx 1+	
	Tx 1-	B6	→	A6	Rx 1-	
	GND	B7	—	A7	GND	
	Tx 2+	B8	→	A8	Rx 2+	
	Tx 2-	B9	→	A9	Rx 2-	
	GND	B10	—	A10	GND	
	Tx 3+	B11	→	A11	Rx 3+	
	Tx 3-	B12	→	A12	Rx 3-	
	GND	B13	—	A13	GND	

Copyright FCI.

spec ref	---		dr	Stu Stoner	2008/02/05	projection	MM
tolerance std --- ---	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Tommy Lin	2012/12/19		
			chr	-	-		
			appr	Roger Cheng	2012/12/24	product family	MiniSAS/SATA
surface	linear	0.X ±0.3	FCI	title	FINAL CABLE ASSEMBLY-ALTERNATE CABLE	dwg no	10084749
		0.XX ±0.10			Mini SAS 2.0/SATA (CRKT)		
		0.XXX ±0.050					
---	angular	0° ±2°°	www.fci.com	cat. no.	-	Product - Customer Drw	sheet 4 of 6

size	scale	rev
A3	1:1	G

ecn no ELX-N-13705-1

rel level **Released**

Pro/E File - REV C - 2009-06-09

PDS: Rev :G STATUS:Released Printed: Dec 24, 2012

NOTES:

(1) - MATERIAL:
BACK SHELLS: ZINC DIECAST
PULL TAB: MOLDED THERMOPLASTIC
LATCH: STAINLESS STEEL
JET MELT: POLYAMIDE POLYMER

2 - ELECTRICAL PERFORMANCE PER CURRENT REVISION
OF SERIAL ATA, T10/1760-D (SAS-2 REQUIREMENTS).

(3) - THIS PRODUCT MEETS THE RESTRICTION OF HAZARDOUS SUBSTANCES IN
ELECTRICAL AND ELECTRONIC EQUIPMENT (RoHS) DIRECTIVE (2002/95/EC)

4 - PART NUMBER DESCRIPTION

10084749 - X XX XX XX LF

LEAD FREE (SEE NOTE 3 AND 10)

KEY SLOT
01: KEY SLOT 2,4
02: KEY SLOT 4,6
03: KEY SLOT 2,4,6
04: KEY SLOT 1,4
05: KEY SLOT 7
06: P1= KEY SLOT 2,4 P2= KEY SLOT 4,6

LENGTH
XX= METERS, XX=CENTIMETERS
0100 = 01 METERS, 00 CENTIMETERS ("DIM L")

GAUGE
M: 24 AWG
N: 26 AWG
P: 28 AWG

(5) - UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE IS TO BE:
< 1 METER = ±25.0mm
> 1 METER TO 6 METERS = ± 2% OF "DIM L"

Copyright FCI.

spec ref	---			dr	Stu Stoner	2008/02/05	projection	MM	size A3 / scale 1:1
tolerance std --- ---	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Tommy Lin	2012/12/19			
				chr	-	-			ecn no ELX-N-13705-1
				appr	Roger Cheng	2012/12/24	product family	MiniSAS/SATA	rel level Released
surface - ✓ ---	linear	0.X	±0.3	FCI	title	FINAL CABLE ASSEMBLY-ALTERNATE CABLE		dwg no 10084749	rev G
		0.XX	±0.10			Mini SAS 2.0/SATA (CRKT)			
		0.XXX	±0.050						
	angular	0°	±2°°	www.fci.com	cat. no.	-	Product - Customer Drw		sheet 5 of 6

NOTES CONTINUED:

(6)- UNLESS OTHERWISE SPECIFIED LABEL POSITION IS TO BE 50mm FROM REAR OF CONNECTOR.
LABEL DETAILS:
MANUFACTURER CODE OR NAME
CUSTOMER P/N OR FCI P/N
REVISION
DATE CODE (YY/MM/DD FORMAT) - SERIAL NUMBER
COUNTRY ORIGIN

FONT SHALL BE CLEARLY VISIBLE AND BLACK IN COLOR.

(7)- ALL CABLE ASSEMBLIES SHALL BE 100% TESTED FOR CONTINUITY AS DEFINED IN WIRING LIST.

(8)- UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BY APPLYING 300V DC FOR A MINIUM OF 10ms, UNLESS ACTIVE COMPONENTS ARE USED IN THIS ASSEMBLY.

9 - OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-548.

10 - PACKAGING OF LEAD FREE PRODUCTS MEETS LABELING AND PACKAGING PER SPECIFICATION GS-14-920. PACKAGE CABLE ASSEMBLIES PER GS-14-1272.

11. THIS DIMENSION IS A FINISHED PRODUCT LENGTH.

12. A "△" SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION. THE CURRENT REVISION WILL BE SHOWN IN THE SYMBOL.

Copyright FCI.

spec ref	---			dr	Stu Stoner	2008/02/05	projection	MM	size A3 / scale 1:1
tolerance std --- ---	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Tommy Lin	2012/12/19			
				chr	-	-			ecn no ELX-N-13705-1
				appr	Roger Cheng	2012/12/24	product family	MiniSAS/SATA	rel level Released
surface -	linear	0.X	±0.3	FCI	title	FINAL CABLE ASSEMBLY-ALTERNATE CABLE		dwg no 10084749	rev G
		0.XX	±0.10			Mini SAS 2.0/SATA (CRKT)			
		0.XXX	±0.050	www.fci.com	cat. no.	-	Product - Customer Drw		sheet 6 of 6
---	angular	0°	±2°°						


Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.