



Product: [73603WS](#)

MachFlex™, 3 C #16 Str BC, PVC Ins, OA TC Brd, PVC Jkt, PVC Jkt, AWM 2587 CLASS K

 Request Sample

Product Description

MachFlex™ for Moderate Flex, 3 Conductor 16AWG (26x30) Bare Copper, PVC Insulation, Overall Tinned Copper Braid(85%) Shield, PVC Inner Jacket, PVC Outer Jacket, AWM 2587 CLASS K

Technical Specifications

Physical Characteristics (Overall)

Conductor

| Element   | AWG | Stranding | Material         | No. of Conductors |
|-----------|-----|-----------|------------------|-------------------|
| Conductor | 16  | 26x30     | BC - Bare Copper | 2                 |
| Ground    | 16  | 26x30     | BC - Bare Copper | 1                 |

Conductor Count: 3

Insulation

| Element   | Material                 | Nominal Diameter | Nominal Wall Thickness |
|-----------|--------------------------|------------------|------------------------|
| Conductor | PVC - Polyvinyl Chloride | 0.104 in         | 0.022 in               |
| Ground    | PVC - Polyvinyl Chloride |                  |                        |

Color Chart

| Color              |
|--------------------|
| Black and Numbered |

Inner Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | .290 in          | .030 in                |

Outer Shield Material

| Type  | Material           | Coverage [%] |
|-------|--------------------|--------------|
| Braid | Tinned Copper (TC) | 85%          |

Outer Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.388 in         | 0.035 in               |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 4.1 Ohm/1000ft        | 2.28 Ohm/1000ft          |

Capacitance

| Nom. Capacitance Conductor to Conductor |
|-----------------------------------------|
| 51 pF/ft                                |

Inductance

| Nominal Inductance |
|--------------------|
|--------------------|

|            |
|------------|
| .180 μH/ft |
|------------|

Voltage

|                   |
|-------------------|
| UL Voltage Rating |
| 600 V             |

Temperature Range

|                       |                                                |
|-----------------------|------------------------------------------------|
| UL Temp Rating:       | 90°C                                           |
| Operating Temp Range: | -40°C To 90°C (Static), -5°C To 90°C (Flexing) |

Mechanical Characteristics

|                                       |                  |
|---------------------------------------|------------------|
| Oil Resistance:                       | Yes              |
| Flex Cycle Rating:                    | 1 Million Cycles |
| Bulk Cable Weight:                    | 194 lbs/1000ft   |
| Max. Pull Tension:                    | 70 lbs           |
| Min Bend Radius (Continuous Flexing): | 3.1 in           |
| Min Bend Radius/Minor Axis:           | 3.1 in           |

Standards

|                          |                                |
|--------------------------|--------------------------------|
| UL AWM Style Compliance: | AWM 2587                       |
| CSA AWM Compliance:      | AWM I/II A/B                   |
| Other Compliance:        | VDE 0472, Section 803 Oil Test |

Applicable Environmental and Other Programs

|                                    |                               |
|------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):     | Yes                           |
| EU Directive 2003/11/EC (BFR):     | Yes                           |
| EU Directive 2011/65/EU (ROHS II): | Yes                           |
| EU Directive 2012/19/EU (WEEE):    | Yes                           |
| EU Directive 2015/863/EU:          | Yes                           |
| EU Directive Compliance:           | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                        | Yes                           |

Flammability, LS0H, Toxicity Testing

|                    |           |
|--------------------|-----------|
| CSA Flammability:  | FT1       |
| UL voltage rating: | 600 V RMS |

Part Number

Variants

| Item #          | Color | Putup Type | UPC          |
|-----------------|-------|------------|--------------|
| 73603WS 008100  | Gray  | Reel       | 612825409731 |
| 73603WS 0081000 | Gray  | Reel       | 612825409748 |
| 73603WS 008500  | Gray  | Reel       | 612825409755 |

History

|                      |                                                 |
|----------------------|-------------------------------------------------|
| Update and Revision: | Revision Number: 0.56 Revision Date: 04-28-2020 |
|----------------------|-------------------------------------------------|

© 2020 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.