


# Rack and Panel Connectors Subminiature Rectangular



SMP20



SMS20

## ELECTRICAL SPECIFICATIONS

**Current Rating:** 7.5 A

**Breakdown Voltage:**

At sea level: 2000 V<sub>RMS</sub>

At 70 000 feet [21 336 meters]: 500 V<sub>RMS</sub>

## PHYSICAL SPECIFICATIONS

**Number of Contacts:** 5, 7, 11, 14, 20, 26, 34, 42, 50, 75

**Contact Spacing:** 0.120" [3.05 mm]

**Contact Gauge:** #20 AWG

**Minimum Creepage Path Between Contacts:**

0.080" [2.03 mm]

**Minimum Air Space Between Contacts:** 0.050" [1.27 mm]

## FEATURES

- Lightweight
- Polarized by guides or screwlocks
- Screwlocks lock connectors together to withstand vibration and accidental disconnect
- Overall height kept to a minimum
- Floating contacts aid in alignment and in withstanding vibration
- Contacts, precision machined and individually gauged, provide high reliability
- Insertion and withdrawal forces kept low without increasing contact resistance
- Contact plating provides protection against corrosion, assures low contact resistance and ease of soldering

## APPLICATIONS

For use wherever space is at a premium and a high quality connector is required in avionics, automation, communications, controls, instrumentation, missiles, computers and guidance systems.

## MATERIAL SPECIFICATIONS

**Contact Pin:** Brass, gold plated

**Contact Socket:** Phosphor bronze, gold plated









(Beryllium copper available on request)


**Guides:** Stainless steel, passivated

**Screwlocks:** Stainless steel, passivated


**Standard Body:** Glass-filled diallyl phthalate per MIL-M-14, Model GDI-30F, green

## DIMENSIONS in inches [millimeters]

|                                                                                                                                      |                                                                                                                                                 |                                                                                                                                          |                                                                                                                                                   |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>SMS</b><br/>With Fixed Standard Guides</p>  | <p><b>SMDS - DETAIL B</b><br/>Dip Solder Contact Option</p>  | <p><b>SMP</b><br/>With Fixed Standard Guides</p>     | <p><b>SMDP - DETAIL C</b><br/>Dip Solder Contact Option</p>  |
| <p><b>SMS</b><br/>With Fixed (SL) Screwlocks</p>  | <p><b>SMP</b><br/>With Turnable (SK) Screwlocks</p>          | <p><b>SMS</b><br/>With Turnable (SK) Screwlocks</p>  | <p><b>SMP</b><br/>With Fixed (SL) Screwlocks</p>             |


**DIMENSIONS** in inches [millimeters]**TERMINAL VARIATIONS** in inches [millimeters]**DIP SOLDER PC BOARD MOUNTING PATTERNS**

Male (SMP) Connector is shown - Female is opposite. Contact row and Mating Hole  $\varnothing$  to  $\varnothing$  Dimensions also applies to Solder Cup Connectors.




**DIMENSIONS** in inches [millimeters]


**NOTE:** The views below show the wiring side of a pin model connector (female is opposite). Socket hardware is assembled at "A" contact end of a pin model connector.




5 CONTACTS




7 CONTACTS




11 CONTACTS




14 CONTACTS




20 CONTACTS




26 CONTACTS




34 CONTACTS





42 CONTACTS






50 CONTACTS



75 CONTACTS


TYPICAL END VIEW  
34 THRU 50 CONTACTS

TYPICAL END VIEW  
75 CONTACTS

**PANEL CUTOUT** in inches [millimeters]

|                                                                                   |                                                                                   |                                                                                   | NUMBER OF CONTACTS | A                | B                | C                | D                | FIGURE |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------|------------------|------------------|------------------|------------------|--------|
|  |  |  | 5                  | 0.230<br>[5.84]  | 0.531<br>[13.49] | 0.410<br>[10.41] | -                | I      |
|                                                                                   |                                                                                   |                                                                                   | 7                  | 0.230<br>[5.84]  | 0.625<br>[15.88] | 0.500<br>[12.70] | -                |        |
|                                                                                   |                                                                                   |                                                                                   | 11                 | 0.340<br>[8.64]  | 0.625<br>[15.88] | 0.530<br>[13.46] | -                |        |
|                                                                                   |                                                                                   |                                                                                   | 14                 | 0.340<br>[8.64]  | 0.750<br>[19.05] | 0.620<br>[15.75] | -                |        |
|                                                                                   |                                                                                   |                                                                                   | 20                 | 0.340<br>[8.64]  | 1.0<br>[25.40]   | 0.910<br>[23.11] | -                |        |
|                                                                                   |                                                                                   |                                                                                   | 26                 | 0.340<br>[8.64]  | 1.25<br>[31.75]  | 1.16<br>[29.46]  | -                |        |
|                                                                                   |                                                                                   |                                                                                   | 34                 | 0.500<br>[12.70] | 1.312<br>[33.32] | 1.16<br>[29.46]  | 0.343<br>[8.71]  | II     |
|                                                                                   |                                                                                   |                                                                                   | 42                 | 0.500<br>[12.70] | 1.562<br>[39.68] | 1.41<br>[35.81]  | 0.343<br>[8.71]  |        |
|                                                                                   |                                                                                   |                                                                                   | 50                 | 0.500<br>[12.70] | 1.812<br>[46.02] | 1.66<br>[42.16]  | 0.343<br>[8.71]  |        |
|                                                                                   |                                                                                   |                                                                                   | 75                 | 0.720<br>[18.29] | 1.812<br>[46.02] | 1.66<br>[42.16]  | 0.562<br>[14.28] | III    |

**ORDERING INFORMATION**

| C                                                                            | SM           | B                                                                                           | S                     | 20           | G                                                                                                                                                                    | 26                                      | R                                                                    | 027 <sup>(1)</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------------------------------|--------------|---------------------------------------------------------------------------------------------|-----------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CONTACTS                                                                     | MODEL        | CONTACT TYPE                                                                                | CONTACT STYLE         | CONTACT SIZE | PLATING                                                                                                                                                              | NUMBER OF CONTACTS                      | (OPTIONAL)                                                           | HARDWARE OPTIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|                                                                              | Subminiature |                                                                                             | P = Pin<br>S = Socket | #20 AWG      |                                                                                                                                                                      | 5, 7, 11, 14, 20,<br>26, 34, 42, 50, 75 |                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| (OPTIONAL)<br>Closed entry socket contacts only. Omit for standard contacts. |              |                                                                                             |                       |              | Optional plating available:<br>G = Gold (0.00003 thick) over nickel<br>G5 = Gold (0.00005 thick) over nickel<br>Omit designator for gold (0.00001 thick) over nickel |                                         | (OPTIONAL)<br>R = Reversed guides or screwlocks<br>Omit for standard |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                                                                              |              | (OPTIONAL)<br>B = Beryllium copper, socket contacts (Solder cup)<br>D = Dip solder contacts |                       |              |                                                                                                                                                                      |                                         |                                                                      | (Omit if no hardware desired)<br>027 = Slotted cres guides 0.090" [2.29 mm] diameter<br>SK = Turnable screwlocks with 2-56 threads<br>SK3 = Turnable screwlocks with 3-48 threads<br>SL = Fixed screwlocks with 2-56 threads<br>SL3 = Fixed screwlocks with 3-48 threads<br>SK030 = Turnable screwlocks with short slotted knobs<br>SK035 = Turnable screwlocks with socket head knobs<br>SK3030 = Turnable screwlocks with short slotted knobs with 3-48 threads<br>SK3035 = Turnable screwlocks with socket head knobs with 3-48 threads |

**EXAMPLES:**  
 SMBS20-26SK035 = Female, 26 beryllium copper socket contacts with socket head knobs on turnable screwlocks for #20 AWG wiring.  
 SMP20-14SL3 = Male, 14 contact pins, fixed screwlocks with 3-48 threads for #20 AWG wiring.

**Note**

<sup>(1)</sup> To order complete connector with hardware supplied unassembled, add suffix "UA" on end of hardware designation.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.