



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A1	REVISED PER ECO-11-005294	13APR11	HMR

COMPONENT	MATERIAL	FINISH
HOUSING MOUNTING NUT	BRASS PER QQ-B-626 COMP. 360, HALF HARD	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
LOCKWASHER	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions	Temperature Rating <u>-65°C to +125°C</u>
Frequency Range (GHz) DC to <u>4</u>	BNC <u>MIL-STD-348A Fig. 301.2</u>	Vibration <u>MIL-STD-202, Method 204, Condition D</u>
Volt Rating (VRMS MAX) <u>Sea Level 335</u>	OSM <u>MIL-STD-348A Fig. 310.2</u>	Shock <u>MIL-STD-202, Method 213, Condition I</u>
VSWR <u>1.30 Max at 0.5 to 4.0 GHz</u>	Recommended Mating Torque <u>4-6 In-Lbs</u>	Thermal Shock <u>MIL-STD-202, Method 107, Condition C, Except High Temp</u>
Insertion Loss (dB MAX) <u>0.2√f(GHz)</u>	Mating Characteristics:	Moisture Resistance <u>MIL-STD-202, Method 106 Shall Be Omitted</u>
RF Leakage (dB MIN) <u>-55, 2 to 3 GHz</u>		Corrosion - <u>MIL-STD-202, Method 101, Condition B, 5% salt spray</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Insertion (Lbs Max) <u>2.0 3.0</u>	
Dielectric Withstanding Voltage (VRMS MIN) <u>Sea Level 1500</u>	Withdrawal (Oz Min) <u>2.0 1.0</u>	
Contact Resistance (Milliohms MAX)	Force to Engage/Disengage	
Center Contact <u>4.1</u>	Longitudinal	
Outer Contact <u>2.2</u>	Force (Lb Max) <u>3.0 N/A</u>	
RF High Potential <u>Sea Level (VRMS MIN @ 5 MHz) 670</u>	Torque (In-Lb Max) <u>2.5 2.0</u>	
I.R.(Megohms MIN) <u>5000</u>	Contact Retention	
	Axial (Lbs) <u>6.0</u>	
	Radial (In-Oz) <u>4.0</u>	
	Weight (Grams) _____	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DATE		
	FRAC. DEC. ANGLES		
± 1/64 ±.005 ± °	AUGUST TARDIFF 5/18/90	TITLE BNC JACK TO OSM JACK BULKHEAD FEEDTHROUGH ADAPTER	
	S. ALLERDICE 6/6/90	SIZE B	CODE IDENT NO. 26805
	B. CLEVELAND 8/3/90	SCALE 2:1	1058117-1
USE ASS'Y PROCEDURE			REV A1
NO. AP. N/A			SHEET 1 OF 1



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.