

Electronic housing - ME 22,5 UT BUS/ 5 KMGY - 2201852

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Component housing with vents, Lower part, Cross connection: integrated bus connector, Color: light gray, Width: 22.5 mm, Constructional height: 114.5 mm, Number of positions cross connector: 5

Why buy this product

- Item is from the ME product range
- Tool-free mounting
- Available in overall widths from 12.5 mm to 90 mm, modular extension is possible
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail
- Optional bus connector that is either integrated or mounted on the DIN rail

Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 |
| GTIN |  4 046356 990615 |
| GTIN | 4046356990615 |
| Custom tariff number | 85369010 |

Technical data

Environmental Product Compliance

| | |
|------------|--|
| China RoHS | No hazardous substances above threshold values |
|------------|--|

Standards and Regulations

| | |
|--|-----|
| Connection in acc. with standard | CUL |
| Flammability rating according to UL 94 | V0 |

Electronic housing - ME 22,5 UT BUS/ 5 KMGY - 2201852

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 8.0 | 27182702 |
| eCl@ss 9.0 | 27182702 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000886 |
| ETIM 5.0 | EC001031 |

Approvals


Approvals


Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

| | | |
|--|-------|-------|
| UL Recognized  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 60425 | | |
| | B | D |
| Nominal current IN | 8 A | 8 A |
| Nominal voltage UN | 300 V | 300 V |

| | | |
|---|-------|-------|
| cUL Recognized  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 60425 | | |
| | B | D |
| Nominal current IN | 8 A | 8 A |
| Nominal voltage UN | 300 V | 300 V |

| |
|-------------|
| EAC B.01742 |
|-------------|

Electronic housing - ME 22,5 UT BUS/ 5 KMGY - 2201852

Approvals

cULus Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

Accessories

Accessories

Filler plug

Electronic housing - ME B-KA KMGY - 2706302



Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS terminal opening, (male side)

Electronic housing - ME B-SA/NS 35 KMGY - 2706700



Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS male side, (female side)

Mounting material

Electronic housing - ME LPZS - 2906911



Component housing

Components of electronic housing - ME DH 27 NS 35 KMGY - 2706289



Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 27 mm

Electronic housing - ME 22,5 UT BUS/ 5 KMGY - 2201852

Accessories

Components of electronic housing - ME DH 36 NS 35 KMGY - 2706292

Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 36 mm



Electronic housing - E/ME TBUS NS35 GY - 2713780



End clamp, stable construction for DIN rail bus connector

Printed-circuit board connector - MCVR 1,5/ 5-ST-3,81 GY7035 AU - 1719684



Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 5, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: light gray, Contact surface: Gold

Printed-circuit board connector - MC 1,5/ 5-ST-3,81 GY7035 AU - 1719697

Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 5, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: light gray, Contact surface: Gold

Printed-circuit board connector - IMC 1,5/ 5-ST-3,81 GY7035 AU - 1719707

Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 5, Pitch: 3.81 mm, Connection method: Screw connection with tension sleeve, Color: light gray, Contact surface: Gold

Necessary add-on products

Electronic housing - ME 22,5 UT BUS/ 5 KMGY - 2201852

Accessories

Electronic housing - ME 22,5 OT-MSTBO KMGY - 2907761



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 22,5 OT-FKDSO KMGY - 2200323



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 22,5 OT-MKDSO KMGY - 2908469



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 22,5 OTU-MKDSO KMGY - 2278953



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 22,5 OT-1MSTBO KMGY - 2914877



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 22,5 UT BUS/ 5 KMGY - 2201852

Accessories

Electronic housing - ME 22,5 OT-3MSTBO KMGY - 2914880



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 51.5 mm

Electronic housing - ME 22,5 OTP-MSTBO PS KMGY - 2279282



Component housing, Upper part, Color: light gray, Width: 22.5 mm, Constructional height: 38.5 mm



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.