




DC Film Capacitors MKT Radial Potted Type



FEATURES

- 10 mm to 27.5 mm lead pitch
- Supplied loose in box taped on ammpack or reel
- Material categorization:
for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE


APPLICATIONS

Blocking, coupling, and decoupling, bypass and energy reservoir, industrial, consumer, lighting.

| QUICK REFERENCE DATA | |
|---|---|
| Capacitance range (E12 series) | 0.01 μ F to 10 μ F |
| Capacitance tolerance | $\pm 10 \%$, $\pm 5 \%$ |
| Climatic testing class according to IEC 60068-1 | 55/105/56 |
| Maximum application temperature | 105 °C |
| Reference standards | IEC 60384-2 |
| Dielectric | Polyester film |
| Electrodes | Metallized |
| Construction | Mono construction |
| Encapsulation | Flame retardant plastic case and epoxy resin UL-class 94 V-0 |
| Leads | Tinned wire |
| Marking | C-value; tolerance; rated voltage; manufacturer's symbol; year and week of manufacture; manufacturer's type designation |
| Rated (DC) voltage | 250 V, 400 V, 630 V |
| Rated (AC) voltage | 63 V, 100 V, 160 V |
| Rated temperature | 85 °C |
| Performance grade | Grade 1 (long life) |


Note

- For more detailed data and test requirements, contact dc-film@vishay.com





COMPOSITION OF CATALOG NUMBER



Note

(1) For detailed tape specifications refer to packaging information: www.vishay.com/doc?28139

| SPECIFIC REFERENCE DATA | | | |
|---|-------------------------|--------------------------|--------------------------|
| DESCRIPTION | VALUE | | |
| | at 1 kHz | at 10 kHz | at 100 kHz |
| Tangent of loss angle: | | | |
| C ≤ 0.1 μF | ≤ 75 x 10 ⁻⁴ | ≤ 130 x 10 ⁻⁴ | ≤ 250 x 10 ⁻⁴ |
| 0.1 μF < C ≤ 0.47 μF | ≤ 75 x 10 ⁻⁴ | ≤ 130 x 10 ⁻⁴ | ≤ 300 x 10 ⁻⁴ |
| 0.47 μF < C ≤ 1.0 μF | ≤ 75 x 10 ⁻⁴ | ≤ 130 x 10 ⁻⁴ | - |
| 1.0 μF < C ≤ 10 μF | ≤ 75 x 10 ⁻⁴ | ≤ 150 x 10 ⁻⁴ | - |
| C > 10 μF | ≤ 75 x 10 ⁻⁴ | - | - |
| Rated voltage pulse slope (dU/dt) _R at | 250 V _{DC} | 400 V _{DC} | 630 V _{DC} |
| L _{max.} = 12.5 mm | 20 V/μs | 45 V/μs | 137 V/μs |
| L _{max.} = 17.5 mm | 11 V/μs | 20 V/μs | 44 V/μs |
| L _{max.} = 26.0 mm | 7 V/μs | 10 V/μs | 17 V/μs |
| L _{max.} = 30.0 mm | 5 V/μs | 8 V/μs | 12 V/μs |
| R between leads, for C ≤ 0.33 μF at 100 V; 1 min | > 30 000 MΩ | > 30 000 MΩ | - |
| R between leads, for C ≤ 0.33 μF at 500 V; 1 min | - | - | > 30 000 MΩ |
| RC between leads, for C > 0.33 μF at 100 V; 1 min | > 10 000 s | > 10 000 s | - |
| RC between leads, for C > 0.33 μF at 500 V; 1 min | - | - | > 10 000 s |
| R between interconnecting leads and casing, 100 V; 1 min | > 30 000 MΩ | | |
| Withstanding (DC) voltage (cut off current 10 mA) (1); rise time ≤ 1000 V/s: | 250 V _{DC} | 400 V _{DC} | 630 V _{DC} |
| | 400 V; 1 min | 640 V; 1 min | 1008 V; 1 min |
| Withstanding (DC) voltage between leads and case for | 250 V _{DC} | 400 V _{DC} | 630 V _{DC} |
| | 500 V; 1 min | 800 V; 1 min | 1260 V; 1 min |
| Maximum application temperature | 105 °C | | |

Note

(1) See "Voltage Proof Test for Metallized Film Capacitors": www.vishay.com/doc?28169



| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | | | | | | | | |
|---|---|---------------------------------|----------------------------|---|------------------------|--|------------------------|--|------------------------|-----|----|----------------------|---------------------------|
| U_{RDC} (V) | CAP. (μ F) | DIMENSIONS w x h x l (mm) | MASS (g) ⁽³⁾ | CATALOG NUMBER BFC2 373 XXYYMZ AND PACKAGING | | | | | | | | C- VALUE ..YYY | PITCH mm CODE MZ |
| | | | | LOOSE IN BOX | | REEL ⁽¹⁾⁽²⁾ | | AMMOPACK ⁽²⁾ | | | | | |
| | | | | $l_t = 4.0 \text{ mm} + 1.0 \text{ mm}/ - 0.5 \text{ mm}$ | | H = 18.5 mm; P ₀ = 12.7 mm | | H = 18.5 mm; P ₀ = 12.7 mm | | | | | |
| | | | | C-TOL. = $\pm 10 \%$ | C-TOL. = $\pm 5 \%$ | C-TOL. = $\pm 10 \%$ | C-TOL. = $\pm 5 \%$ | C-TOL. = $\pm 10 \%$ | C-TOL. = $\pm 5 \%$ | | | | |
| XX (SPQ) | XX (SPQ) | XX (SPQ) | XX (SPQ) | XX (SPQ) | XX (SPQ) | | | | | | | | |
| PITCH = 10.0 mm \pm 0.40 mm; $d_t = 0.60 \text{ mm} \pm 0.06 \text{ mm}$ ($U_{RAC} = 63 \text{ V}$) | | | | | | | | | | | | | |
| 250 | 0.10 | 4.0 x 10.0 x 12.5 | 0.65 | EE... (1000) | EF... (1000) | EL... (1400) | EM... (1400) | EB... (750) | EC... (750) | 104 | MD | | |
| | 0.12 | | | | | | | | | 124 | MD | | |
| | 0.15 | | | | | | | | | 154 | MD | | |
| | 0.18 | | | | | | | | | 184 | MD | | |
| | 0.22 | | | | | | | | | 224 | MD | | |
| | 0.27 | | | | | | | | | 274 | MD | | |
| | 0.33 | 5.0 x 11.0 x 12.5 | 0.87 | EE... (1000) | EF... (1000) | EL... (1100) | EM... (1100) | EB... (600) | EC... (600) | 334 | MD | | |
| | 0.39 | | | | | | | | | 394 | MD | | |
| | 0.47 | 6.0 x 12.0 x 12.5 | 1.15 | EE... (750) | EF... (750) | EL... (900) | EM... (900) | EB... (500) | EC... (500) | 474 | MD | | |
| | 0.56 | | | | | | | | | 564 | MD | | |
| | PITCH = 15.0 mm \pm 0.40 mm; $d_t = 0.60 \text{ mm} \pm 0.06 \text{ mm}$ ($U_{RAC} = 63 \text{ V}$) | | | | | | | | | | | | |
| | 0.56 | 5.0 x 11.0 x 17.5 | 1.1 | EE... (1000) | EF... (1000) | EL... (1100) | EM... (1100) | Not available | | 564 | MF | | |
| 0.68 | 6.0 x 12.0 x 17.5 | 1.5 | EE... (1000) | EF... (1000) | EL... (900) | EM... (900) | 684 | | | MF | | | |
| 0.82 | | | | | | | 824 | | | MF | | | |
| PITCH = 15.0 mm \pm 0.40 mm; $d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}$ ($U_{RAC} = 63 \text{ V}$) | | | | | | | | | | | | | |
| 1.0 | 7.0 x 13.5 x 17.5 | 2.0 | EE... (1000) | EF... (1000) | EL... (800) | EM... (800) | Not available | | 105 | MF | | | |
| 1.2 | 8.5 x 15.0 x 17.5 | 2.7 | EE... (1000) | EF... (1000) | EL... (650) | EM... (650) | | | 125 | MF | | | |
| 1.5 | | | | | | | | | 155 | MF | | | |
| 1.8 | 10.0 x 16.5 x 17.5 | 3.5 | EE... (500) | EF... (500) | EL... (600) | EM... (600) | | | 185 | MF | | | |
| PITCH = 22.5 mm \pm 0.40 mm; $d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}$ ($U_{RAC} = 63 \text{ V}$) | | | | | | | | | | | | | |
| 2.2 | 8.5 x 18.0 x 26.0 | 4.5 | EE... (200) | EF... (200) | EL... (450) | EM... (450) | Not available | | 225 | MI | | | |
| 2.7 | | | | | | | | | 275 | MI | | | |
| 3.3 | | | | | | | | | 335 | MI | | | |
| 3.9 | 10.0 x 19.5 x 26.0 | 5.7 | EE... (200) | EF... (200) | EL... (350) | EM... (350) | | | 395 | MI | | | |
| 4.7 | | | | | | | | | 475 | MI | | | |
| 5.6 | | | | | | | | | 565 | MI | | | |
| 6.8 | 12.0 x 22.0 x 26.0 | 7.8 | EE... (150) | EF... (150) | EL... (300) | EM... (300) | 685 | MI | | | | | |
| 8.2 | | | | | | | 825 | MI | | | | | |
| PITCH = 27.5 mm \pm 0.40 mm; $d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}$ ($U_{RAC} = 63 \text{ V}$) | | | | | | | | | | | | | |
| 6.8 | 13.0 x 23.0 x 31.0 | 10.4 | EE... (100) | EF... (100) | Not available | | Not available | | 685 | MK | | | |
| 8.2 | 15.0 x 25.0 x 31.5 | 12.8 | EE... (100) | EF... (100) | | | | | 825 | MK | | | |
| 10.0 | | | | | | | | | 106 | MK | | | |
| 15.0 | 18.0 x 28.0 x 31.5 | 18.4 | EE... (100) | EF... (100) | | | | | 156 | MK | | | |



ELECTRICAL DATA AND ORDERING INFORMATION

| U _{RDC} (V) | CAP. (μF) | DIMENSIONS w x h x l (mm) | MASS (g) ⁽³⁾ | CATALOG NUMBER BFC2 373 XXYYMZ AND PACKAGING | | | | | | | | C- VALUE ..YYY | PITCH mm CODE MZ |
|---|---|---------------------------------|----------------------------|---|-------------------|--|-------------------|--|-------------------|-------|-----|----------------------|---------------------------|
| | | | | LOOSE IN BOX | | REEL ⁽¹⁾⁽²⁾ | | AMMOPACK ⁽²⁾ | | | | | |
| | | | | l _t = 4.0 mm + 1.0 mm/ - 0.5 mm | | H = 18.5 mm; P ₀ = 12.7 mm | | H = 18.5 mm; P ₀ = 12.7 mm | | | | | |
| | | | | C-TOL. = ± 10 % | C-TOL. = ± 5 % | C-TOL. = ± 10 % | C-TOL. = ± 5 % | C-TOL. = ± 10 % | C-TOL. = ± 5 % | | | | |
| | | XX (SPQ) | XX (SPQ) | XX (SPQ) | XX (SPQ) | XX (SPQ) | XX (SPQ) | | | | | | |
| PITCH = 10.0 mm ± 0.40 mm; d_t = 0.60 mm ± 0.06 mm (U_{RAC} = 100 V) | | | | | | | | | | | | | |
| 400 | 0.082 | 4.0 x 10.0 x 12.5 | 0.65 | | | | | | | 823 | MD | | |
| | 0.10 | | | FE... | FF... | FL... | FM... | FB... | FC... | 104 | MD | | |
| | 0.12 | | | (1000) | (1000) | (1400) | (1400) | (750) | (750) | 124 | MD | | |
| | 0.15 | | | | | | | | | 154 | MD | | |
| | 0.18 | 5.0 x 11.0 x 12.5 | 0.87 | | | | | | | 184 | MD | | |
| | 0.22 | | | FE... | FF... | FL... | FM... | FB... | FC... | 224 | MD | | |
| | 0.27 | | | (1000) | (1000) | (1100) | (1100) | (600) | (600) | 274 | MD | | |
| | 0.33 | 6.0 x 12.0 x 12.5 | 1.15 | | | | | | | 334 | MD | | |
| | | | | | FE... | FF... | FL... | FM... | FB... | FC... | | | |
| | | | | | (750) | (750) | (900) | (900) | (500) | (500) | | | |
| | PITCH = 15.0 mm ± 0.40 mm; d_t = 0.60 mm ± 0.06 mm (U_{RAC} = 100 V) | | | | | | | | | | | | |
| | 0.27 | 5.0 x 11.0 x 17.5 | 1.1 | | | | | | Not available | | 274 | MF | |
| | 0.33 | | | FE... | FF... | FL... | FM... | | | 334 | MF | | |
| | 0.39 | | | (1000) | (1000) | (1100) | (1100) | | | 394 | MF | | |
| | 0.47 | 6.0 x 12.0 x 17.5 | 1.5 | | | | | | | 474 | MF | | |
| | 0.56 | | | FE... | FF... | FL... | FM... | | 564 | MF | | | |
| | | | | | (1000) | (1000) | (900) | (900) | | | | | |
| | PITCH = 15.0 mm ± 0.40 mm; d_t = 0.80 mm ± 0.08 mm (U_{RAC} = 100 V) | | | | | | | | | | | | |
| 0.68 | 7.0 x 13.5 x 17.5 | 2.0 | | | | | | Not available | | 684 | MF | | |
| 0.82 | 8.5 x 15.0 x 17.5 | 2.7 | | | | | | | | 824 | MF | | |
| 1.0 | | | FE... | FF... | FL... | FM... | | | 105 | MF | | | |
| 1.2 | | | (1000) | (1000) | (650) | (650) | | | 125 | MF | | | |
| 1.5 | 10.0 x 16.5 x 17.5 | 3.5 | | | | | | | 155 | MF | | | |
| | | | | FE... | FF... | FL... | FM... | | | | | | |
| | | | | (500) | (500) | (600) | (600) | | | | | | |
| PITCH = 22.5 mm ± 0.40 mm; d_t = 0.80 mm ± 0.08 mm (U_{RAC} = 100 V) | | | | | | | | | | | | | |
| 1.0 | 7.0 x 16.5 x 26.0 | 3.3 | | | | | | Not available | | 105 | MI | | |
| 1.2 | | | FE... | FF... | FL... | FM... | | | 125 | MI | | | |
| 1.5 | | | (200) | (200) | (450) | (450) | | | 155 | MI | | | |
| 1.8 | 8.5 x 18.0 x 26.0 | 4.5 | | | | | | | 185 | MI | | | |
| 2.2 | | | FE... | FF... | FL... | FM... | | 225 | MI | | | | |
| 2.7 | 10.0 x 19.5 x 26.0 | 5.7 | | | | | | | 275 | MI | | | |
| 3.3 | | | FE... | FF... | FL... | FM... | | 335 | MI | | | | |
| 3.9 | 12.0 x 22.0 x 26.0 | 7.8 | | | | | | | 395 | MI | | | |
| | | | | FE... | FF... | FL... | FM... | | | | | | |
| | | | | (150) | (150) | (300) | (300) | | | | | | |
| PITCH = 27.5 mm ± 0.40 mm; d_t = 0.80 mm ± 0.08 mm (U_{RAC} = 100 V) | | | | | | | | | | | | | |
| 2.7 | 9.0 x 19.0 x 31.5 | 5.5 | | | | | | Not available | | 275 | MK | | |
| 3.3 | 11.0 x 21.0 x 31.0 | 7.8 | | | | | | | | 335 | MK | | |
| 3.9 | 13.0 x 23.0 x 31.0 | 10.4 | | | | | | | | 395 | MK | | |
| | | | | FE... | FF... | | | | | | | | |
| | | | | (100) | (100) | | | | | | | | |



| ELECTRICAL DATA AND ORDERING INFORMATION | | | | | | | | | | | | | |
|---|--------------|---------------------------------|----------------------------|---|-------------------|--|-------------------|--|-------------------|--------------------|-----|----------------------|---------------------------|
| U _{RDC} (V) | CAP. (μF) | DIMENSIONS w x h x l (mm) | MASS (g) ⁽³⁾ | CATALOG NUMBER BFC2 373 XXYYMZ AND PACKAGING | | | | | | | | C- VALUE ..YYY | PITCH mm CODE MZ |
| | | | | LOOSE IN BOX | | REEL ⁽¹⁾⁽²⁾ | | AMMOPACK ⁽²⁾ | | | | | |
| | | | | l _t = 4.0 mm + 1.0 mm/ - 0.5 mm | | H = 18.5 mm; P ₀ = 12.7 mm | | H = 18.5 mm; P ₀ = 12.7 mm | | | | | |
| | | | | C-TOL. = ± 10 % | C-TOL. = ± 5 % | C-TOL. = ± 10 % | C-TOL. = ± 5 % | C-TOL. = ± 10 % | C-TOL. = ± 5 % | | | | |
| XX (SPQ) | | XX (SPQ) | | XX (SPQ) | | XX (SPQ) | | | | | | | |
| PITCH = 10.0 mm ± 0.40 mm; d_t = 0.60 mm ± 0.06 mm (U_{RAC} = 160 V) | | | | | | | | | | | | | |
| 0.010 | | 4.0 x 10.0 x 12.5 | 0.65 | GE... (1000) | GF... (1000) | GL... (1400) | GM... (1400) | GB... (750) | GC... (750) | 103 | MD | | |
| 0.012 | | | | | | | | | | 123 | MD | | |
| 0.015 | | | | | | | | | | 153 | MD | | |
| 0.018 | | | | | | | | | | 183 | MD | | |
| 0.022 | | | | | | | | | | 223 | MD | | |
| 0.027 | | | | | | | | | | 273 | MD | | |
| 0.033 | | | | | | | | | | 333 | MD | | |
| 0.039 | | | | | | | | | | 393 | MD | | |
| 0.047 | | 473 | MD | | | | | | | | | | |
| 0.056 | | 563 | MD | | | | | | | | | | |
| 0.068 | | 5.0 x 11.0 x 12.5 | 0.87 | GE... (1000) | GF... (1000) | GL... (1100) | GM... (1100) | GB... (600) | GC... (600) | 683 | MD | | |
| 0.082 | | | | | | | | | | 823 | MD | | |
| 0.100 | | 6.0 x 12.0 x 12.5 | 1.15 | GE... (750) | GF... (750) | GL... (900) | GM... (900) | GB... (500) | GC... (500) | 104 | MD | | |
| PITCH = 15.0 mm ± 0.40 mm; d_t = 0.60 mm ± 0.06 mm (U_{RAC} = 160 V) | | | | | | | | | | | | | |
| 0.082 | | 5.0 x 11.0 x 17.5 | 1.1 | GE... (1000) | GF... (1000) | GL... (1100) | GM... (1100) | Not available | | 823 | MF | | |
| 0.100 | | | | | | | | | | 104 | MF | | |
| 0.120 | | 124 | MF | | | | | | | | | | |
| 0.150 | | 154 | MF | | | | | | | | | | |
| 0.180 | | 6.0 x 12.0 x 17.5 | 1.5 | GE... (1000) | GF... (1000) | GL... (900) | GM... (900) | | | 184 | MF | | |
| PITCH = 15.0 mm ± 0.40 mm; d_t = 0.80 mm ± 0.08 mm (U_{RAC} = 160 V) | | | | | | | | | | | | | |
| 0.22 | | 7.0 x 13.5 x 17.5 | 2.0 | GE... (1000) | GF... (1000) | GL... (800) | GM... (800) | Not available | | 224 | MF | | |
| 0.27 | | | | | | | | | | 274 | MF | | |
| 0.33 | | 8.5 x 15.0 x 17.5 | 2.7 | GE... (1000) | GF... (1000) | GL... (650) | GM... (650) | | | 334 | MF | | |
| 0.39 | | | | | | | | | | 394 | MF | | |
| 0.47 | | 10.0 x 16.5 x 17.5 | 3.5 | GE... (500) | GF... (500) | GL... (600) | GM... (600) | | | 474 | MF | | |
| PITCH = 22.5 mm ± 0.40 mm; d_t = 0.80 mm ± 0.08 mm (U_{RAC} = 160 V) | | | | | | | | | | | | | |
| 0.33 | | 8.5 x 18.0 x 26.0 | 4.5 | GE... (200) | GF... (200) | GL... (450) | GM... (450) | Not available | | 334 | MI | | |
| 0.39 | | | | | | | | | | 394 | MI | | |
| 0.47 | | | | | | | | | | 474 | MI | | |
| 0.56 | | | | | | | | | | 564 | MI | | |
| 0.68 | | | | | | | | | | 684 | MI | | |
| 0.82 | | | | | | | | | | 824 | MI | | |
| 1.00 | | 10.0 x 19.5 x 26.0 | 5.7 | GE... (200) | GF... (200) | GL... (350) | GM... (350) | | | 105 | MI | | |
| 1.20 | | 12.0 x 22.0 x 26.0 | 7.8 | GE... (150) | GF... (150) | GL... (300) | GM... (300) | | | 125 | MI | | |
| PITCH = 27.5 mm ± 0.40 mm; d_t = 0.80 mm ± 0.08 mm (U_{RAC} = 160 V) | | | | | | | | | | | | | |
| 0.82 | | 9.0 x 19.0 x 31.5 | 5.5 | GE... (100) | GF... (100) | Not available | Not available | | | 824 | MK | | |
| 1.00 | | | | | | | | | | 105 | MK | | |
| 1.20 | | | | | | | | | | 11.0 x 21.0 x 31.0 | 7.8 | GE... (100) | GF... (100) |

Notes

- SPQ = Standard Packing Quantity
- (1) H = in-tape height; P₀ = sprocket hole distance; for detailed specifications refer to Packaging Information.
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

MOUNTING

Normal Use

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to type detail information: www.vishay.com/doc?28139

Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that the underside of this product is in good contact with the printed-circuit board:

- For pitches ≤ 15 mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

Ratings and Characteristics Reference Conditions

Unless otherwise specified, all electrical values apply to an ambient temperature of $23\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of $50\% \pm 2\%$.


For reference testing, a conditioning period shall be applied over $96\text{ h} \pm 4\text{ h}$ by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.

Space Requirements on Printed-Circuit Board

The maximum space for length (l_{max}), width (w_{max}), and height (h_{max}) of film capacitors to take in account on the printed-circuit board is shown in the drawings:

- For products with pitch ≤ 15 mm, $\Delta w = \Delta l = 0.3$ mm and $\Delta h = 0.1$ mm
- For products with $15\text{ mm} < \text{pitch} \leq 27.5$ mm, $\Delta w = \Delta l = 0.5$ mm and $\Delta h = 0.1$ mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.



SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile, we refer to the application note:


“Soldering Guidelines for Film Capacitors”: www.vishay.com/doc?28171

Storage Temperature


$T_{\text{stg}} = -25\text{ }^{\circ}\text{C}$ to $+35\text{ }^{\circ}\text{C}$ with RH maximum 75 % without condensation




CHARACTERISTICS




Capacitance as a function of frequency




Capacitance as a function of ambient temperature




Impedance as a function of frequency




Max. DC and AC voltage as a function of temperature




Max. RMS voltage and AC current (sinewave)




Max. RMS voltage and AC current (sinewave)




Max. RMS voltage and AC current (sinewave)



Max. RMS voltage and AC current (sinewave)



Max. RMS voltage and AC current (sinewave)




Max. RMS voltage and AC current (sinewave)


Maximum RMS Current (Sinewave) as a Function of Frequency

The maximum RMS current is defined by $I_{AC} = \omega \times C \times U_{AC}$.


U_{AC} is the maximum AC voltage depending on the ambient temperature in the curves "Max. RMS voltage and AC current as a function of frequency".



Tangent of loss angle as a function of frequency (typical curve)



Maximum allowed component temperature rise (ΔT) as a function of the ambient temperature (T_{amb})



Insulation resistance as a function of the ambient temperature (typical curve)

HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C

| $W_{max.}$ (mm) | HEAT CONDUCTIVITY (mW/°C) | | | |
|--------------------|---------------------------|-------------|---------------|---------------|
| | PITCH 10 mm | PITCH 15 mm | PITCH 22.5 mm | PITCH 27.5 mm |
| 4.0 | 6.0 | - | - | - |
| 4.5 | - | - | - | - |
| 5.0 | 7.5 | 10 | - | - |
| 6.0 | 9.0 | 11 | 19 | - |
| 7.0 | - | 12 | 21 | - |
| 8.5 | - | 16 | 25 | - |
| 10.0 | - | 18 | 28 | - |
| 11.0 | - | - | - | 36 |
| 12.0 | - | - | 34 | - |
| 13.0 | - | - | - | 42 |
| 15.0 | - | - | - | 48 |
| 18.0 | - | - | - | 57 |

POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.


The power dissipation can be calculated according type detail specification “HQN-384-01/101: Technical Information Film Capacitors”, www.vishay.com/doc?28147.

The component temperature rise (ΔT) can be measured (see section “Measuring the component temperature” for more details) or calculated by $\Delta T = P/G$:

- ΔT = component temperature rise ($^{\circ}C$)
- P = power dissipation of the component (mW)
- G = heat conductivity of the component (mW/ $^{\circ}C$)

MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded (T_{amb}) and maximum loaded condition (T_C).

The temperature rise is given by $\Delta T = T_C - T_{amb}$.

To avoid radiation or convection, the capacitor should be tested in a wind-free box.

APPLICATION NOTE AND LIMITING CONDITIONS

These capacitors are not suitable for mains applications as across-the-line capacitors.

For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: dc-film@vishay.com

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage (U_P) shall not be greater than the rated DC voltage (U_{RDC})
2. The peak-to-peak voltage (U_{P-P}) shall not be greater than $2\sqrt{2} \times U_{RAC}$ to avoid the ionization inception level
3. The voltage peak slope (dU/dt) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by U_{RDC} and divided by the applied voltage.

For all other pulses following equation must be fulfilled:

$$2 \times \int_0^T \left(\frac{dU}{dt} \right)^2 \times dt < U_{RDC} \times \left(\frac{dU}{dt} \right)_{rated}$$

T is the pulse duration.

The rated voltage pulse slope is valid for ambient temperatures up to 85 $^{\circ}C$. For higher temperatures a derating factor of 3 % per K shall be applied.

4. The maximum component surface temperature rise must be lower than the limits (see figure Max. Allowed Component Temperature Rise).
5. Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: “Heat Conductivity”
6. When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).



| VOLTAGE CONDITIONS FOR 6 ABOVE | | |
|--|--------------------------------|--|
| ALLOWED VOLTAGES | T_{amb} ≤ 85 °C | 85 °C < T_{amb} ≤ 105 °C |
| Maximum continuous RMS voltage | U _{RAC} | 0.8 x U _{RAC} |
| Maximum temperature RMS-overvoltage (< 24 h) | 1.25 x U _{RAC} | 1.0 x U _{RAC} |
| Maximum peak voltage (V _{O-P}) (< 2 s) | 1.6 x U _{RDC} | 1.3 x U _{RDC} |

INSPECTION REQUIREMENTS

General Notes

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-2 and Specific Reference Data”.

| GROUP C INSPECTION REQUIREMENTS | | |
|---|---|--|
| SUB-CLAUSE NUMBER AND TEST | CONDITIONS | PERFORMANCE REQUIREMENTS |
| SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1 | | |
| 4.1 Dimensions (detail) | | As specified in chapter “General Data” of this specification |
| 4.3.1 Initial measurements | Capacitance at 1 kHz Tangent of loss angle: for C ≤ 470 nF at 100 kHz or for C > 470 nF at 10 kHz | |
| 4.3 Robustness of terminations | Tensile and bending | No visible damage |
| 4.4 Resistance to soldering heat | Method: 1A Solder bath: 280 °C ± 5 °C Duration: 10 s | |
| 4.14 Component solvent resistance | Isopropylalcohol at room temperature Method: 2 Immersion time: 5 min ± 0.5 min Recovery time: min. 1 h, max. 2 h | |
| 4.4.2 Final measurements | Visual examination Capacitance Tangent of loss angle | No visible damage Legible marking ΔC/C ≤ 2 % of the value measured initially Increase of tan δ: ≤ 0.005 for: C ≤ 100 nF or ≤ 0.010 for: 100 nF < C ≤ 220 nF or ≤ 0.015 for: 220 nF < C ≤ 470 nF and ≤ 0.003 for: C > 470 nF Compared to values measured in 4.3.1 |
| SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1 | | |
| 4.6.1 Initial measurements | Capacitance at 1 kHz Tangent of loss angle: for C ≤ 470 nF at 100 kHz or for C > 470 nF at 10 kHz | |
| 4.6 Rapid change of temperature | θA = lower category temperature θB = upper category temperature 5 cycles Duration t = 30 min Visual examination | No visible damage |



| GROUP C INSPECTION REQUIREMENTS | | |
|--|---|---|
| SUB-CLAUSE NUMBER AND TEST | CONDITIONS | PERFORMANCE REQUIREMENTS |
| SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1 | | |
| 4.7 Vibration | Mounting: see section "Mounting" of this specification Procedure B4 Frequency range: 10 Hz to 55 Hz Amplitude: 0.75 mm or Acceleration 98 m/s ² (whichever is less severe) Total duration 6 h | |
| 4.7.2 Final inspection | Visual examination | No visible damage |
| 4.9 Shock | Mounting: see section "Mounting" of this specification Pulse shape: half sine Acceleration: 490 m/s ² Duration of pulse: 11 ms | |
| 4.9.3 Final measurements | Visual examination Capacitance Tangent of loss angle Insulation resistance | No visible damage $ \Delta C/C \leq 5\%$ of the value measured in 4.6.1 Increase of tan δ : ≤ 0.005 for: $C \leq 100$ nF or ≤ 0.010 for: 100 nF $< C \leq 220$ nF or ≤ 0.015 for: 220 nF $< C \leq 470$ nF and ≤ 0.003 for: $C > 470$ nF Compared to values measured in 4.6.1 As specified in section "Specific Reference Data" of this specification |
| SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B | | |
| 4.10 Climatic sequence | | |
| 4.10.2 Dry heat | Temperature: upper category temperature Duration: 16 h | |
| 4.10.3 Damp heat cyclic Test Db, first cycle | | |
| 4.10.4 Cold | Temperature: lower category temperature Duration: 2 h | |
| 4.10.6 Damp heat cyclic Test Db, remaining cycles | | |
| 4.10.6.2 Final measurements | Visual examination Capacitance Tangent of loss angle Insulation resistance | No visible damage Legible marking $ \Delta C/C \leq 5\%$ of the value measured in 4.4.2 or 4.9.3 Increase of tan δ : ≤ 0.007 for: $C \leq 100$ nF or ≤ 0.010 for: 100 nF $< C \leq 220$ nF or ≤ 0.015 for: 220 nF $< C \leq 470$ nF and ≤ 0.005 for: $C > 470$ nF Compared to values measured in 4.3.1 or 4.6.1 $\geq 50\%$ of values specified in section "Specific Reference Data" of this specification |



| GROUP C INSPECTION REQUIREMENTS | | |
|--|---|--|
| SUB-CLAUSE NUMBER AND TEST | CONDITIONS | PERFORMANCE REQUIREMENTS |
| SUB-GROUP C2 | | |
| 4.11 Damp heat steady state | 56 days, 40 °C, 90 % to 95 % RH | |
| 4.11.1 Initial measurements | Capacitance at 1 kHz Tangent of loss angle at 1 kHz | |
| 4.11.3 Final measurements | Visual examination Capacitance Tangent of loss angle Insulation resistance | No visible damage Legible marking $ \Delta C/C \leq 5\%$ of the value measured in 4.11.1. Increase of $\tan \delta \leq 0.005$ Compared to values measured in 4.11.1 $\geq 50\%$ of values specified in section "Specific Reference Data" of this specification |
| SUB-GROUP C3 | | |
| 4.12 Endurance | Duration: 2000 h 1.25 x U_{RDC} at 85 °C 1.0 x U_{RDC} at 105 °C | |
| 4.12.1 Initial measurements | Capacitance at 1 kHz Tangent of loss angle: for $C \leq 470$ nF at 100 kHz or for $C > 470$ nF at 10 kHz | |
| 4.12.5 Final measurements | Visual examination Capacitance Tangent of loss angle Insulation resistance | No visible damage Legible marking $ \Delta C/C \leq 5\%$ compared to values measured in 4.12.1 Increase of $\tan \delta$: ≤ 0.005 for: $C \leq 100$ nF or ≤ 0.010 for: 100 nF $< C \leq 220$ nF or ≤ 0.015 for: 220 nF $< C \leq 470$ nF and ≤ 0.003 for: $C > 470$ nF Compared to values measured in 4.12.1 $\geq 50\%$ of values specified in section "Specific Reference Data" of this specification |
| SUB-GROUP C4 | | |
| 4.13 Charge and discharge | 10 000 cycles Charged to U_{RDC} Discharge resistance: $R = \frac{U_R}{C \times 2.5 \times (dU/dt)_R}$ | |
| 4.13.1 Initial measurements | Capacitance at 1 kHz Tangent of loss angle: for $C \leq 470$ nF at 100 kHz or for $C > 470$ nF at 10 kHz | |
| 4.13.3 Final measurements | Capacitance Tangent of loss angle Insulation resistance | $ \Delta C/C \leq 3\%$ compared to values measured in 4.13.1 Increase of $\tan \delta$: ≤ 0.005 for: $C \leq 100$ nF or ≤ 0.010 for: 100 nF $< C \leq 220$ nF or ≤ 0.015 for: 220 nF $< C \leq 470$ nF and ≤ 0.003 for: $C > 470$ nF Compared to values measured in 4.13.1 $\geq 50\%$ of values specified in section "Specific Reference Data" of this specification |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.