

Hermetic Flat-Pak Resistor Networks



Product may not
be to scale

FEATURES

- Lead (Pb)-free available
- Military/Aerospace
- Hermetically sealed






RoHS*
COMPLIANT

Vishay Thin Film offers a broad line of precision resistor networks in hermetic Flat-Packs for surface mount requirements in military, space or other harsh environmental applications. These networks provide the long-term stability necessary to insure continuous specification and performance over the 20 to 30 year life required for space applications. The fabrication of these devices is performed under tight procedural and environmental controls to insure conformance to all 883C Level H or K requirements. Custom configurations, values and tolerance combinations are available with fast turnaround.

PRODUCT CAPABILITIES

Material	Passivated nichrome
Resistance Range	10 Ω to 1 M Ω total
Absolute Resistance Tolerance	1 % to 0.05 %
Resistance Ratio Tolerance	0.1 % to 0.01 %
Absolute TCR	$\pm 10, 25, 50$ ppm/ $^{\circ}$ C
Ratio TCR	± 5 ppm/ $^{\circ}$ C standard
Absolute Resistor Stability	1000 ppm/2000 h at 70 $^{\circ}$ C
Ratio Resistor Stability	300 ppm/2000 h at 70 $^{\circ}$ C
Package Power Dissipation	800 mW/70 $^{\circ}$ C
Operating Temperature Range	- 55 $^{\circ}$ C to + 125 $^{\circ}$ C

STANDARD CONFIGURATIONS



FP200

Number of Resistors	7, 8
Number of Leads	14, 16
Type Connection	Isolated
Values Available	500 Ω - 100 k Ω

FP201

Number of Resistors	12, 14
Number of Leads	14, 16
Type Connection	Series
Values Available	500 Ω - 100 k Ω

FP202



Number of Resistors	13, 15
Number of Leads	14, 16
Type Connection	Common
Values Available	500 Ω - 100 k Ω

* Pb containing terminations are not RoHS compliant, exemptions may apply

FP 200, 201, 202

Vishay Thin Film

Hermetic Flat-Pak Resistor Networks

PACKAGE OUTLINE DRAWING AND DIMENSIONS
FLAT-PAK FP200

DIMENSIONS in inches				
	14 LEAD		16 LEAD	
	MINIMUM	MAXIMUM	MINIMUM	MAXIMUM
A	0.086	0.106	0.045	0.115
b	0.015	0.019	0.015	0.019
C	0.004	0.007	0.003	0.009
D	0.373	0.383	-	0.440
e	0.047	0.053	0.050	BSC
E	0.250	0.260	0.245	0.285
E ₁	-	0.290	-	0.315
E ₂	0.158	0.172	0.130	-
E ₃	0.030	-	0.030	-
L	-	-	0.250	0.370
Q	0.026	-	0.26	0.045
S	-	0.045	-	0.045
S ₁	0.005	-	0.005	-
K	-	-	0.008	0.015

DIMENSIONS in millimeters				
	14 LEAD		16 LEAD	
	MINIMUM	MAXIMUM	MINIMUM	MAXIMUM
A	2.18	2.69	1.14	2.92
b	0.38	0.48	0.38	0.48
C	0.10	0.18	0.08	0.23
D	9.47	9.73	-	11.18
e	1.19	1.35	1.27	BSC
E	6.35	6.60	6.22	7.24
E ₁	-	7.37	-	8.00
E ₂	4.01	4.37	3.30	-
E ₃	0.76	-	0.76	-
L	-	-	6.35	9.40
Q	0.66	-	0.66	1.14
S	-	1.14	-	1.14
S ₁	0.13	-	0.13	-
K	-	-	0.20	0.38

GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: FP2001681001BFBCW (preferred part number format)

F	P	2	0	0	1	6	8	1	0	0	1	B	F	B	C	W	
F	P	2	0	2	1	6	1	3	1	0	0	1	B	F	B	C	W

GLOBAL MODEL	CASE SIZE	NUMBER OF RESISTORS (1 or 2 digits)	OHMIC VALUE	ABSOLUTE TOLERANCE	RATIO TOLERANCE	ABSOLUTE TCR	RATIO TCR	PACKAGING
FP200	14 16	7 8	The first 3 digits are significant figures and the last digit specifies the number of zeros to follow. "R" designates the decimal point. Example: 10R0 = 10 Ω 1000 = 100 Ω 1001 = 1000 Ω	A = 0.05 % B = 0.1 % C = 0.2 % D = 0.5 % F = 1 % G = 2 % J = 5 % K = 10 % M = 20 %	B = 0.01 % C = 0.025 % D = 0.05 % F = 0.1 % H = 0.25 % J = 0.5 % K = 1 % X = Not applicable	A = 10 ppm/°C B = 25 ppm/°C D = 50 ppm/°C E = 100 ppm/°C	*C = 2 ppm *D = 3 ppm F = 5 ppm G = 10 ppm X = N/A * Value dependant	W = WAFFLE 100 min. 1 mult
FP201	14 16	12 14						
FP202	14 16	13 16						

Historical Part Number example: FP2001681002BFBC (will continue to be accepted)

FP200	16	8	1002	B	F	B	C
MODEL	NUMBER OF LEADS	NUMBER OF RESISTORS	RESISTANCE	ABSOLUTE TOLERANCE	RATIO TOLERANCE	ABSOLUTE TCR	RATIO TCR



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.