



### Features:

- Halogens free
- Current transfer ratio  
(CTR: 50~600% at  $I_F = 5\text{mA}$ ,  $V_{CE} = 5\text{V}$ )  
(CTR: 40~320% at  $I_F = 10\text{mA}$ ,  $V_{CE} = 5\text{V}$ )
- High isolation voltage between input and output ( $V_{iso} = 3750\text{ V rms}$ )
- Compact 4 Pin SSOP with a 2.0 mm profile
- Pb free and RoHS compliant.
- UL approved (No. 214129)
- VDE approval (132249)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CSA approved



### Schematic



### Pin Configuration

1. Anode
2. Cathode
3. Emitter
4. Collector

### Description

The EL3H7-G series devices consist of an infrared emitting diode, optically coupled to a phototransistor detector encapsulated with green compound.

They are packaged in a 4-pin small outline SMD package.

### Applications

- DC-DC Converters
- Programmable controllers
- Telecommunication equipments
- Signal transmission between circuits of different potentials and impedances

**Absolute Maximum Ratings (T<sub>a</sub>=25°C)**

| Parameter                           |  | Symbol           | Rating     | Unit  |
|-------------------------------------|--|------------------|------------|-------|
| Input                               | Forward current  | I <sub>F</sub>   | 50         | mA    |
|                                     | Peak forward current (1us, pulse)                                  | I <sub>FP</sub>  | 1          | A     |
|                                     | Reverse voltage  | V <sub>R</sub>   | 6          | V     |
|                                     | Power dissipation<br>Derating factor (above T <sub>a</sub> = 90°C) | P <sub>D</sub>   | 70         | mW    |
|                                     | 2.0  |                  | mW/°C      |       |
| Output                              | Power dissipation<br>Derating factor (above T <sub>a</sub> = 70°C) | P <sub>C</sub>   | 150        | mW    |
|                                     |  |                  | 3.1        | mW/°C |
|                                     | Collector current  | I <sub>C</sub>   | 50         | mA    |
|                                     | Collector-Emitter voltage  | V <sub>CEO</sub> | 80         | V     |
|                                     | Emitter-Collector voltage  | V <sub>ECO</sub> | 7          | V     |
| Total power dissipation             |  | P <sub>TOT</sub> | 200        | mW    |
| Isolation voltage <sup>*1</sup>     |  | V <sub>ISO</sub> | 3750       | V rms |
| Operating temperature               |  | T <sub>OPR</sub> | -55 ~ +110 | °C    |
| Storage temperature                 |  | T <sub>STG</sub> | -55 ~ +125 | °C    |
| Soldering temperature <sup>*2</sup> |  | T <sub>SOL</sub> | 260        | °C    |

Notes

\*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1 & 2 are shorted together, and pins 3 & 4 are shorted together.

\*2 For 10 seconds.

### Electrical Characteristics ( $T_a=25^{\circ}\text{C}$ unless specified otherwise)

#### Input

| Parameter         | Symbol   | Min. | Typ.* | Max. | Unit          | Condition                |
|-------------------|----------|------|-------|------|---------------|--------------------------|
| Forward voltage   | $V_F$    | -    | 1.2   | 1.4  | V             | $I_F = 20\text{mA}$      |
| Reverse current   | $I_R$    | -    | -     | 10   | $\mu\text{A}$ | $V_R = 4\text{V}$        |
| Input capacitance | $C_{in}$ | -    | 30    | 250  | pF            | $V = 0, f = 1\text{kHz}$ |

#### Output

| Parameter                           | Symbol     | Min. | Typ.* | Max. | Unit | Condition                               |
|-------------------------------------|------------|------|-------|------|------|---|
| Collector-Emitter dark current      | $I_{CEO}$  | -    | -     | 100  | nA   | $V_{CE} = 20\text{V}, I_F = 0\text{mA}$ |
| Collector-Emitter breakdown voltage | $BV_{CEO}$ | 80   | -     | -    | V    | $I_C = 0.1\text{mA}$                    |
| Emitter-Collector breakdown voltage | $BV_{ECO}$ | 7    | -     | -    | V    | $I_E = 0.1\text{mA}$                    |

### Transfer Characteristics ( $T_a=25^{\circ}\text{C}$ unless specified otherwise)

| Parameter              | Symbol | Min. | Typ.* | Max. | Unit | Condition                               |
|------------------------|--------|------|-------|------|------|---|
| Current Transfer ratio | EL3H7  | 50   | -     | 600  | %    | $I_F = 5\text{mA}, V_{CE} = 5\text{V}$  |
|                        | EL3H7A | 80   | -     | 160  |      |   |
|                        | EL3H7B | 130  | -     | 260  |      |   |
|                        | EL3H7C | 200  | -     | 400  |      |   |
|                        | EL3H7D | 300  | -     | 600  |      |   |
|                        | EL3H7E | 100  | -     | 200  |      |   |
|                        | EL3H7F | 150  | -     | 300  |      | $I_F = 10\text{mA}, V_{CE} = 5\text{V}$ |
|                        | EL3H7H | 40   | -     | 80   |      |   |
|                        | EL3H7I | 63   | -     | 125  |      |   |
|                        | EL3H7J | 100  | -     | 200  |      |   |
|                        | EL3H7K | 160  | -     | 320  |      |   |
|                        |        | CTR  |       |      |      |   |

### Transfer Characteristics ( $T_a=25^\circ\text{C}$ unless specified otherwise)

| Parameter                            | Symbol        | Min.               | Typ.* | Max. | Unit          | Condition  |
|--------------------------------------|---------------|--------------------|-------|------|---------------|--|
| Collector-Emitter saturation voltage | $V_{CE(sat)}$ | -                  | 0.1   | 0.2  | V             | $I_F = 10\text{mA}$ , $I_C = 1\text{mA}$                         |
| Isolation resistance                 | $R_{IO}$      | $5 \times 10^{10}$ | -     | -    | $\Omega$      | $V_{IO} = 500\text{Vdc}$ ,<br>40~60% R.H.                        |
| Floating capacitance                 | $C_{IO}$      | -                  | 0.3   | 1.0  | pF            | $V_{IO} = 0$ , $f = 1\text{MHz}$                                 |
| Rise time                            | $t_r$         | -                  | 5     | 18   | $\mu\text{s}$ | $V_{CE} = 2\text{V}$ , $I_C = 2\text{mA}$ ,<br>$R_L = 100\Omega$ |
| Fall time                            | $t_f$         | -                  | 3     | 18   | $\mu\text{s}$ |  |

\* Typical values at  $T_a = 25^\circ\text{C}$

EVERLIGHT

### Typical Performance Curves









Figure 7. Collector Current vs Collector-Emitter Voltage




Figure 8. Collector Dark Current vs Ambient Temperature




Figure 9. Collector-Emitter Saturation Voltage vs Ambient Temperature




Figure 10. Switching Time vs Load Resistance






Figure 11. Switching Time Test Circuit & Waveforms

### Order Information

#### Part Number

# EL3H7(X)(Y)-VG

#### Note

3H7 = Part No.

X = CTR Rank (A, B, C, D, E, F, H, I, J, K or none)


Y = Tape and reel option (TA, TB, EA, EB or none).

V = VDE (optional)


G = Halogens free

| Option | Description                 | Packing quantity    |
|--------|-----------------------------|---------------------|
| None   | Standard SMD option         | 100 units per tube  |
| -V     | Standard SMD option + VDE   | 100 units per tube  |
| (TA)   | TA Tape & reel option       | 5000 units per reel |
| (TB)   | TB Tape & reel option       | 5000 units per reel |
| (TA)-V | TA Tape & reel option + VDE | 5000 units per reel |
| (TB)-V | TB Tape & reel option + VDE | 5000 units per reel |
| (EA)   | TA Tape & reel option       | 1000 units per reel |
| (EB)   | TB Tape & reel option       | 1000 units per reel |
| (EA)-V | TA Tape & reel option + VDE | 1000 units per reel |
| (EB)-V | TB Tape & reel option + VDE | 1000 units per reel |

### Package Drawing (Dimensions in mm)



### Recommended pad layout for surface mount leadform





### Device Marking





### Notes

|     |   |
|-----|---|
| EL  | denotes Everlight                                       |
| 3H7 | denotes Device Number                                   |
| R   | denotes CTR Rank (A, B, C, D, E, F, H, I, J, K or none) |
| Y   | denotes 1 digit Year code                               |
| WW  | denotes 2 digit Week code                               |
| V   | denotes VDE (optional)                                  |

EVERLIGHT



### Tape & Reel Packing Specifications

**Option TA**




Direction of feed from reel

**Option TB**




Direction of feed from reel

### Tape dimensions



|                |            |           |              |             |            |           |
|----------------|------------|-----------|--------------|-------------|------------|-----------|
| Dimension No.  | <b>A</b>   | <b>B</b>  | <b>Do</b>    | <b>D1</b>   | <b>E</b>   | <b>F</b>  |
| Dimension (mm) | 3.0 ± 0.1  | 7.3 ± 0.1 | 1.5 + 0.1/-0 | 1.5 ± 0.1   | 1.75 ± 0.1 | 5.5 ± 0.1 |
| Dimension No.  | <b>Po</b>  | <b>P1</b> | <b>P2</b>    | <b>t</b>    | <b>W</b>   | <b>K</b>  |
| Dimension (mm) | 4.0 ± 0.15 | 4.0 ± 0.1 | 2.0 ± 0.1    | 0.25 ± 0.03 | 12.0 ± 0.2 | 2.4 ± 0.1 |

### Solder Reflow Temperature Profile



### DISCLAIMER

1. The specifications in this datasheet may be changed without notice. EVERLIGHT reserves the authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for use as outlined in this datasheet. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in this datasheet.
3. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.

EVERLIGHT



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



#### Как с нами связаться

**Телефон:** 8 (812) 309 58 32 (многоканальный)

**Факс:** 8 (812) 320-02-42

**Электронная почта:** [org@eplast1.ru](mailto:org@eplast1.ru)

**Адрес:** 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.