EVERLIGHT AMERICAS

DATASHEET

Infrared Receiver Control Receiver Module
EAIRMIA0



Pin Configuration

1. GND
2. GND
3. OUT
4. Vcc

Block Diagram



Features

- High protection ability against EMI
- Circular lens for improved reception characteristics
- Available for various carrier frequencies
- Min burst length: 6 cycles
- Min gap length: 10 cycles
- Suitable for continuous code
- Low operating voltage and low power consumption
- Optimized immunity against TFT backlight interferences
- High immunity against ambient light
- Long reception range
- High sensitivity
- Pb free and RoHS compliant
- Compliance with EU REACH.
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

Description

- The EAIRMIA0 series devices are miniature type infrared receivers which have been developed and designed by using the latest IC technology, specially optimized to suppress interferences from TFT backlight.
- The photo diode and preamplifier are assembled onto a lead frame and molded into an epoxy package which operates as an IR filter.
- The demodulated output signal can directly be decoded by a microprocessor.

Applications

- Light detecting portion of remote control
- AV instruments such as Audio, TV, VCR, CD, MD, etc
- Home appliances such as Air-conditioner, Fan, etc
- 0ther devices using IR remote control
- CATV set top boxes
- Multi-media Equipment

Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Application Circuit



Parts Table

Model No.	Carrier Frequency
EAIRMIA0	36 kHz

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Unit
Supply Voltage	Vcc	6	V
Operating Temperature	Topr	-20 ~ +85	℃
Storage Temperature	Tstg	-40 ~ +85	℃
Soldering Temperature *1	Tsol	260	℃

*1 4mm from mold body for less than 10 seconds

Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Current consumption	Icc	-	0.4	0.6	mA	No input signal
Supply voltage	V_{CC}	2.7	-	5.5	V	
Peak wavelength	λ_p	---	940	---	nm	
Reception range	L_0	8	---	---	m	See chapter ‚Test method'
	L_{45}	5	---	---		
Half angle(horizontal)	φ_h	---	±45	---	deg	
Half angle(vertical)	φ_v	---	±45	---	deg	
High level pulse width	T_H	450	-	700	μs	Test signal according to figure 1
Low level pulse width	T_L	500	-	750	μs	
High level output voltage	V_{OH}	Vcc-0.4	---	---	V	$I_{SOURCE} \leqq 1\mu$ A
Low level output voltage	V_{OL}	---	0.2	0.5	V	$I_{SINK} \leqq 2$mA
Internal pull up resistor	R_{PU}	85	100	115	kΩ	

Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Test method

The specified electro-optical characteristics are valid under the following conditions.

1. Measurement environment
   A place without extreme light reflections.
2. External light
   The environment contains an ordinary, white fluorescent lamp without high frequency modulation. The color temperature is 2856K and the illumination at the IR receiver is less than 10 Lux (Ev≦10Lux).
3. Standard transmitter
   The test transmitter is calibrated by using the circuit shown in figure 2. The radiation intensity of the transmitter is adjusted until **Vo=400mVp-p.** Both, the test transmitter and the photo diode, have a peak wavelength of 940nm. The photo diode for calibration is PD438B (λp=940nm, Vr=5V).
4. The measurement system is shown in Fig.-3

Fig.-1 Transmitter Wave Form





D.U.T output Pulse



Fig.-3 Measuring System



Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Typical Electro-Optical Characteristics Curves

Fig.4 Relative Responsibility vs. Wavelength



Fig.-5 Relative Transmission Distance vs. Direction



Fig.6 Variation Output Pulse Width vs. Distance



Fig.7 Relative Sensitivity vs. Supply Voltage



Fig.8 Relative Sensitivity vs. Frequency



Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Package Dimension

(Dimensions in mm)



Recommended pad layout for surface mount leadform



Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Code information

Protocol	Suitable	Protocol	Suitable
JVC	Yes	RCA	Yes
Matsushita	Yes	Sharp	Yes
Mitsubishi	Yes	Sony 12 Bit	Yes
NEC	Yes	Sony 15 Bit	No
RC5	Yes	Sony 20Bit	No
RC6	Yes	Toshiba	Yes
RCMM	Yes	Zenith	Yes
RCS-80	Yes	Continuous Code	Yes

Tape & Reel Packing Specifications

(Dimensions in mm)



Packing Quantity

1000 pcs / Reel

5 Reels / Carton

Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Label format





Moisture Classification-storage and used condition label

Recommended method of storage

The following are general recommendations for moisture sensitive level (MSL) 4 storage and use:

1. Shelf life in sealed bag from the bag seal date: 12 months at < 40 °C and < 90% relative humidity (RH)
2. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must mounted within 72 hours of factory conditions < 30 °C/60%RH.
3. If the moisture absorbent material (silica gel) has faded away or the IRM has exceeded the storage time. Baking treatment is required, refer to IPC/JEDEC J-STD-033 for bake procedure or recommend the conditions: 60±5°C for 96 hours.

ESD Precaution
Proper storage and handing procedures should be followed to prevent ESD damage to the devices especially when they are removed from the Anti-static bag. Electro-Static Sensitive Devices warning labels are on the packing.

Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Solder Reflow Temperature Profile



Note:

1. Reflow soldering should not be done more than two times.
2. When soldering, do not put stress on the IRM device during heating.
3. After soldering, do not warp the circuit board.

Application Restrictions

1. Above specification may be changed without notice. Everlight Americas will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. Everlight Americas assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of Everlight Americas. Reproduction in any form is prohibited without the specific consent of Everlight Americas.

Copyright © 2010, Everlight Americas Inc. Release Date : Feb. 21, 2012 Issue No: 1 Rev.1

Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits,General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помощь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)
Факс: 8 (812) 320-02-42
Электронная почта: org@eplast1.ru
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.