



N-Channel Enhancement-Mode Vertical DMOS FET

Features

- ▶ Low threshold
- ▶ High input impedance
- ▶ Low input capacitance
- ▶ Fast switching speeds
- ▶ Low on-resistance
- ▶ Free from secondary breakdown
- ▶ Low input and output leakage

Applications

- ▶ Logic level interfaces – ideal for TTL and CMOS
- ▶ Solid state relays
- ▶ Battery operated systems
- ▶ Photo voltaic drives
- ▶ Analog switches
- ▶ General purpose line drivers
- ▶ Telecom switches

General Description

This low threshold, enhancement-mode (normally-off) transistor utilizes a vertical DMOS structure and Supertex's well-proven, silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Ordering Information

Part Number	Package Option	Packing
TN2425N8-G	TO-243AA (SOT-89)	2000/Reel

-G denotes a lead (Pb)-free / RoHS compliant package.


Contact factory for Wafer / Die availability.

Devices in Wafer / Die form are lead (Pb)-free / RoHS compliant.

Product Summary

BV_{DSS}/BV_{DGS}	$R_{DS(ON)}$ (max)	I_{DSS} (min)
25V	3.58Ω	1.5A

Pin Configuration



Absolute Maximum Ratings

Parameter	Value
Drain-to-source voltage	BV_{DSS}
Drain-to-gate voltage	BV_{DGS}
Gate-to-source voltage	±20V
Operating and storage temperature	-55°C to +150°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

Product Marking

TN4CW

W = Code for Week Sealed

_____ = "Green" Packaging

Package may or may not include the following marks: Si or

TO-243AA (SOT-89)

Typical Thermal Resistance

Package	θ_{ja}
TO-243AA (SOT-89)	133°C/W

Thermal Characteristics

Package	I_D (continuous) [†]	I_D (pulsed)	Power Dissipation $@T_c = 25^\circ\text{C}$	I_{DR} [†]	I_{DRM}
TO-243AA (SOT-89)	480mA	1.90A	1.6W [#]	480mA	1.90A

Notes:

[†] I_D (continuous) is limited by max rated T_j .

[#] $T_A = 25^\circ\text{C}$. Mounted on FR5 Board, 25mm x 25mm x 1.57mm. Significant P_D increase possible on ceramic substrate.


Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Sym	Parameter	Min	Typ	Max	Units	Conditions
BV_{DSS}	Drain-to-source breakdown voltage	250	-	-	V	$V_{\text{GS}} = 0\text{V}$, $I_D = 250\mu\text{A}$
$V_{\text{GS(th)}}$	Gate threshold voltage	0.8	-	2.5	V	$V_{\text{GS}} = V_{\text{DS}}$, $I_D = 1.0\text{mA}$
$\Delta V_{\text{GS(th)}}$	Change in $V_{\text{GS(th)}}$ with temperature	-	-	-5.5	mV/ $^\circ\text{C}$	$V_{\text{GS}} = V_{\text{DS}}$, $I_D = 1.0\text{mA}$
I_{GSS}	Gate body leakage	-	-	100	nA	$V_{\text{GS}} = \pm 20\text{V}$, $V_{\text{DS}} = 0\text{V}$
I_{DSS}	Zero gate voltage drain current	-	-	10	μA	$V_{\text{GS}} = 0\text{V}$, $V_{\text{DS}} = \text{Max Rating}$
		-	-	1.0	mA	$V_{\text{DS}} = 0.8\text{Max Rating}$, $V_{\text{GS}} = 0\text{V}$, $T_A = 125^\circ\text{C}$
$I_{\text{D(ON)}}$	On-state drain current	0.8	-	-	A	$V_{\text{GS}} = 4.5\text{V}$, $V_{\text{DS}} = 25\text{V}$
		1.5	-	-		$V_{\text{GS}} = 10\text{V}$, $V_{\text{DS}} = 25\text{V}$
$R_{\text{DS(ON)}}$	Static drain-to-source on-state resistance	-	-	6.0	Ω	$V_{\text{GS}} = 3.0\text{V}$, $I_D = 150\text{mA}$
		-	-	5.0		$V_{\text{GS}} = 4.5\text{V}$, $I_D = 250\text{mA}$
		-	-	3.5		$V_{\text{GS}} = 10\text{V}$, $I_D = 500\text{mA}$
$\Delta R_{\text{DS(ON)}}$	Change in $R_{\text{DS(ON)}}$ with temperature	-	-	1.7	%/ $^\circ\text{C}$	$V_{\text{GS}} = 10\text{V}$, $I_D = 500\text{mA}$
G_{FS}	Forward transductance	500	-	-	mmho	$V_{\text{DS}} = 25\text{V}$, $I_D = 250\text{mA}$
C_{ISS}	Input capacitance	-	105	200	pF	$V_{\text{GS}} = 0\text{V}$, $V_{\text{DS}} = 25\text{V}$, $f = 1.0\text{MHz}$
C_{OSS}	Common source output capacitance	-	25	100		
C_{RSS}	Reverse transfer capacitance	-	7.0	40		
$t_{\text{d(ON)}}$	Turn-on delay time	-	5.0	15	ns	$V_{\text{DD}} = 25\text{V}$, $I_D = 500\text{mA}$, $R_{\text{GEN}} = 25\Omega$
t_r	Rise time	-	10	25		
$t_{\text{d(OFF)}}$	Turn-off delay time	-	25	35		
t_f	Fall time	-	5.0	15		
V_{SD}	Diode forward voltage drop	-	-	1.5	V	$V_{\text{GS}} = 0\text{V}$, $I_{\text{SD}} = 500\text{mA}$
t_{rr}	Reverse recovery time	-	300	-	ns	$V_{\text{GS}} = 0\text{V}$, $I_{\text{SD}} = 500\text{mA}$







Notes:

- All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300 μs pulse, 2% duty cycle.)
- All A.C. parameters sample tested.







Switching Waveforms and Test Circuit




Typical Performance Curves




Typical Performance Curves (cont.)



3-Lead TO-243AA (SOT-89) Package Outline (N8)



Top View



Side View

Symbol		A	b	b1	c	D	D1	E	E1	e	e1	H	L
Dimensions (mm)	MIN	1.40	0.44	0.36	0.35	4.40	1.62	2.29	2.00 ^t	1.50 BSC	3.00 BSC	3.94	0.73 ^t
	NOM	-	-	-	-	-	-	-	-			-	-
	MAX	1.60	0.56	0.48	0.44	4.60	1.83	2.60	2.29			4.25	1.20

JEDEC Registration TO-243, Variation AA, Issue C, July 1986.

^t This dimension differs from the JEDEC drawing

Drawings not to scale.

Supertex Doc. #: DSPD-3TO243AAN8, Version F111010.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: <http://www.supertex.com>)



Компания «ЭлектроПласт» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов;
- Поставка более 17-ти миллионов наименований электронных компонентов;
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Техническая поддержка проекта, помошь в подборе аналогов, поставка прототипов;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- Лицензия ФСБ на осуществление работ с использованием сведений, составляющих государственную тайну;
- Поставка специализированных компонентов (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Aeroflex, Peregrine, Syfer, Eurofarad, Texas Instrument, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Помимо этого, одним из направлений компании «ЭлектроПласт» является направление «Источники питания». Мы предлагаем Вам помошь Конструкторского отдела:

- Подбор оптимального решения, техническое обоснование при выборе компонента;
- Подбор аналогов;
- Консультации по применению компонента;
- Поставка образцов и прототипов;
- Техническая поддержка проекта;
- Защита от снятия компонента с производства.



Как с нами связаться

Телефон: 8 (812) 309 58 32 (многоканальный)

Факс: 8 (812) 320-02-42

Электронная почта: org@eplast1.ru

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, дом 2, корпус 4, литера А.